

Performance characteristics	1 min			1 h			6 h			12 h		24 h
Adjustments	T640	RH, T640	RH, T640, $T$	T640	RH, T640	RH, T640, $T$	T640	RH, T640	RH, T640, $T$	T640	T640, $T$	T640
$\beta_0$	-2.1 (-2.6 to -1.9)	-3.5 (-3.9 to -3.3)	-1.5 (-1.9 to -1.0)	-2.1 (-2.6 to -1.8)	-3.5 (-3.9 to -3.3)	-1.4 (-1.8 to -1.0)	-2.4 (-2.9 to -2.1)	-3.2 (-3.6 to -3)	-0.3 (-0.6-0.1)	-3.4 (-3.9 to -3)	8.7 (8.6-8.7)	-4.1 (-4.6 to -3.6)
$\beta_1$	1.8 (1.7-1.9)	1.4 (1.4-1.5)	1.5 (1.4-1.6)	1.8 (1.7-1.9)	1.4 (1.4-1.5)	1.5 (1.4-1.6)	1.8 (1.7-2)	1.4 (1.3-1.5)	1.5 (1.4-1.6)	1.9 (1.8-2.1)	2.2 (2.1-2.4)	2 (1.9-2.1)
$\beta_2$	-	-	-0.09 (-0.1 to -0.07)	-	-	-0.09 (-0.1 to -0.08)	-	-	-0.13 (-0.14 to -0.11)	-	-0.49 (-0.51 to -0.47)	-
$R^2$	0.66 (0.63-0.67)	0.93 (0.90-0.93)	0.94 (0.93-0.94)	0.66 (0.64-0.68)	0.93 (0.92-0.94)	0.95	0.73 (0.71-0.74)	0.92 (0.91-0.93)	0.95 (0.95-0.96)	0.84 (0.82-0.85)	0.93 (0.92-0.94)	0.94 (0.93-0.94)
Mean of ratios <sup>1</sup>	0.99	1	1	0.99	1	1	1	1	1	1	1 (0.99-1)	1
Error <sup>2</sup>	27 % (27 %-30 %)	11 % (11 %-12 %)	9 % (9 %-10 %)	27 % (26 %-28 %)	10 % (9 %-11 %)	8 % (8 %-9 %)	22 % (21 %-24 %)	10 % (10 %-11 %)	8 % (8 %-9 %)	15 % (15 %-16 %)	11 % (10 %-12 %)	9 %