



Long-term climatology of vertical profiles of polarimetric variables and ice-microphysical retrievals at X-band – Part 1: Radar calibration

Tobias Scharbach¹, Velibor Pejčic¹, and Silke Trömel^{1,2}

¹Section Meteorology, Institute of Geosciences, University of Bonn, Bonn, Germany

²Laboratory for Clouds and Precipitation Exploration, Geoverbund ABC/J, Bonn, Germany

Correspondence: Tobias Scharbach (toscha@uni-bonn.de)

Received: 27 January 2026 – Discussion started: 2 March 2026

Revised: 25 June 2026 – Accepted: 7 September 2026 – Published: 2 October 2026

Abstract. In a two-part series of papers, a climatology of quasi-vertical profiles (QVPs) of polarimetric variables and ice-microphysical retrievals such as ice water content, total number concentration and mean volume diameter is presented. QVPs are generated from plan position indicator scans at 18° elevation angle measured with the X-band radar located in the city of Bonn in western Germany between 2013 and 2023. They have been statistically analysed including error analysis with special emphasis on the characteristics of the melting layer and the dendritic growth layer. This long-term climatology improves the understanding of microphysical processes in stratiform cloud regimes and provides a reference for numerical weather prediction modellers to e.g. advance existing microphysical bulk parameterisation schemes.

While part two analyses and discusses the climatology, this first part of the series describes the prior thorough calibration of the radar reflectivity factor (Z_H) and the differential reflectivity (Z_{DR}). One method uses the relation between Z_H and Z_{DR} in light rain to calibrate Z_H . Best fits are determined from simulated Z_H and Z_{DR} values obtained with T-matrix calculations for various temperatures and values of the width of the canting angle distribution using a large disdrometer dataset of drop size distributions measured over Germany (mostly Bonn). Since this Z_H calibration technique strongly depends on the accuracy of Z_{DR} and encountered deficiencies in the birdbath scan, QVPs in light rain have been used to calibrate Z_{DR} . Obtained Z_H offset values are validated and compared using both satellite information and self-consistency relationships including specific differential phase (K_{DP}). The successful calibration of Z_H is confirmed

by the root-mean-square error (0.70 dB), the mean-absolute error (0.60 dB), and the mean-bias (−0.50 dB) compared to the offsets obtained from satellite information. Offsets calculated by applying self-consistency relations show larger discrepancies, which favours the suitability of the novel method.

1 Introduction

Numerical weather prediction (NWP) models generally struggle with limitations of existing parameterisation schemes to adequately capture the complexity of microphysical processes (Ryzhkov et al., 2020; Fan et al., 2017). Since polarimetric radars enable us to distinguish between hydrometeors with different microphysical properties and/or habits (e.g. shape and number concentration) and to identify so-called polarimetric fingerprints indicating ongoing dominating microphysical processes like e.g. aggregation, size sorting or dendritic growth (Ryzhkov et al., 2016; Trömel et al., 2019; Kumjian, 2013a; Kumjian and Ryzhkov, 2010, among others), they can serve as a powerful tool for improving NWP parameterisation schemes and cloud models (Kennedy and Rutledge, 2011; Ryzhkov et al., 2020). The fusion of radar polarimetry and atmospheric modelling is a promising pathway to improve the representation of clouds and precipitation in NWP (Trömel et al., 2021). Using observation- (forward) operators (Kumjian and Ryzhkov, 2012; Ryzhkov et al., 2020), such as the Efficient Modular VOLUME scan RADAR Operator (EMVORADO; Zeng et al., 2016; Blahak, 2016; Blahak and de Lozar, 2021), synthetic polarimet-

ric variables can be calculated from simulated hydrometeor mass fractions and number concentrations of NWP models and directly compared with observed polarimetric variables (e.g. on the radar grid; Trömel et al., 2023; Shrestha et al., 2022; Xie et al., 2021). E.g., with a detailed model evaluation in radar observation space, Shrestha et al. (2022) identified excessive graupel production in the Consortium for Small scale MOdeling (COSMO) model (Doms and Baldauf, 2018; Doms et al., 2018) with the Seifert-Beheng two-moment microphysical parameterisation (SB2MP) scheme (Seifert and Beheng, 2006). To date, extensive graupel formation is still an ongoing challenge in many microphysical parameterisation schemes. Furthermore, model evaluation studies in radar observation space as well as polarimetric microphysical retrievals and in-situ observations show that existing NWP models coupled with various microphysical schemes tend to overestimate the size of aggregates and underestimate the number concentration of ice particles in general (e.g. Fridlind et al., 2017; Ori et al., 2020; Trömel et al., 2023, among others). Besides case studies, climatologies of polarimetric variables and microphysical retrievals are particularly important and serve as a statistically significant reference to understand and finally improve precipitation processes in atmospheric models.

In order to provide the required reliable information to NWP modelers, but also for most other radar applications in the scientific community and operational services, like quantitative precipitation estimation (QPE), nowcasting, hydrometeor classification and microphysical retrievals, precise calibration is a mandatory prerequisite (e.g. Ryzhkov and Zrnica, 2019; Warren et al., 2020; Houze Jr. et al., 2004; Crisologo, 2019). Although the use of novel gradient approaches (e.g. Planat et al., 2021) and phase-based measurements are gaining increased attention and popularity, it is unlikely that absolute values of the reflectivity factor Z_H and differential reflectivity Z_{DR} will ever become superfluous and instead will always remain a part of hybrid QPE and microphysical retrieval derivations. Calibration is also (even maybe to a lesser extent) relevant for climatologies in order to represent reality with sufficient accuracy and statistical significance by minimizing calibration induced uncertainties as much as possible. In principle, calibration induced uncertainties can be attributed to the characteristics of the receiver, transmitter, and, above all, the antenna, with the latter controlling the link between transmitted and received pulse power (e.g. Schneebeli et al., 2024).

Over the years, many techniques for calibrating Z_H and Z_{DR} have been developed and applied. Examples are the use of disdrometer data (e.g. Frech et al., 2017; Schneebeli et al., 2024; Frech, 2013), corner reflectors or metal spheres (attached on e.g. drones and balloons; e.g. Atlas and Mossop, 1960; Atlas, 2002; Williams et al., 2013; Ye et al., 2024; Joshil and Chandrasekar, 2022), virtually generated radar targets (Schneebeli et al., 2024; Wang et al., 2025; Schneebeli et al., 2025), solar signals (e.g. Frech and Hubbert, 2020;

Holleman et al., 2010; Chu et al., 2019), stable ground clutter signals (e.g. Silberstein et al., 2008; Wolff et al., 2015; Pejčic et al., 2022; Hunzinger et al., 2020) or dominant point targets located close to the radar site (Gabella, 2018), self-consistency relations of polarimetric variables (e.g. Gorgucci et al., 1992; Louf et al., 2019; Gourley et al., 2009), $Z_H - Z_{DR}$ dependencies in light rain (e.g. Ryzhkov and Zrnica, 2019), satellite (spaceborn) radar information (Pejčic et al., 2022; Louf et al., 2019; Louf and Protat, 2023; Crisologo et al., 2018), quasi-vertical profiles (QVPs; Ryzhkov et al., 2016) in light rain (Sanchez-Rivas and Rico-Ramirez, 2022), dry aggregated snow (e.g. Hu et al., 2026, 2024; Ryzhkov et al., 2005; Zittel et al., 2014), clear air Bragg scattering (e.g. Richardson et al., 2017), or the so-called birdbath scan method (e.g. Gorgucci et al., 1999; Frech and Hubbert, 2020; Louf et al., 2019; Ryzhkov and Zrnica, 2019; Pejčic et al., 2022; Sanchez-Rivas and Rico-Ramirez, 2022).

The latter exploits vertical scans, where raindrops appear nearly spherical to the radar, and is one of the most frequently used methods for accurate Z_{DR} calibration. Similarly, Z_{DR} is expected to be 0 dB when the radar is pointing towards the sun, due to the unpolarized nature of solar radiation in this direction. Monitoring the sun allows the detection potential receiver malfunctions or radar antenna misalignment (Holleman et al., 2010). To determine more precisely which components of the radar system are responsible for any system biases, the latter two techniques can be combined, as demonstrated in Figueras i Ventura et al. (2012). In particular, the difference between the Z_{DR} derived from solar signals and that obtained from birdbath scans can be used to identify transmitter biases.

The first part of the paper series focuses on the prior, as noted above, very important calibration of Z_{DR} and Z_H , while the second part deals with the description and the statistical analysis of the climatology of QVPs of polarimetric variables and ice-microphysical retrievals obtained from 10 years of X-band radar data measured in stratiform rain.

Most of the calibration methods briefly presented above are either not retrospectively applicable because e.g. the required scanning strategy is missing, the radar system is simply not capable of setting it up, the required measurements are not saved, or it is not possible to cover the whole time period. Although the birdbath method is widely used to calibrate Z_{DR} , the results were not reliable throughout the entire climatological period; In particular, the offset values obtained for 2014 appeared unrealistically small, limiting the usefulness of the calibrated Z_{DR} . Instead applying the birdbath scan, a modified method adapted from Sanchez-Rivas and Rico-Ramirez (2022) using QVPs in light rain is exploited for Z_{DR} calibration and a Z_H calibration technique applicable to the entire time series from 2013–2023 is presented. It uses the known $Z_H - Z_{DR}$ dependency (Ryzhkov and Zrnica, 2019), but with Z_{DR} as a predictor for Z_H measured on PPI scans at 18° elevation angle. This calibration method of Z_H is validated and compared to Z_H offset values

obtained from satellite measurements, provided for a 5.5 year subset by Pejčic et al. (2022) and self-consistency relations as described in e.g. Louf et al. (2019).

The paper is structured as follows: Section 2 shortly introduces most important technical information and scanning strategies of the used radar and describes the steps of phase processing in more detail. The following Sect. 3 explains the problems encountered when using the birdbath scan method to correct Z_{DR} and presents the above mentioned alternative Z_{DR} calibration method used in this study, followed by the novel Z_H calibration method, its validation and the comparison with the self-consistency relation. Section 4 summarizes the results, highlights deficiencies and identifies potential improvements for future studies.

2 Radar data

The radar data used in this study have been obtained with the polarimetric X-band radar in Bonn, Germany (BoX-Pol), located at 50.7305° N and 7.0717° E and 99.5 m above mean sea level (a.m.s.l). BoXPol measures within a radius of 100 km since 2009 (Fig. 1). The hardware includes an EEC DWSR-2001-X-SDP weather radar without a radome, operating in the simultaneous transmit and receive of horizontally and vertically polarized electromagnetic (EM)-waves (STAR or SHV) mode (Pejčic et al., 2022; Ryzhkov and Zrnić, 2019) using an Enigma signal processor. Plan position indicator (PPI) scans are generated at 10 different elevation angles, ranging from 1–28° and a (90°) birdbath scan in 5 min temporal and 1° azimuthal resolution. The range resolution depends on the chosen configuration of the elevation scan and ranges from 25–200 m. For the 18° elevation angle (used in this two paper series) it is 100 m until the third of April 2017 and afterwards 125 m, where Enigma 3 was updated to Enigma 4. BoXPol operates in dual pulse repetition frequency (PRF) unfolding (staggering) mode 3, with alternating low PRF and high PRF values in the azimuth dimension with values ranging from 400–1150 Hz (1600 Hz for the birdbath scan) and from 320–920 Hz, respectively, for various range resolutions (personal communication with Kai Mühlbauer¹, see also Table 2 in Pejčic et al., 2022). A range height indicator (RHI) scan is included in a 5 min scan schedule as well. For a more detailed information about the scanning strategies, reference is made to Diederich et al. (2015) or Pejčic et al. (2022).

All offset values (Z_{DR} and Z_H) are determined using PPI scans at 18° elevation angle. These measurements are also used in part 2 of this paper series for the climatology. The choice of this elevation angle represents a compromise: It already provides sufficient vertical profile information, but the use of even higher elevation angles would result in a significant degradation of the polarimetric information con-

Table 1. Technical description of the X-band radar in Bonn (BoX-Pol).

Parameter	BoXPol
Radar type	DualPol X-band radar
Longitude	7.0717° E
Latitude	50.7305° N
Altitude	99.5 m
Wavelength (λ)	3.2 cm
Frequency	9.3 GHz
Antenna gain	44.2 dB
3 dB antenna beamwidth	1.07°
Hardware	Radome-less EEC DWSR-2001-X-SDP weather radar
Magnetron (transmit) peak power	200 kW
Signal processor	GAMIC Enigma 3 until 3 April 2017, thereafter Enigma 4
Transmit type	Random-phase magnetron using Simultaneous Dual Polarization (SIDpol)
Mode	STAR or SHV
Temporal resolution	5 min
Radial resolution	25 to 200 m
Elevation angles	1 to 28° with 90° (birdbath scan)
Azimuth dimension	1 to 360°
Dual PRF Unfolding	Staggered PRF mode 3 (four times unfolding, 4/5 staggering)
High PRF	400 to 1150 Hz (1600 Hz in birdbath scan)
Low PRF	250 to 920 Hz
Pulse duration (τ)	0.2 and 0.5 μ s

tent. At angles below 20°, however, only slight acceptable decreases occur (Ryzhkov et al., 2005; Griffin et al., 2018; Trömel et al., 2019).

The height of the radar beam is calculated assuming 4/3 effective earth radius (e.g., Doviak and Zrnić, 1993). No interpolation is applied, i.e. each range bin transforms into one height bin.

¹Further information is available in the GAMIC Enigma 3 manual.




Figure 1. Location of BoXPol and covering area of the PPI scans at 18° elevation angle (550 km maximum range) including terrain height information and city names in the surrounding region given as red points (left). Example illustration of Z_H in a cone of the 18° PPI scan at the 7 October 2014, 00:00 UTC (right). Note that this figure represents the maximum range of BoXPol operating with Enigma 3 until the 4 March 2017.

Within the phase processing, first the system phase offset (ϕ_{DP}^{sys} ; Ryzhkov and Zrnica, 2019) has to be determined and subtracted from ϕ_{DP} . ϕ_{DP}^{sys} is calculated by filtering with $\rho_{HV} \geq 0.9$ and $Z_H \geq 0$ and identifying the position of the first non-NaN measurement of ϕ_{DP} in each ray. Subsequently, the median of the values between this position and 3 km in the range dimension provide ϕ_{DP}^{sys} .

Afterwards, the offset-corrected ϕ_{DP} is smoothed using a moving median with a window length of 11 range bins. The specific differential phase (K_{DP} ; e.g. Trömel et al., 2014; Ryzhkov and Zrnica, 2019; Vulpiani et al., 2012) in degrees per kilometer ($^\circ\text{km}^{-1}$) is calculated applying low-noise Lanczos differentials (Holoborodko, 2015; Diekema and Koornwinder, 2012) implemented in *wradlib*, using a window length of 31 range bins (corresponding to 3.1 km slant range for Enigma 3 and 3.875 km slant range for Enigma 4).

3 Calibration of Z_{DR} and Z_H

Assuming no specific attenuation (A_H ; e.g. Kumjian, 2013b), wet radome effects (e.g. Le Loh et al., 2022) or noise influences (e.g. Schneebeli et al., 2024), a simple representation of the measured Z_H (e.g. Silberstein et al., 2008; Louf and Protat, 2023) based on the well-known radar equation (e.g. Ryzhkov and Zrnica, 2019; Doviak and Zrnica, 1993; Rinehart, 1997), can be used to characterize possible calibration errors with the following equation:

$$Z_H = -10\log_{10} \left(\underbrace{\frac{\pi^3 |K_w|^2}{\lambda^2 \times 1024 \cdot \ln 2 \times 10^{18}} P_t^H (G^H \theta^H)^2 c \tau A_t^H A_r^H}_{C_r^H} \right) + 20\log_{10} r + 10\log_{10} P_r^H. \quad (1)$$

P_r^H is the received and P_t^H the transmitted power of the horizontal polarization channel in W, K_w is the dielectric factor of water, θ^H is the half power antenna beam width of the horizontal polarization channel in rad, c is the speed of light in ms^{-1} , G^H is the antenna gain of the horizontal polarization channel with the assumption that the antenna is for both transmitting and receiving, A_t^H and A_r^H are the transmitter and the receiver gains of the horizontal polarization channel, τ is the pulse duration of transmitted signals in s and r is the radial distance of the target in m.

The underbraced term in Eq. (1) is the so-called radar constant of the horizontal channel C_r^H (e.g. Schneebeli et al., 2024; Ryzhkov and Zrnica, 2019), which can vary over time and due to degradation of radar hardware (e.g. Louf et al., 2019) and represents the main source of potential calibration errors.

Similarly, Eq. (1) is valid for the reflectivity factor of the vertically polarized EM wave (Z_V) in the STAR mode, i.e. superscripts and subscripts “H” can be replaced by “V” (e.g. Ryzhkov and Zrnica, 2019; Schneebeli et al., 2024). As a result, any difference in the radar constants for both polarization channels may also result in a Z_{DR} miscalibration, as il-

Table 2. Logbook of BoXPOL displaying most important changes in hardware and software in the time period from January 2013–March 2023.

Date	Important changes of BoXPOL
2013	No important notifications
24 April 2014	Restart of radar (due to system failures)
3 April 2017	Enigma 3 to Enigma 4 software change
27–28 April 2017	Change of Magnetron (receiving channel calibration)
14 June 2019	Shutdown complete system
26 July 2020	Restart of radar
30–31 January 2021	Radar breakdown
3 July 2021	Restart of radar
10–12 January 2021	Magnetron errors and/or other issues
30 May 2022	Change of Magnetron (receiving channel calibration)
9 March 2023	Last shutdown of radar (Broken Magnetron)

illustrated by the following equation:

$$Z_{\text{DR}} = 10 \log_{10} \left(\frac{P_r^{\text{H}} \cdot C_r^{\text{V}}}{P_r^{\text{V}} \cdot C_r^{\text{H}}} \right). \quad (2)$$

In the case of a perfectly calibrated (fictitious) radar (e.g. for the transmitter channel, for the receiver channel and for the antenna; Schneebeli et al., 2024), $C_r^{\text{H}} = C_r^{\text{V}}$ and thus, Z_{DR} depends on P_r^{V} and P_r^{H} only (e.g. Ryzhkov and Zrnica, 2019). Since a perfect internal calibration for the estimation of C_r is almost impossible, external sources/methods are mandatory for a sufficient calibration of Z_{H} and/or Z_{DR}^2 (Louf et al., 2019).

To enable quantitative applications like Quantitative Precipitation Estimation (QPE), microphysical retrievals or hydrometeor classification, Z_{DR} needs to be calibrated with an accuracy of 0.1–0.2 dB (Frech and Hubbert, 2020; Ryzhkov and Zrnica, 2019). As mentioned before, the birdbath (90° elevation angle) scan method is one of the most powerful calibration methods for Z_{DR} (Ryzhkov and Zrnica, 2019; Frech et al., 2017; Louf et al., 2019). Since the mean angle of incidence of raindrops is close to 0°, they appear spherical when viewed from below. This means that both Z_{H} and Z_{V} should be equal and deviations can be used for calibration of Z_{DR} in light rain (Ryzhkov and Zrnica, 2019). In this study, Z_{DR} offsets from the birdbath scan are calculated using a similar but slightly more rigorous procedure compared to Pejčić et al. (2022). First, mixed phase hydrometeors are excluded

using only data at heights at least 250 m away from the 0 °C isotherm. The temperature information is taken from the European Center for Medium-Range Weather Forecasts Reanalysis v5 (ERA5; Hersbach et al., 2020). Afterwards, the median between the 20th and 80th percentiles of Z_{DR} is calculated (instead of the 10th and 90th percentiles in Pejčić et al., 2022), whereby only days with > 100 non-NaN values and a standard deviation < 0.2 dB are considered as reliable for estimating the daily Z_{DR} offset.

However, serious inconsistencies in the Z_{DR} offset values obtained using the birdbath scan method were discovered. While the method provided reliable offsets for the period between April 2014 and March 2017, inaccuracies of more than 0.2 dB were obtained for other times (especially for 2013 to early 2014). Due to various hardware and software changes between 2013 and 2023 documented in the BoXPOL logbook (private communication with Kai Mühlbauer and Martin Lennefer, 6 March 2024, summarized in Table 2), such as the replacement of hardware components (e.g. Magnetron), software updates (Enigma 3 to Enigma 4), but also unfathomable influences, offsets derived from the birdbath scan seem not to be applicable to the 18° elevation PPI. These circumstances most likely lead to discrepancies in the components of C_r for both channels (see Eq. 2) and also may point to a potentially unsuspected elevation dependence. The ratios of the radar constants for the birdbath (BB) scan ($C_{r,\text{BB}}$) and the 18° elevation scan ($C_{r,18}$) of the horizontal (H) and vertical (V) polarization channels appear to deviate from each other:

$$\frac{C_{r,\text{BB}}^{\text{V}}}{C_{r,\text{BB}}^{\text{H}}} \neq \frac{C_{r,18}^{\text{V}}}{C_{r,18}^{\text{H}}}. \quad (3)$$

This potential elevation dependence could be related either to the mechanical control of elevation angles in the BoXPOL scanning strategy or to issues with the rotary joints between the transmitter/receiver and the antenna (private communication with Martin Lennefer and Kai Mühlbauer, 6 March 2024; Figueras i Ventura et al., 2012). Therefore, the QVPs themselves are used to calculate the Z_{DR} offset (Sanchez-Rivas and Rico-Ramirez, 2022) and to subsequently calibrate Z_{H} based on the offset corrected Z_{DR} .

In the following, Sect. 3.1 describes the Z_{DR} calibration technique and Sect. 3.2 the calibration of Z_{H} , while Sect. 3.2.1 and 3.2.2 compare and validate the results using self-consistency relations and satellite information.

3.1 Z_{DR} Calibration

Light rain conditions are identified with $0 < Z_{\text{H}} < 20 \text{ dBZ}$ and $\rho_{\text{HV}} > 0.985$ (Sanchez-Rivas and Rico-Ramirez, 2022) and $\phi_{\text{DP}} < 30^\circ$. The latter is a precautionary step intended to effectively exclude highly unlikely brief episodes of heavy rain or hail in the event if other thresholds failing. Since an uncalibrated Z_{H} is used to calibrate Z_{DR} , this additional ϕ_{DP} threshold is intended for the unlikely case that the absolute

²Some of these techniques are briefly mentioned above.

value of the Z_H offset could be very large (e.g., > 15 dB). To ensure that the calculation includes liquid hydrometeors exclusively, only data at least 250 m below the height of the 0°C isotherm is used. QVPs are only computed if there are at least 100 valid values in the azimuth dimension. Subsequently, only QVPs with at least 10 valid values in the height dimension are included in the overall calculation of the daily Z_{DR} offset. The mean value of each QVP (calculated over the height dimension) subtracted by the expected simulated average value of Z_{DR} for the range between 0 and 20 dBZ (light rain) defines the offset value of Z_{DR} (Z_{DR}^{off}). To determine the expected Z_{DR} value, T-matrix simulations (Waterman, 1971; Mishchenko et al., 1996) are performed based on drop-size distributions (DSDs) measured with a Thies disdrometer on the rooftop of the Institute of Geosciences, Section Meteorology, University of Bonn, Germany, between November 2011 and December 2019, and with 68 Thies disdrometers of DWD during 30 rainy days between 2015 and 2017.

More detailed information on the processing of the disdrometer dataset can be found in Chen et al. (2021).

T-matrix simulated Z_H and Z_{DR} values at X-band ($\lambda = 3.2$ cm) and 18° elevation angles are obtained using properties of homogeneous non-spherical scatterers assuming a 2D axisymmetric Gaussian distribution of orientations for oblate hydrometeors (Ryzhkov et al., 2011; Ryzhkov and Zrnica, 2019). We set the mean canting angle to 0° , with various values for either the temperature (5, 10, 15, 20 and 30°C , respectively) and the width of the canting angle distribution (std(C) with 5, 8, 10 and 12° , respectively), applying the rain-drop shape model following Brandes et al. (2002). The dielectric constant of water (ϵ_w) is calculated for temperatures between 5 and 30°C following Ray (1972). Figure 2 presents the 2D-distribution of Z_{DR} and Z_H for std(C) of 8° at 10°C and several best fit lines for different temperatures.

Only small differences in average simulated Z_{DR} in light rain ($\overline{Z_{DR}^{\text{T-sim}}}$) and best-fit lines of $Z_{DR} = f(Z_H)$ for different temperatures between 5 and 30°C in Fig. 2 demonstrate that temperature dependencies can be neglected. Thus, $\overline{Z_{DR}^{\text{T-sim}}} = 0.1$ dB is determined as the intrinsic Z_{DR} value in light rain for X-band radar data at elevation angles of 18° . The results are in agreement with those of Sanchez-Rivas and Rico-Ramirez (2022) (with an intrinsic Z_{DR} of 0.18 dB) and Zeyong et al. (2019) (with an intrinsic Z_{DR} in the range from 0.25–0.35 dB), despite slightly smaller values in comparison (most likely due to different radar configurations and varying climatic conditions).

Finally, the median of a day's Z_{DR}^{off} values ($\text{med}[Z_{DR}^{\text{off}}]$) gives the daily Z_{DR} offset. Daily offsets are only calculated if the standard deviation of Z_{DR}^{off} is < 0.2 dB with at least > 100 valid values. Days without defined offset are filled with a centered 30 d rolling mean of $\text{med}[Z_{DR}^{\text{off}}]$. Note, daily Z_{DR} offsets have to be subtracted from the measured Z_{DR} of the PPI scans.




Figure 2. $Z_H - Z_{DR}$ relationship based on T-matrix scattering simulations at 18° elevation angle and 10°C using disdrometer measurements between November 2011 and December 2019 on the roof of the Institute for Geosciences, Department of Meteorology, University of Bonn, and 30 rain days between 2015 and 2017 from 68 Thies disdrometers of DWD (Chen et al., 2021). The best-fit lines of simulated $Z_{DR} = f(Z_H)$ for different temperatures are indicated in different colors including the according inverted equation $Z_H = f(Z_{DR})$ (in green) achieved for 10°C and std(C) of 8° used for Z_H calibration (see also Eq. 4). The mean values of Z_{DR} between 0 and 20 dBZ ($\overline{Z_{DR}^{\text{T-sim}}}$) for the different temperatures are also given.

Z_{DR} offsets derived from the birdbath scan calculated following Pejčic et al. (2022) but with a stricter filtering using only data between 20th and 80th percentile (instead of 10th and 90th percentile) are now compared with the ones obtained with the modified QVP method for the period from June 2014–April 2017. Therefore, the same gap-filling procedure as described above is applied to the birdbath scan Z_{DR} offset values. E.g., on 3 July 2013 the offset values obtained with the two methods show a relatively large difference of 0.18 dB (Fig. 3). Negative Z_{DR} values (between 0 and -0.1 dB) directly above the ML together with even more negative values of up to -1 dB in the liquid phase (panel (c)) indicate that the offset derived with the birdbath method is not adequate for the 18° scan.

The Z_{DR} offset time series obtained with the two methods for the time period from January 2013–March 2023 show similar trends, but deviations of about 0.2 dB or more occur in the period from 2013–April 2014 and from April 2017–June 2019 (Fig. 4). Another period of larger deviations is seen around December 2021–June 2022. Differences between the two methods are most likely associated with changes of the Magnetron (accompanied by receiving channel calibrations), the software change from Enigma 3 to Enigma 4 and general restarts of the radar after system failures. Within the stable period from 24 April 2014–




Figure 3. QVPs of Z_{DR} not offset corrected (a), offset corrected using QVP method (b) and birdbath scan method (c) for the 3 July 2013, from 06:00 to 13:00 UTC.




Figure 4. Daily Z_{DR} offsets calculated using for the period between January 2013–March 2023 the QVP (orange) and birdbath scan (blue) method, respectively. The times of important changes in BoXPOL are given as vertical dashed lines with the respective caption. RMSE, MB and MAE calculated for the time period between 24 April 2014 and 3 April 2017 are shown as well.

3 April 2017, however, the Z_{DR} offsets of the two methods are very close to each other. This is confirmed by a root-mean-square error (RMSE) of 0.1 dB, a mean-absolute er-

ror (MAE) of 0.07 dB and the mean-bias³ (MB) of -0.01 dB (e.g. Von Storch and Zwiers, 2002).

³The mean-bias is the mean value between the difference of the 30 d rolling mean gap-filled Z_{DR} offset obtained from the birdbath scan and from QVPs.

3.2 Z_H calibration using the $Z_H - Z_{DR}$ relationship

In the next step Z_H is calibrated exploiting the $Z_H - Z_{DR}$ relationship (e.g. Ryzhkov and Zrnica, 2019) but with Z_{DR} as a predictor for Z_H on PPIs at 18° elevation angles. In the following the method will be referred to as the reverse $Z_H - Z_{DR}$ method, since, to the authors' knowledge, it has so far only been used to calibrate Z_{DR} .

Again, mixed or solid phase hydrometers are excluded by focusing on data at least 250 m below the height of the 0°C isotherm taken from the ERA5 data set. Unlike for the Z_{DR} calibration, PPIs instead of QVPs are used and are filtered with $\rho_{HV} > 0.99$ and, as in the Z_{DR} calibration, with $\phi_{DP} < 30^\circ$. Like for the Z_{DR} calibration at least 100 non-NaN values are required along the azimuth dimension to be taken into account. Additionally, at least two thirds of the valid Z_H bins of a PPI must show a valid Z_{DR} value. Only days with at least 10 PPIs per day, each with at least 100 valid values, are used for further calculation. Each PPI with a Spearman correlation coefficient $\text{corr}_{\text{spear}} < 0.4$ is excluded from further calculations of the daily Z_H offset. Here, $\text{corr}_{\text{spear}}$ is calculated based on the positive Z_H and Z_{DR} values and is used because of possible deviations from the Gaussian, non-linearities and reduced sensitivity to outliers compared to the Pearson correlation coefficient. Finally, the simulated $Z_H - Z_{DR}$ dependency (Fig. 2) provides the expected Z_H (Z_H^{ideal}) per day based on the Z_{DR} values of the filtered PPIs. More precisely, the best fit of simulated Z_H at 10°C with $\text{std}(\text{C})$ equals 8° is used:

$$Z_H^{\text{ideal}} = 7.55 \cdot Z_{DR}^3 - 30.30 \cdot Z_{DR}^2 + 45.18 \cdot Z_{DR} + 11.23. \quad (4)$$

As outlined before, variations with temperature are neglectable for $Z_{DR} < 2\text{ dB}$ (Fig. 2) and the temperature chosen is roughly the average annual temperature in Germany. Similarly, changing the $\text{std}(\text{C})$ in the range from 5 – 12° has only minor influence (Fig. 5). The expected Z_H^{ideal} is subtracted from the measured Z_H to obtain the calibration offset of a PPI ($Z_H^{\text{off}} = Z_H - Z_H^{\text{ideal}}$). Again, only values between the 20th and 80th percentile of Z_H^{off} and with a standard deviation of $Z_H^{\text{off}} < 4\text{ dB}$ are considered to derive the daily offset. These thresholds have been chosen based on rough visual impressions of the daily standard deviations of the GPM derived Z_H offsets in Pejčic et al. (2022), Louf and Protat (2023) and Protat et al. (2022) (their Figs. 2, 12 and 2, respectively).

Finally, calculating the median of these filtered Z_H^{off} ($\text{med}[Z_H^{\text{off}}]$) gives the daily Z_H offset. Using the median instead of the mean reduces the impact of outliers caused by e.g. size sorting effects.

Consistent with the methodology for the calibration of Z_{DR} , any gaps in the time series of $\text{med}[Z_H^{\text{off}}]$ are filled using a rolling mean of 30 d. Offsets are defined to be subtracted from the measured Z_H values to obtain the offset-corrected Z_H . As an example, Fig. 6 demonstrates the performance of the method, i.e. the offset-corrected $Z_H - Z_{DR}$ distribution is shifted towards the ideal simulated $Z_H - Z_{DR}$ curve. QVPs




Figure 5. As in Fig. 2 but the best-fit lines of simulated $Z_{DR} = f(Z_H)$ at a constant temperature of 10°C with various $\text{std}(\text{C})$ and the mean values of Z_{DR} between 0 and 20 dBZ ($Z_{DR}^{\text{T-sim}}$) for different $\text{std}(\text{C})$ values.




Figure 6. Two-dimensional histograms of offset-corrected Z_{DR} versus Z_H for 3 July 2013: (a) using uncorrected Z_H and (b) using offset-corrected Z_H , based on the reverse $Z_H - Z_{DR}$ method. The thick red line represents the calculated ideal reflectivity (Z_H^{ideal}), corresponding to the best fit obtained from Eq. (4).

of Z_H show the more pronounced bright band and aggregation signature (Figs. 3 and 7), whereby the higher values of Z_H after offset correction appear to be more realistic.

3.2.1 Validation of Z_H -calibration using the self-consistency relationship

The relationship between the ratio $K_{DP}Z_h^{-1}$, with the reflectivity factor in linear scale ($Z_h = 10^{0.1Z_H}$) in $\text{mm}^6\text{ m}^{-3}$, and Z_{DR} in rain (e.g. Gorgucci et al., 2006) represents an alternative opportunity to calibrate radars (e.g. Marks et al., 2011).




Figure 7. QVPs of (a) uncorrected and (b) corrected Z_H using the reverse $Z_H - Z_{DR}$ method for the 3 July 2013, from 06:00 UTC to 13:00 UTC.




Figure 8. T-matrix simulated ($K_{DP} Z_h^{-1}$)– Z_{DR} dependencies at 18° elevation angle and 10°C based on disdrometer measurements for the period from November 2011–December 2019 on the rooftop of the Institute of Geosciences, Section Meteorology, University of Bonn, and 30 rainy days between 2015 and 2017 from 68 Thies disdrometers of the DWD (Chen et al., 2021). The best fit lines of the simulated $f(Z_{DR})$ for different temperatures are also given.

This technique is often utilized to calibrate Z_H of operational radars because, similar to the $Z_H - Z_{DR}$ relationship, it does not require comparative analysis, e.g. with other technical devices or instruments (Lee et al., 2021). However, applying published self-consistency relationships derived in different geographical locations and climate regimes can lead to large discrepancies (Louf et al., 2019).

Since the ratio $K_{DP} Z_h^{-1}$ is also temperature dependent at X-band (Ryzhkov and Zrnica, 2019), we derive a set of self-consistency relationships for Germany at various temperatures based on T-matrix simulated K_{DP} , Z_h and Z_{DR} us-

ing again the DSD dataset and the assumptions outlined in Sect. 3. Only DSDs with $0.5\text{ dB} > Z_{DR} < 2\text{ dB}$ (Louf et al., 2019) are considered to determine the resulting best-fit equations $f(Z_{DR})$ for the ratio $K_{DP} Z_h^{-1}$ as presented in Fig. 8. Subsequently we determine the expected Z_H , in the following referred to as Z_H^{self} , for comparison with the offset corrected Z_H using the reverse $Z_H - Z_{DR}$ method, with the following equation:

$$Z_H^{\text{self}}(i) = 10 \log_{10} \left(\frac{K_{DP}(i)}{f(Z_{DR})(i)} \right), \quad (5)$$

where the index i indicates the different equations for 5, 10, 15, 20 and 30°C , respectively. For a comparison in nearly homogeneous conditions, QVPs of stratiform rain events are generated, whereby in contrast to Sect. 3.1, prior filtering combines the use of the ML detection algorithm by Wolfensberger et al. (2016) but modified for application to QVPs by Trömel et al. (2019) and the Shannon information entropy (see Appendix A, Trömel et al., 2023). Filtering with the minimum Shannon information entropy $\min(\eta(X)_{\text{norm}}) \geq 0.85$ guarantees an increased degree of homogeneity in the PPI scans prior QVP generation. All QVP bins derived with the PPIs at 18° elevation monitored between 2013 and 2023 fulfilling these criteria are considered. The validation based on temperature information obtained from ERA5 further demonstrates the suitability of the stratiform filter technique (in particular the ML detection algorithm, see Appendix B). As above, following Louf et al. (2019) and Ryzhkov and Zrnica (2019), filtering with $0.5\text{ dB} < Z_{DR} < 2\text{ dB}$, $\text{SNR} > 25\text{ dB}$, $\rho_{HV} > 0.99$ and additionally $\phi_{DP} < 30^\circ$ is applied to the QVPs (see Sect. 3.1). Here, K_{DP} and offset-corrected Z_{DR} values of these QVPs are used to calculate Z_H^{self} using Eq. (5) and opposed to the offset-corrected Z_H of the QVPs. The comparison shows a moderate agreement, as indicated by the correlation of 0.63 (Fig. 9). Additionally, the majority of Z_H^{self} values are larger




Figure 9. 2D histogram of Z_H^{self} (see Eq. 5) versus measured and offset corrected Z_H using the reverse $Z_H - Z_{\text{DR}}$ method in the time period from 2013–2023. In addition to the sample size, Pearson correlation coefficient, RMSE, MB and MAE are also given.

than the measured Z_H , showing a MB^4 of 2.15 dB. The RMSE of 3.76 dB and the MAE of 3.08 dB confirm this observation.

Louf et al. (2019) show in their Fig. 15 the Z_H^{self} against calibrated Z_H obtained from the C-band polarimetric radar located near Darwin in northern Australia, using different raindrop shape models at 20 °C temperature and two different std(C). Overall, the distribution shown in Fig. 9 compares well with Fig. 15 in Louf et al. (2019), giving additional confidence also in using the 30 d rolling mean gap-filling procedure of the Z_H offsets. However, Fig. 9 shows higher values of Z_H^{self} and more outliers. Intrinsic uncertainties associated with the K_{DP} processing on the one hand, the temperature dependency, assumptions about the canting angle distribution and the chosen raindrop shape model in the T-matrix simulations on the other hand, may affect the results.

To gain more insight using self consistency Z_H calibration we additionally calculate Z_H offsets on a daily basis in a similar way as the Z_{DR} offsets (Sect. 3.1). In the following section, the two different Z_H offset calibration techniques are compared with each other and validated using satellite information.

3.2.2 Validation of Z_H -calibration using satellite information

Satellite measurements of the Dual-frequency Precipitation Radar (DPR) operating on the Global Precipitation Mission (GPM; e.g. Hou et al., 2014; Pejcic et al., 2020) core satellite, as well as its predecessor the Tropical Rainfall Measurement

Mission (TRMM; see e.g. Kozu et al., 2001; Joss et al., 2006) have been demonstrated to be a valuable data source for the calibration of ground based Z_H radar measurements (e.g., Pejcic et al., 2022; Louf and Protat, 2023; Louf et al., 2019; Warren et al., 2018; Loulli et al., 2025; Anagnostou et al., 2001). Thus, Z_H offsets obtained in this study are compared with the ones calculated by Pejcic et al. (2022) in the period between 2014 and June 2019. Daily average Z_H offsets based on the differences between measurements of BoXPol and the satellite-based K_u -band radar (part of DPR, explained in more detail in Pejcic et al., 2022) are compared with daily offsets obtained using the reverse $Z_H - Z_{\text{DR}}$ method and the self consistency relations (see Fig. 10). The reverse $Z_H - Z_{\text{DR}}$ method provides 544 daily Z_H offsets, whereas the self-consistency method only provides 148. For the point-to-point comparison (nearest time of overflight and 30 d rolling mean gap filled Z_H offsets), both the RMSE of 1.88 dB and the MAE of 1.51 dB ($\text{MB}^5 = -0.36$ dB) are in an acceptable range but relatively high. The differing sample sizes (92 overflights of GPM), may explain part of the deviations. At the same time, however, this comparison demonstrates the applicability of the 30 d rolling mean to obtain a gap-filled time series of Z_H offsets. And even though the DPR itself has a calibration accuracy of less than ± 1 dB (Masaki et al., 2020; Warren et al., 2018), intrinsic uncertainties of ≈ 0.25 – 0.5 dB for the K_u channel of the DPR must be considered in interpreting the accuracy of the reverse $Z_H - Z_{\text{DR}}$ method (see for example Figs. 8 and 9 in Masaki et al., 2020). Furthermore, Pejcic et al. (2022) uses the mean value instead of the median for the respective days, which gives outliers more weight, potentially increasing the discrepancies between GPM derived Z_H offsets and $\text{med}[Z_H^{\text{off}}]$. RMSE and MAE improve only slightly without the 30 d rolling mean gap filled procedure (not shown). For the 30 d rolling mean gap filled Z_H offsets obtained from self-consistency relations, both the RMSE (2.23 dB) and the MAE (1.87 dB) are larger and offsets are more negatively biased compared to results obtained with the reverse $Z_H - Z_{\text{DR}}$ method. The variabilities over the days, however, are rather similar for all three methods.

Additionally, the averaged satellite-derived Z_H offsets in stable calibration time periods identified with the relative calibration adjustment (RCA) technique (see Pejcic et al., 2022, for more information) are compared with according averaged values based on the 30 d rolling mean gap-filled Z_H offsets obtained from the reverse $Z_H - Z_{\text{DR}}$ method and from the self-consistency relations (Fig. 8). The averaging of the offsets obtained from satellite information over this stable time periods reduces the uncertainties of the GPM derived offsets to less than 1 dB (e.g. Louf and Protat, 2023; Protat et al., 2022). Seasonal Variations triggered by e.g. changing vegetation (Louf and Protat, 2023) challenge the RCA method

⁴The mean-bias is the mean value between the difference of Z_H^{self} and the offset corrected Z_H using the reverse $Z_H - Z_{\text{DR}}$ method.

⁵The mean-bias is the mean value between the difference of the Z_H offsets obtained from GPM and the Z_H offsets obtained from the reverse $Z_H - Z_{\text{DR}}$ method.




Figure 10. Daily Z_H offsets obtained from the reverse $Z_H - Z_{DR}$ method (blue dots), the GPM overflights (orange dots; Pejic et al., 2022) and the self-consistency relations ($\Delta_{\text{self}}[Z_H]$) in the period between January 2013–March 2023, respectively. Mean values of Z_H offsets in RCA stable time periods from Pejic et al. (2022) are given as blue, orange and green horizontal lines, respectively.

to identify stable time periods. Seasonal fluctuations are also recognizable in Pejic et al. (2022) (their Fig. 2) and may have impacted the accuracy of the averaged Z_H offset value obtained from GPM overpasses in RCA stable time periods. Especially the stronger deviations between the averaged 30 d rolling mean gap filled Z_H offsets obtained by using the reverse $Z_H - Z_{DR}$ method and the ones from the GPM overpasses in the last time period (19 May 2017–30 June 2019) are likely associated with these seasonal fluctuations. Nevertheless, both smaller RMSE and MAE strengthen confidence in using the reverse $Z_H - Z_{DR}$ method instead of the self-consistency relations (Table 3). In summary, since the self-consistency method bears several uncertainties, as well as a smaller sample size compared to the reverse $Z_H - Z_{DR}$ method (148 versus 544 valid days) and more confidence can be assigned to the comparison with satellite overflights, we conclude on the overall reliability of the reverse $Z_H - Z_{DR}$ method for Z_H calibration.

4 Summary, discussion and outlook

The birdbath method, broadly used for Z_{DR} calibration, provided only for a limited time period (April 2014–April 2017)

of the BoXPOL data set reliable results. Otherwise, inaccuracies of more than 0.2 dB have been detected. Instead, the approach by Sanchez-Rivas and Rico-Ramirez (2022) has been modified and applied successfully to ensure sufficient accuracy of Z_{DR} for the entire period (2013–2023).

This study aims to raise awareness of the need to critically use the birdbath method (or any other method based on one elevation scan only) and not apply the resulting offsets to the entire volume scan without further verification. Elevation dependent offsets have been identified already for other radars as well (e.g. Blanke et al., 2025). It may be necessary to calculate an individual Z_{DR} offset value for each of the elevations of interest, which can be time consuming and computationally expensive.

Since accurately calibrated Z_{DR} values are key for applications such as QPE, HMC, or Z_H calibration exploiting the reverse $Z_H - Z_{DR}$ method, further research is required to ensure reliable quantitative use of Z_{DR} in radar meteorology.

The reverse $Z_H - Z_{DR}$ method has been validated and compared with satellite-based measurements and self-consistency relations. Z_H offsets derived with the reverse $Z_H - Z_{DR}$ methodology agree well with the averaged Z_H offsets derived from GPM overpasses in stable RCA periods

Table 3. RMSE, MAE and MB for the 30 d rolling mean gap-filled Z_H offsets obtained using the reverse $Z_H - Z_{DR}$ method and the self-consistency relations in comparison with GPM overflights (both also for the mean values in RCA stable time periods), as presented in Fig. 10.

Reverse $Z_H - Z_{DR}$ method		
	Z_H offsets (gap filled)	Z_H offsets (gap filled) in RCA stable time periods
RMSE [dB]	1.88	0.70
MAE [dB]	1.51	0.60
MB [dB]	−0.36	−0.50
Self-consistency relations		
	Z_H offsets (gap filled)	Z_H offsets (gap filled) in RCA stable time periods
RMSE [dB]	2.28	1.62
MAE [dB]	1.91	1.37
MB [dB]	1.14	1.37

between 2014 and 2019 (Pejcic et al., 2022). Even a direct point-to-point comparison of daily Z_H offsets, which is critical due to the large difference in sample sizes, shows similar trends and acceptable RMSE and MAE values. To gain additional insights, expected Z_H values using self-consistency relations (Z_H^{self}) based on QVPs have been calculated as well. A stratiform filtering technique (see Trömel et al., 2023 and Appendix A) guarantees a sufficient degree of homogeneity for QVP generation. The comparison of Z_H^{self} and Z_H calibrated with the reverse $Z_H - Z_{DR}$ method are consistent with results shown in Louf et al. (2019), with acceptable values for the RMSE, MAE and MB. In addition, the general overestimation of Z_H^{self} values is in agreement with the more negative daily derived Z_H offset values using self-consistency relations compared to the ones using the reverse $Z_H - Z_{DR}$ method. The small number of outliers in Z_H^{self} can most likely be explained by uncertainties in K_{DP} derivations, DSD variability, temperature dependencies, assumptions on the canting angle distribution and the raindrop shape model used in the T-matrix simulations.

The comparison between Z_H^{self} and the offset corrected Z_H using the reverse $Z_H - Z_{DR}$ method gives confidence in the use of the 30 d rolling mean gap-filling procedure to adequately fill missing Z_H offset values.

In summary, we conclude on the overall reliability of the reverse $Z_H - Z_{DR}$ method for Z_H calibration assuming a sufficiently accurate prior calibration of Z_{DR} . It may serve as a powerful alternative to standard Z_H calibration techniques like self-consistency relationships, and/or can be used, if satellite-based information for most accurate calibration of Z_H is missing. We do not intend to suggest that the self-consistency method is generally inferior. Rather, we wish to emphasize that BoXPols Z_H is calibrated with the method introduced with sufficient accuracy and, compared with an

already established method, with even greater precision. Regarding satellite-based calibration, seasonal variations and their impact on RCA stable time periods (Pejcic et al., 2022) could be addressed in the future by applying a dynamic clutter map (Louf and Protat, 2023) to reduce potential uncertainties in the GPM derived Z_H offset values.

Even though diurnal variations have been partially observed in the Z_{DR} offsets, this study aimed at daily Z_{DR} and Z_H offsets, deleting days with higher variability in the offset values (Z_{DR} offset standard deviation > 0.2 dB; Z_H offset standard deviation > 4 dB). However, calculations of temporally higher resolved offsets could potentially lead to more accurate estimates of offsets and especially reduce potential errors associated with the gap-filling method based on a 30 d rolling mean. To enable also the inclusion of e.g. sequences not fulfilling the filtering criteria for light rain, or even more intense convective events in the offset calculations, other Z_H -calibration methods, e.g. the one proposed by Diederich et al. (2015) using A_H , or methods in the integrated Satellite and Clutter Absolute Radar calibration (SCAR; Louf et al., 2019; Louf and Protat, 2023) scheme like solar calibration could be combined with the introduced reverse $Z_H - Z_{DR}$ method. Further validation of the reverse $Z_H - Z_{DR}$ method in different climate regimes, at different radar wavelengths, and with an increased number of GPM overflights, should be carried out in the future.

Appendix A: Shannon information entropy and Melting Layer (ML) detection to identify homogeneous (stratiform) events

The QVP methodology requires nearly homogeneous weather conditions, such that the inherent averaging process results in a significant reduction of the statistical errors (Ryzhkov et al., 2016), quantified e.g. with the standard error of the mean (Von Storch and Zwiers, 2002). Additional variants of the QVP methodology, e.g. range-defined QVPs (RD-QVPs; Tobin and Kumjian, 2017) using all available elevation scans within an inverse distance weighting procedure, or columnar vertical profiles (CVPs; Murphy et al., 2020) also using multiple elevation scans but in limited range and azimuth sectors, have been developed for different applications. However, the required degree of homogeneity or acceptable inhomogeneities, caused e.g. by embedded convection or nonuniform beam filling (NBF; e.g. Ryzhkov, 2007; Ryzhkov and Zrnica, 2019, especially for higher antenna beamwidths), has not yet been explored for these methodologies to the authors’ knowledge. Instead, rather subjective “by eye” impressions are mostly used.

In order to distinguish between homogeneous (stratiform) and convective events or exclude embedded convection from widespread stratiform rain, an automated and robust method is introduced. It combines ML detection with the Shannon information entropy ($\eta(X)$; Shannon, 1948; Trömel et al.,

2023). The latter measures the average degree of uncertainty of the realisations of a random variable. For the sake of simplicity, a normalised version is used. Given a discrete random variable (X) with possible realisations $x_1, \dots, x_m$ and probabilities $P(x_1), \dots, P(x_m)$, the normalised Shannon information entropy ($\eta(X)_{\text{norm}}$) of X is defined as

$$\begin{aligned}\eta(X)_{\text{norm}} &= \frac{\eta(X)}{\eta(X)_{\text{max}}} \\ &= -\frac{1}{\log_{10}(m)} \sum_{k=1}^m P(x_k) \log_{10}(P(x_k)) \\ &= \frac{1}{\log_{10}(m)} \sum_{k=1}^n P(x_k) I(x_k) .\end{aligned}\quad (\text{A1})$$

In Eq. (A1) the maximum possible Shannon information entropy ($\eta(X)_{\text{max}}$) follows a uniform distribution with sample size m and $P(x_k) = 1/m$ with $k = 1, \dots, m$. $I(x_k)$ denotes the so-called self information (e.g. Borda, 2011) of individual realisations x_k of X and quantifies the level of “surprise” of a specific event. The higher (smaller) the probability of an event, the less (more) “surprising” it is and therefore $I(x_k)$ is smaller (larger). The probabilities are non-negative ($P(x_k) \geq 0$) and additive ($\sum_{k=1}^m P(x_k) = 1$; e.g. Han and Kobayashi, 2002). Thus, $\eta(X)$ represents the expected value of the information content of X ($\eta(X) = E[I(X)]$; e.g. Borda, 2011).

In order to apply Eq. (A1) to PPI scans, the $P(x_k)$ are calculated at each distance (range) over all azimuths, i.e. for a 1° beam width $P(x_k) = x_k / \sum_{k=1}^{360} x_k$. In this study, the values x_k refer to either Z_H in linear scale ($Z_h = 10^{0.1 Z_H}$), Z_{DR} in linear scale ($Z_{dr} = 10^{0.1 Z_{DR}}$) (unitless), K_{DP} or ρ_{HV} at a certain range at azimuth k . Since Eq. (A1) is only defined for positive values, also K_{DP} is limited to values $> 0^\circ \text{ km}^{-1}$.

Values of $\eta(X)_{\text{norm}}$ close to 1 represent homogeneous conditions while values close to 0 represent inhomogeneous conditions. In this study a threshold of 0.85 is used to identify sufficiently homogeneous stratiform PPIs. The impact of embedded, more convective sectors on $\eta(X)_{\text{norm}}$ within an overall stratiform event is illustrated in Fig. A1.

As expected, $\eta(X)_{\text{norm}}$ decreases with increasing μ of $\mathcal{N}(\mu, \sigma)$ describing the embedded convection, but also the amount of inserted convective bins has a strong influence. First, $\eta(X)_{\text{norm}}$ decreases with increasing number of convective bins (see violet versus blue distribution and grey versus red distribution in Fig. A1), however, if the sample size of convective pixels exceeds a certain fraction of the overall PPI, $\eta(X)_{\text{norm}}$ increases again (see yellow distribution) but the PPI is still characterized as inhomogeneous ($\eta(X)_{\text{norm}} < 0.85$). For even higher μ ($10\,000 \text{ mm}^6 \text{ m}^{-3}$; green distribution) $\eta(X)_{\text{norm}}$ is decreasing again. Note that the width of the $\eta(X)_{\text{norm}}$ distributions narrows with increasing μ of the convective $\mathcal{N}(\mu, \sigma)$ distribution and also with the number of inserted convective bins. This can be attributed to the constant and quite small $\sigma = 500 \text{ mm}^6 \text{ m}^{-3}$.

The overall recommended strategy combining ML detection and the Shannon information entropy to identify homogeneous stratiform events is as follows:

1. The ML detection of Wolfensberger et al. (2016) adapted to the QVP methodology (Ryzhkov et al., 2016; Trömel et al., 2014) is applied including the estimation of an average K_{DP} within the ML following Trömel et al. (2019) and removal of contributions of backscatter differential phase (δ). No (differential) attenuation correction is applied to the PPIs measured at 18° elevation. Only PPIs with a detected ML are considered as stratiform and enter as candidates for potentially homogeneous PPIs the ensuing analysis steps.
2. Time steps with a detected ML bottom at higher altitudes than ML top are neglected as well as cases with unrealistic heights for the ML top ($> 10 \text{ km}$).
3. ML top and bottom identified in 2. are treated as first guess estimates and modified to nearby profile locations, where ρ_{HV} returns to values above 0.97 (Giangrande et al., 2008) for better comparability with previous ML statistics as e.g. Trömel et al. (2019).
4. $\eta(X)_{\text{norm}}$ is calculated at each range/height over the azimuth dimension as a function of Z_h , Z_{dr} , ρ_{HV} and K_{DP} (without δ contaminations), respectively.
5. If all $\eta(X)_{\text{norm}}$ values obtained for the polarimetric variables mentioned in 4. are greater than or equal 0.85, the respective range gates are classified as stratiform and included in the overall stratiform data set. The methodology introduced filters both strong convective inclusions and sequences with a low number of valid measurements, e.g. near the cloud top. Assuming always a full 360° circle in Eq. (A1) to determine $\eta(X)_{\text{max}}$, regions with only few valid measurements are automatically filtered out via the enhanced $\eta(X)_{\text{max}}$ in the denominator of Eq. (A1). Note that $\min(\eta(X)_{\text{norm}})$ is mainly dominated by changes in Z_h , but any anomalous values in K_{DP} , Z_{dr} or ρ_{HV} can be treated appropriately to obtain the best possible homogeneous (stratiform) data sequences.
6. Finally, using the temperature information from ERA5, heights of the ML top are only allowed at temperatures between -6 and 4°C , while height levels of the ML bottom are restricted to temperatures between -2 and 8°C .

Figure A2 illustrates the resulting reduction of $\min(\eta(X)_{\text{norm}})$ below the 0.85 threshold due to embedded convection in a measured PPI. Inhomogeneities near the cloud top are filtered out as well. In summary, tests and simulations showed that the $\min(\eta(X)_{\text{norm}})$ threshold of 0.85 used in this study still allows some weaker embedded




Figure A1. Z_h values of a fictitious PPI scan with 360 azimuths times 550 range bins in stratiform rain are described as a realization of a Gaussian distribution with a mean value of $100 \text{ mm}^6 \text{ m}^{-3}$ and a standard deviation of $10 \text{ mm}^6 \text{ m}^{-3}$ ($\mathcal{N}(\mu = 100 \text{ mm}^6 \text{ m}^{-3} \text{ (20 dBZ)}, \sigma = 10 \text{ mm}^6 \text{ m}^{-3} \text{ (10 dBZ)})$). Embedded convection is introduced by replacing for a certain number of azimuths (e.g., 20, 40, and 100 out of 360) at each distance stratiform Z_h values by the ones generated as a realization of a Gaussian distribution with increased μ values (e.g., $3100 \text{ mm}^6 \text{ m}^{-3}$) and constant values of σ of $500 \text{ mm}^6 \text{ m}^{-3}$. For illustration $\eta(X)_{\text{norm}}$ is calculated based on these simulated Z_h values only and for different scenarios of embedded convection using Eq. (A1). Resulting distributions of $\eta(X)_{\text{norm}}$ are shown in violet, blue, grey, red, yellow, and green if embedded convection is introduced with sample size 10×550 following $\mathcal{N}(\mu = 1500 \text{ mm}^6 \text{ m}^{-3} \text{ (32 dBZ)}, \sigma = 500 \text{ mm}^6 \text{ m}^{-3} \text{ (27 dBZ)})$, with sample size 20×550 following $\mathcal{N}(\mu = 1500 \text{ mm}^6 \text{ m}^{-3} \text{ (32 dBZ)}, \sigma = 500 \text{ mm}^6 \text{ m}^{-3} \text{ (27 dBZ)})$, with sample size 20×550 following $\mathcal{N}(\mu = 3100 \text{ mm}^6 \text{ m}^{-3} \text{ (35 dBZ)}, \sigma = 500 \text{ mm}^6 \text{ m}^{-3} \text{ (27 dBZ)})$, with sample size 40×550 following $\mathcal{N}(\mu = 3100 \text{ mm}^6 \text{ m}^{-3} \text{ (35 dBZ)}, \sigma = 500 \text{ mm}^6 \text{ m}^{-3} \text{ (27 dBZ)})$, with sample size 100×550 following $\mathcal{N}(\mu = 3100 \text{ mm}^6 \text{ m}^{-3} \text{ (35 dBZ)}, \sigma = 500 \text{ mm}^6 \text{ m}^{-3} \text{ (27 dBZ)})$, and with sample size 100×550 following $\mathcal{N}(\mu = 10000 \text{ mm}^6 \text{ m}^{-3} \text{ (40 dBZ)}, \sigma = 500 \text{ mm}^6 \text{ m}^{-3} \text{ (27 dBZ)})$, respectively. The black line shows the used threshold in this study series of 0.85 for $\eta(X)_{\text{norm}}$.




Figure A2. PPI of Z_H in an azimuth-height display (a) monitored with the polarimetric X-band radar in Bonn, BoXPol, on 30 May 2016 at 03:11 UTC. ML top and bottom heights are indicated as black lines and excluded inhomogenous sequences are displayed as transparent regions. The according profile of the minimum normalised Shannon information entropy ($\min(\eta(X)_{\text{norm}})$) (b) is shown together the applied threshold for filtering (0.85) as red line.

convective bins within an overall stratiform event (see e.g. the violet and blue distributions in Fig. A1). Depending on requirements, a higher threshold value (e.g. 0.9) for more aggressive filtering, or a weaker threshold value (e.g. 0.8 as in Trömel et al., 2023) for more restrained filtering could be used.

The entropy method can also be applied to different sectors of a PPI or a moving $\min(\eta(X)_{\text{norm}})$ with suitable window sizes over the azimuth dimension could be used to identify homogeneous sectors within a PPI, which may in total not show a sufficient degree of homogeneity. Within the RDQVP framework, the method suggested may also identify the most inhomogeneous elevation scans to adjust the threshold value used for the ranges in the inverse distance weighting procedure (for more information see Tobin and Kumjian, 2017).

Furthermore, the so-called permutation entropy (PE; Henry and Judge, 2019; Bandt and Pompe, 2002) could be implemented in future studies. As described above, $\eta(X)$ is positive semidefinite and negative K_{DP} values can't be taken directly into account. Additionally, the typically smaller range of values of Z_{dr} , ρ_{HV} and K_{DP} compared to Z_{h} reduces the impact of the aforementioned variables on $\min(\eta(X)_{\text{norm}})$. However, PE is based on relative frequencies of permutations of partitioned one-dimensional data (on time-series data as shown in Bandt and Pompe, 2002, or applied on radar data, e.g. Z_{h} values over the azimuth dimension). Thus, by calculating the minimum of the normalized version of PE (PE_{norm} ; Henry and Judge, 2019), it is guaranteed that polarimetric variables covering a smaller range of values (see step 5 above, e.g., for ρ_{HV}) may influence the homogeneity estimate to the same extent as those covering a larger range of values.

Appendix B: Validation of the melting layer detection algorithm using ERA5

ML top heights are mostly located below the 0°C isotherm (e.g. Song et al., 2021; Romatschke, 2021). One possible reason are values of relative humidity with respect to water (RH water) below 100 % favoring sublimation instead of melting (e.g. Heymsfield et al., 2021; Carlin and Ryzhkov, 2019). Thus, the ML top height rather indicates the height of the 0°C wet-bulb temperature (see e.g. <https://glossary.ametsoc.org/wiki/wet-bulb-temperature/>, last access: 26 March 2026). Besides sublimative cooling, faster falling rimed particles with higher density and/or larger aggregates result in a sagging of the ML and typical polarimetric ML (bright band) signatures at lower height levels (e.g. Carlin, 2018; Kumjian et al., 2016; Xie et al., 2016).

In order to evaluate the ML detection algorithm, detected ML top heights are compared with both the heights closest to the 0°C wet-bulb temperature isotherm and environmental temperature isotherm obtained from ERA5 by linearly interpolating from the nearest grid point to the location of BoX-




Figure B1. 2D histogram of the 0°C wet-bulb temperature height levels from ERA5 versus detected ML top heights. In addition, the Pearson correlation coefficient, RMSE, MB and MAE are given for the comparison of the ML top heights with both, the heights of the 0°C wet-bulb temperature isotherm (red) and the 0°C environmental temperature isotherm (black).

Pol, as a 2D distribution (see Fig. B1). To ensure a thorough validation, no predefined temperature thresholds are applied (like in step 6 in Appendix A).

The comparison between both height levels indicates a very good agreement. Also, in terms of statistical quantities, the RMSE with 270.40 m, the MAE with 78.14 m, the MB⁶ with 171.14 m, and especially the Pearson correlation coefficient of 0.95 demonstrate the reliability of the algorithm. Also, for the environmental 0°C temperature isotherm, the statistical quantities show only slightly higher values and in line with e.g. Song et al. (2021), their Fig. 6. Uncertainties may arise due to the interpolation process from the temporally coarser grid of ERA5 (1 h) and intrinsic uncertainties.

Code and data availability. The BoXPol radar data for the 18° elevation scan covering the period from 2013 to 2023 can be downloaded from <https://doi.org/10.60507/FK2/D0NVG5> (Trömel et al., 2026). The codes used to apply the described methodologies for processing the Z_{H} and Z_{DR} offsets, as well as the offsets themselves, are available at <https://doi.org/10.5281/zenodo.20796890> (Scharbach, 2026b). The T-matrix simulations are performed using the Python module *pytmatrix* (Leinonen, 2014; see also <https://github.com/jleinonen/pytmatrix>, last access: 22 September 2026), which is based on the Fortran code provided by Mishchenko (2000). The script used for these calculations is available at <https://doi.org/10.5281/ZENODO.20829591> (Carlin et al., 2026). For the handling, processing and georeferencing of the radar data, the Python module *oradlib* <https://doi.org/10.5194/hess-17-863->

⁶The MB is the mean value between the difference of the heights nearest to the 0°C wet-bulb temperature isotherm calculated from ERA5 temperatures and the detected ML top heights.

2013 (Heistermann et al., 2013) is used (see also <https://docs.wradlib.org/en/stable/index.html>, last access: 26 March 2026). The ERA5 data are provided through the Climate Data Store of the European Center for Medium-Range Weather Forecasts (ECMWF) and can be downloaded from <https://doi.org/10.24381/cds.bd0915c6> (Hersbach et al., 2023). ERA5 variables interpolated to the BoX-Pol grid and used for the offset-value processing can be downloaded from <https://doi.org/10.5281/zenodo.20799703> (Scharbach, 2026a).

Author contributions. The study was designed by TS and supervised by ST. The conceptualization, data processing, analysis, visualization and writing of this study was carried out by TS. VP provided the processed satellite data and served as a significant expert for the radar calibration methodology, particularly with regard to the validation using GPM. ST was involved in funding acquisition, managing the study and providing extensive support. All three authors also reviewed and proofread this study.

Competing interests. The contact author has declared that none of the authors has any competing interests.

Disclaimer. Publisher's note: Copernicus Publications remains neutral with regard to jurisdictional claims made in the text, published maps, institutional affiliations, or any other geographical representation in this paper. The authors bear the ultimate responsibility for providing appropriate place names. Views expressed in the text are those of the authors and do not necessarily reflect the views of the publisher.

Special issue statement. This article is part of the special issue “Fusion of radar polarimetry and numerical atmospheric modelling towards an improved understanding of cloud and precipitation processes (ACP/AMT/GMD inter-journal SI)”. It is not associated with a conference.

Acknowledgements. The Bonn X-band radar (BoXPol) was funded by the German Research Foundation (Deutsche Forschungsgemeinschaft, DFG) within TR32 “Patterns in Soil-Vegetation-Atmosphere Systems”. Tobias Scharbach's research was carried out as part of the DFG-funded priority program SPP-2115 “Polarimetric Radar Observations meet Atmospheric Modelling (PROM, <https://www2.meteo.uni-bonn.de/spp2115>, last access: 14 September 2026)” in the project “Climate model PARAMeterizations informed by RADar (PARA)”. Velibor Pejčic's research was carried out partially in the framework of PROM within the project “An efficient volume scan polarimetric radar forward OPERATOR to improve the representation of HYDROMETEORS in the COSMO model (Operation Hydrometeors)”, as well as in the DFG-funded research project “Near-Realtime Precipitation Estimation and Prediction (RealPEP, <https://www2.meteo.uni-bonn.de/realpep>, last access: 14 September 2026)”. We would like to thank Ju-Yu Chen for her contribution to the idea of calibrating Z_H with the reverse $Z_H - Z_{DR}$ method, as well as Sebastian Buschow for his contribution to the idea of using the Shannon information entropy on PPI scans. We also thank

Martin Lennefer and Kai Mühlbauer for providing the logbook of BoXPol and careful maintenance of BoXPol over many years. We are also grateful to Kai Mühlbauer with respect to the open-source radar library *wradlib* (<https://docs.wradlib.org/en/stable/index.html>, last access: 26 March 2026) for processing and visualization of radar data.

Financial support. This research has been funded by DFG in the framework of PROM (grant nos. 408026929 and 408027387) and RealPEP (grant no. 320397309).

Review statement. This paper was edited by Leonie von Terzi and reviewed by two anonymous referees.

References

- Anagnostou, E. N., Morales, C. A., and Dinku, T.: The Use of TRMM Precipitation Radar Observations in Determining Ground Radar Calibration Biases, *J. Atmos. Ocean. Tech.*, 18, 616–628, [https://doi.org/10.1175/1520-0426\(2001\)018<0616:tuotpr>2.0.co;2](https://doi.org/10.1175/1520-0426(2001)018<0616:tuotpr>2.0.co;2), 2001.
- Atlas, D.: Radar calibration: Some simple approaches, *B. Am. Meteorol. Soc.*, 83, 1313–1316, <https://doi.org/10.1175/1520-0477-83.9.1313>, 2002.
- Atlas, D. and Mossop, S.: Calibration of a weather radar by using a standard target, *B. Am. Meteorol. Soc.*, 41, 377–382, <https://doi.org/10.1175/1520-0477-41.7.377>, 1960.
- Bandt, C. and Pompe, B.: Permutation entropy: a natural complexity measure for time series, *Phys. Rev. Lett.*, 88, 174102, <https://doi.org/10.1103/PhysRevLett.88.174102>, 2002.
- Blahak, U.: RADAR_MIE_LM and RADAR_MIELIB – Calculation of Radar Reflectivity from Model Output, Technical Report 28, Consortium for Small Scale Modeling (COSMO), https://doi.org/10.5676/DWD_pub/nwv/cosmo-tr_28, 2016.
- Blahak, U. and de Lozar, A.: EMVORADO – Efficient Modular VOlume scan RADAR Operator. A User's Guide, Deutscher Wetterdienst, https://www.cosmo-model.org/content/model/documentation/core/emvorado_userguide.pdf (last access: 14 September 2026), 2021.
- Blanke, A., Gergely, M., and Trömel, S.: A new aggregation and riming discrimination algorithm based on polarimetric weather radars, *Atmos. Chem. Phys.*, 25, 4167–4184, <https://doi.org/10.5194/acp-25-4167-2025>, 2025.
- Borda, M.: Fundamentals in information theory and coding, Springer Science and Business Media, <https://doi.org/10.1007/978-3-642-20347-3>, 2011.
- Brandes, E. A., Zhang, G., and Vivekanandan, J.: Experiments in rainfall estimation with a polarimetric radar in a subtropical environment, *J. Appl. Meteorol. Clim.*, 41, 674–685, [https://doi.org/10.1175/1520-0450\(2002\)041<0674:EIREWA>2.0.CO;2](https://doi.org/10.1175/1520-0450(2002)041<0674:EIREWA>2.0.CO;2), 2002.
- Carlin, J.: The use of polarimetric radar data for informing numerical weather prediction models, PhD thesis, University of Oklahoma, <https://hdl.handle.net/11244/299801>, 2018.

- Carlin, J., Scharbach, T., and Chen, J.-Y.: T-matrix calculations for rain, Zenodo [code], <https://doi.org/10.5281/ZENODO.20829591>, 2026.
- Carlin, J. T. and Ryzhkov, A. V.: Estimation of melting-layer cooling rate from dual-polarization radar: Spectral bin model simulations, *J. Appl. Meteorol. Clim.*, 58, 1485–1508, <https://doi.org/10.1175/JAMC-D-18-0343.1>, 2019.
- Chen, J.-Y., Trömel, S., Ryzhkov, A., and Simmer, C.: Assessing the benefits of specific attenuation for quantitative precipitation estimation with a C-band radar network, *J. Hydrometeorol.*, 22, 2617–2631, <https://doi.org/10.1175/JHM-D-20-0299.1>, 2021.
- Chu, Z., Liu, W., Zhang, G., Kou, L., and Li, N.: Continuous monitoring of differential reflectivity bias for C-band polarimetric radar using online solar echoes in volume scans, *Remote Sens.-Basel*, 11, 2714, <https://doi.org/10.3390/rs11222714>, 2019.
- Crisologo, I.: Using spaceborne radar platforms to enhance the homogeneity of weather radar calibration, PhD thesis, Universität Potsdam, <https://publishup.uni-potsdam.de/frontdoor/index/index/docId/44570>, 2019.
- Crisologo, I., Warren, R. A., Mühlbauer, K., and Heistermann, M.: Enhancing the consistency of spaceborne and ground-based radar comparisons by using beam blockage fraction as a quality filter, *Atmos. Meas. Tech.*, 11, 5223–5236, <https://doi.org/10.5194/amt-11-5223-2018>, 2018.
- Diederich, M., Ryzhkov, A., Simmer, C., Zhang, P., and Trömel, S.: Use of specific attenuation for rainfall measurement at X-band radar wavelengths. Part I: Radar calibration and partial beam blockage estimation, *J. Hydrometeorol.*, 16, 487–502, <https://doi.org/10.1175/JHM-D-14-0066.1>, 2015.
- Diekema, E. and Koornwinder, T. H.: Differentiation by integration using orthogonal polynomials, a survey, *J. Approx. Theory*, 164, 637–667, <https://doi.org/10.1016/j.jat.2012.01.003>, 2012.
- Doms, G. and Baldauf, M.: A Description of the Nonhydrostatic Regional COSMO-Model LM. Part I: Dynamics and Numerics, Consortium for Smallscale Modeling (COSMO), https://doi.org/10.5676/DWD_pub/nwv/cosmo-doc_5.05_I, 2018.
- Doms, G., Förstner, J., Heise, E., Herzog, H.-J., Mironov, D., Raschendorfer, M., Reinhardt, T., Ritter, B., Schrodin, R., Schulz, J.-P., and Vogel, G.: A Description of the Nonhydrostatic Regional COSMO-Model. Part II: Physical Parameterization, Consortium for Smallscale Modeling (COSMO), https://doi.org/10.5676/DWD_pub/nwv/cosmo-doc_5.05_II, 2018.
- Doviak, R. J. and Zrnić, D. S.: Doppler Radar and Weather Observations, 2nd edn., Academic Press, San Diego, <https://doi.org/10.1016/C2009-0-22358-0>, 1993.
- Fan, J., Han, B., Varble, A., Morrison, H., North, K., Kollias, P., Chen, B., Dong, X., Giangrande, S. E., Khain, A., Lin, Y., Mansell, E., Milbrandt, J. A., Stenz, R., Thompson, G., and Wang, Y.: Cloud-resolving model intercomparison of an MC3E squall line case: Part I – Convective updrafts, *Journal of Geophysical Research: Atmospheres*, 122, 9351–9378, <https://doi.org/10.1002/2017JD026622>, 2017.
- Figueras i Ventura, J., Boumahmoud, A., Fradon, B., Dupuy, P., and Tabary, P.: Long-term monitoring of French polarimetric radar data quality and evaluation of several polarimetric quantitative precipitation estimators in ideal conditions for operational implementation at C-band, *Q. J. Roy. Meteor. Soc.*, 138, 2212–2228, <https://doi.org/10.1002/qj.1934>, 2012.
- Frech, M.: 9 B. 3 Monitoring the data quality of the new polarimetric weather radar network of the German Meteorological Service, <https://ams.confex.com/ams/36Radar/webprogram/Paper228472.html> (last access: 14 September 2026), 2013.
- Frech, M. and Hubbert, J.: Monitoring the differential reflectivity and receiver calibration of the German polarimetric weather radar network, *Atmos. Meas. Tech.*, 13, 1051–1069, <https://doi.org/10.5194/amt-13-1051-2020>, 2020.
- Frech, M., Hagen, M., and Mammen, T.: Monitoring the absolute calibration of a polarimetric weather radar, *J. Atmos. Ocean. Tech.*, 34, 599–615, <https://doi.org/10.1175/JTECH-D-16-0076.1>, 2017.
- Fridlind, A. M., Li, X., Wu, D., van Lier-Walqui, M., Ackerman, A. S., Tao, W.-K., McFarquhar, G. M., Wu, W., Dong, X., Wang, J., Ryzhkov, A., Zhang, P., Poellot, M. R., Neumann, A., and Tomlinson, J. M.: Derivation of aerosol profiles for MC3E convection studies and use in simulations of the 20 May squall line case, *Atmos. Chem. Phys.*, 17, 5947–5972, <https://doi.org/10.5194/acp-17-5947-2017>, 2017.
- Gabella, M.: On the use of bright scatterers for monitoring Doppler, dual-polarization weather radars, *Remote Sens.-Basel*, 10, 1007, <https://doi.org/10.3390/rs10071007>, 2018.
- Giangrande, S. E., Krause, J. M., and Ryzhkov, A. V.: Automatic designation of the melting layer with a polarimetric prototype of the WSR-88D radar, *J. Appl. Meteorol. Clim.*, 47, 1354–1364, <https://doi.org/10.1175/2007JAMC1634.1>, 2008.
- Gorgucci, E., Scarchilli, G., and Chandrasekar, V.: Calibration of radars using polarimetric techniques, *IEEE T. Geosci. Remote*, 30, 853–858, <https://doi.org/10.1109/36.175319>, 1992.
- Gorgucci, E., Scarchilli, G., and Chandrasekar, V.: A procedure to calibrate multiparameter weather radar using properties of the rain medium, *IEEE T. Geosci. Remote*, 37, 269–276, <https://doi.org/10.1109/36.739161>, 1999.
- Gorgucci, E., Baldini, L., and Chandrasekar, V.: What is the shape of a raindrop? An answer from radar measurements, *J. Atmos. Sci.*, 63, 3033–3044, <https://doi.org/10.1175/JAS3781.1>, 2006.
- Gourley, J. J., Illingworth, A. J., and Tabary, P.: Absolute calibration of radar reflectivity using redundancy of the polarization observations and implied constraints on drop shapes, *J. Atmos. Ocean. Tech.*, 26, 689–703, <https://doi.org/10.1175/2008JTECHA1152.1>, 2009.
- Griffin, E. M., Schuur, T. J., and Ryzhkov, A. V.: A polarimetric analysis of ice microphysical processes in snow, using quasi-vertical profiles, *J. Appl. Meteorol. Clim.*, 57, 31–50, <https://doi.org/10.1175/JAMC-D-17-0033.1>, 2018.
- Han, T. S. and Kobayashi, K.: Mathematics of Information and Coding, vol. 203, American Mathematical Society, <https://doi.org/10.1090/mmono/203>, 2002.
- Heistermann, M., Jacobi, S., and Pfaff, T.: Technical Note: An open source library for processing weather radar data (*wradlib*), *Hydrol. Earth Syst. Sci.*, 17, 863–871, <https://doi.org/10.5194/hess-17-863-2013>, 2013.
- Henry, M. and Judge, G.: Permutation entropy and information recovery in nonlinear dynamic economic time series, *Econometrics*, 7, 10, <https://doi.org/10.3390/econometrics7010010>, 2019.
- Hersbach, H., Bell, B., Berrisford, P., Hirahara, S., Horányi, A., Muñoz-Sabater, J., Nicolas, J., Peubey, C., Radu, R., Schep-

- ers, D., Simmons, A., Soci, C., Abdalla, S., Abellan, X., Balsamo, G., Bechtold, P., Biavati, G., Bidlot, J., Bonavita, M., De Chiara, G., Dahlgren, P., Dee, D., Diamantakis, M., Dragani, R., Flemming, J., Forbes, R., Fuentes, M., Geer, A., Haimberger, L., Healy, S., Hogan, R. J., Hólm, E., Janisková, M., Keeley, S., Laloyaux, P., Lopez, P., Lupu, C., Radnoti, G., de Rosnay, P., Rozum, I., Vamborg, F., Villaume, S., and Thépaut, J.-N.: The ERA5 global reanalysis, *Q. J. Roy. Meteor. Soc.*, 146, 1999–2049, <https://doi.org/10.1002/qj.3803>, 2020.
- Hersbach, H., Bell, B., Berrisford, P., Biavati, G., Horányi, A., Muñoz Sabater, J., Nicolas, J., Peubey, C., Radu, R., Rozum, I., Schepers, D., Simmons, A., Soci, C., Dee, D., and Thépaut, J.-N.: ERA5 hourly data on pressure levels from 1940 to present, Copernicus Climate Change Service (C3S) Climate Data Store (CDS) [data set], <https://doi.org/10.24381/cds.bd0915c6>, 2023.
- Heymsfield, A. J., Bansemer, A., Theis, A., and Schmitt, C.: Survival of snow in the melting layer: Relative humidity influence, *J. Atmos. Sci.*, 78, 1823–1845, <https://doi.org/10.1175/JAS-D-20-0353.1>, 2021.
- Holleman, I., Huuskonen, A., Gill, R., and Tabary, P.: Operational monitoring of radar differential reflectivity using the sun, *J. Atmos. Ocean. Tech.*, 27, 881–887, <https://doi.org/10.1175/2010JTECHA1381.1>, 2010.
- Holoborodko, P.: Low-noise Lanczos differentiators, Online resource, <https://www.holoborodko.com/pavel/numerical-methods/numerical-derivative/lanczos-low-noise-differentiators/> (last access: 14 September 2026), 2015.
- Hou, A. Y., Kakar, R. K., Neeck, S., Azarbarzin, A. A., Kummerow, C. D., Kojima, M., Oki, R., Nakamura, K., and Iguchi, T.: The global precipitation measurement mission, *B. Am. Meteorol. Soc.*, 95, 701–722, <https://doi.org/10.1175/BAMS-D-13-00164.1>, 2014.
- Houze Jr., R. A., Brodzik, S., Schumacher, C., Yuter, S. E., and Williams, C. R.: Uncertainties in oceanic radar rain maps at Kwajalein and implications for satellite validation, *J. Appl. Meteorol. Clim.*, 43, 1114–1132, [https://doi.org/10.1175/1520-0450\(2004\)043<1114:UIORRM>2.0.CO;2](https://doi.org/10.1175/1520-0450(2004)043<1114:UIORRM>2.0.CO;2), 2004.
- Hu, J., Ryzhkov, A., and Dunnavan, E. L.: Vertical profile climatology of polarimetric radar variables and retrieved microphysical parameters in synoptic and lake effect snowstorms, *J. Geophys. Res.-Atmos.*, 129, e2024JD041318, <https://doi.org/10.1029/2024JD041318>, 2024.
- Hu, J., Zhang, P., Krause, J., and Ryzhkov, A.: Calibrating Differential Reflectivity with QZdrCal: An Open System Radar Product Generator (ORPG) update with an upgraded dry aggregated snow method, *J. Atmos. Ocean. Tech.*, <https://doi.org/10.1175/jtech-d-25-0123.1>, 2026.
- Hunzinger, A., Hardin, J. C., Bharadwaj, N., Varble, A., and Matthews, A.: An extended radar relative calibration adjustment (eRCA) technique for higher-frequency radars and range-height indicator (RHI) scans, *Atmos. Meas. Tech.*, 13, 3147–3166, <https://doi.org/10.5194/amt-13-3147-2020>, 2020.
- Joshil, S. S. and Chandrasekar, C. V.: Calibration of D3R Weather Radar Using UAV-Hosted Target, *Remote Sens.-Basel*, 14, 3534, <https://doi.org/10.3390/rs14153534>, 2022.
- Joss, J., Gabella, M., Michaelides, S. C., and Perona, G.: Variation of weather radar sensitivity at ground level and from space: case studies and possible causes, *Meteorol. Z.*, 15, 485–496, <https://doi.org/10.1127/0941-2948/2006/0150>, 2006.
- Kennedy, P. C. and Rutledge, S. A.: S-band dual-polarization radar observations of winter storms, *J. Appl. Meteorol. Clim.*, 50, 844–858, <https://doi.org/10.1175/2010JAMC2558.1>, 2011.
- Kozu, T., Kawanishi, T., Kuroiwa, H., Kojima, M., Oikawa, K., Kumagai, H., Okamoto, K., Okumura, M., Nakatsuka, H., and Nishikawa, K.: Development of precipitation radar onboard the Tropical Rainfall Measuring Mission (TRMM) satellite, *IEEE T. Geosci. Remote*, 39, 102–116, <https://doi.org/10.1109/36.898669>, 2001.
- Kumjian, M. R.: Principles and Applications of Dual-Polarization Weather Radar. Part I: Description of the Polarimetric Radar Variables, *Journal of Operational Meteorology*, 1, <https://doi.org/10.15191/nwajom.2013.0119>, 2013a.
- Kumjian, M. R.: Principles and Applications of Dual-Polarization Weather Radar. Part III: Artifacts., *Journal of Operational Meteorology*, 1, <https://doi.org/10.15191/nwajom.2013.0121>, 2013b.
- Kumjian, M. R. and Ryzhkov, A. V.: The impact of evaporation on polarimetric characteristics of rain: Theoretical model and practical implications, *J. Appl. Meteorol. Clim.*, 49, 1247–1267, <https://doi.org/10.1175/2010JAMC2243.1>, 2010.
- Kumjian, M. R. and Ryzhkov, A. V.: The Impact of Size Sorting on the Polarimetric Radar Variables, *J. Atmos. Sci.*, 69, 2042–2060, <https://doi.org/10.1175/JAS-D-11-0125.1>, 2012.
- Kumjian, M. R., Mishra, S., Giangrande, S. E., Toto, T., Ryzhkov, A. V., and Bansemer, A.: Polarimetric radar and aircraft observations of saggy bright bands during MC3E, *J. Geophys. Res.-Atmos.*, 121, 3584–3607, <https://doi.org/10.1002/2015JD024446>, 2016.
- Le Loh, J., Chang, W.-Y., Hsu, H.-W., Lin, P.-F., Chang, P.-L., Teng, Y.-L., and Liou, Y.-C.: Long-term assessment of the reflectivity biases and wet-radome effect using collocated operational s-and c-band dual-polarization radars, *IEEE T. Geosci. Remote*, 60, 1–17, <https://doi.org/10.1109/TGRS.2022.3170609>, 2022.
- Lee, J.-E., Kwon, S., and Jung, S.-H.: Real-Time Calibration and Monitoring of Radar Reflectivity on Nationwide Dual-Polarization Weather Radar Network, *Remote Sens.-Basel*, 13, 2936, <https://doi.org/10.3390/rs13152936>, 2021.
- Leinonen, J.: Python code for T-matrix scattering calculations, GitHub [code], <https://github.com/jleinonen/pytmatrix> (last access: 6 May 2026), 2013.
- Leinonen, J.: High-level interface to T-matrix scattering calculations: architecture, capabilities and limitations, *Opt. Express*, 22, <https://doi.org/10.1364/oe.22.001655>, 2014.
- Louf, V. and Protat, A.: Real-time monitoring of weather radar network calibration and antenna pointing, *J. Atmos. Ocean. Tech.*, 40, 823–844, <https://doi.org/10.1175/JTECH-D-22-0118.1>, 2023.
- Louf, V., Protat, A., Warren, R. A., Collis, S. M., Wolff, D. B., Raunyar, S., Jakob, C., and Petersen, W. A.: An integrated approach to weather radar calibration and monitoring using ground clutter and satellite comparisons, *J. Atmos. Ocean. Tech.*, 36, 17–39, <https://doi.org/10.1175/JTECH-D-18-0007.1>, 2019.
- Loulli, E., Michaelides, S., Bühl, J., Loukas, A., and Hadjimitsis, D.: Calibration of Two X-Band Ground Radars Against GPM DPR Ku-Band, *Remote Sens.-Basel*, 17, 1712, <https://doi.org/10.3390/rs17101712>, 2025.

- Marks, D. A., Wolff, D. B., Carey, L. D., and Tokay, A.: Quality control and calibration of the dual-polarization radar at Kwajalein, RMI, *J. Atmos. Ocean. Tech.*, 28, 181–196, <https://doi.org/10.1175/2010JTECHA1462.1>, 2011.
- Masaki, T., Iguchi, T., Kanemaru, K., Furukawa, K., Yoshida, N., Kubota, T., and Oki, R.: Calibration of the dual-frequency precipitation radar onboard the Global Precipitation Measurement Core Observatory, *IEEE T. Geosci. Remote*, 60, 1–16, <https://doi.org/10.1109/TGRS.2020.3039978>, 2020.
- Mishchenko, M. I.: Calculation of the amplitude matrix for a non-spherical particle in a fixed orientation, *Appl. Optics*, 39, 1026–1031, 2000.
- Mishchenko, M. I., Travis, L. D., and Mackowski, D. W.: T-matrix computations of light scattering by nonspherical particles: A review, *J. Quant. Spectrosc. Ra.*, 55, 535–575, [https://doi.org/10.1016/0022-4073\(96\)00002-7](https://doi.org/10.1016/0022-4073(96)00002-7), 1996.
- Murphy, A. M., Ryzhkov, A., and Zhang, P.: Columnar vertical profile (CVP) methodology for validating polarimetric radar retrievals in ice using in situ aircraft measurements, *J. Atmos. Ocean. Tech.*, 37, 1623–1642, <https://doi.org/10.1175/JTECH-D-20-0011.1>, 2020.
- Ori, D., Schemann, V., Karrer, M., Dias Neto, J., von Terzi, L., Seifert, A., and Kneifel, S.: Evaluation of ice particle growth in ICON using statistics of multi-frequency Doppler cloud radar observations, *Q. J. Roy. Meteor. Soc.*, 146, 3830–3849, <https://doi.org/10.1002/qj.3875>, 2020.
- Pejčić, V., Saavedra Garfias, P., Mühlbauer, K., Trömel, S., and Simmer, C.: Comparison between precipitation estimates of ground-based weather radar composites and GPM's DPR rainfall product over Germany, *Meteorol. Z.*, <https://doi.org/10.1127/metz/2020/1039>, 2020.
- Pejčić, V., Soderholm, J., Mühlbauer, K., Louf, V., and Trömel, S.: Five years calibrated observations from the University of Bonn X-band weather radar (BoXPOL), *Scientific Data*, 9, 1–9, <https://doi.org/10.1038/s41597-022-01656-0>, 2022.
- Planat, N., Gehring, J., Vignon, É., and Berne, A.: Identification of snowfall microphysical processes from Eulerian vertical gradients of polarimetric radar variables, *Atmos. Meas. Tech.*, 14, 4543–4564, <https://doi.org/10.5194/amt-14-4543-2021>, 2021.
- Protat, A., Louf, V., Soderholm, J., Brook, J., and Ponsonby, W.: Three-way calibration checks using ground-based, ship-based, and spaceborne radars, *Atmos. Meas. Tech.*, 15, 915–926, <https://doi.org/10.5194/amt-15-915-2022>, 2022.
- Ray, P. S.: Broadband Complex Refractive Indices of Ice and Water, *Appl. Optics*, 11, 1836–1844, <https://doi.org/10.1364/AO.11.001836>, 1972.
- Richardson, L. M., Cunningham, J. G., Zittel, W. D., Lee, R. R., Ice, R. L., Melnikov, V. M., Hoban, N. P., and Gebauer, J. G.: Bragg scatter detection by the WSR-88 D. Part I: Algorithm development, *J. Atmos. Ocean. Tech.*, 34, 465–478, <https://doi.org/10.1175/JTECH-D-16-0030.1>, 2017.
- Rinehart, R. E.: *Radar for Meteorologists*, 3rd edn., Rinehart Publications, ISBN: 0965800202, 1997.
- Romatschke, U.: Melting layer detection and observation with the NCAR airborne W-band radar, *Remote Sens.-Basel*, 13, 1660, <https://doi.org/10.3390/rs13091660>, 2021.
- Ryzhkov, A., Pinsky, M., Pokrovsky, A., and Khain, A.: Polarimetric radar observation operator for a cloud model with spectral microphysics, *J. Appl. Meteorol. Clim.*, 50, 873–894, <https://doi.org/10.1175/2010JAMC2363.1>, 2011.
- Ryzhkov, A., Zhang, P., Reeves, H., Kumjian, M., Tschallener, T., Trömel, S., and Simmer, C.: Quasi-vertical profiles – A new way to look at polarimetric radar data, *J. Atmos. Ocean. Tech.*, 33, 551–562, <https://doi.org/10.1175/JTECH-D-15-0020.1>, 2016.
- Ryzhkov, A. V.: The impact of beam broadening on the quality of radar polarimetric data, *J. Atmos. Ocean. Tech.*, 24, 729–744, <https://doi.org/10.1175/JTECH2003.1>, 2007.
- Ryzhkov, A. V. and Zrníc, D. S.: *Radar Polarimetry for Weather Observations*, Springer International Publishing, <https://doi.org/10.1007/978-3-030-05093-1>, 2019.
- Ryzhkov, A. V., Giangrande, S. E., Melnikov, V. M., and Schuur, T. J.: Calibration issues of dual-polarization radar measurements, *J. Atmos. Ocean. Tech.*, 22, 1138–1155, <https://doi.org/10.1175/JTECH1772.1>, 2005.
- Ryzhkov, A. V., Snyder, J., Carlin, J. T., Khain, A., and Pinsky, M.: What polarimetric weather radars offer to cloud modelers: forward radar operators and microphysical/thermodynamic retrievals, *Atmosphere*, 11, 362, <https://doi.org/10.3390/atmos11040362>, 2020.
- Sanchez-Rivas, D. and Rico-Ramirez, M. A.: Calibration of radar differential reflectivity using quasi-vertical profiles, *Atmos. Meas. Tech.*, 15, 503–520, <https://doi.org/10.5194/amt-15-503-2022>, 2022.
- Scharbach, T.: ERA5 reanalysis data interpolated to the 18° QVPs generated with the X-band radar in Bonn (BoXPOL), Zenodo [data set], <https://doi.org/10.5281/zenodo.20799703>, 2026a.
- Scharbach, T.: Python jupyter notebooks for calibration of ZH/ZDR and provided offset values, related to the study: “Long-term climatology of vertical profiles of polarimetric variables and ice-microphysical retrievals at X-band. Part 1: Radar calibration”, Zenodo [data set and code], <https://doi.org/10.5281/zenodo.20796890>, 2026b.
- Schneebeli, M., Leuenberger, A., Frech, M., and Ventura, J.: Weather radar data calibration and monitoring, *Advances in Weather Radar*, 2, 41–97, https://doi.org/10.1049/SBRA557G_ch2, 2024.
- Schneebeli, M., Leuenberger, A., Schmid, P. J., Grazioli, J., Corden, H., Berne, A., Kennedy, P., George, J., Junyent, F., and Chandrasekar, V.: Calibration of weather radars with a target simulator, *Atmos. Meas. Tech.*, 18, 5157–5176, <https://doi.org/10.5194/amt-18-5157-2025>, 2025.
- Seifert, A. and Beheng, K. D.: A two-moment cloud microphysics parameterization for mixed-phase clouds. Part 1: Model description, *Meteorol. Atmos. Phys.*, 92, 45–66, <https://doi.org/10.1007/s00703-005-0112-4>, 2006.
- Shannon, C. E.: A mathematical theory of communication, *Bell Syst. Tech. J.*, 27, 379–423, <https://doi.org/10.1002/j.1538-7305.1948.tb01338.x>, 1948.
- Shrestha, P., Mendrok, J., Pejčić, V., Trömel, S., Blahak, U., and Carlin, J. T.: Evaluation of the COSMO model (v5.1) in polarimetric radar space – impact of uncertainties in model microphysics, retrievals and forward operators, *Geosci. Model Dev.*, 15, 291–313, <https://doi.org/10.5194/gmd-15-291-2022>, 2022.
- Silberstein, D. S., Wolff, D. B., Marks, D. A., Atlas, D., and Pippitt, J. L.: Ground clutter as a monitor of radar stability at Kwajalein, RMI, *J. Atmos. Ocean. Tech.*, 25, 2037–2045, <https://doi.org/10.1175/2008JTECHA1063.1>, 2008.

- Song, J. I., Yum, S. S., Park, S.-H., Kim, K.-H., Park, K.-J., and Joo, S.-W.: Climatology of melting layer heights estimated from cloud radar observations at various locations, *J. Geophys. Res.-Atmos.*, 126, e2021JD034816, <https://doi.org/10.1029/2021JD034816>, 2021.
- Tobin, D. M. and Kumjian, M. R.: Polarimetric radar and surface-based precipitation-type observations of ice pellet to freezing rain transitions, *Weather Forecast.*, 32, 2065–2082, <https://doi.org/10.1175/WAF-D-17-0054.1>, 2017.
- Trömel, S., Ryzhkov, A. V., Zhang, P., and Simmer, C.: Investigations of Backscatter Differential Phase in the Melting Layer, *J. Appl. Meteorol. Clim.*, 53, <https://doi.org/10.1175/JAMC-D-14-0050.1>, 2014.
- Trömel, S., Ryzhkov, A. V., Hickman, B., Mühlbauer, K., and Simmer, C.: Polarimetric Radar Variables in the Layers of Melting and Dendritic Growth at X Band – Implications for a Nowcasting Strategy in Stratiform Rain, *J. Appl. Meteorol. Clim.*, 58, 2497–2522, <https://doi.org/10.1175/JAMC-D-19-0056.1>, 2019.
- Trömel, S., Simmer, C., Blahak, U., Blanke, A., Doktorowski, S., Ewald, F., Frech, M., Gergely, M., Hagen, M., Janjic, T., Kalesse-Los, H., Kneifel, S., Knot, C., Mendrok, J., Moser, M., Köcher, G., Mühlbauer, K., Myagkov, A., Pejčic, V., Seifert, P., Shrestha, P., Teisseire, A., von Terzi, L., Tetoni, E., Vogl, T., Voigt, C., Zeng, Y., Zinner, T., and Quaas, J.: Overview: Fusion of radar polarimetry and numerical atmospheric modelling towards an improved understanding of cloud and precipitation processes, *Atmos. Chem. Phys.*, 21, 17291–17314, <https://doi.org/10.5194/acp-21-17291-2021>, 2021.
- Trömel, S., Blahak, U., Evaristo, R., Mendrok, J., Neef, L., Pejčic, V., Scharbach, T., Shrestha, P., and Simmer, C.: Fusion of radar polarimetry and atmospheric modeling, in: *Advances in Weather Radar, Precipitation science, scattering and processing algorithms*, vol. 2, The Institution of Engineering and Technology (IET), https://doi.org/10.1049/SBRA557G_ch7, 2023.
- Trömel, S., Mühlbauer, K., Lennefer, M., Simmer, C., Scharbach, T., and Pejčic, V.: Polarimetric X-band radar (BoXPoL) data monitored in Bonn, Germany, since 2009 to 2023, *bonndata [data set]*, <https://doi.org/10.60507/FK2/DONVG5>, 2026.
- Von Storch, H. and Zwiers, F. W.: *Statistical Analysis in Climate Research*, Cambridge University Press, ISBN: 0521012309, 2002.
- Vulpiani, G., Montopoli, M., Passeri, L. D., Gioia, A. G., Giordano, P., and Marzano, F. S.: On the use of dual-polarized C-band radar for operational rainfall retrieval in mountainous areas, *J. Appl. Meteorol. Clim.*, 51, 405–425, <https://doi.org/10.1175/JAMC-D-10-05024.1>, 2012.
- Wang, X., Shao, N., Cao, J., Ma, J., Liu, J., Yang, T., Ye, F., and Sun, H.: ARC-Based Absolute Calibration Method for Weather Radar Reflectivity, *IEEE T. Geosci. Remote.*, 63, 1–11, <https://doi.org/10.1109/tgrs.2025.3603593>, 2025.
- Warren, R. A., Protat, A., Siems, S. T., Ramsay, H. A., Louf, V., Manton, M. J., and Kane, T. A.: Calibrating ground-based radars against TRMM and GPM, *J. Atmos. Ocean. Tech.*, 35, 323–346, <https://doi.org/10.1175/JTECH-D-17-0128.1>, 2018.
- Warren, R. A., Ramsay, H. A., Siems, S. T., Manton, M. J., Peter, J. R., Protat, A., and Pillalamarri, A.: Radar-based climatology of damaging hailstorms in Brisbane and Sydney, Australia, *Q. J. Roy. Meteor. Soc.*, 146, 505–530, <https://doi.org/10.1002/qj.3693>, 2020.
- Waterman, P. C.: Symmetry, unitarity, and geometry in electromagnetic scattering, *Phys. Rev. D*, 3, 825, <https://doi.org/10.1103/PhysRevD.3.825>, 1971.
- Williams, E., Hood, K., Cho, J. Y. N., Smalley, D. J., Sandifer, J. B., Zrnić, D., Melnikov, V. M., Burgess, D. W., Forsyth, D., Webster, T. M., and Erickson, D.: End-to-end calibration of NEXRAD differential reflectivity with metal spheres, in: *Proceedings of the 36th Conference on Radar Meteorology*, American Meteorological Society, Breckenridge, Colorado, USA, 16–20 September 2013, <https://ams.confex.com/ams/36Radar/webprogram/Paper228796.html> (last access: 14 September 2026), 2013.
- Wolfensberger, D., Scipion, D., and Berne, A.: Detection and characterization of the melting layer based on polarimetric radar scans, *Q. J. Roy. Meteor. Soc.*, 142, 108–124, <https://doi.org/10.1002/qj.2672>, 2016.
- Wolff, D. B., Marks, D. A., and Petersen, W. A.: General application of the relative calibration adjustment (RCA) technique for monitoring and correcting radar reflectivity calibration, *J. Atmos. Ocean. Tech.*, 32, 496–506, <https://doi.org/10.1175/JTECH-D-13-00185.1>, 2015.
- Xie, X., Evaristo, R., Simmer, C., Handwerker, J., and Trömel, S.: Precipitation and microphysical processes observed by three polarimetric X-band radars and ground-based instrumentation during HOPE, *Atmos. Chem. Phys.*, 16, 7105–7116, <https://doi.org/10.5194/acp-16-7105-2016>, 2016.
- Xie, X., Shrestha, P., Mendrok, J., Carlin, J., Trömel, S., and Blahak, U.: Bonn Polarimetric Radar forward Operator (B-PRO), <https://doi.org/10.5880/TR32DB.41>, 2021.
- Ye, F., Wang, X., Li, L., Chen, Y., Lei, Y., Yu, H., Yin, J., Shi, L., Yang, Q., and Huang, Z.: Weather radar calibration method based on UAV-suspended metal sphere, *Sensors (Basel, Switzerland)*, 24, 4611, <https://doi.org/10.3390/s24144611>, 2024.
- Zeng, Y., Blahak, U., and Jerger, D.: An efficient modular volume-scanning radar forward operator for NWP models: description and coupling to the COSMO model, *Q. J. Roy. Meteor. Soc.*, 142, 3234–3256, <https://doi.org/10.1002/qj.2904>, 2016.
- Zeyong, G., Zhaoping, S., Jia, G., Feifei, L., and Zhichao, B.: A Method for Calibrating Zdr by Using Light Rain Echo in Volume Scan Data, in: *2019 International Conference on Meteorology Observations (ICMO)*, 1–3, IEEE, <https://doi.org/10.1109/icmo49322.2019.9025914>, 2019.
- Zittel, W. D., Cunningham, J. G., Lee, R. R., Richardson, L. M., Ice, R. L., and Melnikov, V.: Use of hydrometeors, Bragg scatter, and sun spikes to determine system ZDR biases in the WSR-88D fleet, in: *Extended Abstracts of the Eighth European Conference on Radar in Meteorology and Hydrology (ERAD 2014)*, vol. 12, Garmisch-Partenkirchen, Germany, https://www.pa.op.dlr.de/erad2014/programme/ExtendedAbstracts/132_Zittel.pdf (last access: 14 September 2026), 2014.