

## ***Interactive comment on “Validation of an AOT product over land at the 0.6 $\mu\text{m}$ channel of the SEVIRI sensor onboard MSG” by E. Bernard et al.***

**S.-H. Ham**

shham@snu.ac.kr

Received and published: 4 July 2011

Recently it has been reported that SEVIRI 0.6- $\mu\text{m}$  radiance measurements may have 6~7% of low bias against MODIS measurements (Ham and Sohn, 2011; Doelling et al., 2004). This low bias of SEVIRI radiances could partly contribute to differences between SEVIRI and MODIS AOTs (Figs. 8 and 12). Moreover, in Fig. 4, except cloud contamination, many points are located below one-to-one line (SEVIRI AOT < AERONET AOT), which may be related to low bias of SEVIRI radiance measurements. Authors should address the possible impact of SEVIRI calibration errors on their results.

References:

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



Doelling, D., Nguyen, L., and Minnis, P.: Calibration comparisons between SEVIRI, MODIS, and GOES data, EUMETSAT Meteorological Satellite Conference, Prague, Czech Republic, 77–83, 2004.

Ham, S. H. and Sohn, B. J.: Assessment of the calibration performance of satellite visible channels using cloud targets: application to Meteosat-8/9 and MTSAT-1R, Atmos. Chem. Phys., 10, 11131–11149, 2010.

---

Interactive comment on Atmos. Meas. Tech. Discuss., 4, 3147, 2011.

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

