

Interactive
Comment

Interactive comment on “An inverse modelling approach for frequency response correction of capacitive humidity sensors in ABL research with small unmanned aircraft” by N. Wildmann et al.

N. Wildmann et al.

norman.wildmann@uni-tuebingen.de

Received and published: 18 July 2014

Many thanks for the detailed review. In the following I will comment on each point. The referee comments will be repeated in blue italic before the answer. In general, we believe we need to more clearly describe in the revised manuscript for which purpose we developed this sensor model and where the limitations and benefits are. Since the referee mentions the comparison to Miloshevich et al.(2004) several times, we need to address better how measurements from RPA serve a different purpose than radiosonde and ground observations. This concerns the requirements of a sensor, and also the environment, in which the sensor is used.

C1785

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper



Detailed answers to the referee comments are given in the attached PDF-file.

Please also note the supplement to this comment:

<http://www.atmos-meas-tech-discuss.net/7/C1785/2014/amtd-7-C1785-2014-supplement.pdf>

Interactive comment on Atmos. Meas. Tech. Discuss., 7, 4407, 2014.

AMTD

7, C1785–C1786, 2014

Interactive
Comment

Full Screen / Esc

Printer-friendly Version

Interactive Discussion

Discussion Paper

C1786

