

**Development of
a digital mobile solar
tracker**

S. Baidar et al.

This discussion paper is/has been under review for the journal Atmospheric Measurement Techniques (AMT). Please refer to the corresponding final paper in AMT if available.

Development of a digital mobile solar tracker

S. Baidar^{1,2}, N. Kille^{2,3}, I. Ortega^{1,2}, R. Sinreich¹, D. Thomson², J. Hannigan⁴, and R. Volkamer^{1,2,3}

¹Department of Chemistry and Biochemistry, University of Colorado, Boulder, CO 80309, USA

²Cooperative Institute for Research in Environmental Sciences (CIRES), University of Colorado, Boulder, CO 80309, USA

³Department of Atmospheric and Oceanic Sciences (ATOC), University of Colorado, Boulder, CO 80309, USA

⁴National Center for Atmospheric Research (NCAR), Boulder, CO 80301, USA

Received: 15 September 2015 – Accepted: 18 October 2015 – Published: 2 November 2015

Correspondence to: R. Volkamer (rainer.volkamer@colorado.edu)

Published by Copernicus Publications on behalf of the European Geosciences Union.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Abstract

We have constructed and deployed a fast digital solar tracker aboard a moving ground-based platform. The tracker consists of two rotating mirrors, a lens, an imaging camera, and a motion compensation system that provides the Euler angles of the mobile platform in real time. The tracker can be simultaneously coupled to UV-Vis and FTIR spectrometers making it a versatile tool to measure the absorption of trace gases using solar incoming radiation. The integrated system allows the tracker to operate autonomously while the mobile laboratory is in motion. Mobile direct sun Differential Optical Absorption Spectroscopy (mobile DS-DOAS) observations using this tracker were conducted during summer 2014 as part of the Front Range Photochemistry and Pollution Experiment (FRAPPE) in Colorado, USA. We demonstrate an angular precision of 0.052° (about 1/10 of the solar disk diameter) during research drives, and verify this tracking precision from measurements of the center to limb darkening (CLD, the changing appearance of Fraunhofer lines) in the mobile DS-DOAS spectra. The high photon flux from direct sun observation enables measurements of nitrogen dioxide (NO_2) slant columns with high temporal resolution, and reveals spatial detail in the variations of NO_2 vertical column densities (VCDs). The NO_2 VCD from DS-DOAS is compared with a co-located MAX-DOAS instrument. Overall good agreement is observed amid a highly heterogeneous air mass.

1 Introduction

Mobile column measurements provide a means to characterize the distribution of trace gases over a large spatial scale while capturing the atmospheric variability over the column. Combined with wind measurements, mobile column measurements of trace gases have been shown to be very useful to constrain emission of trace gases from source regions by applying a mass conservation approach (e.g. Baidar et al., 2013b; Ibrahim et al., 2010; Johansson et al., 2014a, b; Mellqvist et al., 2010; Shaiganfar et al.,

AMTD

8, 11401–11427, 2015

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



2011; Wang et al., 2012). Mobile column measurements from various platforms have previously been used to estimate nitrogen oxides (NO_x) emissions from cities (Baidar et al., 2013b; Ibrahim et al., 2010; Shaiganfar et al., 2011; Wang et al., 2012), nitrogen dioxide (NO_2), Sulfur dioxide (SO_2) (Johansson et al., 2014a) and formaldehyde (HCHO) (Johansson et al., 2014b) from industries using the Differential Optical Absorption Spectroscopy (DOAS) (Platt and Stutz, 2008) technique and fugitive volatile organic compounds (VOC) emissions from refineries (e.g., Mellqvist et al., 2010; Johansson et al., 2014a, b) using the Solar Occultation Flux (SOF) (Mellqvist et al., 2010) method. The DOAS method typically is limited to the UV-Visible wavelength region and uses scattered sunlight; while the SOF method uses direct sun observations in the mid IR wavelengths.

DOAS measurements of scattered sunlight are particularly attractive to conduct mobile column measurements, because scattered sunlight measurements do not require clear sky conditions, and the relative ease to operate such instruments. In particular, the stability of the elevation angle (EA), i.e. angle relative to the horizon, is less crucial at higher EA typically used for mobile DOAS measurements. Logistical challenges arise when measurements observe the direct solar beam from a moving platform, e.g., due to highly uncorrelated motions of vehicles on roads. However, there are advantages of using direct sun measurements also at UV-Vis wavelengths. The biggest benefit is the availability of high photon flux in the direct solar beam. This enables fast measurements (and subsequently high spatial resolution) with good signal to noise. Other advantages include: (1) simple determination of the air mass factor (depends only upon the solar zenith angle) and (2) no need to account for the Ring effect (Grainger and Ring, 1962) in the DOAS analysis, which makes the retrievals more straightforward. These advantages hold potential to improve precision with direct sun measurements. In addition, extending the capabilities to measure trace gases using the direct sun observations in the UV-Visible region enables us to make simultaneous measurements of NO_x and VOC precursor molecules for ozone (O_3) and other secondary pollutants on similar temporal and spatial scale to study different processes in the atmosphere.

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



In this work we describe a fast, digital mobile solar tracker that is able to motion stabilize and track the sun while moving on roads. The new tracker receives simultaneous input about the vehicle orientation from a motion compensation system and from an imaging feedback loop. This enables the tracker to autonomously locate the sun while moving and also make measurements under thin cloud conditions. The tracker transfer optics have been designed to facilitate the flexible coupling of multiple spectrometers for direct sun absorption measurements at UV-Vis-NIR and mid IR wavelengths. The tracker was successfully deployed from 21 July–3 September 2014 to conduct simultaneous measurements of VOC and NO₂ columns as part of the Front Range Air Pollution and Photochemistry Experiment (FRAPPE 2014) in Colorado. Figure 1 shows the schematic of the measurement principle for the instruments deployed aboard the mobile laboratory during FRAPPE 2014. In Sect. 2, we describe the instrument configuration during FRAPPE 2014 as deployed during 16 research drives (RD). The tracker performance is characterized in Sect. 3, and is demonstrated based on tracking precision as quantified from the imaging data as well as the UV-Vis spectral data from RD#11 on 13 August 2014. In Sect. 4, we present NO₂ VCD data measured by the UV-Vis spectrometer during RD#14 on 18 August 2014, when a MAX-DOAS instrument was co-located and provides independent NO₂ VCD measurements.

2 Instrumentation and retrievals

2.1 Mobile solar tracker

The mobile solar tracker as deployed aboard the mobile laboratory is shown in Fig. 2a. It is an alt-azimuthal tracker consisting of two mirrors. The first mirror is mounted at a 45° angle directly on a stepper motor and allows access to any EA. The direct coupling of the mirror permits fast backlash free movements. The second mirror is mounted at a 45° angle opposite to the first mirror. The two mirrors are mounted on a rotational stage that is driven by a second stepper motor. The electrical connection is realized

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



to the LabVIEW vision toolkit from National Instruments. The choice of ellipse vs. circle algorithm is made for efficiency, as well as due to limitations of each algorithm. The circle algorithm is significantly faster than the ellipse algorithm, as it only searches for a circle to fit within a well-defined region of the image, centered around the aperture, whereas the ellipse algorithm searches the entire camera pixel space. A consistency check is performed for the radii of fitted circles/ellipses before calculating the difference in the centers of the solar disk and aperture. Once the deviation between the aperture and the solar disk centers is determined from the camera data, a small correction is applied based on historical MMQ data to account for the motion of the platform during the control loop time, i.e. the time from when the picture was recorded and the new motor target position is commanded.

One of the major challenges with tracking the sun from a moving platform is accounting for the platform motion that happens over the course of each control loop interval. As the platform is in continuous uncorrelated motion, the orientation at the time of the recording of the image is different to that when the motor positions are updated. We used fast MMQ data at 100 Hz to account for this change in orientation and correct the pixel offset data from the imaging system. It was empirically determined that the correction based on the most recent data from MMQ ($t = 0$) and the data 4 points back in time ($t = -40$ ms) yielded the best result. The difference in pitch and roll angles between these two points ($n = 0$ and $n = -4$) and the relationship between degree and pixel is used to correct the pixel offset data from the imaging system. The corrected pixel data is converted to mirror angles to update the mirror positions in order to align the two centers and subsequently keep them aligned. Application of this correction for motion of the platform lead indeed to measurable improvements of the tracking during research drives. A cumulative density plot of percentage of points within a certain distance off of the center of the solar disk when this correction is (i) applied and (ii) not applied during segments of a research drive is shown in Supplement Fig. S1. An additional 9% of data (an improvement of $\sim 23\%$ relative) was found to lie in the closest bin to the center (0–20 pixels, 0.075°) when the correction is applied.

3. Straightforward operation of the instrument. Only a rough alignment is needed to orient the tracker mirrors and the motion compensation system. The final tracking accuracy is based only on the imaging loop.
4. High precision tracking of the sun.

2.2 Direct Sun DOAS (DS-DOAS)

The solar tracker was coupled to an Ocean Optics QE65000 spectrometer with Hamamatsu S7031-1006 thermo-electrically cooled charge coupled device (CCD) array detector via optical fiber bundles for DS-DOAS measurements. A 12 m long 1.5 mm diameter fiber bundle transfers the direct solar beam from the solar tracker to a 10 m long 1.7 mm diameter single core silica fiber to minimize polarization effects. The other end of the mono-fiber is connected to a fiber bundle that delivers light to a single UV-Vis spectrometer, or to a bifurcated fiber bundle connected to two or more UV-Vis spectrometers. The mono-fiber was found to be critical during the DOAS analysis of the UV-Vis spectra. Without the mixing mono-fiber the root mean square (RMS) of the DOAS fit increased gradually over a short period of time, which was not observed when the mixing fiber was in place. A single spectrometer that covered the wavelength range of 390 to 520 nm with ~ 0.55 nm resolution (full width at half maximum or FWHM) was used during FRAPPE 2014 to measure NO₂ VCDs. The optical resolution was determined by measuring a Krypton emission line at 450.235 nm. This emission line was also used to determine the instrumental slit function and later to convolve high resolution literature cross sections to the optical resolution of the instrument for DOAS analysis. The optical spectrometer bench was heated and kept constant at a temperature of 40 ± 0.05 °C, to minimize changes in optical properties, while the detector itself was cooled to -10 °C to reduce dark current. The temperature stability was maintained by using a two stage temperature controlled housing described in Coburn et al. (2011). The integration time for each spectrum was 2 s. An absorptive neutral density filter with

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

⏪

⏩

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



an optical density of 1.6 (e-based) was placed above the focusing lens of the solar tracker to avoid saturation of the detector.

2.3 Mobile Multi-Axis DOAS (MAX-DOAS)

The MAX-DOAS instrument uses scattered sunlight as the light source. The collected spectra are then analyzed for trace gases such as NO₂, glyoxal, HCHO, O₄ using the DOAS method. The MAX-DOAS instrument is described in detail in Sinreich et al. (2010) and Coburn et al. (2011). Briefly, the MAX-DOAS telescope was mounted on the roof of the mobile laboratory next to the solar tracker and collected scattered photons at different EAs. Spectra collected from different EAs contain information from different layers in the atmosphere and hence can be used to obtain information about the vertical distribution of the trace gases. However, due to the horizontal gradient of the trace gases of interest, MAX-DOAS measurements from a mobile platform are focused on obtaining VCDs using one or two EAs (e.g. Ibrahim et al., 2010; Shaiganfar et al., 2011; Wang et al., 2012). During FRAPPE 2014, the MAX-DOAS instrument made measurements at 30° (facing backward relative to the mobile platform) and 90° (zenith) EAs. The collected photons are transferred to a spectrometer/CCD detector system via an optical glass fiber bundle. The measured spectra at 30° EA were analyzed for NO₂ using a zenith reference spectrum and the resulting differential slant column densities (dSCD) were converted into VCDs using the geometric air mass factor (which is 2 for 30° EA).

2.4 Data retrievals

2.4.1 DOAS analysis

The wavelength range of 434–460 nm was used for DOAS retrieval of NO₂. Trace gas reference cross sections for NO₂ at 298 K (Vandaele et al., 1998), orthogonal NO₂ at 220 K, O₃ (Serdyuchenko et al., 2014), H₂O (Rothman et al., 2013), O₄ (Thalman

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



and Volkamer, 2013), glyoxal (Volkamer et al., 2005), and a Center to Limb Darkening (CLD) reference spectrum (Bosch et al., 2003) were simultaneously fitted using a non-linear least square fitting routine. The CLD correction reference spectrum was calculated as described in Bosch et al. (2003) and fitted to account for uneven decreases in intensity of solar spectrum at the center and at the limb of the solar disk. CLD is also used to evaluate tracker performance (see Sect. 2.4.2). A fifth order polynomial to account for scattering processes and broadband absorption in the atmosphere as well as broadband instrumental features, and an additional intensity offset to account for instrument stray light were also included in the fitting procedure. A spectrum from a clean background region was included as the Fraunhofer reference spectrum in the analysis. Supplement Fig. S2 shows a spectral fit for NO_2 and the corresponding residual from the DOAS fit.

The MAX-DOAS analysis used the same settings as the DS-DOAS analysis. The only difference is that a Ring spectrum was used to correct for the Ring effect in place of the CLD reference spectrum.

2.4.2 Center to Limb Darkening (CLD)

The effective emission temperature for solar radiation coming from the center is higher compared to the edges of the solar disk. This decrease in effective emission temperature results in an observed decrease in solar intensity towards the edges of the solar disk. This effect is known as the center-to-limb darkening (Hestroffer and Magnan, 1998). The optical depth (OD) of the solar Fraunhofer lines also decreases from the center to the edges of the solar disk and results in the need for the CLD correction in DOAS analysis for UV-Vis solar occultation measurements (e.g. Bosch et al., 2003; Butz, 2006; Gill et al., 2000). An empirical approach to correct for the CLD effect was developed by Bosch et al. (2003) and showed that the addition of a CLD correction improved DOAS retrieval of iodine monoxide (IO) and chlorine dioxide (OCIO) from balloon borne solar occultation measurements. High resolution solar spectrum taken from the solar disk center and spectrum averaged over the solar disk were used to

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



create a reference pseudo absorber cross-section and included in DOAS fits (spectra available at: <http://www.hs.uni-hamburg.de/DE/Oef/Inf/Einbl/Sospec/sonnspec.html>).

We evaluated the UV-Vis spectra in the wavelength window from 400–440 nm for the CLD correction fit coefficient to estimate the effective tracking precision from spectral data. This fit window was chosen to include two strong Fraunhofer lines (H δ at 410.2 nm and H γ at 434.0 nm) in the DOAS analysis. For radiation from the central portion of the solar disk we expect near zero CLD. We expect a significant CLD signal when the pointing accuracy is suboptimal, i.e., when radiation from near the edges of the solar disk contributes significantly to the overall photon flux of our UV-Vis spectra. Figure 4 shows the spectral proofs of CLD correction fits for spectrum taken at the center of the solar disk, 25 pixels (0.095°), and 50 pixels (0.19°) off of the center. Figure 4 clearly illustrates that the CLD correction becomes more important as spectra are collected further away from the center of the solar disk. The inclusion of CLD reference spectrum in the retrieval (1) improved NO₂ fit, (2) minimized residuals and (3) reduced scattering in the retrieved NO₂ slant columns.

3 Results and discussion

3.1 Evaluation of the tracker accuracy from the imaging feedback

The pointing accuracy of the solar tracker was determined from the deviation of the centers of the two fitted circles (i.e. aperture and solar disk) shown in Fig. 2c. The deviation in x and y direction in camera FOV was converted to angular deviation using the relationship between the diameter of the sun in the camera picture and its angular diameter in the sky. The locations of the center of the solar disk for every circle/ellipse fit from the RD#11 (duration \sim 8 h) on 13 August 2014 are shown in Supplement Fig. S3. Figure 5 shows two histograms of the angular deviation between the centers of the two circles in x and y direction during the RD#11 (only data taken when the vehicle was in motion are included). The 1σ standard deviation in x and y direction determined

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



from a Gaussian fit (black lines) are 0.035 and 0.039° respectively giving us an overall pointing precision of 0.052° . Hence the pointing precision (1σ) of about one-tenth of the solar disk angular diameter in the sky was achieved during mobile operation. Note that data points when the solar disk was not in the FOV of the camera are excluded from this analysis. On average the solar disk was outside the FOV of the camera every 3–4 s but was highly variable. Figure 6a and b shows the box plot of angular deviation as a function of vehicular speed and solar zenith angle (SZA) respectively. The top and bottom of the box represent the 25th and 75th percentile of the data respectively while the middle line is the median. The distribution appears to be slightly larger at larger speeds, and above 50° SZA; however, the means were not found to be statistically different. Future improvement in the tracker could involve incorporating a faster camera and motor in order to decrease the control loop time. Note that a much higher precision tracking ($< 0.005^\circ$) is achieved in the stationary mode which is not affected by the control loop time.

3.2 Evaluation of the tracker accuracy from the CLD

Supplement Fig. S4 shows CLD fit coefficient (absolute value) as a function of distance from the center. The chosen Fraunhofer reference spectrum from the center of the solar disk for the DOAS analysis does not always have the highest OD for the Fraunhofer lines since it also depends upon the SZA. Thus, depending upon the SZA of the reference spectrum and the measured spectrum, the CLD fit coefficient can change sign and requiring the use of absolute value. The fit coefficient gradually increases with the increasing distance from the center of the disk until it is 25–30 pixels off of the center. After that the increase in the fit coefficient is much more pronounced. In fact, from 0–30 pixels the CLD fit coefficient is not very sensitive to the pixel offset. This is because CLD is a power law function of distance from the center of the solar disk to the limb and hence is not very sensitive close to the center (Hestroffer and Magnan, 1998). This insensitivity closer to the center is likely further pronounced in our setup for the following reasons: (1) the size of the aperture used to collect the radiation for the UV-Vis

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



spectra (~ 40 pixels in radius) results in radiance weighted average spectra that show no significant need for CLD correction until it is 25–30 pixels off of the center. (2) As the SZA of the sun changes the observed CLD is a combination of the solar movement and pointing inaccuracy and can have compensating effects over small scales. It is clearly evident from Supplement Fig. S4 that the CLD OD from DOAS fits are a robust method of quantitatively determining whether an individual spectrum was taken within 30 pixels of the center or outside this threshold. The CLD OD from the DOAS analysis for the RD#11 is shown in Supplement Fig. S5 as a histogram and a cumulative probability distribution function for different fit coefficient bins. Supplement Fig. S5 shows that 95 % of the data are within the CLD OD of 0.13, which corresponds to pixel offset of ~ 30 pixels or an angular precision of about 0.12° (2σ). This is consistent with angular tracking precision of 0.052° (1σ) determined from the camera data. The precision of the CLD correction fits from DOAS analysis has been crosschecked using the CLD correction fit from the NO_2 retrieval window and showed excellent agreement (slope = 1.07, intercept = 1.77×10^{-3} , $R^2 = 0.97$; see Supplement Fig. S6). The 7 % increase in slope is very likely due to the wavelength dependence of CLD. A 9 ± 3 % increase in CLD fit coefficient is expected based on the wavelength dependence from 420 to 450 nm (Hestroffer and Magnan, 1998).

3.3 Field applications: comparison with MAX-DOAS

NO_2 VCDs measured by DS-DOAS using the mobile solar tracker were compared with VCDs from a co-located MAX-DOAS instrument on our mobile laboratory. NO_2 dSCD from both instruments were converted into VCDs using a geometric air mass factor ($\text{geoAMF} = \frac{1}{\sin(\text{EA})}$). Figure 7b shows the time series of NO_2 VCDs measured by the two instruments during RD#14 on 18 August 2014 in northern Colorado. The drive track for the research drive is shown in Supplement Fig. S7. The NO_2 detection limit and precision (1σ) for the direct sun measurements are 7×10^{14} and 3×10^{14} molecules cm^{-2} respectively for a 2 s integration time. Even though the two instruments are co-located

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



and used a similar retrieval, the comparison is not straightforward because: (1) the viewing geometries of the two instruments are not the same. MAX-DOAS measurements were made at 30° EA facing towards the back of the mobile laboratory. DS-DOAS observations depend upon the solar elevation and azimuth angle (Az) at the time of the measurements. Thus, the two instruments are typically not looking at the same air mass. (2) Both instruments make measurements averaged horizontally over a distance that depends upon the EA. For example, for a boundary layer height of 1 km, the MAX-DOAS observations at 30° EA averages over a horizontal distance of 1.7 km (geometric path). In contrast, the direct sun observation only averages over a horizontal distance of 0.6 km at solar elevation of 60° . The EA and azimuth angles at the time of measurements for the two instruments are shown in Fig. 7a. As expected, the agreement between NO_2 VCDs is found to be best when the two instruments have similar viewing geometry. An expanded view of NO_2 VCD over two nine minute periods when (i) EA and Az angles for the two instruments are relatively similar (i.e. looking at the same air mass; $\delta\text{EA} \sim 10^\circ$ and $\delta\text{Az} \sim 70^\circ$) and (ii) difference in EA and Az angles are larger (i.e. looking at the different air masses; $\delta\text{EA} \sim 25^\circ$ and $\delta\text{Az} \sim 140^\circ$) are shown in Fig. 7c and d respectively. The agreement between the two instruments is indeed better in Fig. 7c compared to Fig. 7d. During the period shown in Fig. 7d, the two instruments were almost looking in opposite direction along the drive track. As the MAX-DOAS was looking towards the back of the mobile laboratory, it observes the air mass probed by the solar tracker after a certain time which is dependent upon the speed of the vehicle. Figure 7d shows a small offset in the magnitude of NO_2 VCD as well as time (see peak at 5.37 p.m.). The small offset in magnitude is likely due the difference in EA where the MAX-DOAS averages over a larger distance while the offset in time is a result of Az viewing geometry.

Despite these complications, the time series for NO_2 measured by the two instruments track each other very well. High photon flux in the direct solar beam enabled fast measurements with high signal to noise and this is evident in the time series. The DS-DOAS measurements captured variability in NO_2 at much finer scale than the

MAX-DOAS data. This has potentially important benefits with resolving column enhancements of spatially confined emission sources, and the spatial variations within plumes.

The good agreement between the DS-DOAS and MAX-DOAS observations is reflected in the slope of 0.97 ± 0.03 for the orthogonal distance regression of the two data sets (Supplement Fig. S8, offset = $-1.1 \pm 1.3 \times 10^{14}$ molecules cm^{-2}). All data shown in Fig. 7b are included in the comparison regardless of the EA and azimuth angle difference. The DS-DOAS data are averaged for 20 s to the MAX-DOAS timestamp. If the data is filtered for the solar EA (i) below 45° and (ii) above 45° , the slopes of the orthogonal least squares fits improve to unity (1.01 ± 0.04 for case (i) and 1.00 ± 0.04 for case (ii)) but not significantly different from the fit to all data. The offset is larger ($-5.0 \pm 1.7 \times 10^{14}$ molecules cm^{-2}) for the second case. Such good agreement gives confidence in the validity of the new Solar Tracker measurements for NO_2 and other species using the DS-DOAS method. The data will be used to quantify emissions of trace gases from various sources such as power plants, refineries, farms, and feedlots, and will be part of subsequent publications.

4 Conclusion and outlook

A digital solar tracker design is presented that meets the criteria to track the sun from a moving platform such as a ground-based mobile laboratory. It provides access to the solar beam with a pointing precision of 0.052° from a platform that is in motion. The effective pointing precision was verified using CLD measurements. These characteristics have proven to be adequate to acquire high resolution atmospheric absorption spectra with a high signal-to-noise ratio at UV-Vis wavelengths. NO_2 VCDs were measured with the mobile solar tracker (DS-DOAS) and compared with VCDs from a co-located MAX-DOAS instrument. A good overall agreement is found amid a highly inhomogeneous environment. In the future, the setup provides potential for 1–2 orders of magnitude higher photon intensity that could be exploited to maximize the signal-to-noise ratio

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



to measure trace gases at UV wavelengths (e.g., HONO, HCHO), to conduct night-time atmospheric measurements with the moon as a light source, or to couple multiple spectrometers to observe other trace gases at UV-Vis-NIR or mid-IR wavelengths.

**The Supplement related to this article is available online at
doi:10.5194/amtd-8-11401-2015-supplement.**

Acknowledgements. This work was supported by an Energy Initiative seed grant from CIRES, and Colorado Department for Public Health and the Environment (CDPHE) contract #14FAA64390 (R.V.). S. Baidar is recipient of an ESRL-CIRES Graduate Fellowship. The authors thank Jim Kastengren and CIRES Instrument shop for instrument design and fabrication, Philip Handley and Owen Cooper for support during FRAPPE, Caroline Fayt and Michel van Roozendaal for the WinDOAS software.

References

- Baidar, S., Oetjen, H., Coburn, S., Dix, B., Ortega, I., Sinreich, R., and Volkamer, R.: The CU Airborne MAX-DOAS instrument: vertical profiling of aerosol extinction and trace gases, *Atmos. Meas. Tech.*, 6, 719–739, doi:10.5194/amt-6-719-2013, 2013a.
- Baidar, S., Volkamer, R., Alvarez II, R. J., Brewer, W. A., Davies, F., Langford, A. O., Oetjen, H., Pearson, G., Senff, C. J., and Hardesty, R. M.: Combining active and passive airborne remote sensing to quantify NO₂ and O_x production near Bakersfield, CA, *British Journal of Environment and Climate Change*, 3, 566–586, doi:10.9734/BJECC/2013/5740, 2013b.
- Bertleff, M.: Camera based sun tracking system for mobile platforms, Masters thesis, Karlsruhe Institute of Technology, Karlsruhe, 51 pp., Germany, 2014.
- Bosch, H., Camy-Peyret, C., Chipperfield, M. P., Fitzenberger, R., Harder, H., Platt, U., and Pfeilsticker, K.: Upper limits of stratospheric IO and OIO inferred from center-to-limb-darkening-corrected balloon-borne solar occultation visible spectra: implications for total gaseous iodine and stratospheric ozone, *J. Geophys. Res.-Atmos.*, 108, 4455, doi:10.1029/2002JD003078, 2003.

Development of a digital mobile solar tracker

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



**Development of
a digital mobile solar
tracker**

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Butz, A.: Case studies of stratospheric nitrogen, chlorine and iodine photochemistry based on balloon borne UV/Vis and IR absorption spectroscopy, Ph.D. dissertation, Ruperto Carola University of Heidelberg, Heidelberg, Germany, 254 pp., 2006.

Coburn, S., Dix, B., Sinreich, R., and Volkamer, R.: The CU ground MAX-DOAS instrument: characterization of RMS noise limitations and first measurements near Pensacola, FL of BrO, IO, and CHOCHO, *Atmos. Meas. Tech.*, 4, 2421–2439, doi:10.5194/amt-4-2421-2011, 2011.

Gil, M., Puentedura, O., Yela, M., and Cuevas, E.: Behavior of NO₂ and O₃ columns during the eclipse of February 26, 1998, as measured by visible spectroscopy, *J. Geophys. Res.-Atmos.*, 105, 3583–3593, doi:10.1029/1999JD900973, 2000.

Gisi, M., Hase, F., Dohe, S., and Blumenstock, T.: Camtracker: a new camera controlled high precision solar tracker system for FTIR-spectrometers, *Atmos. Meas. Tech.*, 4, 47–54, doi:10.5194/amt-4-47-2011, 2011.

Grainger, J. and Ring, J.: Anomalous Fraunhofer line profiles, *Nature*, 193, p. 762, doi:10.1038/193762a0, 1962.

Hestroffer, D. and Magnan, C.: Wavelength dependency of the solar limb darkening, *Astron. Astrophys.*, 333, 338–342, 1998.

Ibrahim, O., Shaiganfar, R., Sinreich, R., Stein, T., Platt, U., and Wagner, T.: Car MAX-DOAS measurements around entire cities: quantification of NO_x emissions from the cities of Mannheim and Ludwigshafen (Germany), *Atmos. Meas. Tech.*, 3, 709–721, doi:10.5194/amt-3-709-2010, 2010.

Johansson, J. K. E., Mellqvist, J., Samuelsson, J., Offerle, B., Lefer, B., Rappenglueck, B., Flynn, J., and Yarwood, G.: Emission measurements of alkenes, alkanes, SO₂, and NO₂ from stationary sources in southeast Texas over a 5 year period using SOF and mobile DOAS, *J. Geophys. Res.-Atmos.*, 119, 1973–1991, doi:10.1002/2013JD020485, 2014a.

Johansson, J. K. E., Mellqvist, J., Samuelsson, J., Offerle, B., Moldanova, J., Rappenglueck, B., Lefer, B., and Flynn, J.: Quantitative measurements and modeling of industrial formaldehyde emissions in the Greater Houston area during campaigns in 2009 and 2011, *J. Geophys. Res.-Atmos.*, 119, 4303–4322, doi:10.1002/2013JD020159, 2014b.

Kille, N., Baidar, S., Sinreich, R., Ortega, I., Cooper, O., Hannigan, J., Hase, F., and Volkamer, R.: The CU Mobile Solar Occultation Flux instrument: measurements of NH₃, C₂H₆, HCHO and NO₂, in preparation, 2015.

**Development of
a digital mobile solar
tracker**

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



- Mellqvist, J., Samuelsson, J., Johansson, J., Rivera, C., Lefer, B., Alvarez, S., and Jolly, J.: Measurements of industrial emissions of alkenes in Texas using the solar occultation flux method, *J. Geophys. Res.-Atmos.*, 115, D00F17, doi:10.1029/2008JD011682, 2010.
- Merlaud, A., De Maziere, M., Hermans, C., and Cornet, A.: Equations for solar tracking, *Sensors*, 12, 4074–4090, doi:10.3390/s120404074, 2012.
- Platt, U. and Stutz, J.: *Differential Optical Absorption Spectroscopy: Principles and Applications*, Springer Verlag, Berlin-Heidelberg, Germany, 135–174, 2008.
- Rothman, L. S., Gordon, I. E., Babikov, Y., Barbe, A., Benner, D. C., Bernath, P. F., Birk, M., Bizzocchi, L., Boudon, V., Brown, L. R., Campargue, A., Chance, K., Cohen, E. A., Coudert, L. H., Devi, V. M., Drouin, B. J., Fayt, A., Flaud, J., Gamache, R. R., Harrison, J. J., Hartmann, J., Hill, C., Hodges, J. T., Jacquemart, D., Jolly, A., Lamouroux, J., Le Roy, R. J., Li, G., Long, D. A., Lyulin, O. M., Mackie, C. J., Massie, S. T., Mikhailenko, S., Mueller, H. S. P., Naumenko, O. V., Nikitin, A. V., Orphal, J., Perevalov, V., Perrin, A., Polovtseva, E. R., Richard, C., Smith, M. A. H., Starikova, E., Sung, K., Tashkun, S., Tennyson, J., Toon, G. C., Tyuterev, V. G., and Wagner, G.: The HITRAN 2012 molecular spectroscopic database, *J. Quant. Spectrosc. Ra.*, 130, 4–50, doi:10.1016/j.jqsrt.2013.07.002, 2013.
- Serdyuchenko, A., Gorshelev, V., Weber, M., Chehade, W., and Burrows, J. P.: High spectral resolution ozone absorption cross-sections – Part 2: Temperature dependence, *Atmos. Meas. Tech.*, 7, 625–636, doi:10.5194/amt-7-625-2014, 2014.
- Shaiganfar, R., Beirle, S., Sharma, M., Chauhan, A., Singh, R. P., and Wagner, T.: Estimation of NO_x emissions from Delhi using Car MAX-DOAS observations and comparison with OMI satellite data, *Atmos. Chem. Phys.*, 11, 10871–10887, doi:10.5194/acp-11-10871-2011, 2011.
- Sinreich, R., Coburn, S., Dix, B., and Volkamer, R.: Ship-based detection of glyoxal over the remote tropical Pacific Ocean, *Atmos. Chem. Phys.*, 10, 11359–11371, doi:10.5194/acp-10-11359-2010, 2010.
- Thalman, R. and Volkamer, R.: Temperature dependent absorption cross-sections of O₂-O₂ collision pairs between 340 and 630 nm and at atmospherically relevant pressure, *Phys. Chem. Chem. Phys.*, 15, 15371–15381, doi:10.1039/c3cp50968k, 2013.
- Vandaele, A., Hermans, C., Simon, P., Carleer, M., Colin, R., Fally, S., Merienne, M., Jenouvrier, A., and Coquart, B.: Measurements of the NO₂ absorption cross-section from 42 000 cm⁻¹ to 10 000 cm⁻¹ (238–1000 nm) at 220 K and 294 K, *J. Quant. Spectrosc. Ra.*, 59, 171–184, doi:10.1016/S0022-4073(97)00168-4, 1998.

**Development of
a digital mobile solar
tracker**

S. Baidar et al.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures



Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



- Volkamer, R., Spietz, P., Burrows, J., and Platt, U.: High-resolution absorption cross-section of glyoxal in the UV-vis and IR spectral ranges, *J. Photoch. Photobio. A*, 172, 35–46, doi:10.1016/j.jphotochem.2004.11.011, 2005.
- 5 Volkamer, R., Baidar, S., Campos, T. L., Coburn, S., DiGangi, J. P., Dix, B., Eloranta, E. W., Koenig, T. K., Morley, B., Ortega, I., Pierce, B. R., Reeves, M., Sinreich, R., Wang, S., Zondlo, M. A., and Romashkin, P. A.: Aircraft measurements of BrO, IO, glyoxal, NO₂, H₂O, O₂–O₂ and aerosol extinction profiles in the tropics: comparison with aircraft-/ship-based in situ and lidar measurements, *Atmos. Meas. Tech.*, 8, 2121–2148, doi:10.5194/amt-8-2121-2015, 2015.
- 10 Wang, S., Zhou, B., Wang, Z., Yang, S., Hao, N., Valks, P., Trautmann, T., and Chen, L.: Remote sensing of NO₂ emission from the central urban area of Shanghai (China) using the mobile DOAS technique, *J. Geophys. Res.-Atmos.*, 117, D13305, doi:10.1029/2011JD016983, 2012.

Development of a digital mobile solar tracker

S. Baidar et al.




Figure 1. Illustration of measurement principle of the mobile solar tracker and the MAX-DOAS aboard the mobile laboratory deployment during FRAPPE 2014.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

◀

▶

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Development of a digital mobile solar tracker

S. Baidar et al.




Figure 2. Instrumental setup during FRAPPE 2014. **(a)** The digital solar tracker mounted inside the roof hatch of the mobile laboratory; **(b)** optical schematic of the solar tracker; **(c)** processed image of the solar disk on the aperture plate showing fitted circles (green). The red circles show search region for circle fitting algorithm.

Title Page

Abstract

Introduction

Conclusions

References

Tables

Figures

◀

▶

◀

▶

Back

Close

Full Screen / Esc

Printer-friendly Version

Interactive Discussion



Development of a digital mobile solar tracker

S. Baidar et al.




Figure 3. Flowchart of the algorithm (see text for the details).

Title Page	
Abstract	Introduction
Conclusions	References
Tables	Figures
◀	▶
◀	▶
Back	Close
Full Screen / Esc	
Printer-friendly Version	
Interactive Discussion	



Development of
a digital mobile solar
tracker

S. Baidar et al.




Figure 4. Spectral fits of CLD reference for spectra taken at 0, 25 (0.095°) and 50 pixels (0.19°) off of the center of the solar disk. The optical density of the CLD fit result, and the Root Mean Square (RMS) residual that remains after subtracting all absorbers are also shown.

[Title Page](#)[Abstract](#)[Introduction](#)[Conclusions](#)[References](#)[Tables](#)[Figures](#)[◀](#)[▶](#)[◀](#)[▶](#)[Back](#)[Close](#)[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)

Development of a digital mobile solar tracker

S. Baidar et al.




Figure 5. Pointing precision during the RD#11 on 13 August 2014. Distributions of the deviations between the solar disk center and the aperture center in (a) x direction, (b) y direction. The black lines show the Gaussian fits to the data.

[Title Page](#)[Abstract](#)[Introduction](#)[Conclusions](#)[References](#)[Tables](#)[Figures](#)[Back](#)[Close](#)[Full Screen / Esc](#)[Printer-friendly Version](#)[Interactive Discussion](#)

Development of a digital mobile solar tracker

S. Baidar et al.




Figure 6. Pointing precision as a function of **(a)** vehicle speed, and **(b)** solar zenith angle during the RD#11 on 13 August 2014. The top, center and bottom of the box represent 75th, 50th (median) and 25th percentiles of the data.

Development of
a digital mobile solar
tracker

S. Baidar et al.




Figure 7. Timeseries of NO_2 VCD measured by the DS-DOAS (blue) and the MAX-DOAS (red) aboard the mobile laboratory during the RD#14 on 18 August 2014 in Northern Colorado. The EA (green) and the azimuth angle (Az, brown) for the DS-DOAS (dashed) and the MAX-DOAS (solid) instruments are shown in (a). (c and d) show expansion into two nine minutes period (grey boxes) when (i) difference in EA and Az between the two instruments were $\sim 10^\circ$ and $\sim 70^\circ$ and (ii) difference in EA and Az were $\sim 25^\circ$ and $\sim 140^\circ$. The yellow line represents the DS-DOAS data averaged to the MAX-DOAS timestamp.