Atmos. Meas. Tech. Discuss., 8, 12329–12381, 2015 www.atmos-meas-tech-discuss.net/8/12329/2015/ doi:10.5194/amtd-8-12329-2015 © Author(s) 2015. CC Attribution 3.0 License.



This discussion paper is/has been under review for the journal Atmospheric Measurement Techniques (AMT). Please refer to the corresponding final paper in AMT if available.

Evaluation of three lidar scanning strategies for turbulence measurements

J. F. Newman^{1,a}, P. M. Klein¹, S. Wharton², A. Sathe³, T. A. Bonin^{1,b}, P. B. Chilson^{1,4}, and A. Muschinski⁵

¹School of Meteorology, University of Oklahoma, Norman, OK, USA

²Atmospheric, Earth and Energy Division, Lawrence Livermore National Laboratory, Livermore, CA, USA

³DTU Wind Energy, Risø Campus, Roskilde, Denmark

⁴Advanced Radar Research Center, University of Oklahoma, Norman, OK, USA

⁵NorthWest Research Associates, Boulder, CO, USA

^anow at: National Wind Technology Center, National Renewable Energy Laboratory, Golden, CO, USA

^bnow at: Cooperative Institute for Research in the Environmental Sciences,

University of Colorado, and National Oceanic and Atmospheric Administration/Earth System Research Laboratory, Boulder, CO, USA

Received: 23 October 2015 – Accepted: 6 November 2015 – Published: 24 November 2015

Correspondence to: J. F. Newman (jennifer.newman@nrel.gov)

Published by Copernicus Publications on behalf of the European Geosciences Union.



Abstract

Several errors occur when a traditional Doppler-beam swinging (DBS) or velocityazimuth display (VAD) strategy is used to measure turbulence with a lidar. To mitigate some of these errors, a scanning strategy was recently developed which employs six

- ⁵ beam positions to independently estimate the *u*, *v*, and *w* velocity variances and covariances. In order to assess the ability of these different scanning techniques to measure turbulence, a Halo scanning lidar, WindCube v2 pulsed lidar and ZephIR continuous wave lidar were deployed at field sites in Oklahoma and Colorado with collocated sonic anemometers.
- Results indicate that the six-beam strategy mitigates some of the errors caused by VAD and DBS scans, but the strategy is strongly affected by errors in the variance measured at the different beam positions. The ZephIR and WindCube lidars overestimated horizontal variance values by over 60 % under unstable conditions as a result of variance contamination, where additional variance components contaminate the true
- value of the variance. A correction method was developed for the WindCube lidar that uses variance calculated from the vertical beam position to reduce variance contamination in the *u* and *v* variance components. The correction method reduced WindCube variance estimates by over 20% at both the Oklahoma and Colorado sites under unstable conditions, when variance contamination is largest. This correction method can
- ²⁰ be easily applied to other lidars that contain a vertical beam position and is a promising method for accurately estimating turbulence with commercially available lidars.

1 Introduction

Atmospheric turbulence, a measure of small-scale fluctuations in wind speed, impacts a number of fields, including air quality (e.g. Collier et al., 2005), aviation (e.g., Clark

et al., 2000), and numerical weather prediction (e.g., Bright and Mullen, 2002). In particular, lidar-measured turbulence is a significant parameter in the wind energy indus-





try, where high-resolution measurements are often needed in remote locations. Wind power production can differ substantially as a result of turbulence (e.g., Wharton and Lundquist, 2012; Clifton and Wagner, 2014), and turbulence can induce damaging loads on the turbine blades, reducing the turbine's reliability and expected lifetime (e.g.,

⁵ Kelley et al., 2006). Thus, turbulence is an extremely important parameter to measure in the wind farm site selection and design process.

In the wind power industry, turbulence is typically estimated from cup anemometer measurements on meteorological towers. Measurements from cup anemometers are limited by tower height and can be plagued by issues with overspeeding and slow

- ¹⁰ response times, which can lead to inaccurate mean wind speed and turbulence measurements (Kaimal and Finnigan, 1994). Sonic anemometers can measure turbulence much more accurately than cup anemometers, but are also limited by tower height. In response to these issues, remote sensing devices, such as sodars (sound detection and ranging) and lidars (light detection and ranging), have recently emerged as
- ¹⁵ a promising alternative to anemometers on towers. Although the ability of wind lidars to accurately measure mean horizontal wind speeds has been well-documented in the literature (e.g., Sjöholm et al., 2008; Pichugina et al., 2008; Peña et al., 2009; Barthelmie et al., 2013; Machta and Boquet, 2013; Sathe et al., 2015), the measurement of turbulence with lidars is still an active area of research (Sathe and Mann, 2013).
- ²⁰ While cup anemometers measure wind speed at a small point in space, remote sensing devices report an average wind speed from a probe volume (typically 30–150 m in the vertical) and usually take measurements less frequently than tower-mounted instruments. These differences in spatial and temporal resolution lead to differences in the turbulence measured by cup anemometers and remote sensing devices (e.g.,
- Peña et al., 2009; Westerhellweg et al., 2010; Krishnamurthy et al., 2014). In addition, the scanning strategy used by the remote sensing device can induce errors in the different turbulence components (Sathe and Mann, 2012).

Most commercially available lidars employ a Doppler beam-swinging (DBS; Strauch et al., 1984) technique or a velocity–azimuth display (VAD; Browning and Wexler, 1968)





technique to collect wind speed measurements. Using lidar DBS and VAD scans, the variances of the *u*, *v*, and *w* velocity components are not directly measured; rather, the DBS and VAD techniques combine radial velocity measurements from different points around the scanning circle to calculate instantaneous values of the velocity components. The time series of *u*, *v*, and *w* are then used to calculate the velocity variances, whereby it is implicitly assumed that the instantaneous velocity values are constant across the scanning circle. In turbulent flow, this assumption is not valid even if the mean flow is homogenous across the scanning circle, and the standard DBS and VAD approach for computing variances is thus flawed by variance contamination er-

- ¹⁰ rors (Sathe and Mann, 2012). A different variance calculation approach was proposed by Sathe (2012) using a novel six-beam scanning technique, which utilizes the radial velocity variance values from six lidar beam positions to independently calculate the six unique components of the Reynolds stress tensor, i.e., the velocity variances and covariances.
- Sathe et al. (2015) evaluated the six-beam technique at the Danish National Test Center for Large Wind Turbines in Høvsøre, Denmark using the WindScanner lidar developed at Denmark Technical University. Sathe et al. (2015) found that the six-beam technique measured higher values of variance than the VAD technique for all stability classes, with values that were greater in magnitude and closest to the cup anemome-
- ter values under stable conditions. These findings are in contrast to observations presented by Sathe et al. (2011) for the same site, which indicate that lidars measure much larger values of variance under unstable conditions due to the larger turbulent motions present under these conditions. Sathe et al. (2015) attribute this difference to the wind directions selected for each of the studies; while only westerly wind directions
- were analyzed in the six-beam study, Sathe et al. (2011) analyzed only data that were associated with easterly wind directions. Since the WindScanner used by Sathe et al. (2015) was located 2 km east of the coast of the North Sea, data from the westerly wind direction could be influenced by the land-sea transition. As discussed by Sathe et al. (2015), this transition likely caused an internal boundary layer to develop, which,





in conjunction with the current atmospheric stability regime, would affect the turbulent scales of motion intercepted by the lidar and the cup anemometer.

The six-beam technique, like the DBS and VAD techniques, is affected by volume averaging within the lidar probe volume. All three of these techniques also assume the

- three-dimensional flow is horizontally homogeneous across the scanning circle used by the lidar, which is often not a valid assumption (e.g., Wainwright et al., 2014; Lundquist et al., 2015), especially in complex terrain (e.g., Bingöl et al., 2009). All lidar scanning strategies are subject to sources of error, and the magnitude of these errors is largely dependent on atmospheric stability, measurement height, and the particular type of lidor used (a.g., Sother et al., 2011). Wind energy developers and researchere must known.
- dar used (e.g., Sathe et al., 2011). Wind energy developers and researchers must know how accurately their lidar can measure turbulence under different conditions if they want to use turbulence information for resource assessment or site suitability studies.

The main goals of this study are to evaluate the accuracy of lidar turbulence measurements and to provide guidance about lidar scanning strategies for wind energy ap-

- plications. To this end, three main research questions are addressed in this work: (1) how well do two commonly used scanning strategies (the DBS and VAD techniques) measure turbulence under different stability conditions? (2) How well does the new six-beam technique measure turbulence under different stability conditions? and (3) can new data processing techniques reduce the errors in velocity variance calculations
- from lidar DBS scans? To address these questions, turbulence measured with the various techniques is compared to turbulence measured by 3-D sonic anemometers on tall towers at sites in Oklahoma and Colorado. Sonic anemometer data from the Boulder Atmospheric Observatory (BAO) in Colorado are used to quantify the additional terms that occur as a result of variance contamination and to develop improved data pro-
- ²⁵ cessing techniques that reduce variance contamination errors. Data from the Southern Great Plains Atmospheric Radiation Measurements (ARM) site in Oklahoma provide a second location to test the new processing techniques with the DBS scan.

To the authors' knowledge, this work represents the first time the six-beam technique has been experimentally validated with high-frequency sonic anemometers and





commercially available lidars. The use of commercially available lidars allows for an evaluation of turbulence measured with lidar technologies and scanning strategies that are commonly employed in the wind energy industry.

2 Lidar scanning strategies and estimation of turbulence parameters

5 2.1 Current lidar technology

10

One frequently used lidar in the wind energy industry is the Leosphere WindCube lidar, a pulsed Doppler lidar that emits short pulses of laser energy to measure radial wind speed. The time series of the returned signal is then split up into blocks that correspond to range gates and processed to estimate the average radial wind speed at each range gate. The sign and magnitude of the radial wind speed are determined from the Doppler shift of the returned signal with respect to the original signal (Huffaker and Hardesty, 1000). The Leosphere WindCube we medal use used in this work.

1996). The Leosphere WindCube v2 model was used in this work.

Another type of Doppler lidar using pulsed 1.5 µm lasers is the Halo Streamline manufactured by Halo Photonics (Pearson et al., 2009). The Halo Streamline (thereafter referred to as Halo lidar) is a scanning lidar, which allows the user to configure and choose different types of scanning routines. In our study, the Halo was used to evaluate a six-beam and VAD scanning technique which are further detailed in the next section.

Unlike the WindCube and Halo lidars, the ZephIR is a continuous wave lidar and focuses the laser beam at different heights to obtain wind speed measurements. The ZephIR must collect velocity measurements individually at each measurement height, so it takes approximately 15 s to complete a full volumetric scan with 10 measurement heights. The probe length of the focused ZephIR beam increases with height, and thus, the size of the range gates is not constant. (The probe length is approximately 10 m at

²⁵ a range of 100 m, but much smaller closer to the ground; Slinger and Harris, 2012.) The ZephIR continuously receives backscattered radiation, so it can collect data at ranges



as low as 10 m. However, the ZephIR cannot determine the direction of the Doppler shift in the received time series, and there is a 180° ambiguity in the wind direction. The ZephIR 300, which was used in this work, has an attached met station with wind direction measurements, which can provide an estimate for the remotely measured wind direction (Slinger and Harris, 2012). However, this estimated wind direction was not always accurate during our field campaign in Colorado, and wind direction information from the sonic anemometers had to be used to correct the ZephIR wind direction measurements.

2.2 General conventions

- In this work, we follow standard meteorological conventions for u, v, and w, where u is the east-west component (u > 0 for wind coming from the west), v is the north–south component (v > 0 for wind coming from the south), and w is the vertical component (w > 0 for upward motion). Lidar data are presented using a spherical coordinate system, where θ is the azimuthal angle of the lidar beam measured clockwise from true
- ¹⁵ north and ϕ is the elevation angle of the lidar beam measured from the ground. The radial velocity, v_r , measured by the lidar is defined as positive for motion away from the lidar and negative for motion toward the lidar.

All three lidar systems evaluated in this study use some variant of a plan-position indicator (PPI) scan to measure the three-dimensional wind components, where the lidar takes measurements at several azimuth angles around a scanning circle at a constant elevation angle. In a horizontally homogeneous atmosphere, the radial velocity values measured by a lidar completing a PPI scan should take the following form (Weitkamp, 2005):

 $v_{\rm r} = u \sin \theta \cos \phi + v \cos \theta \cos \phi + w \sin \phi.$

²⁵ When calculating velocity variances from Eq. (1), two different approaches can be used. The standard method is to apply DBS or VAD analysis techniques to the PPI



(1)

data to compute instantaneous values of u, v, and w for each time stamp. The variances are then computed using

$$\overline{{u'_i}^2} = \overline{(u_i(t) - \overline{u_i})^2},$$

5

whereby the index i = 1, 2, 3 refers to the three velocity components u, v, and w and the overbar denotes temporal averaging.

The second method involves first computing the variance of the radial velocities given by Eq. (1):

$$\overline{v_r'^2} = \overline{u'^2}\cos^2\phi\sin^2\theta + \overline{v'^2}\cos^2\phi\cos^2\theta + \overline{w'^2}\sin^2\phi + 2\overline{u'v'}\cos^2\phi\cos\theta\sin\theta + 2\overline{u'w'}\cos\phi\sin\phi\sin\theta + 2\overline{v'w'}\cos\phi\sin\phi\cos\theta.$$

¹⁰ The variances and covariances of the velocity components u, v, and w create a set of six unknown variables. By using six different beam positions (i.e., different combinations of θ and ϕ), a set of equations can be solved for the six unknown variables (Sathe, 2012).

The different lidar scanning and data analysis approaches for computing mean val-¹⁵ ues and variances of *u*, *v*, and *w* are discussed in more detail in the following sections. For reference, a schematic of the DBS and VAD scanning strategies can be found in Sect. 12.4.3 of Weitkamp (2005).

2.3 WindCube v2: DBS technique

The WindCube v2 measures wind speed with a DBS technique, where an optical switch is used to point the lidar beam in the four cardinal directions (north, east, south, and west) at an elevation angle of 62° from the ground. Equations for the instantaneous radial velocities measured at the four beam positions can be derived by letting



(2)

(3)

$\theta = 0$	0,	90,	180,	and	270°	in	Eq.	(1)):
--------------	----	-----	------	-----	------	----	-----	-----	----

 $v_{r1} = v_1 \cos \phi + w_1 \sin \phi,$

$$v_{r2} = u_2 \cos \phi + w_2 \sin \phi$$

$$v_{r3} = -v_3 \cos \phi + w_3 \sin \phi,$$

$${}_{5} \quad v_{r4} = -u_4 \cos \phi + w_4 \sin \phi,$$

10

where u_j , v_j , and w_j are the instantaneous values of the velocity components at the 4 beam positions, and the index j = 1,2,3, and 4 describes the values measured by the north-, east-, south-, and west-pointing beams, respectively. Some WindCube lidars, including the model used here, add a vertically pointing beam position, v_{rz} , which provides a direct measurement of the vertical velocity, w ($v_{r5} = w_5$). It takes the Wind-Cube lidar one second to collect data at each beam location and steer the beam to the next beam location such that a full DBS scan takes approximately 4–5 s. However, the

WindCube velocity algorithm calculates the *u*, *v*, and *w* components every one second using the current radial velocity and the radial velocities obtained from the previous three beam locations (Peña et al., 2015).

In lidar studies, Eqs. (4)–(7) are usually solved for u, v, and w assuming that the flow is homogenous, i.e., the mean values of the three-dimensional wind components do not change across the scanning circle (e.g., Peña et al., 2015). Letting $\overline{u_2} = \overline{u_4} = \overline{u}$, $\overline{v_1} = \overline{v_3} = \overline{v}$, and $\overline{w_1} = \overline{w_2} = \overline{w_3} = \overline{w_4} = \overline{w}$ equations for the mean velocity values can be found:

$$\overline{u} = \frac{\overline{v_{r2}} - \overline{v_{r4}}}{2\cos\phi},$$

$$\overline{v} = \frac{\overline{v_{r1}} - \overline{v_{r3}}}{2\cos\phi},$$

$$\overline{w} = \frac{P(\overline{v_{r1}} + \overline{v_{r3}}) + Q(\overline{v_{r2}} + \overline{v_{r4}})}{2\sin\phi},$$
(8)
(9)
(10)

Discussion Paper AMTD 8, 12329-12381, 2015 **Evaluation of three** lidar scanning strategies for **Discussion** Paper turbulence measurements J. F. Newman et al. **Title Page** Abstract Introduction **Discussion** Paper Conclusions References Tables Figures Back Close **Discussion** Paper Full Screen / Esc Printer-friendly Version Interactive Discussion

(4)

(5) (6)

(7)

where $P = \cos^2\Theta$, $Q = \sin^2\Theta$, and Θ (degrees) is the wind direction. The \overline{w} equation is a slightly modified version of the true DBS solution and is used by Leosphere to calculate the *w* velocity for the WindCube lidar (e.g., Sathe et al., 2011). If a fifth, vertical beam is used, the mean value of the vertical velocity component can also be calculated as $\overline{w} = \overline{v_{r5}}$.

Equations (8)–(10) are derived assuming that the values of u, v, and w remain constant across the scanning circle. While this assumption is valid when computing mean values in homogenous flow, instantaneous velocity values will be highly variable due to the nature of turbulent flow, and the computation of instantaneous velocity values with Eqs. (8)–(10) is inaccurate. However, the standard DBS velocity variance calcula-

with Eqs. (8)–(10) is inaccurate. However, the standard DBS velocity variance calculation method uses Eqs. (8)–(10) to compute instantaneous values of u, v, and w, which leads to the variance contamination errors discussed in the literature (Sathe and Mann, 2012).

2.4 WindCube v2: novel method to reduce DBS variance contamination

¹⁵ The errors associated with the standard DBS variance method can be illustrated by applying Reynolds decomposition to the instantaneous velocity values at each beam position. For the first and third beam positions, the following set of equations is obtained:

 $v_{1} = \overline{v} + v'_{1}$ $w_{1} = \overline{w} + w'_{1}$ $v_{3} = \overline{v} + v'_{3} = v_{1} - v'_{1} + v'_{3}$ $w_{3} = \overline{w} + w'_{3} = w_{1} - w'_{1} + w'_{3},$

whereby the mean values \overline{v} and \overline{w} can be assumed to be constant across the scanning circle but the turbulent velocity fluctuations will differ ($v'_1 \neq v'_3$ and $w'_1 \neq w'_3$). Combining Eqs. (4)–(7), an equation for the instantaneous velocity at beam position 1 can then be



(11)



derived:

V

$$v_1 = \frac{v_{r1} - v_{r3} - dv\cos\phi + dw\sin\phi}{2\cos\phi},$$
 (12)

whereby $dv = v'_3 - v'_1$ and $dw = w'_3 - w'_1$. Comparing Eqs. (12) and (9), illustrates how turbulent fluctuations at the different beam positions, reflected by nonzero values of dv and dw, affect the computation of instantaneous velocity values.

Taking the variance of Eq. (12) gives the following equation:

$$\overline{v_{1}^{\prime 2}} = \frac{1}{4\cos^{2}\phi} \left(\overline{v_{r1}^{\prime 2}} + \overline{v_{r3}^{\prime 2}} - 2\overline{v_{r1}^{\prime}v_{r3}^{\prime}} - 2\overline{v_{r1}^{\prime}dv}\cos\phi + 2\overline{v_{r1}^{\prime}dw}\sin\phi + 2\overline{v_{r3}^{\prime}dv}\cos\phi - 2\overline{v_{r3}^{\prime}dw}\sin\phi + \overline{dv^{2}}\cos^{2}\phi - 2\overline{dvdw}\sin\phi\cos\phi + \overline{dw^{2}}\sin^{2}\phi \right)$$
$$= \frac{1}{4\cos^{2}\phi} \left(\overline{v_{r1}^{\prime 2}} + \overline{v_{r3}^{\prime 2}} - 2\overline{v_{r1}^{\prime}v_{r3}^{\prime}} + \overline{dv^{2}}\cos^{2}\phi - 2\overline{dvdw}\sin\phi\cos\phi + \overline{dw^{2}}\sin^{2}\phi \right),$$
(13)

- where in the final version of the equation, primes denote deviations from the temporal mean and for homogeneous flow, we can assume that $v_{r1}dv = v_{r3}dv$, $v_{r1}dw = v_{r3}dw$, and dv = dw = 0. The terms involving dv and dw appear because data are being combined from two different beam positions to estimate the v variance. These terms can be further modified by taking into account that $dv = v'_3 - v'_1$ and $dw = w'_3 - w'_1$. Assuming
- ¹⁵ $\overline{v'_3 w'_3} = \overline{v'_3 w'_1} = \overline{v'_1 w'_3} = \overline{v'_1 w'_1}$, the term $\overline{dv dw} = 0$. We can further assume that ${v'_3}^2 = {v'_1}^2$ and that velocity fluctuations at beam position 3 can be expressed as velocity fluctuations at beam position 1 translated in space and time. Thus, we let $v'_3 = v'_1(x + r, t + \tau)$, i.e., $\overline{v'_1 v'_3} = \rho_v(r, \tau) \overline{v'_1}^2$, whereby $\rho_v(r, \tau)$ is the autocorrelation function of the *v* component, *r* describes the spatial separation distance between the two beams, and τ the ²⁰ time shift between the measurements at the two beam locations. Similar arguments





can be made for the terms involving the w components, which leads to the following equations for the remaining extra terms:

$$\overline{dv^2} = 2\overline{v_1'^2}(1 - \rho_v(r, \tau)), \qquad (14)$$

$$\overline{dw^2} = 2\overline{w_1'^2}(1 - \rho_w(r, \tau)). \qquad (15)$$

Combining Eqs. (14) and (15) with Eq. (13) gives the final expression for the variance 5 of the v velocity component, whereby the beam location index is only used when referring to the radial velocities, and the subscript DBS is added to the variances of the velocity components to indicate that these equations are in fact applied when using the standard DBS calculation method:

$${}_{10} \quad \overline{v'^{2}}_{\text{DBS}} = \frac{\overline{v'_{r1}^{2}} + \overline{v'_{r3}^{2}} - 2\overline{v'_{r1}v'_{r3}} + 2(1 - \rho_{w}(r, \tau))\overline{w'^{2}}\sin^{2}\phi}{2(1 + \rho_{v}(r, \tau))\cos^{2}\phi}, \quad (16)$$

where the vertical velocities are assumed to be directly measured with a fifth vertically pointing beam. Following the same approach, the equation for the variance of the u velocity component can be derived:

$$\overline{{u'}^2}_{\text{DBS}} = \frac{\overline{v'_{r2}}^2 + \overline{v'_{r4}}^2 - 2\overline{v'_{r2}}v'_{r4}} + 2(1 - \rho_w(r, \tau))\overline{w'}^2 \sin^2\phi}{2(1 + \rho_u(r, \tau))\cos^2\phi}.$$
(17)

For collocated, simultaneous measurements ($r = \tau = 0$), the value of the autocorrela-15 tion functions $\rho_{\nu}(r,\tau) = \rho_{\mu}(r,\tau) = \rho_{\mu}(r,\tau) = 1$ and Eqs. (16) and (17) reduce to

$$\overline{v'^{2}_{00}} = \frac{\overline{v'_{r1}^{2} + v'_{r3}^{2} - 2v'_{r1}v'_{r3}}}{\frac{4\cos^{2}\phi}{\frac{4\cos^{2}\phi}{\frac{1}{v'^{2}_{00}}}},$$
$$\overline{v'^{2}_{00}} = \frac{\overline{v'_{r2}^{2} + v'_{r4}^{2} - 2v'_{r2}v'_{r4}}}{4\cos^{2}\phi},$$

strategies for **Discussion** Paper turbulence measurements J. F. Newman et al. **Title Page** Abstract Introduction Discussion Paper Conclusions References Tables Back **Discussion** Pape Full Screen / Esc Printer-friendly Version Interactive Discussion

AMTD

8, 12329-12381, 2015

Evaluation of three lidar scanning

Discussion Paper

(18)

(19)



Figures

Close

12340

where the index indicates that $r = \tau = 0$. Equations (18) and (19) describe the velocity variances that would represent point-like statistics and that we would like to retrieve from the lidar observations. Combining Eqs. (16) and (17) with Eqs. (18) and (19) leads to:

$$\overline{v'^{2}_{00}} = \frac{(1+\rho_{v}(r,\tau))}{2} \overline{v'_{\text{DBS}}}^{2} - \frac{(1-\rho_{w}(r,\tau))w'^{2}\sin^{2}\phi}{2\cos^{2}\phi},$$
(20)

$${}_{5} \quad \overline{{u'}^{2}}_{00} = \frac{(1+\rho_{u}(r,\tau))}{2} \overline{{u'}_{\text{DBS}}}^{2} - \frac{(1-\rho_{w}(r,\tau)) \overline{{w'}^{2}} \sin^{2} \phi}{2\cos^{2} \phi}.$$
(21)

Given the actual spatial separation and time shift between different lidar beams, the autocorrelation function values are all less than 1 and the correction terms in Eqs. (20) and (21) may become significant.

The second term in Eqs. (20) and (21) contains the ratio $\sin^2 \phi / \cos^2 \phi$, which is ap-¹⁰ proximately equal to 3.54 for the WindCube v2 elevation angle of 62°. This illustrates that ignoring the contribution of fluctuations in the instantaneous values of *w* for the WindCube v2 can lead to a large overestimation of the horizontal velocity variances during convective conditions when w'^2 is large. The actual values of the autocorrelation functions will depend on atmospheric stability and wind speed, which complicates ¹⁵ applying corrections to the DBS variance calculations.

If we assume that $dv^2 = dw^2$, which can be justified if the variances and autocorrelation functions of the vertical and horizontal velocity coordinates are similar (see Eqs. 14 and 15), Eq. (13) can be further simplified to

$$\overline{v'_{\text{DBS}}^{2}} = \frac{1}{4\cos^{2}\phi} \left(\overline{v'_{r1}}^{2} + \overline{v'_{r3}}^{2} - 2\overline{v'_{r1}v'_{r3}} + \overline{dw^{2}} \right)$$
$$= \overline{v'_{00}}^{2} + \frac{1}{4\cos^{2}\phi} \left(\overline{dw^{2}} \right)$$
$$= \overline{v'_{00}}^{2} + \frac{1}{4\cos^{2}\phi} 2\overline{w'_{1}}^{2} (1 - \rho_{w}(r, \tau)),$$

20

Discussion Paper AMTD 8, 12329-12381, 2015 **Evaluation of three** lidar scanning strategies for **Discussion** Paper turbulence measurements J. F. Newman et al. **Title Page** Abstract Introduction **Discussion** Paper Conclusions References Figures Tables Back Close **Discussion** Pape Full Screen / Esc Printer-friendly Version Interactive Discussion

CC II

(22)

(23)

and similarly,

10

$$\overline{{u'}_{\text{DBS}}^2} = \overline{{u'}_{00}^2} + \frac{1}{4\cos^2\phi} 2\overline{{w'}_1^2}(1 - \rho_w(r, \tau)).$$

These simplified equations provide the advantage that the variances of *u* and *v* computed from the DBS equations can be corrected if the vertical velocity component is ⁵ measured with a direct vertical beam, as was the case in our study, and an estimate of $\rho_w(r, \tau)$ can be made.

In Sect. 5.1, sonic anemometer and lidar measurements are used to evaluate the autocorrelation function $\rho_w(r, \tau)$, and the feasibility of applying the simplified correction algorithm (Eqs. 23 and 24) under a range of different stability conditions is discussed. Testing the more general expression (Eqs. 20 and 21) is planned in future studies but it will require more detailed measurements of the autocorrelation functions.

2.5 ZephIR 300: VAD technique

The ZephIR lidar employs a rotating mirror to conduct a 50-point VAD scan at each measurement height, using a similar elevation angle to the WindCube lidar ($\phi = 60^{\circ}$

¹⁵ for the ZephIR compared to $\phi = 62^{\circ}$ for the WindCube lidar). For the VAD technique, the radial velocities measured by the instrument should create a rectified cosine curve as a function of azimuth angle (Lhermitte and Atlas, 1961), as in Eq. (1). In a standard VAD analysis, the curve is assumed to fit the following equation:

$$v_{\rm r}(\theta) = a + b\cos(\theta - \theta_{\rm max}),$$

²⁰ where θ (degrees) is the azimuthal angle of the lidar beam, a (ms⁻¹) is the offset of the curve from the zero-velocity line, b (ms⁻¹) is the amplitude of the curve, and θ_{max} (degrees) is the phase shift of the curve. Assuming a homogeneous flow field with no convergence or divergence, the horizontal wind speed, wind direction, and vertical



(24)

(25)



wind speed are then derived from the following relations:

$$v_{\rm h} = \frac{b}{\cos(\phi)},$$
$$WD = \theta_{\rm max},$$
$$w = \frac{a}{\sin(\phi)},$$

⁵ where *a*, *b*, and θ_{max} are typically determined from a least-squares approach. The values of *u* and *v* can then be derived from the horizontal wind speed, v_h , and the wind direction.

Equations (26)–(28) are derived from the first-order coefficients of a Fourier decomposition of the radial velocity field, while higher-order terms in the Fourier decomposi-

- tion are related to divergence and deformation (Browning and Wexler, 1968). Although these higher-order terms are typically ignored in VAD analysis of lidar data, neglecting the terms can lead to errors in the estimated wind speed and direction (e.g., Koscielny et al., 1984). Errors in the turbulent components can arise as a result of variance contamination. Similar to the DBS technique, the VAD technique involves combining data
- ¹⁵ from different beam positions with the assumption that the instantaneous velocity field is homogeneous across the scanning circle.

2.6 Six-beam technique

20

As discussed in the previous two sections, the use of either the DBS or the VAD technique introduces a number of known systematic errors into lidar turbulence calculations. Some of these errors can be mitigated when applying the second variance calculation method (Eq. 3), which involves solving a set of equations for different combinations of θ and ϕ to obtain all six components of the covariance matrix.

In this work, the six-beam technique developed by Sathe (2012) was evaluated using the user-configurable Halo lidar. Sathe (2012) developed the technique by using



(26)

(27)

(28)

a minimization algorithm to determine the optimum combination of θ and ϕ values that minimizes the random errors in the variance estimates. The optimal configuration found was as follows: five beams at an elevation angle of 45° that are equally spaced 72° apart (i.e., located at azimuths of 0, 72, 144, 216, and 288°), and one vertically pointed beam. This scanning strategy is hereafter referred to as the six-beam technique.

Solving Eq. (3) with the chosen values of θ and ϕ , the equations for the variances $\overline{u'^2}$, $\overline{v'^2}$, and $\overline{w'^2}$ based on the six-beam technique are:

$$\overline{u_{6b}^{\prime 2}} = -0.4 \overline{v_{r1}^{\prime 2}} + 1.05 \left(\overline{v_{r2}^{\prime 2}} + \overline{v_{r5}^{\prime 2}} \right) + 0.15 \left(\overline{v_{r3}^{\prime 2}} + \overline{v_{r4}^{\prime 2}} \right) - \overline{v_{r6}^{\prime 2}},$$

$$\overline{v_{6b}^{\prime 2}} = 1.2 \overline{v_{r1}^{\prime 2}} - 0.25 \left(\overline{v_{r2}^{\prime 2}} + \overline{v_{r5}^{\prime 2}}\right) + 0.65 \left(\overline{v_{r3}^{\prime 2}} + \overline{v_{r4}^{\prime 2}}\right) - \overline{v_{r6}^{\prime 2}},$$
(30)

 $W_{6b}^{\prime 2} = V_{r6}^{\prime 2},$

where subscript 6*b* indicates that the horizontal velocity variances are computed apply-

ing the six-beam technique, and subscripts 1–6 refer to the beam positions, with beams 1–5 spaced 72° apart in the scanning circle and beam 6 pointing vertically upward.

3 Measurement campaigns

- ¹⁵ The DBS and six-beam strategies were evaluated at a field site in Oklahoma, while all three scanning strategies were evaluated at a field site in Colorado. As the Colorado site featured a large amount of 3-D sonic anemometer verification data, this site will be described first and will be primarily used to draw conclusions about the accuracy of lidar turbulence measurements. These results will be corroborated by data collected during the Oklahama evacument.
- ²⁰ during the Oklahoma experiment. Instruments used to evaluate the various scanning techniques are summarized in Table 1.



(29)

(31)



3.1 LATTE

The Lower Atmospheric Thermodynamics and Turbulence Experiment (LATTE) was conducted from 10 February to 28 March 2014, with a small-scale extension of the project from 28 March to 28 April 2014. LATTE was conducted at the Boulder Atmospheric Observatory (BAO), a NOAA facility located in Erie, Colorado (Fig. 1a). The BAO site is situated approximately 25 km east of the foothills of the Rocky Mountains. Although the diurnal heating cycle can induce upslope and downslope winds in the vicinity of a mountain range (e.g., Defant, 1951), these effects are only expected to influence flow at the BAO when the synoptic-scale pressure gradient is weak (Hahn, 1091). During LATTE windo ware primerily partherly and wasterly the lower

¹⁰ 1981). During LATTE, winds were primarily northerly and westerly throughout the lower boundary layer and appeared to be mainly associated with the upper-level flow pattern.

One of the primary goals of LATTE was to evaluate the accuracy of lidar turbulence measurements. Thus, the 300 m tower at the BAO was instrumented with 3-D sonic anemometers at six different heights. As a result of a collaboration with the National

- ¹⁵ Center for Atmospheric Research (NCAR), NorthWest Research Associates, and the National Oceanic and Atmospheric Administration (NOAA) Earth System Research Laboratory (ESRL), we were able to mount two sonic anemometers at each measurement height on opposite booms such that at each height there would be at least one set of 3-D sonic anemometer measurements that were not strongly influenced by the wake
- of the tower. A Halo lidar owned by the University of Oklahoma (OU) along with a Wind-Cube v2 and ZephIR 300 lidar, both owned by Lawrence Livermore National Laboratory (LLNL), were deployed at the BAO for LATTE, in addition to several instruments owned by NCAR. The OU Halo lidar was located approximately 600 m south-southwest of the 300 m tower so that it could be used to verify wind speeds from an NCAR wind profiler.
- The WindCube was located in the same enclosure as the 300 m tower from 14 to 28 February 2014, then moved to the same location as the OU Halo lidar from 1 March to 28 April 2014. The ZephIR remained in the tower enclosure for the duration of the experiment (Fig. 1b).





3.2 LABLE 2

The Lower Atmospheric Boundary Layer Experiment (LABLE), took place in two phases: LABLE 1 was conducted from 18 September to 13 November 2012 and LABLE 2 was conducted from 12 June to 2 July 2013. LABLE 2 was a multi-lidar
⁵ experiment designed to test different scanning strategies and will be discussed in this work. Detailed information on the research goals and instrumentation of LABLE can be found in Klein et al. (2015). Both LABLE campaigns took place at the central facility of the Southern Great Plains Atmospheric Radiation Measurement (ARM) site. The ARM site is operated by the Department of Energy and serves as a field site for an extensive suite of various in situ and remote sensing instruments (Mather and Voyles, 2013). The location of the ARM site in northern Oklahoma is shown in Fig. 2a.

Locations of the lidars deployed during LABLE 2 are shown in Fig. 2b. The ARM Halo lidar is a scanning lidar operated by the ARM site and is nearly identical to the OU Halo lidar. The Galion lidar is a lidar rented by OU that has identical hardware to

- the two scanning Halo lidars. Data from 3-D sonic anemometers on a 60 m tower were also available at the ARM site, but could not be used to verify the six-beam lidar measurements as the tower was too short to overlap with the scanning lidar measurement heights (first range gate is 105 m). Data from the 60 m sonic anemometer could be directly compared to corresponding measurements from the WindCube lidar, which has
- a first range gate of 40 m, so only data from the WindCube lidar are shown in this work.
 Results from the scanning lidar portion of LABLE 2 are presented in Newman et al. (2015).





4 Data processing

20

4.1 Coordinate rotation

A coordinate rotation was applied to the sonic anemometer and lidar data to reduce the effects of alignment and tilt errors on the variance estimates (Foken, 2008). Following

- ⁵ the procedure outlined by Kaimal and Finnigan (1994), the coordinate axes were first rotated such that the mean meridional wind speed, \overline{v} , was set to zero and u was aligned with the 10 min mean wind direction. In the next step, the coordinate axes were rotated such that \overline{w} was equal to zero.
- Typically, the coordinate rotation is applied to the raw wind speed components before the variance is calculated, such that the variance is also defined in the new coordinate system. However, instead of first rotating the raw wind speed components, the variance values themselves from the old coordinate system can also be rotated such that *u* is aligned with the mean wind direction and \overline{v} is forced to 0, as in Sathe et al. (2015). The rotated variance components are described as follows:

¹⁵
$$\overline{u'^2}_{rot} = \overline{u'^2} \sin^2 \Theta + \overline{v'^2} \cos^2 \Theta + \overline{u'v'} \sin 2\Theta,$$
$$\overline{v'^2}_{rot} = \overline{u'^2} \cos^2 \Theta + \overline{v'^2} \sin^2 \Theta - \overline{u'v'} \sin 2\Theta,$$
$$\overline{w'^2}_{rot} = \overline{w'^2},$$

where Θ is the mean wind direction and the subscript rot refers to variance components in the rotated coordinate system. This rotation has the same effect as applying the first coordinate rotation to the original wind speed components before taking the variance. Thus, in comparisons with the six-beam technique, only the first coordinate rotation was applied to the lidar and sonic data to be consistent with the coordinate rotation used by Sathe et al. (2015).



(32)

(33)

(34)



4.2 Quality control

The actual sampling frequencies of the sonic anemometers and lidars drifted slightly around their prescribed sampling frequencies throughout the measurement campaigns, which is problematic for the calculation of variance. Thus, the raw wind speed data from the different instruments were linearly interpolated onto temporal grids with constant spacing that matched the sampling frequency of each instrument (1 Hz/0.25 Hz for the WindCube v2, 0.067 Hz for the ZephIR, 0.033 Hz for the Halo lidar, and 30 Hz (60 Hz) for the north (south) sonic anemometers at the BAO tower). The sonic anemometer data were additionally averaged to form 10 Hz data streams.

- The 10 Hz data streams were used in further calculations, as they served to reduce high-frequency noise in the sonic anemometer data as well as reduce processing time. (Values of the 30 min variance calculated from the 10 Hz data streams did not differ significantly from values calculated from the raw sonic anemometer data streams.) The 60 m sonic anemometer data at the ARM site were also interpolated to a 10 Hz grid.
- No averaging was needed for the ARM sonic data, as the output frequency of the ARM sonic anemometers is already 10 Hz (Table 1).

The spike filter developed by Højstrup (1993) and adapted by Vickers and Mahrt (1997) was used to flag outliers in the data. A 10 min window was shifted through the raw lidar and sonic anemometer data, and any point that was more than 3.5 standard deviations from the 10 min block average was flagged as a possible spike and removed from the dataset. This process was repeated until no more spikes were detected. For each pass through the spike filter, the factor of 3.5 standard deviations was increased by 0.1 standard deviations.

By default, WindCube radial velocities that were associated with Signal-to-Noise ratios (SNRs) lower than -23dB were flagged as missing values. For the scanning lidars, SNR thresholds were set to -23 and -17dB for the horizontal and vertical beams, respectively. The ZephIR lidar obtains an estimate of the mean noise level by taking measurements with the shutter closed before each full scan. Only signals with power





that exceeds a threshold of five standard deviations above this mean noise level are used to estimate the velocity (Slinger and Harris, 2012).

As Doppler lidars use the Doppler shift from aerosols to estimate radial velocity, they are adversely affected by the presence of precipitation particles, which can result in ⁵ beam attenuation and increased vertical velocities (e.g., Huffaker and Hardesty, 1996; Pearson et al., 2009). Thus, lidar data that were collected when rain gauges at the different field sites recorded precipitation were flagged as erroneous data.

4.3 Selection of averaging times

In order to mitigate the effects of random errors on variance calculations, Mahrt et al. (1996) and Vickers and Mahrt (1997) recommend averaging products of perturbations over a period of time that is longer than the local averaging length, *T*, the averaging time that is used to calculate mean values from which the perturbations are derived. In this work, the variance of each velocity component was defined as the mean value of $u_i'^2$ (calculated using *T* = 10 min) over a 30 min period, with *i* = 1,2,3 corresponding to

- u_i (calculated using r = 10 min) over a so min period, with r = 1, 2, 3 corresponding to the *u*, *v*, and *w* estimates, respectively. The typical averaging period for wind energy studies is 10 min, but a 30 min averaging period was used in this work to reduce the effects of noise on variance estimates, as in Sathe et al. (2015). The variance calculated with this method is hereafter referred to as the "30 min variance", although it differs from the standard calculation of 30 min variance.
- Mesoscale motions can also induce errors in variance calculations, as the mean of each variable can change significantly over the averaging period used to calculate variance as a result of a frontal passage or wind direction shift (Vickers and Mahrt, 1997). Thus, raw wind speed data were detrended using a linear detrend method for each hour-long record. The detrending method served to reduce high variance values that were associated with large shifts in wind speed or wind direction.



4.4 Stability classification

At the BAO, temperature and wind speed data were available at multiple heights on the tower, so the gradient Richardson number, Ri, was used as a stability parameter. Ri is defined by the following equation (Arya, 2001):

5
$$\operatorname{Ri} = \frac{g}{T_o} \frac{\frac{\partial \theta}{\partial z}}{(\frac{\partial U}{\partial z})^2}$$

10

where g (ms⁻²) is the gravitational acceleration, T_o (K) is the surface temperature, and $\frac{\partial U}{\partial z}$ (s⁻¹) and $\frac{\partial \theta}{\partial z}$ (Km⁻¹) are the vertical gradients of horizontal wind speed and potential temperature, respectively. In this work, the potential temperature gradient was approximated by adding the dry adiabatic lapse rate, Γ_d , to the temperature gradient, and the derivatives of temperature and wind speed were approximated by using a finite differencing approach, similar to the procedure used by Bodine et al. (2009):

$$\mathsf{Ri} = \frac{g[(T_{z2} - T_{z1})/\Delta z_T + \Gamma_d]\Delta z_U^2}{T_{z1}(U_{z2} - U_{z1})^2},$$

where *z*1 and *z*2 correspond to two different measurement heights, and Δz_T and Δz_U refer to the differences in measurement levels for *T* and *U*. As wind shear was often ¹⁵ extremely low during the daytime hours at the BAO, a bulk wind shear quantity was used in Eq. (36), i.e., $z_1 = 0$ m was assumed for wind speed, with $U_{z1} = 0 \text{ m s}^{-1}$. This bulk approximation eliminated the extremely large negative Ri values that were often produced at the BAO under unstable conditions as a result of the small difference between U_{z2} and U_{z1} .

²⁰ Due to unexpected tower maintenance at the ARM site, it was not often possible to measure the temperature and wind speed at two heights simultaneously. Thus, the Monin–Obukhov length, L (m), from the 60 m sonic was used to define stability instead.



(35)

(36)

L is defined by the following equation:

$$L = -\frac{u_*^3 \overline{\theta_v}}{\kappa g \overline{w' \theta_v'}},$$

where u_* (ms⁻¹) is the friction velocity, $\overline{\theta_{\nu}}$ (K) is the mean virtual potential temperature at the measurement height, κ is the von Kármán constant (commonly set to 0.4), and $\overline{w'\theta'_{\nu}}$ (ms⁻¹ K) is the heat flux measured at the surface (e.g., Arya, 2001). Negative values of both *L* and Ri indicate unstable conditions while positive values indicate stable conditions. As the datasets analyzed in this work are relatively small, only a broad classification of conditions as either stable or unstable was made.

5 Comparison of turbulence parameters: LATTE

- Figure 3 demonstrates the typical diurnal cycle of turbulence (\(\sigma_u^2\), \(\sigma_v^2\), and \(\sigma_w^2\)) at the BAO, with low values of turbulence occurring during the evening and overnight hours (approximately 00:00–12:00 UTC) and high values of turbulence occurring during day-time, convective conditions (approximately 12:00–00:00 UTC). (Note that for all LATTE plots, data from the NCAR sonics are shown, unless the mean wind direction corresponded to the NCAR sonic wake sector, in which case the OU sonics were used. Local time is UTC–7.) During this period, the wind direction generally shifted between easterly/southeasterly and northerly (Fig. 3e). However, from approximately 18:00 UTC
 - 23 March to 06:00 UTC 24 March, winds were primarily from the west/northwest, which is the direction of the Rocky Mountains. Flow from the mountains was associated with
- higher mean wind speeds and variances of the u and v velocity components in comparison to the rest of the period (Fig. 3).

The following sections focus on measurements from 25 March 2014, which was a calm, clear day with no precipitation when all three lidars had good data availability. Variance estimates from each lidar and scanning strategy are compared to similar



(37)

measurements made by the sonic anemometers and the other lidars. For most comparison plots, variance estimates from the measurement height where the lidar data availability was greatest are shown. For the WindCube and ZephIR lidars, which only collect measurements up to 200 ma.g.l., data from 100 ma.g.l. are shown. For the Halo lidar, which has a minimum range gate of 105 m, data from 200 ma.g.l. are shown.

5.1 DBS technique: WindCube

5

During the overnight hours of 25 March, variance values computed from the WindCube DBS data agreed well with sonic anemometer data, but between 15:00 and 21:00 UTC, the WindCube substantially overestimated the u and v variance (Fig. 4a and b). Sathe et al. (2011) attribute this overestimation to variance contamination, which artificially in-

creases the lidar-measured variance and is most prominent under unstable conditions, when the effects of volume averaging are minimized due to the relatively large turbulent eddy sizes. In Sect. 2.4, we presented a framework that further details the causes of variance contamination errors and provides equations for correcting variances com-¹⁵ puted from lidar DBS scans. These equations are now evaluated using sonic and lidar data.

5.1.1 Variance correction

As discussed in Sect. 2.4, instantaneous velocity values calculated from lidar DBS data contain extra terms, for example, the dv and dw terms in Eq. (12), which become large under convective conditions. The addition of these extra terms causes the WindCube to overestimate the magnitude of the instantaneous u and v velocity and artificially increases the variance, as shown in Eq. (13) and seen in Fig. 4a and b. Since these extra terms cannot be easily quantified from lidar data, sonic anemometer data were used to examine the impacts of temporal and spatial changes in the instantaneous velocity components on the resultant variance estimates.





At the BAO tower, two sonic anemometers were located approximately 11.5 m apart on opposite booms at each measurement height, which were used to simulate the measurement technique used by the WindCube lidar. First, sonic data were projected into the directions of the WindCube beam positions and projected data from the south sonic were shifted forward in time by two seconds to simulate the time it takes the WindCube lidar beam to move from one side of the scanning circle to the other. The time-shifted and projected sonic data were first used to compute the difference dw of the instantaneous velocity values at opposite booms on the tower, which allows evaluating the extra term involving dw^2 in Eqs. (23) and (24). Equation (15) can then be used to solve for the value of the autocorrelation function, $\rho_w(r, \tau)$, for r = 11.5 m and $\tau = 2$ s.

Sonic anemometer data from 22 to 26 March 2014 were used to estimate values of $\rho_w(r, \tau)$ for times when neither sonic was waked by the tower. Mean values of $\rho_w(r, \tau)$ calculated for stable and unstable conditions were 0.63 and 0.74, respectively. These values indicate that *w* does change significantly in both space and time and that values of *w* become decorrelated more quickly under stable conditions as a result of the presence of smaller turbulent scales of motion.

The mean values of $\rho_w(r,\tau)$ calculated from the sonic data were then used with Eqs. (23) and (24) to correct the sonic data. In the correction term, $(1/4\cos^2\phi)w_1'^2(1-$

²⁰ $\rho_w(r, \tau)$), the value of w'_1^2 was taken to be the velocity variance measured by the Wind-Cube vertical beam. Corrected *u* and *v* variance values on 25 March 2014 are indicated by the black dashed lines in Fig. 4. The variance correction does not significantly change variance values under stable conditions, when the value of $\overline{w'}^2$ is small, but it serves to reduce estimates of $\overline{u'}^2$ and $\overline{v'}^2$ by over 20% under unstable conditions, bringing them closer to the values measured by the sonics. In reality, the value of $\rho_w(r, \tau)$ needed for the correction should be smaller than the value that was calculated for the sonics, as the sonics were only located 11.5 m apart while the WindCube scanning cone has a diameter of 106 m at a measurement height of 100 m. Thus, there





is still some variance contamination present in the corrected u and v variance values shown in Fig. 4, as the values of $\rho_w(r, \tau)$ used in the correction do not fully represent the degree of decorrelation that occurs between the WindCube beams.

Another method to calculate values of $\rho_w(r, \tau)$ is to use a least-squares approach to

⁵ find the value of $\rho_w(r, \tau)$ that provides the best estimate for the sonic variance $({u'_{nn}}^2$ and

 v'_{00}^{2}) in Eqs. (23) and (24). This method yielded values of approximately 0.4 for $\rho_{w}(r, \tau)$ for both stable and unstable conditions, which is, as expected, lower than the values calculated from the sonic data. A true estimate of $\rho_{w}(r, \tau)$ for the distances spanned by the WindCube beams would require either sonic anemometers at different towers or a numerical model that provides wind speed data with high spatial and temporal resolution.

5.1.2 Methods for estimating *w* variance

10

Contamination errors also affect the variance of the w component if it is computed applying the DBS method, although it generally does not lead to variance overestimates, as volume averaging for the w component is more significant than it is for the u and

- *v* components (Sathe et al., 2011). However, the WindCube v2 lidar utilizes a vertical beam position once per scan to obtain a direct measurement of the vertical velocity directly above the lidar, which is only minimally affected by variance contamination. Both the vertical beam method and the DBS method (Eq. 10) were investigated in this work
- ²⁰ to determine the advantage of having a vertically pointed beam position to measure *w* variance. At the BAO, the *w* variance measured by the WindCube lidar's vertical beam was much higher and more accurate than the *w* variance calculated from the DBS equations, particularly under convective conditions (Fig. 4c). This is not surprising, as the vertical beam variance is a measure of the variance directly above the lidar (bar-
- ²⁵ ring the effects of volume averaging), while the DBS-estimated variance is an average across the scanning circle. Thus, in all further plots, *w* variance from the WindCube lidar is calculated from the vertical beam.



5.2 VAD technique: ZephIR, Halo

During post-processing, a VAD technique (Browning and Wexler, 1968) was used to calculate variance from the six-beam Halo data. The five off-vertical beams were fit to a sine curve to estimate the horizontal wind speed, wind direction, and vertical wind speed from each scan. This information was then used to create a time series for the u, v, and w components from which the variance could be calculated. Variance from the Halo VAD technique was compared to the variance estimated by the ZephIR lidar, which employs a 50-point VAD at each height as part of its scanning strategy, as well as variance measured by the sonic anemometers.

- ¹⁰ While the ZephIR-estimated *u* variance values were quite close to those measured by the sonic anemometers and the Halo lidar (Fig. 5a), the ZephIR overestimated the *v* variance under unstable conditions during some half-hourly periods (Fig. 5b), which could indicate that the ZephIR lidar VAD technique is also affected by variance contamination, similar to the WindCube lidar. Although the WindCube and ZephIR lidars use
- similar elevation angles (Table 1), the overestimation of v variance by the ZephIR lidar was not nearly as large as it was for the WindCube lidar. The ZephIR has variable range gate sizes and takes nearly four times as long to complete a full scan from 10 to 200 m as the WindCube lidar, so the lower temporal resolution of the ZephIR scans may have caused it to measure lower variance values than the WindCube lidar. The Halo lidar
- ²⁰ produced the most accurate VAD-estimated *u* and *v* variance values throughout the day (Fig. 5a and b), suggesting that a VAD technique with a lower elevation angle can measure horizontal variance values more accurately. The Halo lidar used an elevation angle of 45° while the WindCube and ZephIR lidars used elevation angles of 62° and 60°, respectively. Although the values of d*v* and d*w* were likely larger for the Halo lidar,
- ²⁵ since it used a wider scanning cone, the contribution of the dw^2 term to the *v* variance in Eq. (13) is smaller for lower values of ϕ . Additionally, the temporal resolution of the Halo lidar likely led to the measurement of lower variance values than the WindCube and ZephIR lidars, which may have masked the effects of variance contamination.





The ZephIR and Halo lidars measured similar *w* variance values with the VAD technique, which were underestimates in comparison to the sonic anemometer values for nearly all stability conditions throughout the day (Fig. 5c). As previously discussed, the most accurate lidar method for measuring the *w* variance appears to be the use of a vertical beam position to obtain a direct measurement of the vertical wind speed (Figs. 4c and 6c).

5.3 Halo: six-beam technique

Variance measured using the six-beam technique with the Halo lidar is compared to variance measured by the sonic anemometers in Fig. 6. Similar to the WindCube lidar, the six beam technique includes a vertically pointed beam to obtain a direct measure.

- the six-beam technique includes a vertically pointed beam to obtain a direct measurement of the vertical velocity. Vertical variance estimated by the Halo six-beam technique was much higher and more accurate than the vertical variance measured by the Halo VAD technique (Figs. 5c and 6c). However, larger discrepancies occurred in the *u* and *v* variance values. During strongly unstable conditions from 17:00 to 21:00 UTC, the Uple air beam technique often underectimeted the *u* and *u* variance values.
- ¹⁵ Halo six-beam technique often underestimated the *u* and *v* variance in comparison to the sonic anemometers (Fig. 6a and b). In some extreme cases, the *u* and *v* variance values became negative, which should be mathematically impossible given the definition of variance $(\sigma_{u_i}^2 = (u_i - \overline{u_i})^2)$.

In order to determine the cause of this horizontal variance underestimation and the negative variance values, it is instructive to examine the equations used to calculate the variance components with the six-beam technique (Eqs. 29–31). Equations (29) and (30) for the *u* and *v* variance, respectively, both include the term $-v_{r_6}^{\prime 2}$, meaning that the variance calculated from the vertical beam radial velocity is subtracted from the combination of the other terms. Thus, when $v_{r_6}^{\prime 2}$ is large, as is often the case under convective conditions (Fig. 6c), or overestimated due to instrument noise, a large value is subtracted in Eqs. (29) and (30), and the *u* and *v* variance can become negative if the other radial variances are not measured accurately. The other negative terms in



Eqs. (29) and (30) could also decrease the horizontal variance components and cause them to become negative. Similarly, if the positive terms in Eqs. (29) and (30) are underestimated, the variance values would also likely be underestimated. Although negative values of σ_u^2 and σ_v^2 only comprised approximately 5% of the horizontal variance values at 200 m during the 5 day analysis period, the underestimation of horizontal variance components by the six-beam technique is a significant issue that warrants further investigation.

Velocity data from the 200 m sonic anemometers were projected into the directions of the different Halo beam locations in order to assess the accuracy of the measurements from each beam position. Time series plots of the 30 min mean radial wind speeds and radial variance values measured by the sonics and Halo lidar on 25 March 2014 are shown in Fig. 7. During the afternoon of 25 March, mean wind speeds were very low (Fig. 7i), which is reflected by the low radial wind speeds measured by the Halo lidar and calculated from the projected sonic data (Fig. 7a–f). Some minor differences in the radial wind speeds measured by the Halo and sonic anemometer were evident

- in the late afternoon, as well as strongly underestimated and negative Halo u and v variance values (Fig. 7g and h). The largest discrepancies between the radial variance values also occurred in the late afternoon, when the Halo strongly underestimated the variance of the radial velocity at the third, fourth, and fifth beam positions (Fig. 7c–e). In
- ²⁰ the initial six-beam equations, terms $\overline{v'_{r3}^{2}}$, $\overline{v'_{r4}^{2}}$, and $\overline{v'_{r5}^{2}}$ have positive coefficients in the *u* variance equation (Eq. 29), and terms v'_{r3}^{2} and $\overline{v'_{r4}^{2}}$ have positive coefficients in the *v* variance equation while the $\overline{v'_{r5}^{2}}$ term has a negative coefficient (Eq. 30). The actual coefficients of the radial beam variances will change once the coordinate rotation is applied (Eqs. 32–34), but for the most part, weighted values of $\overline{v'_{r3}^{2}}$, $\overline{v'_{r4}^{2}}$, and $\overline{v'_{r5}^{2}}$ are added to the weighted values of the other radial beam variances to obtain values for the *u* and *v* variance. Thus, if the variance measured at beam positions 3, 4, and 5 is



12358

¹⁰ erogeneity and high values of variance could cause large amounts of scatter about the VAD sine curve (Weitkamp, 2005). The differences between the instantaneous radial velocities and the fit VAD sine curve (Eq. 25) were examined for 25 March, but no no-

underestimated, the u and v variance will also be underestimated. Similar trends were

Several factors may have caused the Halo lidar to underestimate the variance at cer-

tain beam positions more strongly than at other beam positions. One possible explanation for the variance discrepancies could be the presence of horizontal heterogeneity

across the lidar scanning circle. The six-beam technique requires the assumption that flow is homogeneous in the scanning circle encompassed by the five off-vertical beams,

and this assumption may not have been valid at the BAO, which is located in the vicinity

of complex terrain, especially at a measurement height of 200 m a.g.l. Horizontal het-

also observed on 24 March 2014 (not shown).

ticeable differences were evident for the different beam positions, although residuals were much larger under unstable conditions. A modeled flow field and lidar simulator
 ¹⁵ would likely be needed to definitively quantify the effect of horizontal heterogeneity on the variances measured by the different lidar beam positions.

Relative intensity noise (RIN) also may have affected the variance values measured by the Halo lidar on 25 March. RIN results from spontaneous radiation emissions from the laser, which cause intensity fluctuations in the laser oscillator (Chang, 2005). In

- a coherent heterodyne lidar, RIN appears as pink noise; i.e., it is mainly present in the low-frequency part of the Doppler spectrum (Courtney et al., 2008). Since low wind speeds would also be detected in the low frequency part of the spectrum, RIN can impact the accuracy of Doppler velocity measurements under low wind speeds. Peña et al. (2009) found that a ZephIR lidar most strongly underestimated the turbu-
- ²⁵ lence intensity measured by cup anemometers when weak wind speeds were measured.

As several of the Halo radial beams measured radial wind speeds that were close to 0 m s^{-1} during the afternoon of 25 March (Fig. 7a–f), it is possible that RIN caused the Halo lidar to underestimate the variance at certain beam positions. To further



CC ①

investigate this possibility, mean radial velocity and variance values were calculated for 6 March 2014, a date from the campaign when atmospheric conditions were less strongly convective and wind speeds were higher during the late afternoon (Fig. 8). Although there were some small biases in the radial wind speed measurements from

- the Halo lidar (Fig. 8a–f), there were no large discrepancies in the radial variance measurements on 6 March and no strongly underestimated or negative *u* and *v* variance values (Fig. 8g–h). This suggests that the six-beam technique is more accurate when wind speeds are higher, as radial variance estimates are more accurate under higher wind speed conditions and more accurate horizontal variance estimates are produced
- ¹⁰ as a result. However, it is difficult to make this assessment with the limited dataset available. For the five-day period selected for this study, there was no clear trend between the mean radial wind speed measured at each beam location and the error in Halo-measured variance at each beam location. It should be noted that the mean wind speeds measured during the afternoon of 25 March rarely exceeded 3 m s⁻¹, which ¹⁵ is below the typical cut-in speed for a modern wind turbine (e.g., Burton et al., 2001).
- Thus, variance measurements under low wind speeds would likely not be used for wind energy applications.

5.4 Application of six-beam technique to WindCube lidar

A technique similar to the six-beam strategy can be applied to the WindCube data by substituting the DBS values of θ and ϕ into Eq. (3). The u'v' term drops out because either $\cos \theta$ or $\sin \theta$ is equal to 0 for every beam position, resulting in five equations and five unknowns. Similar to the Halo six-beam technique, these equations can be solved simultaneously to obtain values of the *u*, *v*, and *w* variance, which can then be rotated into the coordinate system aligned with the mean wind.

Variance measured by the individual WindCube beams is compared to variance calculated from projected sonic data in Fig. 9. Similar to the Halo lidar (Figs. 7 and 8), the variance of the radial velocities was sometimes overestimated by the WindCube lidar and sometimes underestimated. Although there were no large discrepancies between





the WindCube and sonic radial variance under unstable conditions (14:00–23:00 UTC), the five-beam technique produced large u and v variance underestimates and several negative variance values (Fig. 9f and g). Thus, even when a lidar with better temporal resolution and a smaller scanning circle than the Halo lidar is used, the simultaneous use of all the radial beam velocity variances to calculate the u and v variance can result

in large uncertainties, especially during unstable conditions.

In summary, at this site, the WindCube and Halo lidars were not able to measure the radial beam variances accurately enough to estimate the horizontal variance values with a five- or six-beam technique, possibly because wind speeds at the site were often too low to accurately measure variance with lidars. In the next section, the five-

¹⁰ often too low to accurately measure variance with lidars. In the next section, the fivebeam technique is evaluated at the ARM site, where mean wind speeds were much higher in comparison to the BAO.

6 Comparison of turbulence parameters: LABLE 2

Plots of the 30 min variance, mean wind speed and direction, and Monin–Obukhov
length from the 60 m sonic over five days at the ARM site are shown in Fig. 10. Diurnal trends in the LABLE 2 turbulence parameters are similar to those seen in the LATTE data: turbulence is fairly low during overnight, stable conditions before increasing during daytime, convective conditions. However, mean wind speeds at the ARM site were generally much higher than at the BAO, and winds were nearly constantly from the south/southeast. In addition, variance values were generally much higher at the ARM site is located in much simpler terrain and SNR values tended to be much higher, so lidar variance measurements are expected to be more accurate.

Time series of 30 min radial variance values estimated at 60 m from projected sonic data and WindCube lidar data during LABLE 2 on 23 June 2013 are shown in the right panels of Fig. 9. In contrast to the case shown from the BAO (left panels in Fig. 9), variance values are higher throughout the day and the WindCube lidar nearly always



CC ① BY underestimated the radial variance values calculated from the projected sonic data (Fig. 9a-e). However, when applying the DBS method, the WindCube again overestimated the *u* and *v* variance under unstable conditions as a result of variance contamination (Fig. 9f and g).

- ⁵ The five-beam method and the variance correction method described in Sect. 5.1.1 were also applied to the 60 m WindCube data at the ARM site. Values of $\rho_w(r, \tau)$ obtained from the sonics at the BAO were used in the variance correction equations (Eqs. 23 and 24) to determine how well this correction worked at a different site. At the ARM site, both the five-beam method and variance correction method produced particular independent of the sonic state of the so
- ¹⁰ nearly identical variance values under stable conditions, while the five-beam method produced much lower variance values under unstable conditions (Fig. 9f and g). However, none of the five-beam u and v variance values were negative, in contrast to the BAO data. This likely occurred because the WindCube underestimated the variance from the radial velocities by approximately the same amount throughout the day. In
- ¹⁵ particular, the WindCube measured lower *w* variance values than the sonic anemometer during nearly all time periods on 23 June 2013 at the ARM site (Fig. 9e, right panel) while the WindCube measured *w* variance values that were approximately the same as or slightly higher than those measured by the sonic anemometers at the BAO (Fig. 9e, left panel). Similar to the six-beam equations, the value of the vertical variance is
- ²⁰ subtracted from the sum of the other terms in the five-beam equations. As discussed in Sect. 5.3, when the value of the vertical variance is large or the vertical variance is over-estimated, this can cause the calculated *u* and *v* variance to become negative. This did not occur at the ARM site, as values of the vertical variance were much smaller than variance values from the other beam positions under unstable conditions, in contrast
- to the BAO, where the vertical variance values were similar to the variance estimated from the horizontal radial beams. Thus, the vertical variance term had a much larger influence on the u and v variance values for the example shown at the BAO than it did at the ARM site.





Velocity spectra from the two sites were calculated in order to examine the scales of turbulence measured at the different locations. Averaged spectra for unstable conditions are shown in Fig. 11. The spectral power calculated from the ARM site data is much higher than for the BAO data, which is reflected by the higher values of variance measured at the ARM site in comparison to the BAO (Figs. 3 and 10). The largest difference between the spectral shapes occurs for the *w* spectra, where the peak in the ARM site spectrum is shifted to higher frequencies in comparison to the BAO spectrum. The difference in the *w* spectra could be partially due to measurement height; the BAO spectra were calculated from 100 m data while the ARM site spectra were calculated from 60 m data, where turbulent scales are expected to be smaller. However, similar trends were found when the 50 m sonic spectra from the BAO were compared to the 60 m sonic spectra from the ARM site. Thus, the vertical turbulent scales present during the campaign at the ARM site appear to be generally smaller than those measured

¹⁵ underestimate the *w* variance at the ARM site, as the effects of temporal resolution and volume averaging are more significant for smaller turbulent scales. SNR values were also generally higher at the ARM site than at the BAO, so lower amounts of noise in the raw velocity data also likely led to the measurement of smaller vertical variance values. In addition, differences in season and measurement site characteristics may
 ²⁰ have affected the turbulent scales observed at the two sites. Higher mean wind speeds at the ARM site (Fig. 9h) also likely led to more accurate variance values in comparison

at the BAO site under unstable conditions. This caused the WindCube lidar to often

7 Summary and conclusions

to the BAO.

The VAD and DBS scanning strategies, a novel correction method for the DBS strategy, and the six-beam lidar scanning strategy (Sathe, 2012) were evaluated at two measurement sites: the Southern Great Plains ARM site and the Boulder Atmospheric





Observatory. As a 300 m tower with twelve sonic anemometers was located at the BAO, the evaluation primarily focused on data collected there.

One of the primary disadvantages of using a VAD or DBS technique with a high scanning elevation angle is the variance contamination that can occur as a result of differences in the instantaneous velocity at different parts of the scanning circle. In our work, the VAD and DBS techniques often measured variance values that were 60–80 % larger than those measured by a sonic anemometer as a result of variance contamination. Although using a smaller scanning cone mitigates the effects of horizontal heterogeneity on wind speed estimates, it also increases the contribution of variance contamination.

- ¹⁰ contamination (Eqs. 23 and 24). In this work, a method was developed to correct DBSestimated variance values for contamination. The additional variance terms were quantified using estimates of the autocorrelation function $\rho_w(r, \tau)$ from sonic anemometer data at the BAO and vertical variance measured by the WindCube's vertical beam. The correction method reduced WindCube variance overestimates by over 20% under
- ¹⁵ unstable conditions at both the BAO and the ARM site. The correction method can be applied to other lidars that have a vertical beam position and does not require the use of a scanning lidar or complex calculations. Thus, it is a method that can be easily used by wind farm managers or researchers with commercially available lidars.

Another way to reduce variance contamination is to combine the radial velocity variance values and solve a set of equations to calculate the variance. This method was suggested by Sathe (2012) as a scanning strategy with six beam positions, and it can also be applied to the five beam positions used by the WindCube lidar. At the BAO, the calculation of horizontal variance with the five- and six-beam equations often led to variance underestimates and even negative *u* and *v* variance values (Figs. 6 and 9).

²⁵ The technique appears to be strongly affected by inaccurate variance measurements from one or more beam positions, which could be due to the low wind speeds and low SNR values measured at the BAO. At the ARM site, wind speeds were much higher and the WindCube lidar nearly always underestimated the radial velocity variances, likely as a result of the smaller turbulent scales present at the ARM site. The uniform





underestimation of the radial velocity variances around the scanning circle led to more accurate five-beam variance estimates at the ARM site.

Acknowledgements. The authors would like to thank the staff of the Southern Great Plains ARM site, Tim Lim from NCAR, Lucas Root from NorthWest Research Associates, Shiril
 ⁵ Tichkule from the University of Colorado at Boulder, Bruce Bartram and Daniel Wolfe from NOAA/ESRL's Physical Sciences Division, Marc Fischer and Sebastien Biraud from Lawrence Berkeley National Laboratory, the Boundary Layer Integrated Sensing and Simulation group at OU, and the technical support staff at Campbell Scientific, Leosphere, and Halo Photonics for their assistance during the experiments. LABLE 2 data were obtained from the Atmospheric
 ¹⁰ Radiation Measurement (ARM) Climate Research Facility, a U.S. Department of Energy Office of Science user facility sponsored by the Office of Biological and Environmental Research. J. F. Newman and S. Wharton received funding from the Laboratory Directed Research and Devel-

opment (LDRD) award number 12-ERD-069 from the Lawrence Livermore National Laboratory.

References

20

¹⁵ Arya, S. P.: Introduction to Micrometeorology, vol. 79 of International Geophysics Series, 2nd edn., Academic Press, Cornwall, UK, 2001. 12350, 12351

Barthelmie, R. J., Crippa, P., Wang, H., Smith, C. M., Krishnamurthy, R., Choukulkar, A., Calhoun, R., Valyou, D., Marzocca, P., Matthiesen, D., Brown, G., and Pryor, S. C.: 3-D wind and turbulence characteristics of the atmospheric boundary layer, B. Am. Meteorol. Soc., 95, 743–756, 2013. 12331

Bingöl, F., Mann, J., and Foussekis, D.: Conically scanning lidar error in complex terrain, Meteorol. Z., 18, 189–195, 2009. 12333

Bodine, D., Klein, P. M., Arms, S. C., and Shapiro, A.: Variability of surface air temperature over gently sloped terrain, J. Appl. Meteorol. Clim., 48, 1117–1141, 2009. 12350

- ²⁵ Bright, D. R. and Mullen, S. L.: The sensitivity of the numerical simulation of the Southwest monsoon boundary layer to the choice of PBL turbulence parameterization in MM5, Weather Forecast., 17, 99–114, 2002. 12330
 - Browning, K. A. and Wexler, R.: The determination of kinematic properties of a wind field using Doppler radar, J. Appl. Meteorol., 7, 105–113, 1968. 12331, 12343, 12355





- 12365
- Klein, P., Bonin, T. A., Newman, J. F., Turner, D. D., Chilson, P. B., Wainwright, C. E., Blumberg, W. G., Mishra, S., Carney, M., Jacobsen, E. P., Wharton, S., and Newsom, R. K.: LABLE:

- Burton, T., Sharpe, D., Jenkins, N., and Bossanyi, E.: Wind Energy Handbook, Wiley, West Sussex, UK, 2001. 12359
- Chang, W. S.: Principles of Lasers and Optics, Cambridge University Press, New York, NY, USA, 2005. 12358
- ⁵ Clark, T. L., Hall, W. D., Kerr, R. M., Middleton, D., Radke, L., Ralph, F. M., Neiman, P. J., and Levinson, D.: Origins of aircraft-damaging clear-air turbulence during the 9 December 1992 Colorado downslope windstorm: numerical simulations and comparison with observations, J. Atmos. Sci., 57, 1105–1131, 2000. 12330

Clifton, A. and Wagner, R.: Accounting for the effect of turbulence on wind turbine power curves,

J. Phys. Conf. Ser., 524, 012109, doi:10.1088/1742-6596/524/1/012109, 2014. 12331
 Collier, C. G., Davies, F., Bozier, K. E., Holt, A. R., Middleton, D. R., Pearson, G. N., Siemen, S., Willetts, D. V., Upton, G. J. G., and Young, R. I.: Dual-Doppler lidar measurements for improving dispersion models, B. Am. Meteorol. Soc., 86, 825–838, 2005. 12330

Courtney, M., Wagner, R., and Lindelöw, P.: Commercial lidar profilers for wind energy: a com-

- parative guide, in: European Wind Energy Conference, Brussels, Belgium, 1 April 2008, 359, 2008. 12358
 - Defant, F.: Local Winds, in: Compendium of Meteorology, American Meteorological Society, Boston, MA, USA, 655–672, 1951. 12345

Foken, T.: Micrometeorology, Springer, Heidelberg, Germany, 2008. 12347

- ²⁰ Hahn, C.: A study of the diurnal behavior of boundary-layer winds at the Boulder Atmospheric Observatory, Bound.-Lay. Meteorol., 21, 231–245, 1981. 12345
 - Højstrup, J.: A statistical data screening procedure, Meas. Sci. Technol., 4, 153–157, 1993. 12348

Huffaker, R. M. and Hardesty, R. M.: Remote sensing of atmospheric wind velocities using solid-state and CO₂ coherent laser systems, P. IEEE, 84, 181–204, 1996. 12334, 12349

- solid-state and CO₂ coherent laser systems, P. IEEE, 84, 181–204, 1996. 12334, 12349
 Kaimal, J. and Finnigan, J.: Atmospheric Boundary Layer Flows: Their Structure and Measurement, Oxford University Press, New York, NY, USA, 1994. 12331, 12347
 - Kelley, N. D., Jonkman, B. J., and Scott, G. N.: The Great Plains turbulence environment: its origins, impact and simulation., Tech. Rep., NREL/CP-500-40176., National Renewable Energy
- ³⁰ Laboratory, Golden, CO, USA, 2006. 12331

AMTD 8, 12329-12381, 2015 **Evaluation of three** lidar scanning strategies for turbulence measurements J. F. Newman et al. **Title Page** Abstract Introduction Conclusions References Tables Figures Back Close Full Screen / Esc

Discussion

Paper

Discussion

Paper

Discussion Paper

Discussion Paper

Printer-friendly Version

Interactive Discussion



A multi-institutional, student-led, atmospheric boundary-layer experiment, B. Am. Meteorol. Soc., 96, 1743–1764, 2015. 12346

- Koscielny, A. J., Doviak, R. J., and Zrnic, D. S.: An evaluation of the accuracy of some radar wind profiling techniques, J. Atmos. Ocean. Tech., 1, 309–320, 1984. 12343
- Krishnamurthy, R., Boquet, M., and Machta, M.: Turbulence intensity measurements from a variety of Doppler lidar instruments, in: Proc. European Wind Energy Association Annual Meeting, Barcelona, Spain, 12 March 2014, PO.080, 2014. 12331
 - Lhermitte, R. M. and Atlas, D.: Precipitation motion by pulse Doppler radar, in: Proc. Ninth Weather Radar Conference, Amer. Meteor. Soc., Boston, USA, 218–223, 1961. 12342
- ¹⁰ Lundquist, J. K., Churchfield, M. J., Lee, S., and Clifton, A.: Quantifying error of lidar and sodar Doppler beam swinging measurements of wind turbine wakes using computational fluid dynamics, Atmos. Meas. Tech., 8, 907–920, doi:10.5194/amt-8-907-2015, 2015. 12333
 - Machta, M. and Boquet, M.: State of the art of measuring wind turbulence with pulsed lidars, in: European Wind Energy Association Annual Meeting, Vienna, Austria, 5 February 2013, 324PO, 2013. 12331
- ¹⁵ 324PO, 2013. 12331

20

25

Mahrt, L., Vickers, D., Howell, J., Højstrup, J., Wilczak, J. M., Edson, J., and Hare, J.: Sea surface drag coefficients in the Risø Air Sea Experiment, J. Geophys. Res.-Oceans, 101, 14327–14335, 1996. 12349

Mather, J. H. and Voyles, J. W.: The ARM Climate Research Facility: a review of structure and

capabilities, B. Am. Meteorol. Soc., 94, 377–392, 2013. 12346

- Newman, J. F., Bonin, T. A., Klein, P. M., and Wharton, S.: Optimizing multi-lidar scanning strategies for wind energy turbulence measurements, Wind Energy, in review, 2015. 12346
 Pearson, G., Davies, F., and Collier, C.: An analysis of the performance of the UFAM pulsed Doppler lidar for observing the boundary layer, J. Atmos. Ocean. Tech., 26, 240–250, 2009. 12349
- Peña, A., Hasager, C. B., Gryning, S.-E., Courtney, M., Antoniou, I., and Mikkelsen, T.: Offshore wind profiling using light detection and ranging measurements, Wind Energy, 12, 105–124, 2009. 12331, 12358

Peña, A., Hasager, C. B., Badger, M., Barthelmie, R. J., Bingöl, F., Cariou, J.-P., Emeis, S.,

Frandsen, S. T., Harris, M., Karagali, I., Larsen, S. E., Mann, J., Mikkelsen, T. K., Pitter, M., Pryor, S., Sathe, A., Schlipf, D., Slinger, C., and Wagner, R.: Remote Sensing for Wind Energy, Tech. Rep., DTU Wind Energy-E-Report-0084, Denmark Technical University, available at: http://orbit.dtu.dk/files/111814239/DTU_Wind_Energy_Report_E_0084.pdf, 2015. 12337



- Pichugina, Y. L., Tucker, S. C., Banta, R. M., Brewer, W. A., Kelley, N. D., Jonkman, B. J., and Newsom, R. K.: Horizontal-velocity and variance measurements in the stable boundary layer using Doppler lidar: sensitivity to averaging procedures, J. Atmos. Ocean. Tech., 25, 1307–1327, 2008. 12331
- Sathe, A.: Influence of wind conditions on wind turbine loads and measurement of turbulence using lidars, PhD thesis, Delft University Wind Energy Research Institute, Delft, the Netherlands, 2012. 12332, 12336, 12343, 12362, 12363
 - Sathe, A. and Mann, J.: Measurement of turbulence spectra using scanning pulsed wind lidars, J. Geophys. Res.-Atmos., 117, D01201, doi:10.1029/2011JD016786, 2012. 12331, 12332, 12338
 - Sathe, A. and Mann, J.: A review of turbulence measurements using ground-based wind lidars, Atmos. Meas. Tech., 6, 3147–3167, doi:10.5194/amt-6-3147-2013, 2013. 12331

10

- Sathe, A., Mann, J., Gottschall, J., and Courtney, M. S.: Can wind lidars measure turbulence?, J. Atmos. Ocean. Tech., 28, 853–868, 2011. 12332, 12333, 12338, 12352, 12354
- ¹⁵ Sathe, A., Mann, J., Vasiljevic, N., and Lea, G.: A six-beam method to measure turbulence statistics using ground-based wind lidars, Atmos. Meas. Tech., 8, 729–740, doi:10.5194/amt-8-729-2015, 2015. 12331, 12332, 12347, 12349
 - Sjöholm, M., Mikkelsen, T., Mann, J., Enevoldsen, K., and Courtney, M.: Time series analysis of continuous-wave coherent Doppler lidar wind measurements, IOP. C. Ser. Earth. Env., 1, 012051, doi:10.1088/1755-1307/1/1/012051, 2008. 12331
- 012051, doi:10.1088/1755-1307/1/1/012051, 2008. 12331
 Slinger, C. and Harris, M.: Introduction to continuous-wave Doppler lidar, in: Summer School in Remote Sensing for Wind Energy, Boulder, USA, 11 June, 2012. 12334, 12335, 12349
 - Strauch, R. G., Merritt, D. A., Moran, K. P., Earnshaw, K. B., and De Kamp, D. V.: The Colorado wind-profiling network, J. Atmos. Ocean. Tech., 1, 37–49, 1984. 12331
- Vickers, D. and Mahrt, L.: Quality control and flux sampling problems for tower and aircraft data, J. Atmos. Ocean. Tech., 14, 512–526, 1997. 12348, 12349
 - Wainwright, C. E., Stepanian, P. M., Chilson, P. B., Palmer, R. D., Fedorovich, E., and Gibbs, J. A.: A time series sodar simulator based on large-eddy simulation, J. Atmos. Ocean. Tech., 31, 876–889, 2014. 12333
- Weitkamp, C.: Lidar: Range-Resolved Optical Remote Sensing of the Atmosphere, Springer Series in Optical Sciences, Vol. 102, Springer, New York, NY, USA, 2005. 12335, 12336, 12358





- Westerhellweg, A., Cañadillas, B., Beeken, A., and Neumann, T.: One year of LiDAR measurements at FINO1-Platform: comparison and verification to met-mast data, in: Proc. of the 10th German Wind Energy Conference DEWEK, Bremen, Germany, 17–18 November, 2010. 12331
- ⁵ Wharton, S. and Lundquist, J. K.: Atmospheric stability affects wind turbine power collection, Environ. Res. Lett., 7, 014005, doi:10.1088/1748-9326/7/1/014005, 2012. 12331





Table 1. Overview of instruments used to evaluate different scanning strategies during LABLE 2and LATTE.

Campaign Instrumentation						
Instrument	Campaign	Measurement Range	Temporal Resolution	Scanning Strategy	Owner	
WindCube v2 Pulsed Doppler Lidar	LABLE 2 LATTE	40–200 m 12 measurement heights 20 m range gates	1 Hz Full scan: 4 s	DBS 62° elevation angle	LLNL	
ZephIR 300 Continuous Wave Doppler Lidar	LATTE	10–200 m 10 measurement heights Variable range gate size (0.1–44 m)	0.07 Hz Full scan: 15 s	VAD 60° elevation angle	LLNL	
Halo Streamline Pro Scanning Doppler Lidar	LABLE 2 LATTE	105 m–9.6 km 30 m range gates	1 Hz Full scan: 30 s	Six-beam 45° elevation angle	OU	
Gill Windmaster Pro 3-D Sonic Anemometer	LABLE 2	60 m	10 Hz	-	Lawrence Berkeley National Laboratory	
RM Young 3-D Sonic Anemometers	LATTE	50, 100, 150, 200, 250, and 300 m, NW booms	30 Hz	-	OU	
Campbell Scientific CSAT3 3-D Sonic Anemometers	LATTE	50, 100, 150, 200, 250, and 300 m, SE booms	60 Hz	-	NCAR	

AMTD					
8, 12329–1	8, 12329–12381, 2015				
Evaluation of three lidar scanning strategies for turbulence measurements J. F. Newman et al.					
Titlo					
The	Fage				
Abstract	Introduction				
Conclusions	References				
Tables	Figures				
14	▶1				
•	•				
Back	Close				
Full Screen / Esc					
Printer-friendly Version					
Interactive	Interactive Discussion				

Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper





Figure 1. (a) Google Earth image of the state of Colorado. Location of BAO site is denoted by red marker. **(b)** Google Earth image of the BAO site. Instrument locations are denoted by red markers. Approximate distance between instruments is indicated by blue line and label. Only the initial location of the WindCube lidar is shown.



Discussion Paper

Discussion Paper

Discussion Paper

Discussion Paper







Figure 2. (a) Google Earth image of the state of Oklahoma. Location of Southern Great Plains ARM site is denoted by red marker. (b) Google Earth image of the central facility of the Southern Great Plains ARM site. Instrument locations are denoted by red markers. Approximate distances between instruments are indicated by blue lines and labels.



Discussion Paper







Figure 3. 30 min (a) *u* variance, (b) *v* variance, (c) *w* variance, (d) mean wind speed and (e) mean wind direction at 100 m from sonic anemometers at BAO and (f) Richardson number calculated from tower data. Data are shown from 22 to 26 March 2014, and tick marks for each date correspond to 00:00 UTC on that day.



Figure 4. 30 min (a) *u* variance, (b) *v* variance, and (c) *w* variance at 100 m from sonic anemometers and WindCube DBS technique at BAO and (d) Richardson number calculated from tower data. Data are shown from 25 March 2014. In (a) and (b), solid blue line indicates DBS-calculated variance and dashed black line indicates corrected variance. In (c), solid blue line indicates DBS-calculated *w* variance and dashed blue line indicates *w* variance calculated from vertically pointing beam. The corrected *u* and *v* variance data show substantial improvement over the uncorrected dataset during unstable conditions.





Figure 5. 30 min (a) u variance, (b) v variance, and (c) w variance at 100 m from sonic anemometers and lidar VAD techniques at BAO and (d) Richardson number calculated from tower data. Data are shown from 25 March 2014. Comparison of the Halo and ZephIR VADprocessed data suggest that a lower elevation angle may be advantageous (e.g., lower v variance values measured by the Halo lidar, which uses a lower elevation angle, shown in **b**). Note the smaller u and v variance values shown here for the Halo and ZephIR (VAD) as compared to the Wind Cube (DBS) in Fig. 4.











Figure 7. 30 min mean velocity values (left panels) and variance values (right panels) for (a) v_{r1} , (b) v_{r2} , (c) v_{r3} , (d) v_{r4} , (e) v_{r5} and (f) v_{r6} measured by Halo lidar and calculated from projected sonic data. Values of (g) u variance and (h) v variance are also shown for reference, where sonic values are from standard variance calculation and Halo values are from six-beam calculation. Mean wind speed from sonic is shown in (i) and Richardson number from tower is shown in (j). Data are shown from 25 March 2014 at 200 ma.g.l. at the BAO tower.







Figure 8. As in Fig. 7, but for 6 March 2014. Richardson number is not shown, because the 10 m temperature sensor had data quality issues on this day (possibly related to tower icing).







Figure 9. 30 min (a) v_{r1} , (b) v_{r2} , (c) v_{r3} , (d) v_{r4} and (e) v_{r5} variance values measured by Wind-Cube lidar and calculated from projected sonic data, where positions 1–4 are located at azimuths of 0, 90, 180, and 270°, respectively, at an elevation angle of 62° and position 5 is pointed vertically. Values of (f) *u* variance and (g) *v* variance are also shown for reference, where sonic values are from standard variance calculation and WindCube values are shown from DBS calculation (solid blue line), five-beam calculation (green line), and corrected DBS calculation (dashed black line). Mean wind speed from sonic anemometer is shown in (h). Data are shown from the BAO on 25 March 2014 at 100 m a.g.l. (left panels) and from the ARM site on 23 June 2013 at 60 m a.g.l. (right panels). The WindCube 5-beam method results in large underestimates of *u* and *v* variance, especially under convective conditions at the BAO, while much better agreement is seen with the new variance correction method.







Figure 10. 30 min (a) u variance, (b) v variance, (c) w variance, (d) mean wind speed, (e) mean wind direction and (f) Monin–Obukhov length at 60 m from sonic anemometer at the ARM site. Data are shown from 19 to 23 June 2013, and tick marks for each date correspond to 00:00 UTC on that day.







Figure 11. Averaged (a) u spectra, (b) v spectra and (c) w spectra for unstable conditions measured by the south BAO sonic at 100 m and the ARM sonic at 60 m. Black line denotes theoretical -2/3 slope for inertial subrange. Note the larger amount of energy contained at the lowest frequency scales at the BAO for the w component.



Full Screen / Esc

Printer-friendly Version

Interactive Discussion