

Author's Response

These are the corrections included in the manuscript:

AUTHORS

We have included a new coauthor: Dr. Carmen Guirado (Valladolid University, Izaña Atmospheric Research Center). She is in charge of the operation, calibration and quality assurance of the AERONET data in Izaña, which has served us to perform the AOD correction presented in this paper. So, we consider she has actively contributed to the present study.

We have also changed the order of the affiliations.

INTRODUCTION

According to Referee's 2 comments (C1), we have reduced the introduction to improve the readability of the paper. This is the new introduction:

"Aerosols can significantly influence the climate in several ways: through aerosol-radiation and aerosol-cloud-precipitation interactions (Foster et al., 2007, IPCC 2013). This fact has motivated notable efforts in atmospheric sciences envisaged to increase the understanding of the role played by aerosols in the global climate balance.

Aerosol optical depth (AOD) is a valuable parameter accounting for aerosol load in the atmosphere because it is a measure of the extinction of the solar beam by absorption and scattering processes caused by aerosols. Sun photometry provides useful information to retrieve columnar aerosol optical and microphysical properties with an excellent spatial coverage but with the lack of vertical resolution (Holben et al., 1998, Eck et al., 1999, Holben et al., 2001, Eck et al., 2009, 2010). A good example of the spatial extent of Sun photometry techniques is the widespread ground-based AErosol RObotic NETwork (AERONET) (Holben et al., 1998) and its federated networks, including hundreds of stations globally distributed. However, aerosols at night-time have been studied to a much lesser extent (Barreto et al., 2013a,b, Baibakov et al., 2015). There is a growing interest in studying the diurnal dynamics and evolution of atmospheric aerosols (Pérez-Ramírez et al., 2012a), as well as understanding the nucleating role of aerosols and their net radiative effects (Baibakov et al., 2015). Therefore, new technological developments try to fill the night-period gaps in AOD time series. As Baibakov et al. (2015) pointed out, star and Moon photometry have arisen as plausible solutions to this problem. Star photometer technique (Leitener et al., 1995, Pérez-Ramírez et al., 2015, Baibakov et al., 2015) has been revealed as a useful tool to infer aerosol information during night-period. However, infrastructure and logistic constraints still represent an important limitation for the operational use of stellar measurements, especially for global networks such as AERONET. Alternatively, Moon photometry is a technique that can be implemented more easily, and at a lower cost, in an operational way (Barreto et al., 2016). Nevertheless, Moon photometry technique is still affected by notable limitations. Despite the Moon is our nearest celestial neighbor, our knowledge about its spectral irradiance is far from being as precise as the spectra from the Sun or bright stars like Vega (Cramer et al., 2013). The main important obstacle in Moon photometry is the fact that the Moon is a variable reflector of sunlight and, as a result, it is a highly variable source of visible light (Miller et al., 2012).

Pioneering works in lunar photometry were developed by Esposito et al. (1998), Berkoff et al. (2011) and Barreto et al. (2013a,b). Recently, Barreto et al. (2016) presented the new photometer CE318-T which combines the features of the extensively used CE318 Cimel Sun photometer standard model in AERONET network, with the lunar photometer prototype previously presented in (Barreto et al, 2013a,b). The higher precision of this new instrument compared to the previous versions of Sun and Moon photometers and its ability to monitor atmospheric aerosols in a diurnal cycle, have made it a suitable instrument to replace the CE318-AERONET reference instrument.

As many authors have stated (Berkoff et al., 2011, Barreto et al, 2013a,b, Barreto et al., 2016), a precise Moon irradiance model is mandatory in Moon photometry to take the continuous change of Moon's brightness over the cycle into account. In this respect, RObotic Lunar Observatory (ROLO) model, developed by Kieffer and Stone (2005), is the most careful radiometric study on the Moon's brightness to date (Cramer et al., 2013). The ROLO model has recently emerged as a unique tool for Moon photometry (Berkoff et al., 2011, Barreto et al, 2013a,b, Barreto et al., 2016), and is an essential part of the calibration process. Although this model provides precise information about the change of Moon's irradiance with the phase angle (α) and lunar librations, small systematic effects have been found in this model. Lacherade et al. (2013, 2014) and Viticchié et al. (2013) found a small phase angle dependence of the ROLO calibration using the Pleiades Orbital Lunar Observations (POLO) and Meteosat Second Generation (MSG) Spinning Enhanced Visible and Infrared Imager (SEVIRI) solar bands. Cramer et al. (2013) developed a novel apparatus to accurately measure the lunar spectral irradiance with the aim of estimating these systematic effects in the ROLO model. Barreto et al. (2016) used the CE318-T and the ROLO model to retrieve AOD at day and night-time in Izaña, a high altitude observatory located at Tenerife (The Canary Islands, Spain). These authors observed an important dependence of the AOD uncertainty with phase angle and also a faint nocturnal cycle in AOD, indicating a possible dependence of AOD uncertainty on the Moon's zenith (θ) and phase angles. As these authors stated, the reason for these discrepancies remain unclear, although it is likely to be due to a sum of causes, such as inaccurate instrument calibration, possible systematic errors in the ROLO model, instrumental problems and/or uncertainties in night-time AOD calculation.

This work is based on all of the previous results to improve the AOD retrieval at night-time by selecting a set of clean and stable night-time conditions at Izaña in which day-time AOD data could be considered a good proxy for nocturnal AOD. Clean and stable conditions of days used in this study have been ensured using AERONET daytime data at the station and Micropulse lidar version 3 (MPL-3) atmospheric vertical profiles extracted from a nearby coastal station. The main aim of this study is to identify the errors sources, thereby trying to fix experimentally some of the problems currently affecting Moon photometry.

Section 2 describes the experiment site, instruments and methods used in this study. A description of the methodology developed to improve nocturnal AOD measurements and the corresponding validation performed at Izaña, as well as in other complementary stations, is presented in section 3. Finally conclusions are shown in section 4."

SECTION 2

Pag. 4, line 10: "... as well as two additional **measurements** at 1020 nm and 1640 nm using..."

Pag. 4, line 11: "The UV **spectral bands** do not ..."

Pag. 5, line 9: The sentence has been slightly changed in order to highlight we are using an implementation of the ROLO model based exclusively on Eq. 10 published by Kieffer and Stone (2005): "..., calculated using our own implementation of the ROLO model based rigorously on the Eq. (10) published in Kieffer and Stone (2005)..."

Pag. 5, line 24: According to Referee's 2 comment (C2) we have included the following information about the Lunar Langley as well as the Langley methods.

"...AOD_V2.html).

The calibration constant κ_λ has been calculated by means the Lunar-Langley method developed by Barreto et al. (2013a). The main equations involved in this method are the Eq. 2, derived from the Beer-Lambert-Bouguer Law (the basis of the Langley calibration technique described by many authors in sunphotometry, such as Shaw, 1976, 1983, Holben, 1998, among others) and the Eq. 3 (the basis of the Lunar-Langley calibration technique), which defines the calibration constant as the ratio of V_0 to I_0 .

$$\ln(V_\lambda) = \ln(V_{0,\lambda}) - m(\theta) \cdot \tau_\lambda \quad (2)$$

$$V_{0,\lambda} = I_{0,\lambda} \cdot \kappa_\lambda \quad (3)$$

SECTION 3

Pag. 6, line 7. As Referee 2 suggested (C3), we have completed the information about how stable AOD conditions are verified: "... 500 nm) at Izaña. **The AOD stability criterion involves an AOD difference between the 1-h average AERONET AOD of two consecutives days (sunset versus sunrise) ≤ 0.005 at 870 nm.**"

Pag. 6, line 11. Regarding the previous Referee's 2 comment (C2) we have included the following information: *"Nocturnal measurements were performed by means of a master CE318-T installed at Izaña station. This instrument has been calibrated following the Lunar-Langley calibration method proposed by Barreto et al. (2013a) (Eqs. 2 and 3. This is a new absolute calibration technique, specifically developed for lunar photometry, which avoids the determination of one different calibration coefficient every night required by the common Langley technique (Eq. 2). It is important to emphasize the moon's illumination variation inherent to the lunar cycle, which means the V_0 and I_0 terms in Eq. 3 are continuously changing, even during the ≈ 2 hour observation time period required to perform the Langley calibration. Even if we discard the I_0 variation during the Langley period, the extraterrestrial voltages V_0 should be determined every day, which is not plausible considering the restrictive requirements in terms of atmospheric stability and cloudiness of this calibration technique. In spite the simplicity of the Lunar-Langley technique, its accuracy relies on the uncertainty involved in the ROLO model. The uncertainty ..."*

Pag. 6, line 23: "A comparison of the two absolute calibration techniques, Langley and Lunar-Langley, has been carried out in this paper."

Pag 6, line 26: "To this end we have used the **Eq. 3.**"

Pag. 7, line 3-4: Added one reference as well as the following information: "This phase angle dependence of the ROLO model has been also reported by Lacherade et al. (2013, **2014**) and Vitichie et al. (2013), as well as its asymmetry within the Moon cycle Lacherade et al. (2013, **2014**). **Lacherade et al. (2014) found a variation up to 5% with the phase angle between $\pm 90^\circ$, the validity range of the ROLO model. These results are in agreement with the relative differences higher than 4% found in this study.**"

Pag. 8, line 29. We have included the dates for these three nights (see Referee 1 comment #3). We have included: "... one near full moon (**8 October**, with g ranging between -9° to -3°) and two nights with low illumination conditions (**6 April and 16 October**, with g between $\pm 93^\circ$ and $\pm 96^\circ$), in which..."

Pag. 8, line 29. We have also corrected the typo error (see Referee 1 comment C4): "...with g ranging between -9° to **-3°** ".

Pag. 9, line 10: "... which are the **spectral bands** more affected...."

Pag. 9, line 11: "... longer wavelength **bands** show...."

Pag. 9, line 14: "... are 0.19 for 1020 nm and below 0.10 for the rest of **bands**...."

Pag. 9, line 18. According to Referee's 1 (comment #1), we have introduced new clarifications about the different slopes observed in Fig. 5 in the case of 1020 nm spectral band. We have included the following information:

"The more important differences were retrieved for 1020 nm spectral band. We attribute the two branches above and below the horizontal line to a systematic error in our empirical model, which reproduces an amplified phase angle dependence in this 1020 nm spectral band. This effect is less appreciable but still discernible for 1640 nm. The points above the diagonal correspond to overcorrected AOD values. It happens for high and positive phase angles. On the contrary, the points below the diagonal line represent those conditions poorly corrected, and happens for high and negative phase angles. Finally, the third branch with $\delta_{g,0}$ values up to 0.09 is observed for high and positive phase angles in some days in October and November, 2014. We suspect that instrumental problems are behind such overcorrection cases."

Pag. 9, lines 21 and 23: We have changed "1h" for "1-h".

Pag. 9, line 23: We have changed "sun and moon" for "Sun and Moon".

Pag. 10, line 5. The title in section 3.4 has been changed by this one "Evaluation of the AOD correction at Izaña".

Pag. 10, line 12: "... in the rest of **spectral bands**."

Pag. 10, line 14. The title in section 3.5 has been changed by this one "Evaluation of the AOD correction at other sites: Carpentras, Dakar and Lille", according to Referee's 2 (C5).

Pag. 10, line 19. Changed "relatively clean conditions" for "relatively low AOD conditions".

Pag. 11, line 3: "This evaluation analysis in different stations seems to corroborate that this correction procedure is applicable to other instruments and sites. However, it is fair to admit this correction has been performed by means of a unique instrument, with certain optical interference filters. The difference in the filter responses as well as the degradation of optical filters with time are the limiting factors. They could add an extra uncertainty depending on the different band responses between instruments. Further studies will be focused on the estimation of this extra uncertainty."

Pag. 11, line 11: "... in a nearby coastal station **as well as by means of an AOD stability criterion using daytime AERONET data.**".

Pag. 11, line 12: "We detected an important bias correlated to Moon's phase and zenith angles **(g and θ) in all the spectral bands. However, the important phase angle dependence found for 1020 nm and 1640 nm might be an artifact caused by a systematic error in our empirical model.**"

Pag. 11, line 21: "The authors would like to admit this is only a preliminary AOD correction proposal **developed using one single instrument** which might be **refined** and used to correct the lunar irradiance model **in future studies.**"

TABLES

Table 1: Corrected the typo error (-0.71 for 0.71). See Referee's 2 comment #7.

FIGURES

Fig. 4: We have added information about the dates of these three nights, according to Referee's 1 comment #5.

Fig. 8: We have improved this figure to address the Referee's 2 comment #8. We have enlarged this figure as well as decreased the frequency of points in the case of Carpentras.

REFERENCES

Two references have been eliminated from the final manuscript: Eplee et al., 2011 and Eplee et al., 2012, as well as Lopatin et al., 2013.

We have corrected the two references for Barreto et al., 2013 (2013**a** and 2013**b**) and Pérez-Ramírez et al., 2012.

We have added the following references: Esposito et al., 2003; Lacherade et al. (2014).

We have added the following dois: Campbell et al. (2002), Holben et al. (1998), Holben et al. (2001), IPCC (2013), Kieffer and Stone (2005), Shaw (1976), Shaw (1983) and Welton and Campbell (2002).

Response to Referee #1

The authors would like to thank the referee #1 for their constructive and useful suggestions. Please, find below our answers to their comments.

>> C1 P9.L17-18. What did you mean with “more important ones”? I think it refers to the increased deviation of the 1020nm channel compared to other channels in Fig.5. It looks like you can split the data of the 1020nm channel in Fig.5 to three, or maybe four, different cases with different slopes. Could this be related to temperature differences, as it is stated in the same sentence?

With “the more important ones” we are referring to the highest ΔAOD_{fit} values. We agree these different slopes should be clarified. Even though it is well known and documented the temperature dependence of 1020nm measurements performed with the common silicon detectors, we have to admit that the three branches observed in Fig. 5 are not caused by this effect, but by the strong asymmetry with phase angle found in the empirical model parameterized as $\delta_{g,\theta}$ for 1020nm and 1640nm spectral bands. So, we have two characteristic branches in these two bands: one above and one below the diagonal line. The points above the diagonal line correspond to overcorrected AOD values. It happens for high positive phase angles. On the contrary, the points below the diagonal represent those conditions poorly corrected, and it happens for high negative phase angles. We consider this is a systematic error in our empirical model which reproduces an amplified phase angle dependence in these spectral bands.

Finally, the first and most obvious of branches, with $\delta_{g,\theta}$ values up to 0.09, is observed in the case of high and positive phase angles in some days in October and November, 2014. We suspect that instrumental problems are behind such overcorrection cases.

We will introduce in the text these new clarifications, highlighting that the important phase angle dependence found in 1020nm and 1640nm channels might be an artifact.

>> C2 P4.22-23. Another question to concerning the 1020nm channels. There are two channels with a nominal wavelength of 1020nm. Are both combined to one channel, or which channel measurements are used in this manuscript? Also it is stated, that the silicon 1020nm channel is temperature corrected. How could the deviation of the 1020nm channel in Fig.5 be related to the temperature then? (see comment 1).

Yes, the CE318-T has one spectral filter with 1020nm as nominal wavelength, and two silicon and InGaAs detectors can be additionally used to measure in this spectral band. The one used in this paper is the silicon 1020nm channel. See comment 1.

>> C3 P8.L29 “the three nights”: Which three nights? Either spare the “the” or give the Dates.

We will add the dates of these three nights (April 6th, October 8th and October 16th).

>> C4 P8.L29 “ranging from -9° to 3°” → ranging from -9° to -3°

Done.

>> C5 Fig4. I think it would be good to provide the dates.

We will provide dates (see comment 3).

Response to Referee #2

We thank the reviewer #2 for the positive and constructive comments. Listed below are our responses to the eight different discussion points.

>> C1 As stated above, the Introduction is rather long compared to the other sections of the paper. A possible solution may be to split up the introduction into a more concise version and a second section containing background information and references. In my view this will add to the readability of the paper

According to the referee's comment we have reduced the introduction in order to improve the readability of the paper. This is the new introduction:

"Aerosols can significantly influence the climate in several ways: through aerosol-radiation and aerosol-cloud-precipitation interactions (Foster et al., 2007, IPCC 2013). This fact has motivated notable efforts in atmospheric sciences envisaged to increase the understanding of the role played by aerosols in the global climate balance.

Aerosol optical depth (AOD) is a valuable parameter accounting for aerosol load in the atmosphere because it is a measure of the extinction of the solar beam by absorption and scattering processes caused by aerosols. Sun photometry provides useful information to retrieve columnar aerosol optical and microphysical properties with an excellent spatial coverage but with the lack of vertical resolution (Holben et al., 1998, Eck et al., 1999, Holben et al., 2001, Eck et al., 2009, 2010). A good example of the spatial extent of Sun photometry techniques is the widespread ground-based AERosol RObotic NETwork (AERONET) (Holben et al., 1998) and its federated networks, including hundreds of stations globally distributed. However, aerosols at night-time have been studied to a much lesser extent (Barreto et al., 2013a,b, Baibakov et al., 2015). There is a growing interest in studying the diurnal dynamics and evolution of atmospheric aerosols (Pérez-Ramírez et al., 2012a), as well as understanding the nucleating role of aerosols and their net radiative effects (Baibakov et al., 2015). Therefore, new technological developments try to fill the night-period gaps in AOD time series. As Baibakov et al. (2015) pointed out, star and Moon photometry have arisen as plausible solutions to this problem. Star photometer technique (Leitener et al., 1995, Pérez-Ramírez et al., 2015, Baibakov et al., 2015) has been revealed as a useful tool to infer aerosol information during night-period. However, infrastructure and logistic constraints still represent an important limitation for the operational use of stellar measurements, especially for global networks such as AERONET. Alternatively, Moon photometry is a technique that can be implemented more easily, and at a lower cost, in an operational way (Barreto et al., 2016). Nevertheless, Moon photometry technique is still affected by notable limitations. Despite the Moon is our nearest celestial neighbor, our knowledge about its spectral irradiance is far from being as precise as the spectra from the Sun or bright stars like Vega (Cramer et al., 2013). The main important obstacle in Moon photometry is the fact that the Moon is a variable reflector of sunlight and, as a result, it is a highly variable source of visible light (Miller et al, 2012).

Pioneering works in lunar photometry were developed by Esposito et al. (1998), Berkoff et al. (2011) and Barreto et al. (2013a,b). Recently, Barreto et al. (2016) presented the new photometer CE318-T which combines the features of the extensively used by the Cimel Sun photometer, standard model in AERONET network, with the lunar photometer prototype previously presented in (Barreto et al, 2013a,b). The higher precision of this new instrument

compared to the previous versions of Sun and Moon photometers and its ability to monitor atmospheric aerosols in a diurnal cycle, have made it a suitable instrument to replace the CE318-AERONET reference instrument.

As many authors have stated (Berkoff et al., 2011, Barreto et al, 2013a,b, Barreto et al., 2016), a precise Moon irradiance model is mandatory in Moon photometry to take the continuous change of Moon's brightness over the cycle into account. In this respect, RObotic Lunar Observatory (ROLO) model, developed by Kieffer and Stone (2005), is the most careful radiometric study on the Moon's brightness to date (Cramer et al., 2013). The ROLO model has recently emerged as a unique tool for Moon photometry (Berkoff et al., 2011, Barreto et al, 2013a,b, Barreto et al., 2016), and is an essential part of the calibration process. Although this model provides precise information about the change of Moon's irradiance with the phase angle (g) and lunar librations, small systematic effects have been found in this model. Lacherade et al. (2013) and Viticchié et al. (2013) found a small phase angle dependence of the ROLO calibration using the Pleiades Orbital Lunar Observations (POLO) and Meteosat Second Generation (MSG) Spinning Enhanced Visible and Infrared Imager (SEVIRI) solar bands. Cramer et al. (2013) developed a novel apparatus to accurately measure the lunar spectral irradiance with the aim of estimating these systematic effects in the ROLO model. Barreto et al. (2016) used the CE318-T and the ROLO model to retrieve AOD at day and night-time in Izaña, a high altitude observatory located at Tenerife (The Canary Islands, Spain). These authors observed an important dependence of the AOD uncertainty with phase angle and also a faint nocturnal cycle in AOD, indicating a possible dependence of AOD uncertainty on the Moon's zenith (θ) and phase angles. As these authors stated, the reason for these discrepancies remain unclear, although it is likely to be due to a sum of causes, such as inaccurate instrument calibration, possible systematic errors in the ROLO model, and uncertainties in night-time AOD calculation.

This work is based on all of the previous results to improve the AOD retrieval at night-time by selecting a set of clean and stable night-time conditions at Izaña in which day-time AOD data could be considered a good proxy for nocturnal AOD. Clean and stable conditions of days used in this study have been ensured using AERONET daytime data at the station and Micropulse lidar version 3 (MPL-3) atmospheric vertical profiles extracted from a nearby coastal station. The main aim of this study is to identify the errors sources, thereby trying to fix experimentally some of the problems currently affecting Moon photometry.

Section 2 describes the experiment site, instruments and methods used in this study. A description of the methodology developed to improve nocturnal AOD measurements and the corresponding validation performed at Izaña, as well as in other complementary stations, is presented in section 3. Finally conclusions are shown in section 4."

>> C2 - In Sections 2 and 3 the two methods for calibration are mentioned; the "common Langley technique" and the "Lunar-Langley technique". Although well-informed readers are familiar with the two techniques I suggest to spend a few more words on the techniques and its limitations, in particular the "every-night requirement" for the common technique (including an explanation).

Information about the common Langley and the Lunar Langley as well as their limitations has been included in the text as follows:

Pag. 5, line 24: "...AOD_V2.html). The calibration κ_λ is calculated by means the Lunar-Langley method developed by Barreto et al. (2013a). The main equations involved in this method are the Eq. 2, derived from the Beer-Lambert-Bouguer Law (the basis of the Langley calibration technique described by many authors in sunphotometry -Shaw, 1976, 1983, Holben, 1998; among others-) and the Eq. 3 (the basis of the Lunar-Langley calibration technique), which defines the calibration constant as the ratio of V_0 to I_0 .

$$\ln(V_\lambda) = \ln(V_{0,\lambda}) - m(\theta) \cdot \tau_\lambda \quad (2)$$

$$V_{0,\lambda} = I_{0,\lambda} \cdot \kappa_\lambda \quad (3)''$$

Pag. 6, line 11: "Nocturnal measurements were performed by means of a master CE318-T installed at Izaña station. This instrument has been calibrated following the Lunar-Langley calibration method (Barreto et al., 2013a) previously described. This is a new absolute calibration technique, specifically developed for lunar photometry, which avoids the determination of one different calibration coefficient every night required by the common Langley technique (Shaw, 1976, 1983). It is important to emphasize the moon's illumination variation inherent to the lunar cycle, which means the V_0 and I_0 terms in Eq. 3 are continuously changing, even during the ≈ 2 hour observation time period required to perform the Langley calibration. Even if we discard the I_0 variation during the Langley period, the extraterrestrial voltages V_0 should be determined every day, which is not plausible considering the restrictive requirements in terms of atmospheric stability and cloudiness of this calibration technique. In spite the simplicity of the Lunar-Langley technique, its accuracy relies on the uncertainty involved in the ROLO model."

>> C3 Section 3.1: it is stated that stable AOD conditions are selected using ancillary vertical information from an MPL-3 lidar. Although Fig. 1 is useful I suggest to give some more information on what exactly is meant by "stable" and how stable periods are selected (is there a quantitative criterion?). The interpolation method to get nighttime AOD from daytime values is a crucial aspect in the paper, so the background of how to select stable data deserves more attention/explanation.

We have verified the stable AOD conditions with MPL-3 lidar aerosol backscattering information, and using an AOD stability criterion in the 1-h average AERONET AOD of two consecutive days at 870 nm. Doing so, the night is considered stable if the average of the AOD difference between two consecutive days is ≤ 0.005 . This information will be included in the final manuscript.

>> C4 An interesting and good aspect of the work is that the AOD correction has been applied to three other stations in different aerosol climates. The question that arises is: is the correction (the coefficients presented in Table 1 fully instrument-independent?

Since the correction is wavelength-dependent, the assumption that the parameterization can be applied to other instruments seems to rely on comparable spectral characteristics (in particular the filters) of the reference instrument and the instruments to which the correction is applied. I suggest the authors spend a few words on explaining why the correction can safely (?) be applied to the Carpentras, Dakar and Lille instruments, and on the possible introduction of extra uncertainty.

Our results showed that the correction can be applied to any other instrument and location. However, we will include in the text the following information:

Pag. 11, line 3: "This evaluation analysis in different stations seems to corroborate the applicability of this correction procedure to other instruments and sites. However, it is fair to admit this correction has been performed by means of an unique instrument, with certain optical interference filters. The difference in the filter responses as well as the degradation of optical filters with time are the limiting factors. They could add an extra uncertainty depending on the different band responses between instruments. Further studies will be focused on the estimation of this extra uncertainty."

>> C5 The title of Section 3.5 is not entirely correct since the method is not really validated. The authors have applied their correction method to AOD retrievals at the three sites but a real validation has not been performed. I suggest changing the title into something more appropriate ("Impact of correction. . ." or something equivalent). We agree with this comment. We will replace the current title by "Evaluation of the AOD empirical correction at other sites: Carpentras, Dakar and Lille".

>> C6 Section 3.4 (line 19): Lille is considered to be affected by "relatively clean conditions". I think that this cannot be stated in general considering the highly polluted environment the site is located in. The AOD may be not particularly high during the selected period but "clean conditions" is maybe a bit too optimistic. We agree. We will replace "clean" by "relatively low AOD conditions".

>> C7 Table 1: R-squared: the value -0.71 seems to be incorrect. We have corrected this mistake.

>> C8 Although Fig. 8 can be understood, it is not very easy to distinguish between the asterisks and the circles. It maybe an idea to present AOD differences instead of absolute values in order to avoid unclearness. If this is not desirable, the authors may think of another way to make the figure more clear.

AOD differences don't show whether the correction actually improves the AOD retrievals, so we consider AOD absolute values the best way to confirm the correction presented in this work functions adequately. However, we have improved this figure to make it clearer to the reader. We have enlarged the figure and we have also decreased the frequency of points in the case of Carpentras site.

Assessment of nocturnal Aerosol Optical Depth from lunar photometry at Izaña high mountain Observatory

África Barreto^{1,2,3}, Roberto Román^{4,5}, Emilio Cuevas³, Alberto J. Berjón², A. Fernando Almansa^{1,2,3}, Carlos Toledano², Ramiro González², Yballa Hernández³, Luc Blarel⁶, Philippe Goloub⁶, Carmen Guirado^{2,3}, and Margarita Yela⁷

¹Cimel Electronique, Paris, France

²Grupo de Óptica Atmosférica, Universidad de Valladolid, Valladolid, Spain

³Izaña Atmospheric Research Center, Meteorological State Agency of Spain (AEMET), Spain

⁴Department of Applied Physics, University of Granada, Granada, Spain

⁵Andalusian Institute for Earth System Research, IISTA-CEAMA, University of Granada, Junta de Andalucía, Granada, Spain

⁶Laboratoire d'Optique Atmosphérique (LOA), Université de Lille, Villeneuve d'Ascq, France

⁷Instrumentation and Atmospheric Research Department, National Institute for Aerospace Technology (INTA), Madrid, Spain

Correspondence to: Emilio Cuevas
(ecuevasa@aemet.es)

Abstract. This work is a first approach to correct the systematic errors observed in the aerosol optical depth (AOD) retrieved at night-time using lunar photometry and calibration techniques dependent on the lunar irradiance model. To this end, nocturnal AOD measurements were performed in 2014 using the CE318-T master Sun-sky-lunar photometer (Lunar-Langley calibrated) at Izaña high mountain Observatory. This information has been restricted to 59 nights characterized as clean and stable according to lidar vertical profiles. A phase angle dependence as well as an asymmetry within the Moon's cycle of the ROLO model could be deduced from the comparison in this 59-nights period of the CE318-T calibration performed by means of the Lunar-Langley and the calibration performed every single night by means of the common Langley technique. Nocturnal AOD has also been compared in the same period with a reference AOD based on daylight AOD extracted from the AERONET network at the same station. Considering stable conditions, the difference ΔAOD_{fit} , between AOD from lunar observations and the linearly interpolated AOD (the reference) from daylight data, has been calculated. The results show that ΔAOD_{fit} values are strongly affected by Moon phase and zenith angles. This dependency has been parameterized using an empirical model with two independent variables (Moon phase and zenith angles) in order to correct the AOD for these residual dependencies. The correction of this parameterized dependency has been checked at four stations with quite different environmental conditions (Izaña, Lille, Carpentras and Dakar) showing a significant reduction of the AOD dependence on phase and zenith angles, and an improved agreement with daylight reference data. After the correction, absolute AOD differences for day-night-day clean and stable transitions remain below 0.01 for all wavelengths.

1 INTRODUCTION

Aerosols can significantly influence the climate in several ways: through aerosol-radiation and aerosol-cloud-precipitation interactions (Foster et al., 2007; IPCC, 2013). This fact has motivated notable efforts in atmospheric sciences envisaged to increase the understanding of the role played by aerosols in the global climate balance.

5 Aerosol optical depth (AOD) is a valuable parameter accounting for aerosol load in the atmosphere because it is a measure of the extinction of the solar beam by absorption and scattering processes caused by aerosols. Sun photometry provides useful information to retrieve columnar aerosol optical and microphysical properties with an excellent spatial coverage but with the lack of vertical resolution (Holben et al., 1998; Eck et al., 1999; Holben et al., 2001; Eck et al., 2009, 2010). A good example of the spatial extent of Sun photometry techniques is the widespread ground-based AERosol RObotic NETwork (AERONET) 10 (Holben et al., 1998) and its federated networks, including hundreds of stations globally distributed. However, aerosols at night-time have been studied to a much lesser extent (Barreto et al., 2013a, b; Baibakov et al., 2015). There is a growing interest in studying the diurnal dynamics and evolution of atmospheric aerosols (Pérez-Ramírez et al., 2012a), as well as understanding the nucleating role of aerosols and their net radiative effects (Baibakov et al., 2015). Therefore, new technological developments try to fill the night-period gaps in AOD time series. As Baibakov et al. (2015) pointed out, star and Moon photometry have arisen 15 as plausible solutions to this problem. Star photometer technique (Leitener et al., 1995; Pérez-Ramírez et al., 2015; Baibakov et al., 2015) has been revealed as a useful tool to infer aerosol information during night-period. However, infrastructure and logistic constraints still represent an important limitation for the operational use of stellar measurements, especially for global networks such as AERONET. Alternatively, Moon photometry is a technique that can be implemented more easily, and at a lower cost, in an operational way (Barreto et al., 2016). Nevertheless, Moon photometry technique is still affected by notable 20 limitations. Despite the Moon is our nearest celestial neighbor, our knowledge about its spectral irradiance is far from being as precise as the spectra from the Sun or bright stars like Vega (Cramer et al., 2013). The main important obstacle in Moon photometry is the fact that the Moon is a variable reflector of sunlight and, as a result, it is a highly variable source of visible light (Miller et al., 2012).

Pioneering works in lunar photometry were developed by Esposito et al. (1998), Esposito et al. (2003), Berkoff et al. (2011) 25 and Barreto et al. (2013a, b). Recently, (Barreto et al., 2016) presented the new photometer CE318-T which combines the features of the extensively used CE318 Cimel Sun photometer standard model in AERONET network, with the lunar photometer prototype previously presented in Barreto et al. (2013a, b). The higher precision of this new instrument compared to the previous versions of Sun and Moon photometers and its ability to monitor atmospheric aerosols in a diurnal cycle, have made it a suitable instrument to replace the CE318-AERONET reference instrument.

30 As many authors have stated (Berkoff et al., 2011; Barreto et al., 2013a, b, 2016), a precise Moon irradiance model is mandatory in Moon photometry to take the continuous change of Moon's brightness over the cycle into account. In this respect, RObotic Lunar Observatory (ROLO) model, developed by Kieffer and Stone (2005), is the most careful radiometric study on the Moon's brightness to date (Cramer et al., 2013). The ROLO model has recently emerged as a unique tool for Moon photometry (Berkoff et al., 2011; Barreto et al., 2013a, b, 2016), and is an essential part of the calibration process. Although

this model provides precise information about the change of Moon's irradiance with the phase angle (g) and lunar librations, small systematic effects have been found in this model. Lacherade et al. (2013, 2014) and Viticchié et al. (2013) found a small phase angle dependence of the ROLO calibration using the Pleiades Orbital Lunar Observations (POLO) and Meteosat Second Generation (MSG) Spinning Enhanced Visible and Infrared Imager (SEVIRI) solar bands. Cramer et al. (2013) developed a novel apparatus to accurately measure the lunar spectral irradiance with the aim of estimating these systematic effects in the ROLO model. Barreto et al. (2016) used the CE318-T and the ROLO model to retrieve AOD at day and night-time in Izaña, a high altitude observatory located at Tenerife (The Canary Islands, Spain). These authors observed an important dependence of the AOD uncertainty with phase angle and also a faint nocturnal cycle in AOD, indicating a possible dependence of AOD uncertainty on the Moon's zenith (θ) and phase angles. As these authors stated, the reason for these discrepancies remain unclear, although it is likely to be due to a sum of causes, such as inaccurate instrument calibration, possible systematic errors in the ROLO model, instrumental problems and/or uncertainties in night-time AOD calculation.

This work is based on all of the previous results to improve the AOD retrieval at night-time by selecting a set of clean and stable night-time conditions at Izaña in which day-time AOD data could be considered a good proxy for nocturnal AOD. Clean and stable conditions of days used in this study have been ensured using AERONET daytime data at the station and Micropulse lidar version 3 (MPL-3) atmospheric vertical profiles extracted from a nearby coastal station. The main aim of this study is to identify the errors sources, thereby trying to fix experimentally some of the problems currently affecting Moon photometry.

Section 2 describes the experiment site, instruments and methods used in this study. A description of the methodology developed to improve nocturnal AOD measurements and the corresponding validation performed at Izaña, as well as in other complementary stations, is presented in section 3. Finally conclusions are shown in section 4.

2 MEASUREMENT SITE

2.1 Test site

Nocturnal measurements have been carried out at Izaña Global Atmosphere Watch (GAW) Observatory (<http://izana.aemet.es>), managed by the Izaña Atmospheric Research Center (IARC) from the State Meteorological Agency of Spain (AEMET). The Izaña Observatory is a testbed for aerosols and water vapor remote sensing instruments of the World Meteorological Organization (WMO) Commission for Instruments and Methods of Observations (CIMO). It is a high mountain station (2373m a.s.l.) located in Tenerife (The Canary islands, Spain) at $28^{\circ} 18' N$, $16^{\circ} 29' W$. The main features of this station have been extensively described by Rodríguez et al. (2011); Cuevas et al. (2013); Guirado (2014) and Cuevas et al. (2015).

The station is characterized by NW subsiding air from the descending branch of the Hadley-cell, resulting in a strong temperature inversion normally located below the altitude of the station (800 to 1500 m a.s.l.). This structure usually separates the humid layer, potentially laden with some anthropogenic pollution from lower parts of the island, from the dry and clean troposphere above. Environmental conditions at Izaña make the site quite suitable for aerosol sensors calibrations because the wide range of AOD values: from AOD at 500 nm (AOD_{500}) below 0.01 under background almost-Rayleigh conditions to

AOD₅₀₀ > 0.15 under Saharan dust intrusions. Around 85% of the days present quite stable and low AOD₅₀₀ values, below 0.15 (Guirado, 2014). Pristine conditions make Izaña a suitable place to calibrate photometers using the Langley method.

2.2 Instruments

2.2.1 CE318-T photometer

5 The new Sun-sky-lunar multiband photometer (CE318-T) has recently been presented in Barreto et al. (2016) as an advanced system which combines the features of the Sun photometer CE318-N, extensively used as a reference instrument in AERONET network (Holben et al., 1998), with the lunar photometer prototype CE318-U presented in Barreto et al. (2013a, b). The new CE318-T photometer is capable of measuring Sun, Moon and sky radiances at an approximate field of view of 1.29° at eight nominal wavelengths of 1020, 937, 870, 675, 500, 440, 380 and 340 nm, using a silicon photodiode detector, as well as two
10 additional **measurements** at 1020 nm and 1640 nm using an InGaAs detector. Silicon 1020 nm channel has been temperature corrected following the methodology presented in Holben et al. (1998). The UV **spectral bands** do not allow an accurate AOD retrieval at night due to the low lunar signal in this wavelength range. The CE318-T master used in the present study has been calibrated by means of the Lunar-Langley calibration method presented in Barreto et al. (2013a). Cloud-screening of night-time AOD data has been performed by visual inspection and using the triplet criterion presented in Barreto et al. (2016).

15 2.2.2 MPL-3 Lidar

Vertical range corrected signal profiles from the MPL-3 Lidar installed in Santa Cruz de Tenerife (Tenerife, Canary Islands, Spain; 28° 30' N, 16° 12' W; 52 m a.s.l.) have been used to check the AOD stability. This instrument contains a solid-state laser system emitting at 532 nm in full-time continuous mode with a high-pulse repetition rate of 2500 Hz. More details of this system and the on-site maintenance and calibration techniques are described by Campbell et al. (2002) and Welton and
20 Campbell (2002).

2.3 ROLO model

RObotic Lunar Observatory (ROLO) model, developed as a part of the USGS and NASA-funded program for space-borne calibration, is considered an accurate tool for exo-atmospheric lunar spectral irradiance (I_0) estimation for a given position of the observer on the Earth's surface and at a given time (Kieffer and Stone, 2005). This empirically-based model provides
25 Moon's irradiance at 32 wavelengths, with an uncertainty between 5% and 10% in the absolute scale, using only geometrical variables: the absolute phase angle, the selenographic latitude and longitude of the observer and the selenographic longitude of the Sun. I_0 values have been calculated in this work as the convolution of the product of Moon reflectances, **calculated using our own implementation of the ROLO model based rigorously on the Eq. (10) published in Kieffer and Stone (2005)**, the solar spectrum given by Wehrli (1986) and the Earth-Moon and Sun-Moon distances, with each of the CE318-T filter responses. The
30 result must be multiplied by the solid angle of the Moon ($\sigma_M = 6.4177 \cdot 10^{-5}$ sr) divided by π , according to Kieffer and Stone (2005). The lunar ephemeris have been extracted using the Navigation Ancillary Information Facility (NAIF) of the NASA

Jet Propulsion Laboratory (JPL) (<http://naif.jpl.nasa.gov/naif.html>), which uses data of the orbital position of many celestial bodies known as kernels or Spacecraft, Planet, Instrument, C-matrix (pointing), and Events (SPICE) data files. This NAIF SPICE toolkit is free available at <http://naif.jpl.nasa.gov/>.

2.4 AOD retrieval method

- 5 Following Barreto et al. (2013a) and Barreto et al. (2016), AOD at night-time ($\tau_{a,night}$) for a given wavelength, λ , can be calculated using the following equation:

$$\tau_{a,night,\lambda} = \frac{\ln(\kappa_\lambda) - \ln\left(\frac{V_\lambda}{I_{0,\lambda}}\right) - m_{atm}(\theta) \cdot \tau_{atm,\lambda}}{m_a(\theta)}. \quad (1)$$

- 10 In this expression κ_λ is the calibration constant, V_λ is the measured voltage, $I_{0,\lambda}$ is the extraterrestrial Moon irradiance given by the ROLO model, m_{atm} and τ_{atm} are the air mass and the optical depth of all atmospheric attenuators with the exception of aerosols (Rayleigh scattering, and O_3 and NO_2 absorption), and m_a is the aerosol air mass. θ stands for the Moon's zenith angle. Sub-index λ makes reference to the respective λ -wavelength. All these terms have been calculated using the AERONET version 2 procedure (http://aeronet.gsfc.nasa.gov/new_web/data_description_AOD_V2.html).

- The calibration constant κ_λ has been calculated by means the Lunar-Langley method developed by Barreto et al. (2013a). The main equations involved in this method are the Eq. 2, derived from the Beer-Lambert-Bouguer Law (the basis of the Langley calibration technique described by many authors in sunphotometry, such as Shaw (1976, 1983); Holben et al. (1998), among others) and the Eq. 3 (the basis of the Lunar-Langley calibration technique), which defines the calibration constant as the ratio of V_0 to I_0 .

$$\ln(V_\lambda) = \ln(V_{0,\lambda}) - m(\theta) \cdot \tau_\lambda \quad (2)$$

$$V_{0,\lambda} = I_{0,\lambda} \cdot \kappa_\lambda \quad (3)$$

- 20 Following the error propagation analysis performed by Barreto et al. (2016), the total combined uncertainty on the AOD retrieved using the CE318-T photometer is the sum of the relative uncertainties associated with the instrument calibration, the ROLO model ($\sim 1\%$, independent of orbital parameters) and instrumental errors. Only uncertainties related to instrumental errors were expected to be dependent on Moon's phase angle (g).

3 RESULTS

3.1 Identifying bias in the lunar irradiance model

A set of 59 nights characterized by pristine and stable AOD conditions at Izaña covering different Moon cycles, from March to December 2014, has been selected in this study. We have ensured stable AOD conditions using ancillary vertical information from the MPL-3 lidar running at Santa Cruz de Tenerife station. These stable AOD conditions are confirmed by means of the range-corrected signal from the MPL-3 lidar at Santa Cruz and the AOD (day-time from AERONET and night-time from CE318-T, both at 500 nm) at Izaña. The AOD stability criterion involves an AOD difference between the 1-h average AERONET AOD of two consecutives days (sunset versus sunrise) ≤ 0.005 at 870 nm. The MPL-3 profiles and the AOD evolution for one moon cycle in the period 3-17 October, 2014, are shown in Fig. 1. AOD is stable in the whole period with the exception of 3-5 October and 10 October, and these three nights are discarded from the fitting analysis. AERONET daytime AOD in this period ranges from 0.004 in 1640 nm to 0.016 in 440 nm.

Nocturnal measurements were performed by means of a master CE318-T installed in Izaña station. This instrument has been calibrated following the Lunar-Langley calibration method proposed by Barreto et al. (2013a) (Eqs. 2 and 3). This is a new absolute calibration technique, specifically developed for lunar photometry, which is able to avoid the determination of one different calibration coefficient every night required by the common Langley technique (Eq. 2). It is important to emphasize the moon's illumination variation inherent to the lunar cycle, which means the V_0 and I_0 terms in Eq. 3 are continuously changing, even during the ~ 2 hour observation time period required to perform the Langley calibration. Even if we discard the I_0 variation during the Langley period, the extraterrestrial voltages V_0 should be determined every day, which is not plausible considering the restrictive requirements in terms of atmospheric stability and cloudiness of this calibration technique. In spite the simplicity of the Lunar-Langley technique, its accuracy relies on the uncertainty involved in the ROLO model. The uncertainty estimation of the Lunar-Langley method was performed by Barreto et al. (2016) assuming a relative ROLO accuracy of $\sim 1\%$, independent of any orbital parameter. As a result, if the existence of some bias in the ROLO model is confirmed, the accuracy of the Lunar-Langley technique for absolute calibration should be revised.

CE318-T Lunar-Langley calibration was performed on three different nights within the 10 Moon-cycles period used in this paper: 13 March, 12 June and 9 October. These three nights were characterized by Moon's illumination between 93% and 99%, with phase angles (g) between -31° and 19° . Meanwhile, CE318-T Langley calibration was performed on 51 different nights covering phase angles from -94° to 83° .

A comparison of the two absolute calibration techniques, Langley and Lunar-Langley, has been carried out in this paper. In the case of κ 's obtained using the Lunar-Langley technique, we have calculated the average I_0 from the ROLO model during the calibration period to obtain the calibration coefficient (V_0). To this end, we have used the Eq. 3.

We found nearly stable I_0 values during the Langley period (≤ 2 h), with average standard deviations below 1.6%. Relative V_0 differences with phase angle (Langley versus Lunar-Langley) are shown in Fig. 2 for 870 nm channel. Relative differences $> 4\%$ are observed, especially near full Moon and near waning Moon. Small differences were found for phase angles between -20° and 60° ($< 1\%$) and between 20° and 60° ($< 2\%$), in addition to an asymmetry of the differences with phase angle (higher

differences after full Moon). It is worth mentioning the Lunar-Langley calibration technique systematically underestimates V_0 throughout the lunar cycle.

This phase angle dependence of the ROLO model has been also reported by Lacherade et al. (2013, 2014) and Viticchié et al. (2013), as well as its asymmetry within the Moon cycle (Lacherade et al., 2013, 2014). Lacherade et al. (2014) found a variation up to 5% with the phase angle between $\pm 90^\circ$, the validity range of the ROLO model. These results are in agreement with the relative differences higher than 4% found in this study.

It is important to highlight that Barreto et al. (2016) considered negligible the contribution of the covariance term in the combined uncertainty of two magnitudes expected to be correlated: κ and I_0 . This last assumption, which neglects the effect of possible Moon's irradiance uncertainties on calibration, is only valid considering that there are not relevant systematic errors in the irradiance model. Our results prove this statement is wrong, and the existence of a bias in the lunar irradiance model must be taken into account in lunar photometry.

3.2 Correction of artificial AOD variations at night-time

Once we have verified the existence of a bias in the lunar irradiance model which introduces calibration and AOD uncertainties dependent on Moon's phase angle, we propose an empirical correction method for the AOD retrieval at night-time. This method is exclusively focused on the AOD retrieval and it does not involve any correction to the lunar irradiance model.

We propose an empirical correction based on the use of day-time AOD information as proxy for nocturnal AOD providing aerosol content remains stable. A total of 6997 night-time AOD measurements corresponding to the same 59 pristine and stable nights period (March to December 2014) in addition to 14575 daylight AOD measurements have been selected in this study. These clean conditions allow us to accurately estimate AOD at night-time considering a smooth AOD variation by linear interpolation using AERONET daylight information. AOD differences at night-time (ΔAOD_{fit}) are defined through the comparison of the night-time AOD estimated from linear interpolation using AERONET daylight data ($AOD_{night,interp}$) and the AOD obtained directly from nocturnal CE318-T measurements using Eq. (1) (AOD_{night}). Then, ΔAOD_{fit} can be obtained by means the following expression:

$$\Delta AOD_{fit} = \Delta AOD_{night,interp} - AOD_{night} \quad (4)$$

These differences are displayed in Fig. 3a with asterisks. We observe a clear dependence with the phase angle (g), increasing considerably for higher g values. This dependence is more evident for higher wavelengths and seems somewhat asymmetric (higher differences for positive g , namely, after full Moon, especially for 1020 nm channel), in agreement with the results obtained in Sect. 3.1. We have found the best fit for this dependency (δ_g) to be a second-order polynomial (Eq. (3)), as it is displayed in Fig. 3a with solid lines.

$$\delta_g(\lambda) = a_0(\lambda) + a_1(\lambda) \cdot g + a_2(\lambda) \cdot g^2 \quad (5)$$

The coefficients a_i in Eq. (3) are calculated for each channel centered at λ . In addition, the presence of a nocturnal cycle on ΔAOD_{fit} is also evident from Fig. 3a. These results are also in agreement with those found by Barreto et al. (2016), who found higher AOD discrepancies with respect to daytime AERONET data for higher phase angles, and a faint nocturnal AOD cycle.

- 5 The increasing uncertainty in AOD with g and the asymmetry of this dependence within the Moon cycle can be attributed, at least partially, to the existence of some residuals on the ROLO model, according to the results presented in Sect. 3.1. This effect results in a systematic g -dependent AOD error observed in Fig. 3a, with values up to 0.035 before full Moon (1640 nm) and > 0.06 after full Moon (1020 nm), both for the highest phase angles. As Barreto et al. (2016) found, relative uncertainties associated with lunar measurements performed under higher phase angles (low illumination) are about 0.5% due to lower
10 signal-to-noise ratio (SNR) compared with the 0.1% expected for near full Moon conditions. Note that these uncertainties change with g . However, this second factor introduces a random error, which we do not expect to introduce any bias in the AOD retrieval process.

- The observed AOD cycle at night-time is similar to the AOD cycle detected by many authors in sun photometry (Cachorro et al., 2004, 2008a, b), but with an amplitude dependent on g . The characteristics of this AOD cycle are expected to be similar
15 to those of sun photometry: systematic and symmetrical around the lunar noon (Moon at maximum height), with maximum values at lunar noon and vanishing for larger air masses, being independent of AOD. The systematic artificial AOD behavior and the persistence of this feature for different atmospheric conditions indicate it is not an atmospheric effect nor is it directly related to the ROLO model (ROLO's outputs are not θ -dependent). It is likely produced by a calibration problem caused by the use of a biased ROLO model during calibration. Since the nocturnal calibration is normally performed at high illumination
20 conditions, and AOD is subsequently calculated in these conditions using the ROLO irradiances (I'_0 s in Eq. (1)), we suspect the possible bias in ROLO is cancelled for lower phase angles. However, when calibration constants (independent in essence on Moon's phase) and the I'_0 s are applied to low illumination conditions in AOD calculation, some g -dependent AOD residuals are expected to appear, causing the artificial nocturnal cycle observed in the AOD residuals. Since this systematic effect can be modulated by the inverse of air mass, we propose to include the effect of zenith angle on AOD difference as a function of
25 $1/m_a$ (δ_θ in Eq. (4)).

$$\delta_\theta(\lambda) = \frac{\beta_0(\lambda)}{m_a(\theta)} \quad (6)$$

- The coefficient β_0 in Eq. (4) is calculated for each channel centered at λ . The functional form of this corrective factor against the air mass (not including any dependence on g), shows that the closer the Moon is to the zenith the higher AOD differences are (Fig. 3b). We have displayed δ_θ in a whole night at different phase angles and we found an impact of zenith angle on AOD
30 between 0.005 (at 500 nm) and 0.016 (at 1020 nm), as it is shown in Fig. 4. A similar and symmetrical nocturnal cycle is displayed in the three nights, one near full moon (8 October, g ranging from -9° to -3°) and two nights with low illumination conditions (6 April and 16 October, with g between $\pm 93^\circ$ and $\pm 96^\circ$), in which approximately the half of the Moon's trajectory between rising to setting times is displayed (due to sunlight).

3.3 Improvement of AOD retrieval at Izaña

The two effects parameterized in Eqs. (3) and (4) are considered independent. Since these two variables are uncorrelated we propose a final parametrization based in these two effects: phase angle dependence (quadratic dependence) modulated by zenith angle. This parametrization, for each channel centered at λ , is presented in Eq. (5), where $\delta_{g,\theta}$ represents the functional form

5 for ΔAOD_{fit} .

$$\delta_{g,\theta}(\lambda) = \frac{\beta_0(\lambda)}{m_a(\theta)} \cdot [a_0(\lambda) + a_1(\lambda) \cdot g + a_2(\lambda) \cdot g^2] \quad (7)$$

The main results for this regression analysis, including simultaneously g and θ dependences, are presented in Table 1, in which we observe R-squared values ranging from 0.78 in 1020 nm to 0.60 in 440 nm. These results indicate this fitted model is able to account for $\sim 78\%$ and 60% of the variation observed in ΔAOD_{fit} for 1020 nm and 1640 nm, respectively, which are the spectral bands more affected by the g and θ dependence, within the 95% confidence bounds. RMSE values range from 0.009 in 1020 nm to 0.004 in 870 nm, indicating a low variance of the residuals. In fact longer wavelength bands show higher RMSEs because they are more sensitively affected by this dependence. In this respect we observe this empirical model is able to reproduce the asymmetry with phase angle, especially notable in case of 1020 nm. The total residual sum squares (SSE) of this fitting analysis are 0.19 for 1020 nm and below 0.10 for the rest of bands. This fitting analysis can be used to define a corrected night-time AOD (AOD_{corr}) as the addition of the measured AOD (AOD_{night}) and $\delta_{g,\theta}$ ($AOD_{corr} = AOD_{night} + \delta_{g,\theta}$). The scatterplot between $\delta_{g,\theta}$ and ΔAOD_{fit} is shown in Fig. 5, where a good agreement between parameterized and measured differences is found in the case of shorter wavelengths ($\lambda \leq 870$ nm). The more important differences were retrieved for 1020 nm spectral band. We attribute the two branches above and below the horizontal line to a systematic error in our empirical model, which reproduces an amplified phase angle dependence in this 1020 nm spectral band. This effect is less appreciable but still discernible for 1640 nm. The points above the diagonal correspond to overcorrected AOD values. It happens for high and positive phase angles. On the contrary, the points below the diagonal line represent those conditions poorly corrected, and happens for high and negative phase angles. Finally, the third branch with $\delta_{g,\theta}$ values up to 0.09 is observed for high and positive phase angles in some days in October and November, 2014. We suspect that instrumental problems are behind such overcorrection cases.

25 We have performed an AOD day-night-day transition coherence test at Izaña in order to check this correction procedure. In this test we have compared nocturnal (CE318-T master) and day-time (CE318-N AERONET master) AOD corresponding to the consecutive 1-h time period during Moonset-Sunrise (MS-SR) and Sunset-Moonrise (SS-MR) in those 59 day-night-day transitions in 2014 classified as stable in terms of aerosol loads. In this test analysis ΔAOD_{trans} represents the AOD difference between 1-h of Sun and Moon data. ΔAOD_{trans} before and after correction for phase angles ranging from -100° to 100° is presented in Fig. 6 and Table 2 for the six channels. We have verified the reduction in the systematic errors of ΔAOD_{trans} after the correction, even though some problems of overcorrection are detected in the case of 1020 nm for $g > 50^\circ$ and 500 nm for $g < -50^\circ$. AOD correction near full Moon is very low, as we expected from Eq. (5). We have found AOD differences within ± 0.01 after correction for any illumination condition, below the instrumental precision expected for the CE318-T photometer

Barreto et al. (2016). This nocturnal AOD improvement is also evident in Fig. 7, especially for longer wavelength channels at low illumination conditions.

Finally, we present in Table 3 the mean AOD difference after and before the AOD correction (ΔAOD) in the 59 nights AOD-stable period in 2014 at Izaña as a function of phase angle. These differences are below 0.01 in the case of near full moon conditions, but higher in the case of low illumination conditions: up to 0.04 and 0.03 for 1020 nm and 1640 nm, respectively, and below 0.018 in the rest of channels. These results indicate the successful AOD correction, especially in longer wavelength channels, and the effective correction of the asymmetries through the Moon's cycle.

It is worth mentioning $\delta_{g,\theta}$ could be introduced in Eq. (1) to obtain AOD_{corr} , and therefore $\delta_{g,\theta}$ could be subsequently used to define an I_0 correction only dependent on Moon's phase angle ($I'_0 = I_0/\delta_g$).

3.4 Evaluation of the AOD correction at Izaña

We have carried out the validation of the AOD correction presented ($\delta_{g,\theta}$ in Eq. (5) with the coefficients in Table 1) using night-time AOD extracted from the CE318-T master at Izaña in the period June to August, 2016. This is a 43-night period which includes pristine conditions and some dust outbreaks with a maximum AOD at 500 nm of 0.61 (June, 2016). This period is suitable to assess the AOD correction in a time period different than that used to parameterize the correction empirical model (parameterization period) and at different AOD loads. Similar results were observed in this case (see Table 4), with average AOD differences (after and before correction) up to 0.037 (1020 nm) and 0.023 (1640 nm) in the case of low illumination conditions, and below 0.016 in the rest of spectral bands. We have observed again, as in the parameterization period in 2014, a considerably reduction in the g and θ dependence on AOD after correction.

3.5 Evaluation of the AOD correction at other sites: Carpentras, Dakar and Lille

As a complementary validation analysis, we have extended the implementation of the previous correction procedure to other three test sites, affected by different aerosol conditions. We have applied to the nocturnal AOD obtained at these other sites the same AOD correction ($\delta_{g,\theta}$ in Eq. (5)) with the same coefficients presented in Table 1, in order to ensure the validity of this empirical model to sites with quite different aerosols content. Carpentras (44° 4' N, 5° 3' E, 100 m a.s.l.) and Lille (50° 36' N, 3° 8' E, 60 m a.s.l.), are two calibration sites located in France. Both sites are affected by relatively low AOD conditions and fine mode particles as the dominant aerosol size distribution (average AOD at 500 nm of 0.14 and 0.19, respectively, and average Angström Exponent of 1.4 and 1.2, respectively). In contrast, the station located in Dakar (M'Bour, Senegal, 14° 23' N, 16° 57' W, 0 m a.s.l.) presents a significant contribution of marine aerosols and biomass burning aerosols during the dry season, but also mineral dust with maximum influence in summer (Leon et al., 2009). In this case the averaged AOD at 500 nm and Angström Exponent are 0.45 and 0.37, respectively, indicating the predominant coarse-mode aerosol at this station.

We have used nocturnal CE318-T AOD data at Carpentras in a 9-night period from 15-24 February 2016, 10-night period at Dakar from 18-29 April 2016, and a 12-night period at Lille from 13-28 April 2016. These three instruments have been calibrated using the Lunar-Langley calibration technique at Izaña. AOD difference after and before correction (ΔAOD) for these three stations are quantified in Table 4 and displayed for different phase angles in Fig. 8 (only for 1640 nm, 1020 nm and

440 nm, to improve visualization). We found ΔAOD values similar to those obtained for Izaña, between 0.021 (1640 nm in Carpentras) and 0.005 (500 nm in Lille) in case of phase angle $g \leq -50^\circ$, below 0.01 in case of near full moon conditions, and ranging from 0.033 (1020 nm in Dakar) to 0.010 (675, 500 and 440 nm in Dakar) for $g \geq 50^\circ$. It is worth mentioning we have observed at these three stations a similar asymmetry of ΔAOD with the Moon's cycle previously detected at Izaña, in which AOD differences are higher for 1020 nm in case of high and positive phase angles (see Fig. 8b) while maximum differences are observed in 1640 nm when phase angle g is strongly negative (see Figs. 8a and 8c). These results corroborate the existence of a residual phase angle dependence on nocturnal AOD, and also exhibit a similar-in-magnitude zenith angle dependence as the one observed at Izaña, discarding the instrumental problem as the source of these errors. This evaluation analysis in different stations seems to corroborate that this correction procedure is applicable to other instruments and sites. However, it is fair to admit this correction has been performed by means of an unique instrument, with certain optical interference filters. The difference in the filter responses as well as the degradation of optical filters with time are the limiting factors. They could add an extra uncertainty depending on the different band responses between instruments. Further studies will be focused on the estimation of this extra uncertainty.

4 CONCLUSIONS

The comparison of the CE318-T calibration performed by means of the Lunar-Langley and the calibration performed every single night by means of the common Langley technique indicates the existence of some systematic errors on the ROLO's lunar irradiances. These systematic errors could have an important impact on the AOD retrieved by means of lunar photometry. In order to reduce the uncertainties in the AOD retrieved at night-time using a calibration technique dependent on this lunar irradiance model (the Lunar-Langley and the intercomparison techniques Ratio Sun and Ratio Moon), we have studied the evolution of the AOD at night-time at Izaña high mountain observatory in a period characterized as clean and stable. These conditions were ensured by means of vertical profiles from an MPL-3 lidar installed in a nearby coastal station as well as by means of an AOD stability criterion using daytime AERONET data. We detected an important bias correlated to Moon's phase and zenith angles (g and θ) in all the spectral bands. However, the important phase angle dependence found for 1020 nm and 1640 nm might be an artifact caused by an systematic error in our empirical model. Working under stable AOD conditions, we have parameterized this residual dependence in nocturnal AOD in terms of Moon's phase and zenith angles through an empirical regression model. Our results show AOD at night-time is significantly corrected, with absolute errors < 0.01 , i.e., below the instrument precision, in spite of the absence of a robust cloud screening system.

We attribute the phase angle dependence on AOD residuals to the inherent limitations of the ROLO model. The nocturnal cycle observed in AOD with a g -dependent amplitude could be related to the existence of a propagation of systematic calibration errors as a result of the use of a biased irradiance model for calibration (performed under high illumination conditions) and its subsequent use for AOD calculation. As a result, the use of a biased model during the Lunar-Langley calibration unavoidably introduces systematic calibration uncertainties that should be corrected using the empirical equations proposed in this study. The authors would like to admit this is only a preliminary AOD correction proposal developed using one single instrument

which might be refined and used to correct the lunar irradiance model in future studies.

Since long-term lunar observations are required for an accurately modelling of the Moon's phase and librations effects, several years of lunar measurements are required to perform an adequate correction, in terms of both AOD or I_0 . In this respect, we strongly recommend the use of the unique calibration method independent on any lunar irradiance model: the Sun-Moon Gain factor method, proposed by Barreto et al. (2016). Further investigations will be carried out to check the suitability of this technique for different locations and Moon's illumination conditions.

It should be highlighted that in this study the authors only intend to correct as much as possible the AOD retrieval at night-time affected by these biases. It is out of the scope of the present study to propose and perform corrections on the ROLO USGS model. This issue is beginning to be addressed thoroughly by several groups. An example is the Global Space-based Inter-Calibration System (GSICS) Lunar Observation Dataset (GLOD), a collaborative effort to use the Moon as a common and unique calibration reference at international level. This database includes Moon observations from several space organizations such as the European Space Agency (ESA), the European Organization for the Exploitation of Meteorological Satellites (EU-METSAT), the National Centre for Space Studies (CNES), The Japan Aerospace Exploration Agency (JAXA), the National Satellite Meteorological Center from China Meteorological Administration (NSMC/CMA) or the National Aeronautics and Space Administration (NASA), among others.

Acknowledgements. This work has been developed within the framework of the activities of the World Meteorological Organization (WMO) Commission for Instruments and Methods of Observations (CIMO) Izaña Testbed for Aerosols and Water Vapor Remote Sensing Instruments.

AERONET Sun photometers at Izaña have been calibrated within the AERONET Europe TNA, supported by the European Union's Horizon 2020 research and innovation programme under grant agreement No 654109 (ACTRIS-2). The authors also thank AERONET team for their support. The GAW-PFR network for AOD at WMO-GAW global observatories has been implemented by the World Optical Depth Research and Calibration Center (WORCC).

References

- Baibakov, K., O'Neill, N. T., Ivanescu, L., Duck, T. J., Perro, C., Herber, A., Schulz, K.-H., and Schrems, O.: Synchronous starphotometry and lidar measurements at Eureka in High Canadian Arctic, *Atmos. Meas. Tech.*, 8, 3789-3809, doi:10.5194/amt-8-3789-2015, 2015.
- Barreto, Á., Cuevas, E., Damiri, B., Guirado, C., Berkoff, T., Berjón, A. J., Hernández, Y., Almansa, F., and Gil, M.: A new method for nocturnal aerosol measurements with a lunar photometer prototype, *Atmos. Meas. Tech.* 6, 585-598, doi:10.5194/amt-6-585-2013, 2013a.
- Barreto, Á., Cuevas, E., Damiri, B., Romero, P. M., and Almansa, F.: Column water vapor determination in night period with a lunar photometer prototype, *Atmos. Meas. Tech.*, 6, 2159-2167, doi:10.5194/amt-6-2159-2013, 2013b.
- Barreto, Á., Cuevas, E., Granados-Muñoz, M.-J., Alados-Arboledas, L., Romero, P. M., Gröbner, J., Kouremeti, N., Almansa, A. F., Stone, T., Toledano, C., Román, R., Sorokin, M., Holben, B., Canini, M., and Yela, M.: The new Sun-sky-lunar Cimel CE318-T multiband photometer – a comprehensive performance evaluation, *Atmos. Meas. Tech.*, 9, 631-654, doi:10.5194/amt-9-631-2016, 2016.
- Berkoff, T. A., Sorokin, M., Stone, T., Eck, T. F., Hoff, R., Welton, E., and Holben, B.: Nocturnal aerosol optical depth measurements with a small-aperture automated photometer using the moon as a light source, *J. Atmos. Ocean. Tech.*, 28, 1297-1306, doi:10.1175/JTECH-D-10-05036.1, 2011.
- Cachorro, V. E., Romero, P. M., Toledano, C., Cuevas, E., de Frutos, A. M.: The fictitious diurnal cycle of aerosol optical depth: A new approach for “in situ” calibration and correction of AOD data series, *Geophys. Res. Lett.*, 31, L12106, doi: 10.1029/2004GL019651, 2004.
- Cachorro, V. E., Toledano, C., Berjón, A. J., de Frutos, A. M., Sorribas, M.: Comment on “On Langley plots in the presence of a systematic diurnal aerosol cycle centered at noon: A comment on recently proposed methodologies” by F. Marengo, *J. Geophys. Res.*, 113, D11210, doi: 10.1029/2007JD009137, 2008a.
- Cachorro, V. E., Toledano, C., Berjón, A. J., de Frutos, A. M., Torres, B., Sorribas, M., Laulainen, N. S.: An “in situ” calibration correction procedure (KCICLO) based on AOD diurnal cycle: Application to AERONET–El Arenosillo (Spain) AOD data series, *J. Geophys. Res.*, 113, D12205, doi: 10.1029/2007JD009673, 2008b.
- Campbell, J.R., Hlavka, D.L., Welton, E.J., Flynn, C.J., Turner, D.D., Spinhirne, J.D., Scott, V.S., and Hwang, I.H.: Full-time, Eye-Safe Cloud and Aerosol Lidar Observation at Atmospheric Radiation Measurement Program Sites: Instrument and Data Processing, *J. Atmos. Oceanic Technol.*, 19, 431-442, doi: [https://doi.org/10.1175/1520-0426\(2002\)019<0431:FTESCA>2.0.CO;2](https://doi.org/10.1175/1520-0426(2002)019<0431:FTESCA>2.0.CO;2), 2002.
- Cramer, C. E., Lykke, K. R., Woodward, J. T., and Smith, A. W.: Precise measurements of lunar spectral irradiance at visible wavelengths, *J. Res. Natl. Inst. Stan.*, 118, doi: <http://dx.doi.org/10.6028/jres.118.020>, 2013.
- Cuevas, E., González, Y., Rodríguez, S., Guerra, J. C., Gómez-Peláez, A. J., Alonso-Pérez, S., Bustos, J., and Milford, C.: Assessment of atmospheric processes driving ozone variations in the subtropical North Atlantic free troposphere, *Atmos. Chem. Phys.*, 13, 1973-1998, doi:10.5194/acp-13-1973-2013, 2013.
- Cuevas, E., Camino, C., Benedetti, A., Basart, S., Terradellas, E., Baldasano, J. M., Morcrette, J. J., Marticorena, B., Goloub, P., Mortier, A., Berjón, A., Hernández, Y., Gil-Ojeda, M., and Schulz, M.: The MACC-II 2007-2008 reanalysis: atmospheric dust evaluation and characterization over northern Africa and the Middle East, *Atmos. Chem. Phys.*, 15, 3991-4024, doi:10.5194/acp-15-3991-2015, 2015.
- Eck, T., Holben, B., Reid, J. S., Dubovik, O., Smirnov, A., O'Neill, N. T., Slutsker, I., and Kinne, S.: Wavelength dependence of the optical depth of biomass burning urban and desert dust aerosols, *J. Geophys. Res.*, 104, 31333–31349, doi: 10.1029/1999J00923, 1999.
- Eck, T. F., Holben, B. N., Reid, J. S., Sinyuk, A., Hyer, E. J., O'Neill, N. T., Shaw, G. E., Vande Castle, J. R., Chapin, F. S., Dubovik, O., Smirnov, A., Vermote, E., Schafer, J. S., Giles, D., Slutsker, I., Sorokine, M., and Newcomb, W. W.: Optical properties of boreal region

- biomass burning aerosols in central Alaska and seasonal variation of aerosol optical depth at an Arctic coastal site, *J. Geophys. Res.*, 114, doi:10.1029/2008JD010870, 2009.
- Eck, T. F., Holben, B. N., Sinyuk, A., Pinker, R. T., Goloub, P., Chen, H., Chatenet, B., Li, Z., Singh, R. P., Tripathi, S. N., Reid, J. S., Giles, D. M., Dubovik, O., O'Neill, N. T., Smirnov, A., Wang, P., and Xia, X.: Climatological aspects of the optical properties of fine/coarse mode aerosol mixtures, *J. Geophys. Res.*, 115, doi:10.1029/2010JD014002, 2010.
- Esposito, F., Serio, C., Pavesse, G., Auriemma, G., and Satriano, C.: Measurements of nighttime atmospheric optical depth. Preliminary data from mountain site in southern Italy, *J. Aerosol Sci.*, 29, 1213-1218, 1998.
- Esposito, F., Mari, S., Pavese, G., and Serio, C.: Diurnal and Nocturnal Measurements of Aerosol Optical Depth at a Desert Site in Namibia, *Aer. Sci. Tech.*, 37:4, 392-400, doi: 10.1080/027868203000972, 2003.
- 10 Guirado C.: Caracterización de las propiedades de los aerosoles en columna en la región subtropical, Ph.D. thesis, Universidad de Valladolid, Valladolid, Spain, 2014.
- Holben, B. N., Eck, T. F., Slutsker, I., Tanré, D., Buis, J. P., Setzer, A., Vermote, E., Reagan, J. A., Kaufman, Y. J., Nakajima, T., Lavenue, F., Jankowiak, I., and Smirnov A.: AERONET – A federated instrument network and data archive for aerosol characterization, *Remote Sens. Environ.*, 66, 1-16, doi:https://doi.org/10.1016/S0034-4257(98)00031-5, 1998.
- 15 Holben, B.N., D. Tanré, A. Smirnov, T. F. Eck, I. Slutsker, N. Abuhassan, W. W. Newcomb, J. Schafer, B. Chatenet, F. Lavenue, Y. J. Kaufman, J. Vande Castle, A. Setzer, B. Markham, D. Clark, R. Frouin, R. Halthore, A. Karnieli, N. T. O'Neill, C. Pietras, R. T. Pinker, K. Voss, and G. Zibordi: An emerging ground-based aerosol climatology: Aerosol Optical Depth from AERONET, *J. Geophys. Res.*, 106, 12 067-12 097, doi: 10.1029/2001JD900014, 2001.
- IPCC: Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate Change, edited by: Stocker, T. F., Qin, D., Plattner, G.-K., Tignor, M., Allen, S. K., Boschung, J., Nauels, A., Xia, Y., Bex, V., and Midgley, P. M., Cambridge University Press, Cambridge, UK and New York, NY, USA, 1535 p., doi:10.1017/CBO9781107415324, 2013.
- 20 Forster, P., Ramaswamy, V. , Artaxo, P. , Bernsten, T., Betts, R., Fahey, D.W., Haywood, J., Lean, J., Lowe, D. C., Myhre, G., Nganga, J., Prinn, R., Raga, G., Schulz, M., and Van Dorland, R.: Changes in Atmospheric Constituents and in Radiative Forcing. In: Climate Change 2007: The Physical Science Basis. Contribution of Working Group I to the Fourth Assessment Report of the Intergovernmental Panel on Climate Change. Solomon, S., D. Qin, M. Manning, Z. Chen, M. Marquis, K.B. Averyt, M.Tignor and H.L. Miller (Eds.). Cambridge University Press, Cambridge, United Kingdom and New York, NY, USA., 2007.
- 25 Kieffer, H. H. and Stone, T. C.: The spectral irradiance of the moon, *The Astronomical Journal*, 129, 2887-2901, doi: https://doi.org/10.1086/430185, 2005.
- 30 Lacherade, S., Viticchié, B., Stone, T., Lebégue, L., Wagner, S., and Hewison, T.: On the phase-angle dependence of the moon calibration results, *GSICS Quat: Lunar calibration*, 7, 3, 2013..
- Lacherade, S., Aznay, O., Fougne, B., and Lebégue, L.: POLO: a unique dataset to derive the phase angle dependence of the Moon irradiance, *Proc. SPIE 9241, Sensors, Systems, and Next-Generation Satellites XVIII*, 924112 (October 7, 2014), doi:10.1117/12.2067283, 2014.
- Leiterer, U., Naebert, A., Naebert, T., and Alekseeva, G.: A new star photometer developed for spectral aerosol optical thickness measurements in Lindenberg, *Contrib. Atmos. Phys.*, 68, 133-141, 1995.
- Leon, J.-F., Derimian, Y., Chiapello, I., Tanré, D., Podvin, T., Chatenet, B., Diallo, A., and Deroo, C.: Aerosol vertical distribution and optical properties over M'Bour (16.96° W; 14.396° N), Senegal from 2006 to 2008, *Atmos. Chem. Phys.*, 9, 9249-9261, doi:10.5194/acp-9-9249-2009, 2009.

- Miller, S. D., Combs, C. L., and Kidder, S. Q.: Assessing Moonlight Availability for Nighttime Environmental Applications by Low-Light Visible Polar-Orbiting Satellite Sensors, *J. Atmos. Oceanic Tech.*, 29, 538-557, doi: 10.1175/JTECH-D-11-00192.1, 2012.
- Pérez-Ramírez, D., Lyamani, H., Olmo, F. J., Whiteman, D. N., Navas-Guzmán, F., and Alados-Arboledas, L.: Cloud screening and quality control algorithm for star photometer data: assessment with lidar measurements and with all-sky images, *Atmos. Meas. Tech.*, 5, 1585–1599, doi: 10.5194/amt-5-1585-2012, 2012.
- Pérez-Ramírez, D., Veselovskii, I., Whiteman, D. N., Suvorina, A., Korenskiy, M., Kolgotin, A., Holben, B., Dubovik, O., Siniuk, A., and Alados-Arboledas, L.: High temporal resolution estimates of columnar aerosol microphysical parameters from spectrum of aerosol optical depth by linear estimation: application to long-term AERONET and star-photometry measurements, *Atmos. Meas. Tech.*, 8, 3117–3133, doi: 10.5194/amt-8-3117-2015, 2015.
- 10 Rodríguez, S., Alastuey, A., Alonso-Pérez, S., Querol, X., Cuevas, E., Abreu-Afonso, J., Viana, M., Pérez, N., Pandolfi, M., and de la Rosa, J.: Transport of desert dust mixed with North African industrial pollutants in the subtropical Saharan Air Layer, *Atmos. Chem. Phys.*, 11, 6663-6685, doi:10.5194/acp-11-6663-2011, 2011.
- Shaw, G. E.: Error analysis of multi-wavelength Sun photometry, *Pure Appl. Geophys.*, 114, 1-14, doi: 10.1007/BF00875487, 1976.
- Shaw, G. E.: Sun photometry, *Bull. Am. Meteorol. Soc.*, 64, 4-10, doi: [https://doi.org/10.1175/1520-0477\(1983\)064<0004:SP>2.0.CO;2](https://doi.org/10.1175/1520-0477(1983)064<0004:SP>2.0.CO;2),
15 1983.
- Viticchié, B., Wagner, S., Hewison, T. and Stone, T.: Lunar calibration of MSG/SEVIRI solar bands, *GSICS Quat: Lunar calibration*, 7, 3, 2013.
- Wehrli, C.: *Spectral Solar Irradiance Data* (WMO ITD 149; Geneva: WMO), 1986.
- Welton, E. J., and Campbell, J. R.: Micro-pulse lidar signals: Uncertainty analysis, *J. Atmos. Oceanic Technol.*, 19, 2089-2094, doi:
20 [https://doi.org/10.1175/1520-0426\(2002\)019<2089:MLSUA>2.0.CO;2](https://doi.org/10.1175/1520-0426(2002)019<2089:MLSUA>2.0.CO;2), 2002.

Table 1. Results of ΔAOD_{fit} parameterization for each channel: model coefficients, coefficient of determination (R-squared) and root-mean-squared-error (RSME) within 95% confidence bounds.

Channel (nm)	a_0	a_1	a_2	a_3	R-squared	RMSE
1640	0.1260	0.0441	0.0040	0.0017	0.64	0.007
1020	-0.7311	-0.8115	-0.0220	-0.0004	0.78	0.009
870	-0.0917	-0.0919	-0.0062	-0.0007	0.78	0.004
675	-0.0260	-0.0132	-0.0174	-0.0002	0.71	0.005
500	-0.0022	-0.0001	-0.0001	-0.9755	0.68	0.005
440	0.0097	0.0155	0.0009	0.0037	0.60	0.006

Table 2. Averaged AOD differences between CE318-AERONET day-time and CE318-T night-time data (ΔAOD_{trans}) during Sunset-Moonrise and Moonset-Sunrise in three ranges of Moon’s phase angles (g) with and without $\delta_{g,\theta}$ correction.

g range	# cases	correction	1640	1020	870	675	500	440
$\leq -50^\circ$	39	no	0.024	0.019	0.017	0.014	0.011	0.010
		yes	0.008	0.007	0.007	-0.003	-0.005	-0.003
$-50^\circ > g > 50^\circ$	81	no	0.011	-0.003	0.008	0.007	0.005	0.002
		yes	0.008	-0.001	0.006	0.005	0.004	0.002
$\geq 50^\circ$	26	no	0.022	0.025	0.014	0.013	0.010	0.010
		yes	0.002	-0.006	0.001	0.002	-0.001	0.001

Table 3. Average AOD difference between corrected and non-corrected AOD (ΔAOD) measured at Izaña station as a function of the Moon’s phase angle (g) in degrees in a 59 nights period transition coherence test in 2014. Number of night-time measurements (N) is included.

g range	N	1640	1020	870	675	500	440
$\leq -50^\circ$	891	0.020	0.015	0.012	0.014	0.008	0.008
$-50^\circ > g > 50^\circ$	5076	0.003	0.003	0.002	0.002	0.001	0.001
$\geq 50^\circ$	1030	0.026	0.041	0.018	0.014	0.014	0.013

Table 4. Average AOD difference between corrected and non-corrected AOD (ΔAOD) measured at four different stations in 2016. Number of night-time measurements (N) are included.

g range	station	N	1640	1020	870	675	500	440
$\leq -50^\circ$	Izana	870	0.016	0.011	0.010	0.012	0.006	0.006
	Carpentras	350	0.021	0.015	0.013	0.015	0.008	0.009
	Lille	55	0.015	0.009	0.010	0.011	0.005	0.006
	Dakar	0	—	—	—	—	—	—
$-50^\circ > g > 50^\circ$	Izana	3459	0.003	0.004	0.002	0.002	0.001	0.001
	Carpentras	660	0.003	0.001	0.002	0.002	0.001	0.001
	Lille	423	0.003	0.001	0.002	0.002	0.001	0.001
	Dakar	527	0.002	0.002	0.002	0.002	0.001	0.001
$\geq 50^\circ$	Izana	631	0.023	0.037	0.016	0.012	0.012	0.011
	Carpentras	0	—	—	—	—	—	—
	Lille	7	0.011	0.018	0.008	0.006	0.006	0.005
	Dakar	31	0.020	0.033	0.014	0.010	0.010	0.010




Figure 1. Lidar range-corrected backscattering signal from the MPL-3 installed at Santa Cruz and AOD (at 500 nm) evolution (day in pink circles and night in black circles) extracted from the CE318-T installed in Izaña in October, 2014. Horizontal white line represents the Izaña's Observatory altitude.




Figure 2. Calibration coefficients (V_0) relative difference (%) at 870 nm when Langley and Lunar-Langley absolute calibration techniques are compared. Smoothing by means of LOESS (locally estimated scatterplot smoothing) is shown with solid line. The shaded areas represent the 95% confidence interval.




Figure 3. (a) AOD differences between daylight interpolated and night-time measured values (ΔAOD_{fit} with data points) and AOD differences predicted from the fitting analysis with Moon's phase angle (δ_g with coloured lines). (b) AOD differences predicted from the fitting analysis with Moon's zenith angle (δ_{θ}).




Figure 4. Predicted AOD differences from the fitting analysis with θ (δ_θ) for different phase angles: (a) 6 April, (b) 8 October and (c) 16 October.




Figure 5. Scatterplot with parameterized ($\delta_{g,\theta}$) and measured (ΔAOD_{fit}) AOD differences. Solid line is the diagonal ($y = x$).




Figure 6. AOD differences with the Moon's phase angle in the AOD day/night transition coherence test between day-time CE318-N AERONET AOD and CE318-T night-time AOD during Sunset-Moonrise and Moonset-Sunrise period before (circles) and after (triangles) the AOD correction.




Figure 7. AOD evolution for one Moon cycle (June, 2014) at Izaña. Opaque colors represent daylight data. Nocturnal AOD before (a) and after (b) correction is plotted.




Figure 8. AOD before correction (BC) and after correction (AC) on AOD in (a) Carpentras, (b) Dakar and (c) Lille in 2016. Opaque colors represent daylight data. The black line and right y axis correspond to the phase angle evolution in this period.