

Interactive comment on “Evaluation of atmospheric profiles derived from single- and zero-difference excess phase processing of BeiDou System radio occultation data of the FY-3C GNOS mission” by Weihua Bai et al.

Weihua Bai et al.

liucongliang1985@gmail.com

Received and published: 13 November 2017

We thank the referees very much for the constructive comments and recommendations and for the overall positive rating that this is a significant scientific paper. We thoroughly considered all comments and carefully revised the manuscript accounting for most of them. In addition, we carefully complemented these revisions with a range of further improvements throughout the manuscript text in the spirit of the comments.

(Please read the amt-2017-177-supplement.pdf by the link at end of this document, in

[Printer-friendly version](#)

[Discussion paper](#)



which you can find the response to all the referees and the revised manuscript)

AMTD

This paper presents results from the “GNOS” radio occultation (RO) measurements aboard the Chinese FY-3C satellite. It is shown that BeiDou GNSS observations, analyzed in single-differencing (SD) and zero-differencing (ZD) mode, produce bending angle and refractivity profiles of equivalent quality, when compared to ECMWF and co-located radiosonde data. In addition, due to the non-uniform global coverage of the current BeiDou space segment the ZD data set includes about 20% more events compared to the SD set because occasionally suitable BeiDou satellites providing the reference link were not available within the receiver’s antenna field of view. Furthermore, a unique feature of the BDS system is that the signal transmitters are placed into three diverse orbits (MEO, IGSO, GEO). The present study convincingly shows that these orbit differences significantly modify the zonal and meridional distribution of RO events, but have no appreciable impact on the quality of the derived atmospheric profiles. This well-written paper is a valuable contribution to the present knowledge on single versus zero-differencing RO analysis and I definitely recommend publication with some minor modifications described below.

Thank you.

General comments: As emphasized by the authors the successful application of zero-differencing is made possible by the presence of an ultra-stable oscillator driving the GNOS instrument. It would be instructive to illustrate the performance of this clock by providing clock offset statistics. These could be extracted from the results of the FY-3C precise orbit determination.

Ok, it's a good advice, a detailed comparison analysis of the ZD and SD algorithms is a very interesting study point for us as well, and we plan to do it by an extra paper. For this paper, we preferred to give a concise algorithms description and focus on our initial FY-3C GNOS data evaluation and validation.

The comparisons of SD and ZD with ECMWF and radiosonde data are instructive and

Interactive comment

Printer-friendly version

Discussion paper



illuminating. In addition, the direct comparison between SD and ZD bending angle profiles would be worthwhile to consider, in order to substantiate the hypothesis that no biases between the SD and ZD results exist. If possible, I would encourage the authors to add a corresponding figure in the revised paper.

Ok, it's a good idea to show the direct comparison between SD and ZD bending angle and other retrieved profiles to substantiate the consistency of the SD and ZD results (but not the hypothesis of strictly no biases between the SD and ZD results, we believe, because if the LEO satellite clock is stable and accurate enough, the ZD results should be with higher accuracy than the ZD results, theoretically). On the other hand, the topic of this paper is 'evaluation of atmospheric profiles derived from single- and zero-difference excess phase processing of BeiDou System radio occultation data of the FY-3C GNOS mission', but not comparison analysis of ZD and SD algorithms. Therefore, we preferred to keep the comparisons of SD and ZD with ECMWF and radiosonde data so far, since those figures are very helpful to provide an initial evaluation and validation of the SD and ZD retrievals in a scientifically reasonable way. Moreover, the readers somehow can see the level of consistency of the SD and ZD retrievals through these comparison figures. Considering the main topic and space limitation of this paper, we therefore preferred to keep the current comparison strategy and figures (and leave rigorous SD, ZD intercomparisons as next steps of refined analyses).

Specific remarks and questions: Page 3, lines 21ff: "One of these LEO missions is China's GNss Occultation Sounder (GNOS) onboard first time on the FengYun 3 series C satellite (FY-3C), [...]." For completeness I suggest to add the reference Bai, W. H., Sun, Y. Q., Du, Q. F., Yang, G. L., Yang, Z. D., Zhang, P., Bi, Y. M., Wang, X. Y., Cheng, C., and Han, Y.: An introduction to the FY3 GNOS instrument and mountain-top tests, *Atmos. Meas. Tech.*, 7, 1817–1823, 10.5194/amt-7-1817-2014, 2014. Ok, done.

Page 4, lines 6–7: "So far, a large dataset of FY-3 GNOS RO observations has been obtained." If I understand correctly, GNOS measurements aboard FY-3C started in September 2013. Thus, as of now the available data set should cover more than 3.5



Interactive
comment

years. I suggest to add a comment clarifying the decision to restrict the data analysis to the time period of three months between October and December 2013. Thank you for this suggestion. Right, the available GNOS RO data set is more 3.5 years now. We used the first three month GNOS BDS RO data set in this paper because this period is the GNOS in-orbit testing time, and we have done lots of evaluation and analysis using this dataset. And in our opinion a 3-month GNOS BDS RO dataset is sufficient for in-orbit testing and this initial BDS RO validation paper. Future more climate-oriented analyses will use longer data records.

Page 6, lines 9ff: "Specifically, in this study, we use the BDS satellite data as orbital data inputs and outputs, while time-wise also using GPS time for the processing of the BDS data." I'm not sure I understand this sentence. Is GPS time used for time-tagging of GPS as well as BDS observations? Please explain. Yes, the GPS time is used for time-tagging of GPS as well as BDS observations, as described in Section 2.1.

Page 6, eqn. (1), page 7, eqn. (2), and elsewhere: To avoid a potential misunderstanding, I suggest to define $_{ta}$ as the LEO clock error (offset) at the time of signal reception and similarly $_{tb}$ as the GNSS clock error (offset) at the time of signal transmission. With this change there is no need to regard $_{ta}$ and $_{tb}$ as functions and the function arguments in brackets (which might be confused with brackets marking an algebraic expression) could be dropped. Ok, done. We have revised the related equations following this criterion, for the clock terms with only a subscript 'a' and only a superscript 'b' or 'c', since we agree this anyway clearly indicates reception time and transmission time. And for the terms with both the subscript 'a' and superscript 'b' or 'c', we just kept the simple argument ' (t_r) ' to make sure we indicate the allocation to reception time.

Page 7, lines 13ff: "The GNSS satellite orbits (positions and velocities) and the GNSS clock offset estimates [...] are provided by the International GNSS Service [...]." IGS orbits are provided in a terrestrial reference frame. Here, a (quasi-)inertial trueof-date frame (page 5, section 2.1 "Basic algorithm of the excess phase processing") is used. For clarity, I suggest to add a remark indicating that a corresponding frame transfor-

[Printer-friendly version](#)[Discussion paper](#)

mation has been applied. Yes, in our processing, the GNSS satellites' position and velocity information came from IGS orbit products, and then transferred all the position and velocity from ITRF to TOD (ECI) coordination system. We have added such a remark.

Page 8, eqn. (7) and (8): Which one of the two equations is used in the actual processing? Equation (7); we have added this in the text now.

Page 9, lines 19ff: "In order to use that specific reference satellite that most likely has the best signal quality and lowest ionospheric influence, our FY-3C GNOS processing chooses the GNSS satellite with highest elevation angle as the reference satellite." From Bai et al. (2014) (see reference above) I had assumed that the decision which satellite to track as reference is already taken at the receiver level and not during data processing. Second, it would be interesting to note if the reference satellite is tracked by the occultation or zenith antenna. In the latter case SNR at high elevation angles is expected to be higher at the expense of an additional attitude dependence which must be corrected for. Please clarify. Yes, for the FY-3C GNOS, the reference satellite is determined by the software onboard the satellite, and it selects the GNSS satellite with the biggest elevation as a reference satellite. The reference satellite's signal is received by the positioning antenna. We have clarified this in the text now.

Page 9, lines 19ff: "In practice, less than 0 deg means that there is in fact no reference satellite in view and [...]" At a (sun-synchronous) orbit height of about 840 km (reference) satellites at elevation angles down to 27_ could indeed be visible. Please clarify and/or rephrase the sentence. Ok, done.

Page 10, line 24: "In our data processing, a quality control algorithm has been used." I suggest to quote the fraction of RO events removed by quality control. Ok, done.

Page 12, lines 15ff: "The target domain for the comparative statistical analysis is from 5 km to 35 km height [...], since commonly the data quality above 35 km and below 5 km is less good, due to the ionospheric effects and tropospheric multipath effects,

[Printer-friendly version](#)

[Discussion paper](#)



respectively [...]” I assume that the data retrieval is based on geometric optics and wave optical methods (CT, FSI) have not applied. Please clarify. Our RO data processing system from excess phase onwards is based on the ROPP software. So similar to ROPP, our data retrieval is mainly based on the geometric optics (CT), while below 20 km height, both the geometric optics (CT) and wave optical method were used.

Pages 25 & 26, Figs. 6 & 7: From the figure inserts it appears that the analysis is based on the intersection of the SD and ZD data sets and that the intersection contains less events than both, the SD and ZD data set. Why are there 192 (if I counted correctly) events found in the (quality-controlled) SD data set, which did not make it into the ZD set? I suggest to add a clarifying remark. Ok, clarifying remark added in the fig. caption.

Page 26 & 27, Figs. 7 & 8: Why is geopotential height instead of geometric height used as vertical coordinate? Please clarify. We used the geopotential height for Figures 7 and 8, because the data obtained from the ECMWF model and the radiosonde observations used the geopotential height as the vertical coordinate.

Technical corrections:

Page 7, eqn. (2): Ok, done.

Page 7, eqn. (3): and the three bracketed expressions need to be squared. Ok, done.

Page 7, eqn. (4): I suggest to replace the horizontal bars in eqn. (4) ($\bar{rb};c$ and $\bar{vb};c$) by a more conventional notation indicating vectors Ok, done.

Page 8, eqn. (6): Here, in contrast to eqn. (4), the horizontal bar seems to differentiate between transmitter and receiver dipole vector. I suggest to clarify the notation. Ok, done.

Page 13, line 10: There appears to be a reference missing (empty bracket). Ok, was a typo left, corrected.

Printer-friendly version

Discussion paper



Please also note the supplement to this comment:

<https://www.atmos-meas-tech-discuss.net/amt-2017-177/amt-2017-177-AC2-supplement.pdf>

AMTD

Interactive comment on *Atmos. Meas. Tech. Discuss.*, doi:10.5194/amt-2017-177, 2017.

Interactive
comment

