Review of amt-2017-401

By Viswanathan Bringi, Merhala Thurai and Darrel Baumgardner

Manuscript Title – Raindrop Fall Velocities from an Optical Array Probe and 2D-Video Disdrometer

Response to Reviewer # 1

GENERAL COMMENTS

In the manuscript the Authors analyzed three precipitation events occurred in USA (Colorado and Alabama) that differs for the climatology of the colocations and for the wind conditions. The aim of the study is to evaluate the wind influence on the raindrops terminal fall speed measured by two different type of devices, namely the Meteorological Particle Spectrometer (MPS) and the 2D video disdrometer (2DVD). The manuscript is well organized however I think that the aim of the study and in particular its practical applications should be specified in the Introduction section. As stated also by the Authors more case studies should be added or at least the analysis should be extended to larger drops (see for example comment 6 and 9 below). Furthermore section 2 need to be enlarged with information regarding the data processing (see comment 3 below) and more analytical comparison should be done to confirm the consistency of fall speed measurements from the two devices (see comment 1 below). Finally I have some specific comments, that are shown below.

We appreciate the reviewer's comments and our response is given in italics while the modifications to the manuscript are highlighted as below.

General: The first sentence in the Introduction gives three applications with three pertinent references. We believe these are also "practical" references. For example, the modeling of collisional processes is in part based on assigning a unique terminal fall speed for a given mass of raindrop. Same is true for retrieval of DSD from vertical pointing profilers. We have also added in a new reference to Yu et al. (2016) in AMT who also suggest that ambient flow and turbulence may play a role in modifying drop fall speeds.

We have added the following sentences to clarify this point in the Introduction:

"In these and other applications it is nearly universally accepted that there is a unique fall speed ascribed to drops of a given mass or diameter and that it equals the terminal speed with adjustment for pressure (e.g., *Beard* 1976)."

"Thus, there is some evidence that rain drops may not fall at their terminal velocity except under calm conditions and that the concept of a fall speed distribution for a drop of given mass (or, diameter) might need to be considered which is the topic of this paper. The implications are rather profound especially for numerical modeling of collision-coalescence and breakup processes which are important for shaping the drop size distribution."

Our response to SPECIFIC COMMENTS.

SPECIFIC COMMENTS

1. Line 24-25: in the manuscript the consistency of fall speed measurements from the two devices is provided only qualitatively (i.e. "excellent visual agreement") some quantitative results should be provided for all the diameters in the overlapping region.

We have added a new Table 1 that compares the mean and standard deviation from MPS and 2DVD for both sites in the overlap diameter range 0.7 to 2 mm.

2. Line 109: please clarify which are the "other factors" that gives the threshold of 0.7 mm for the drop diameter. The 2DVD is able to measures drops with D < 0.7 mm. Usually the minimum detectable diameter for 2DVD is considered 0.2 mm or 0.3 mm. In this case the overlapping between the two instruments can be enlarged. Please provide a clarification of this threshold or consider the option of enlarging the overlapping region.</p>

In line 107 we have given three references that discuss 2DVD accuracy. In particular, Bernauer et al. (2015) carefully document the accuracy of sizing and fall speed for solid precipitation. The main problem for D < 0.7 mm is that the drop image in Camera A has to be "matched" to the corresponding drop image in Camera B which is difficult given the resolution of 170 microns. This has been mentioned in second para of Section 3. But we have added the "mis-match" problem in original line 109.

"Considering the horizontal pixel resolution of 170 µm and other factors (such as "mis-matched" drops), the effective sizing range is D> 0.7 mm. To clarify the "mis-matched" drop problem: it is very difficult to match a drop detected in the top light-beam plane of the 2DVD to the corresponding drop in the bottom plane for tiny drops resulting in erroneous fall speeds."

The smallest calibration spheres that are provided by the manufacturer is 0.5 mm and these are extremely difficult to drop in the sensor area and to collect them below. According to Bernauer et al. accurate sizing with errors <5% is only possible for D> 1 mm based on solid (snow) precipitation. In our experience for rain drops which are

smooth shaped the threshold is lower at 0.7 mm which is what we have quoted in our paper. While the mid-point of the first "bin" of the 2DVD sizing is 0.25 mm, the accuracy is very questionable as calibration is not possible. Hence we cannot enlarge the overlapping region. The whole point of our paper is to use high resolution MPS and lower resolution 2DVD to cover the entire size range with good-to-excellent accuracy.

3. Line 114-115: As reported in numerous papers in the literature, the 2DVD measures a number of spurious drops that can are usually removed from the data using proper filter criterion, such as the one based on the relation between measured and theoretical fall velocities. Please note that in my experience most of the spurious drops have small diameters (D<2 mm) and therefore are within the range of diameters analyzed in this study. Did the Authors use any kind of criterion to filter out these drops? If yes which is the impact of the filtering on the results. If not, how can the Authors be sure that those drops are real drops and not spurious ones? I think that the Authors should clarify this point in the manuscript because it is crucial for the validity on the results obtained in the study.

We clearly state in original lines 114-115 that ..." The only fall velocity threshold used for the 2DVD is the lower limit set at 0.5 m s⁻¹ in accordance with the manufacturer guidelines for rain measurements." We do not use any velocity filter in our analysis as doing so would be counter to the detection of sub- or super terminal fall speeds. Please see our response above to point (2) specifically the threshold of 0.7 mm which we use to eliminate mis-matched or "spurious" drops. Our confidence of sizing and fall speed measurement using 2DVD for D>0.7 mm is reinforced by the agreement with MPS in the overlap region (please see new Table 1). Finally, the use of a DFIR wind shield appears to have reduced the occurrence of "spurious" drops.

4. Line 119: How do the Authors identify the different rain types?

The identification of rain types was based on CSU-CHILL radar data as described in the quoted reference (Thurai et al. 2017).

5. Line 131: I suggest to change the word "excellent" with the word "good". The MPS underestimates the fall velocities for 0.7 mm < D < 1 mm with respect to 2DVD, while the 2DVD overestimates the fall velocities for 1 mm < D < 2 mm with respect to the Gunn and Kinzer fit. Furthermore a more quantitative agreement should be performed.</p>

Please see new Table 1 for a quantitative comparison between MPS and 2DVD in the overlap region. The agreement between the two instruments is, in our opinion, excellent for both sites given the quoted accuracies in fall speed measurement for both instruments.

We have replaced the fit to Gunn-Kinzer data with the 9th order polynomial fit given in Foote and du Toit (1969) as opposed to using the exponential fit of Atlas et al. (1973) in

both figs. 1a and 3a. The latter fit is not as accurate for the small drop end (e.g., it does not pass through the origin). We have added in Section 2.1:

"Also shown is the (*Foote and du Toit 1969*) (henceforth FT fit) to the terminal fall speed measurements of (*Gunn and Kinzer*, 1949) at sea level and after applying altitude corrections (*Beard*, 1976) for the elevation of 1.4 km MSL for Greeley."

The pressure adjustment to the Gunn-Kinzer fit to account for the altitude (1.4 km MSL) of the Greeley site is in excellent agreement with the 2DVD measurements. The slight underestimation of the MPS fall speeds relative to the fit of Foote and du Toit to the data of Gunn-Kinzer in the range 0.7-1.5 mm (max deviation of 0.5 m/s or 10%) is puzzling given the excellent agreement for the Huntsville site (sea level). We have added sentence below.

"However, the altitude-adjusted FT fit is slightly higher than the measured values as shown in Table 1."

6. Figure 1b and Figure 2b: I suggest to plot the fall velocity histogram also for other drop diameters (let say 0.7 mm and 1.5 mm for example) so the readers can have more cases to evaluate the agreements between 2DVD and MPS.

Done as suggested...see new panel c in figs. 1 and 3.

7. Line 187: similarly to comment 5, also here the word "excellent" is not appropriate due to the overestimation of MPS with respect to Gunn and Kinzer fit for D < 0.5 mm.

As noted in our response to (5) above, after replacing the Atlas et al fit by the Foote and du Toit fit in Fig. 3a the agreement between MPS and the latter fit is considered to be excellent.

8. Figure 3a: can the Authors provide an explanation of the differences in the mean fall velocity between Gunn and Kinzer fit and MPS measurements for D > 1.5 mm?

Please see our response to (7) above. The differences in Fig. 3a are no longer an issue.

9. Figure 5: what about large drops? Which is the effect of wind on large drops? I suggest to use the 2DVD data to made the same analysis for larger D.

We have added new panels Fig. 5e,f which show the effect of wind/gusts for 3 mm drops. The trend is similar to 2 mm drops. We cannot show larger drops due to very low number of samples.

TECHNICAL CORRECTIONS 1. Line 286: probably "wind range" should be "wide range".

Corrected. Thank you for pointing this out.

Interactive comment on "Raindrop Fall Velocities from an Optical Array Probe and 2D-video Disdrometer" by Viswanathan Bringi et al.

H. Leijnse (Referee) hidde.leijnse@knmi.nl Received and published: 11 December 2017

Response to Reviewer # 2

This paper describes results from two measurement campaigns with a Meteorological Particle S ensor (MPS) and a 2D-Video Disdrometer (2DVD). The analyses presented in this paper are focussed on the fall speeds of droplets measured by the different instruments, and whether these deviate from results from laboratory experiments (superor sub-terminal fall speeds). Observed sub-terminal fall speeds are then linked to turbulence intensity. I think this is an interesting paper. It contributes to the scientific discussion on the puzzling super-terminal small raindrops by showing results where these were not observed. However, the paper would benefit from a clearer description of its aims, and, if possible, stronger conclusions. As far as I understand it, there are three main messages in the paper: 1) there is no evidence of super-terminal raindrops (contrary to Montero-Martinez et al., 2009 and Larsen et al., 2014); 2) the fall velocities of real drops closely follow the relations found by Gunn and Kinzer (1949) down to very small drops; and 3) there is a clear effect of strong turbulence on the mean and the standard deviation of fallspeeds of drops of a given diameter. If this is indeed the case, then I think this should be more clearly stated in the introduction, and should be discussed more elaborately in the conclusions. So I think that after revisions, this paper is suitable for publication in Atmospheric Measurement Techniques. Specific comments are given below.

We thank the reviewer for the positive comments. Our response is in italics while the text modifications are highlighted and in quotes.

We have added in the Introduction the following:

"In these and other applications it is generally accepted that there is a unique fall speed ascribed to drops of a given mass or diameter and that it equals the terminal speed with adjustment for pressure (e.g., *Beard* 1976)."

We are reluctant to draw firmer or more elaborate conclusions than what is stated in our paper since, (a) the database is rather small (3 cases but from two different climatologies), (b) we do not have a direct measurement of turbulence and (c) we cannot quantify if the DFIR wind shield is affecting the sensor area in some subtle way. These questions will be addressed in the future.

In Section 3 last para we have clarified as follows:

"One caveat is that the response of the DFIR wind shield to ambient winds in terms of producing subtle vertical air motions near the sensor area is yet to be evaluated as future work. Analysis

of further events with direct measurement of turbulent intensity, for example using a 3D-sonic anemometer at the height of the sensor, would be needed to generalize our findings."

Specific comments

1. In the introduction it should be more clearly stated what the exact aims of this paper are.

We have added the following in the Introduction:

"Thus, there is some evidence that rain drops may not fall at their terminal velocity except under calm conditions and that the concept of a fall speed distribution for a drop of given mass (or, diameter) might need to be considered which is the topic of this paper. The implications are rather profound especially for numerical modeling of collision-coalescence and breakup processes which are important for shaping the drop size distribution."

2. On lines 66-74, the use of a DFIR is discussed along with its effects on the local windfield. For studying the relation between turbulence intensity and raindrop fall speeds, how does this double fence affect the turbulence just above the instrument? I can imagine that by reducing the average wind speed, the turbulence is also reduced. On the other hand, as stated on line 74, the fence itself also generates up- and downdrafts. I think that the effects of the use of a DFIR on the results presented in this paper should be discussed and, if possible, quantified.

As mentioned in the text we do not have a direct measurement of turbulence at the height of the sensor. Rather we use the wind/gusts from the anemometer at 10 m high tower as a proxy for turbulence. Regarding the DFIR perturbing our results, there is unfortunately not many articles describing the DFIR affect on the ambient flow other than the quoted reference of Theriault et al. (2015). Most articles are related to the "catch efficiency" of snow gages located inside the DFIR relative to gages with standard wind skirts. In the future we will locate one 2DVD inside the DFIR and one outside as well as collocated 3D-sonic anemometers both inside and outside…but this is another field project for which we have to acquire funding. Unfortunately, we cannot quantify the effect of the DFIR in this paper.

3. In Fig.1 (especially panel a) the MPS seems to detect slightly (but systematically) lower fall velocities than the 2DVD in the Greeley data. This is not the case for the Huntsville data (Fig. 3). Please give an explanation for this.

Please see new Table 1 for a quantitative comparison between MPS and 2DVD in the overlap region. The agreement between the two instruments is, in our opinion, excellent for both sites given the quoted accuracies in fall speed measurement for both instruments.

We have replaced the fit to Gunn-Kinzer data with the 9th order polynomial fit given in Foote and du Toit (1969) as opposed to using the exponential fit of Atlas et al. (1973) in both figs. 1a and 3a. The latter fit is not as accurate for the small drop end (e.g., it does not pass through the origin).

The pressure adjustment to the Gunn-Kinzer fit to account for the altitude (1.4 km MSL) of the Greeley site is in excellent agreement with the 2DVD measurements. The slight underestimation of the MPS fall speeds relative to the fit of Foote and du Toit to the data of Gunn-Kinzer in the range 0.7-1.5 mm (max deviation of 0.5 m/s or 10%) is puzzling given the excellent agreement for the Huntsville site (sea level). We have re-worded the sentences in Section 2.1 as follows:

"Panel (a) demonstrates the excellent "visual" agreement between the two instruments in the overlap size range (0.7-2 mm) which is quantified in Table 1. However, the altitude-adjusted FT fit is slightly higher than the measured values as shown in Table 1."

4. On lines 208-215, the correlation between E on the one hand, and the mean and standard deviation of the raindrop fall speeds on the other is discussed. I agree that this correlation is there. However, judging from Fig. 4, I think there is also some correlation with the rain rate R (especially the peak at 10 UTC). Please elaborate on the role of the rain rate for these correlations.

The reviewer is correct in that there is a correlation with rain rate (as shown in the figure below for the reviewer's benefit) but this can be misleading in that heavy rain can and does occur during calm conditions and the opposite also occurs. So it is difficult to come to a firm conclusion unless we look at many cases which is reserved for future work.



Figure 1: The mean fall speed versus rain rate for 30 Nov 2016 Huntsville for 1.3 and 2 mm drops.

5. On lines 224-225, the observed near-linear decrease of the mean fall speed with turbulence intensity (or at least its proxy E) is mentioned. How significant is this relation?

Not sure if what is meant by "significant" relation. We can do a linear fit and compute correlation coefficient but this won't add much to what is already fairly obvious. We do not wish to quantify this as E is only a proxy for turbulence.

6. On lines 247-254, the results presented by Montero-Martinez et al. (2009) are compared to those presented in this paper. What could be the explanation for this difference? Could it be something similar to what is discussed in the next paragraph (lines 255-262) about the findings of Larsen et al. (2014)? Please elaborate on this.

We can only speculate why Montero-Martinez et al. found strongly skewed distribution for 0.44 mm drops. The instruments they used, 2D-C and 2D-P, were designed for use on aircraft and not as fixed disdrometers. The airspeed clock is about a factor of 10 higher in their implementation. The calibration method is not discussed in any detail by them whereas the MPS can be calibrated as often as needed with a special device. They did not use any wind shield as far as we can ascertain.

The Larsen et al. study used a 2DVD which has "mis-matched" drop problem not present in the 2D-C, P probes.

7. On lines 272-281, the relation to the findings of Stout et al. (1995) are discussed. Is there an empirical relation between E and the rms velocity fluctuations due to turbulence? If so it would be interesting to see whether the 35% reduction in mean velocity is observed at similar rms velocity fluctuations-to-terminal fall speed ratios (0.8).

We do not think there is a way to relate our estimate of E based on 3-s wind data to what a 3Dsonic anemometer would measure in terms of velocity fluctuations at much higher sampling rate. This for a future project where we would locate a sonic anemometer next to the 2DVD/MPS inside the DFIR.

Technical comments

1. In Figs 2b and 4b, would it be possible to use a second y-axis for R instead of presenting R/10 on the existing y-axis?

Done as suggested.

2. On line 275, "greater that" should be "greater than".

Corrected. Thanks for pointing this out.

Interactive comment on Atmos. Meas. Tech. Discuss., doi:10.5194/amt-2017-401, 2017

Review of AMT-2017-401 By V. Bringi, M. Thurai and D. Baumgardner Manuscript Title – Raindrop Fall Velocities from an Optical Array Probe and 2D-Video Disdrometer.

Response to Reviewer # 3

This manuscript reports on raindrop fall velocity measurements by using two different instruments: a MPS (Meteorological Particle Spectrometer) which measures drops in the 0.1-3 mm range, and the wildly used 2DVD (two-Dimensional Video Disdrometer), which measures size and fall velocity of drops between 0 and 10 mm. The MPS and 2DDVD were used to measure fall velocity of drops in the 0.1-2 and larger than 0.7 mm diameter range. The overlapping region 0.7-2 mm diameter was used to cross-validate the two measurements. Three different case studies were analyzed in order to relate the properties of the drop fall velocity to different precipitation systems (one stratiform, one squallline and one super-cell case with low and high turbulence associate for the first two and the third case, respectively). The paper is linear and quite easy to read. I have only one major comment that can give a contribution, in my opinion, to the generalization of the results. It is reported below together with minor comments that, once addressed, will allow the publication of the paper on the Atmospheric Measurement Techniques journal.

The authors appreciate the above general comments and our response is given below in italics whereas the text modifications are highlighted.

Major comment.

- Section 2.2: in the Section 2.1 the authors investigated a stratiform case, while in the Section 2.2 a squall line and a super-cell case. The squall line case reported generally low rainfall rate and turbulence (comparable to the values registered in the stratiform case). It could be useful, in my opinion add (or substitute) a convective event, a sort a middle point between a convective and tornadic case, in order to have a general overview of the characteristics of drop fall velocity in a broader range of precipitation systems.

In Section 2.2 it is clearly stated that..." About 3 h later several squall-line type storm cells passed over the site from 0700-0900 UTC again with strong winds but considerably lower E values 2-4 $m^2 s^{-2}$ and maximum R of 80 mm h⁻¹. After 1000 UTC the E values were much smaller (< 0.5 $m^2 s^{-2}$) indicating calm conditions. The peak R is also smaller at 30 mm h⁻¹ at 1000 UTC." Hence, Fig. 4b already depicts high and moderate-low rain rate conditions. Perhaps the reviewer overlooked the rain rate scale (where we plotted R/10) which has now been changed, the values now on the right Y-axis without any scaling.

Minor comments.

- Line 141: what does it mean that the finite bin width causes a spread of 0.5 m/s? Can the authors explain better? The same is reported in other parts of the text.

The bin width for the histograms is ± 0.1 mm about the center value of 0.5 mm, for example in Fig. 1b all fall speeds that fall in the range 0.4 to 0.6 mm are included in the histogram. The spread of 0.5 m/s is just V(0.6 mm)-V(0.4 mm). In Section 2.1 we have clarified as:

"The finite bin width used (0.9-1.1 mm) causes a corresponding fall speed "spread" of around 0.5 m s⁻¹ which is clearly a significant contributor to the measured coefficient of variation."

Please see new Table 1 which quantifies the finite bin width spread in Column 1.

- Lines 211-215: what is the explanation that the authors give to the decrease of fall speed during the most intense wind and rainfall rate? Does it can be related to the presence of ascending flow?

In Section 3 we refer to Stout et al. (1995) who have simulated the effects of turbulence to cause a decrease in fall speed relative to still air conditions. The effect is due to increase in the non-linear drag due to both vertical and horizontal gusts. We defer to the explanation in Stout et al. (1995) but we introduce this reference earlier in Section 2.2.

- Lines 224-225: similar to the previous comment. How do they justify the decrease of fall speed when E (turbulence) increases?

Please refer to our response above.

- Panel (b) of Figures 2 and 4: the rain rate should be reported on the right y-axis avoiding the necessity to show its values scaled on a factor ten.

Done as requested.

- Figure 2a: the y-axis limit should not exceed 10 m/s to improve the detail of the plot.

Done as requested.

Interactive comment on "Raindrop Fall Velocities from an Optical Array Probe and 2D-video Disdrometer" by Viswanathan Bringi et al.

Anonymous Referee #4 Received and published: 18 December 2017

Response to Reviewer # 4

GERNERAL COMMENTS This is an excellent paper, addressing the issue of in-situ measurements of rain drops over their full size range, with focus on the drops' fall velocities. Especially the characteristics of very small drops still are not investigated thoroughly up to here. The investigation of the relationship between wind turbulence and rain drops' fall velocity is convincing and in the future will allow new refinements in the related remote sensing algorithms. The study is presented in a clear and concise way. The reviewer likes to point out, that such work does not only address academic interests, but points to a number of applications, like remote sensing of the atmosphere, as the authors shortly mention in their introduction. Other applications include knowledge of channel characteristics for satellite communications at EHF frequency bands. Thus the study is very relevant for these fields of science and applications. The work is based on the combined analyses of data from 2 instruments at same site, the Meteorological Particle Spectrometer (MPS) and the 2D-video disdrometer (2DVD). Field measurement of rain drops still may be considered as challenge, with quite a few solutions being around, but none of the instruments may claim to be perfect. The presented results do rise a fe w relevant questions, which are given in below specific comments. Summarizing it is said, that this paper gives an excellent contribution, bringing new aspects for the relevant fields of science and applications.

We appreciate the very positive comments by the reviewer. Our response is in italics below and modifications to the text are highlighted.

SPECIFIC COMMENTS

*** Line 98 / 99: "All possible corrections have been applied, including the removal of artifacts due to splashing,..." Careful preprocessing, verification and validation of data is of utmost importance for the present study. The results presented require correctness of challenging measurement processes. Some of the result given actually leave a few questions open, as addressed in below comment to Fig 1a and Fig3a. To be sufficiently self-contained, thus the paper might shortly describe the mentioned correction algorithms.

We have replaced the sentence: "All possible corrections have been applied, including the removal of artifacts due to splashing, and oversizing that results from out-of-focus droplets (Korolev 2007)." With

"There are a number of potential artifacts that arise when making measurements with optical array probes (Baumgardner et al., 2017): droplet breakup on the probe tips that form satellite droplets, multiple droplets imaged simultaneously, and out-of-focus drops whose images are usually larger than the actual drop (Korolev, 2007). The measured images have been analyzed to remove satellite droplets whose interarrival times are usually too short to be natural drops, multiple drops are detected by shape analysis and removed, and out-of-focus drops are detected and size corrected using the technique described by Korolev (2007)."

*** Line 157: "The histogram from MPS for the 0.5 mm sizes shows positive skewness" Can the authors give an explanation / discussion / assumption?

The histogram in Fig. 1b for 0.5 mm size is skewed towards higher values...the tail extends from 2.6 to 4 m/s. Given that the mean is 1.8 m/s and σ =0.65 m/s, there is a finite occurrence of super-terminal fall speeds that exceed mean+1 σ or 2.45 m/s. Such super-terminal speeds have been noted by Montero-Martinez et al using 2DC,P probes for similar sized drops in fact with much longer tail or skewness than our observations.

*** Fig. 1a and Fig. 3a: Mean fall velocities from the MPS are read from these figures approximately as: Fig. 1a: D = 0,7 mm, v = 2.55 m/s

Fig. 3a: D = 0.7 mm, v = 3.05 m/s

That represents an exceedance by more than 16 % (Fig. 3a over Fig. 1a), in spite of the lower pressure in Greely (Fig 1a) leading to the expectation of faster drops than in Huntsville (Fig 3a). The authors please could discuss this.

We refer to new Table 1 from which we now have:

Greeley site D=0.7 mm mean MPS=2.6 m/s

Huntsville D=0.7 mm mean MPS=2.6 m/s

We have also added new histograms for 0.7 and 1.5 mm from both sites (new Fig. 1c and 3c). The 0.7 mm histogram from Greeley is slightly skewed (Fig. 1c) whereas the Hunsville histogram is more symmetric. For small drops (< 1 mm) the pressure adjustment is not significant (see Fig. 1a) and this is reflected by Table 1 data.

*** Fig. 3a: Mean fall velocities from the MPS are read from this figure approximately as:

D = 1.5 mm, v = 5.28 m/s

D = 1.6 mm, v = 6.31 m/s

D = 1.7 mm, v = 6.5 m/s

D = 1.8 mm, v = 5.93 m/s

These values differ significantly from the fit to Gunn-Kinzer, further from the expected monotonic behaviour. The authors please could discuss this.

We have added a new Table 1 which quantifies the measurement comparison between MPS and 2DVD in the overlap region for the 2 sites. The agreement in the mean fall speed is excellent for both sites. The mean values quoted above by the reviewer are not accurate but we do appreciate the effort involved to read values of a graph. In particular at D=1.7 mm, from Table 1 the mean is 6 ± 0.3 m/s (and not 5.93 m/s as quoted above). At D=1.8 mm, interpolation gives 6.25 m/s which is monotonic behavior. Table 1 also gives the expected values using the Foote and du Toit (1969) 9th order polynomial fit (FT) to Gunn-Kinzer which is more accurate than the exponential fit of Atlas et al especially for the smaller drops. We list below the FT fit value and mean MPS from Table 1 for Huntsville site.

0.7 mm	FT fit=2.9 m/s	MPS=2.6	2DVD=2.5	
0.9	3.65	3.4	3.3	
1.1	4.3	4.2	4.1	
1.3	4.9	4.9	4.9	
1.5 Fig. 3c)	5.45	5.4	5.4 (see new histogram i	in
1.7	5.9	6.0	5.8	
1.9	6.3	6.5	6.3	

For 0.7 and 0.9 mm sizes the MPS and 2DVD mean values are systematically lower than the FT fit

by 7-10%. For comparison, Yu et al. (2016; new reference added in revised text) found that their high speed camera measurement of fall speeds in the interior stair-case of a building also were systematically lower by 5% (for sizes in the range 0.4 to 1.6 mm) relative to the same FT fit as used here (their fig. 7).

TECHNICALCOMMENTS:

*** Line 230: "(σf) versus E is shown in panels 6 (b,d)." It probabaly should read as "(σf) versus E is shown in panels (b,d) of Fig 5."

Done...thank you for pointing this out.

Interactive comment on Atmos. Meas. Tech. Discuss., doi:10.5194/amt-2017-401, 2017.

Interactive comment on "Raindrop Fall Velocities from an Optical Array Probe and 2Dvideo Disdrometer" by Viswanathan Bringi et al. Anonymous Referee #5

Response to Reviewer # 5

We appreciate the reviewer's comments and our response is given in blue bold italics. The modifications to revised manuscript based on earlier 4 reviews (major revision) are attached and highlighted. The modifications of the manuscript based on this last review are very minor but included also.

This manuscript is a summary of observations of the fall speeds of small raindrops near the ground, in a field setting. It is comforting to see that the observations are generally consistent with the familiar Gunn and Kinzer laboratory measurements in conditions not strongly affected by wind and turbulence.

In the latter situation the measured fall speeds tended to be less, and therein lays a puzzle that warrants more discussion in the manuscript. Certainly turbulence in the low atmosphere could increase the spread of the drop fall speeds, but it does not produce a significant vertical mass flux. If the turbulence were isotropic (which may not be the case here) Stout et al. did find indications of reduced fall speeds. However, it's not clear why there would not be a similar neutral effect on the overall raindrop flux. If the drops are falling at normal terminal speeds in the free atmosphere and at reduced speeds near the surface there would have to be an accumulation of rain at some level above the disdrometer. Of course there might be intermittent episodes of "super-" and "sub-terminal" fall speeds but the duration of the latter in the observations is a substantial fraction of an hour. I do not have an explanation but invite the authors to offer one, or at least discuss the subject.

Response to General Comments: What the reviewer is assuming as best as we can ascertain is related to the sedimentation of raindrops i.e., time rate of change of mass equals negative of the height derivative of mVt. This neglects other important processes such as evaporation and source/sink terms for coalescence-breakup. Plus the fall speeds increase at lower pressure aloft. We do not feel we can offer any more explanation and hence no modifications to the manuscript have been made.

My other comments are relatively minor:

There are instances of singular-plural subject-verb disagreement in the manuscript.

The manuscript has been revised substantially in response to Reviews 1-4 which is now attached to this response.

L15ff: "micron" is not an SI unit (and compare with L57).

We have changed 'microns' to 'µm' throughout the text.

L41: The authors might add the very useful fall speed relationship from Uplinger (Uplinger WG. 1989. A new formula for raindrop terminal velocity. Preprints, 20th Conference Radar Meteorology, 389–391).

In our revised manuscript we have used the fit of Foote and du Toit (1969) to replace the fit of Atlas et al. (1973). The figure below compares the Foote and du Toit fit to Uplinget (1977). Since the agreement is excellent we feel no need to use the latter fit and hence no modifications have been made to the manuscript.



L81-103 (maybe 105-115 as well): What about possible edge effects on the measurements?

Under the conditions listed in L199-207, a 1 mm drop at terminal fall speed would approach the instrument at an angle of <22 deg from horizontal. Viewing the measurement plane from that angle, there's a lot more edge than when the approach is vertical.

The 2DVD and MPS instruments were collocated inside a DFIR wind shield so the drop trajectories are different as opposed to un-shielded case. Note also that the DFIR reduces the wind speed at the center of the fence by nearly a factor of three relative to the environment wind speed. The edge effect under strong horizontal winds can be easily noted by partial filling of the 2DVD's 10X10 cm sensor area which is not the case as shown in figure below, i.e., the 2 mm drops uniformly fill the sensor area during the high wind period of the squall lines (0600-1000 UTC) in Fig. 4.



Each point is the location of drop in the 10X10 cm sensor area of the 2DVD. All drops in the range 1.9-2.1 mm during the time segment 0600-1000 UTC on 30 Nov 2016 are shown.

L89: How does the "true air speed clock" work in this situation?

We understand the question posed by the reviewer although the effect that the reviewer is referring to will depend on the trajectory of the drop with respect to the diode array. We use the fin (wind vane) to minimize the angle issue, i.e. if the array is completely perpendicular to the trajectory of the drop, the horizontal motion of the drop will have no impact. If, however, in the worse case the drop trajectory is parallel to the array, there can be a potential for oversizing but the error will still be quite small since the amount of time that it takes to capture the image slice is very small compared to how far across the array a droplet travels horizontally during that time. In other words, the captured image appears as if it is going through at an angle, but the maximum width will still be the same as the drop.

We note that in our paper the MPS was configured without a wind vane as it was sited inside the DFIR wind shield. The diode array was oriented perpendicular to the environmental mean wind direction for both Greeley and Huntsville site.



Sample of drop images recorded by the MPS. Schematic of drop whose trajectory is parallel to the diode array.

L162: The expression in parentheses is not what is really meant.

We have deleted the expression in parenthesis as it is not necessary. Thank you for pointing this out.

L230: " ...panel 5 (b,d)."

Corrected. Thank you.

L251-252: If these (1 and 5) are fall speeds, include the units. Fig. 3a: Any clue what caused the MPS hiccup after 1.5 mm size?

Units inserted as suggested. The revised figure does not have the "hiccup".

Raindrop Fall Velocities from an Optical Array Probe and 2D-Video Disdrometer

Viswanathan Bringi¹, Merhala Thurai¹ and Darrel Baumgardner²

¹ Department of Electrical and Computer Engineering, Colorado State University, Fort Collins, Colorado, USA

² Droplet Measurements Technologies, Longmont, Colorado, USA

Correspondence to: V.N. Bringi

Email: <u>bringi@colostate.edu</u>

Abstract

We report on fall speed measurements of rain drops in light-to-heavy rain events from two climatically different regimes (Greeley, Colorado, and Huntsville, Alabama) using the high resolution (50 µm) Meteorological Particle Spectrometer (MPS) and a 3rd generation (170 µm resolution) 2D-video disdrometer (2DVD). To mitigate wind-effects, especially for the small drops, both instruments were installed within a 2/3-scale Double Fence Intercomparison Reference (DFIR) enclosure. Two cases involved light-tomoderate wind speeds/gusts while the third case was a tornadic supercell and several squall-lines that passed over the site with high wind speeds/gusts. As a proxy for turbulent intensity, maximum wind speeds from 10-m height at the instrumented site recorded every 3 s were differenced with the 5-min average wind speeds and then squared. The fall speeds versus size from 0.1-2 mm and >0.7 mm were derived from the MPS and the 2DVD, respectively. Consistency of fall speeds from the two instruments in the overlap region (0.7-2 mm) gave confidence in the data quality and processing methodologies. Our results indicate that under low turbulence, the mean fall speeds agree well with fits to the terminal velocity measured in the laboratory by Gunn and Kinzer from 100 µm up to precipitation sizes. The histograms of fall speeds for 0.5, 0.7, 1 and 1.5 mm sizes were examined in detail under the same conditions. The histogram shapes for the 1 and 1.5 mm sizes were symmetric and in good agreement between the two instruments with no evidence of skewness or of sub- or super-terminal fall speeds. The histograms of the smaller 0.5 and 0.7 mm drops from MPS while generally symmetric showed that occasional occurrences of sub- and super-terminal fall speeds could not be ruled out. In the supercell case, the very strong gusts and inferred high turbulence intensity caused a significant broadening of the fall speed distributions with negative skewness (for drops of 1.3, 2 and 3 mm). The mean fall speeds were also found to decrease nearly linearly with increasing turbulent intensity attaining values about 25-30% less than the terminal velocity of Gunn-Kinzer, i.e. sub-terminal fall speeds.

1 Introduction

Knowledge of the terminal fall speed of raindrops as a function of size is important in modelling collisional break-up and coalescence processes (e.g., List et al., 1987), in the radar-based estimation of rain rate, in retrieval of drop size distribution using Doppler spectra at vertical incidence (e.g., Sekhon and Srivastava, 1971) and in soil erosion studies (e.g., Rosewell 1986). In these and other applications it is generally accepted that there is a unique fall speed ascribed to drops of a given mass or diameter and that it equals the terminal speed with adjustment for pressure (e.g., Beard 1976). The terminal velocity measurements of Gunn and Kinzer, 1949) under calm laboratory conditions, and fits to their data (e.g., Atlas et al., 1973; Foote and du Toit, 1969; Beard and Pruppacher, 1969) are still considered the standard against which measurements using more modern optical instruments in natural rain are compared (Löffler-Mang and Joss, 2000; Barthazy et al., 2004; Schönhuber et al., 2008; Testik and Rahman, 2016; Yu et al., 2016). More recently, the broadening and skewness of the fall speed distributions of a given size (3 mm) in one intense rain event were attributed to mixedmode amplitude oscillations (Thurai et al., 2013). Super- and sub-terminal fall speeds in intense rain shafts have been detected and attributed, respectively, to drop breakup fragments (sizes < 0.5 mm), and high wind/gusts (sizes 1-2 mm) (Montero-Martinez et al., 2009; Larsen et al., 2014; Montero-Martinez and Garcia-Garcia, 2016). Thus, there is some evidence that rain drops may not fall at their terminal velocity except under calm conditions and that the concept of a fall speed distribution for a drop of given mass (or, diameter) might need to be considered which is the topic of this paper. The implications are rather profound especially for numerical modeling of collisioncoalescence and breakup processes which are important for shaping the drop size distribution.

The fall speeds and concentration of small drops (< 1 mm) in natural rain are difficult to measure accurately given the poor resolution (>170 μ m) of most optical disdrometers and/or sensitivity issues. While cloud imaging probes (with high resolution 25-50 μ m) on aircraft have been used for many years they generally cannot measure the fall speeds. A relatively new instrument, the Meteorological Particle Spectrometer (MPS) is a droplet imaging probe that was built by Droplet Measurements Technologies (DMT, Inc.) under contract from the US Weather Service specifically designed for drizzle as small as 50 μ m and rain drops up to 3 mm. This instrument in conjunction with a lower resolution 2D-Video Disdrometer (*Schoenhuber et al.*, 2008) is used in this paper to measure fall speed distributions in natural rain.

This paper briefly describes the instruments used, presents fall speed measurements from two sites under relatively low wind conditions, and one case from an unusual

tornadic supercell with high winds and gusts and ends with a brief discussion and summary of the results.

2 Instrumentation and Measurements

The principal instruments used in this study are the MPS and 3rd generation 2D-video disdrometer (2DVD), both located within a 2/3-scale Double Fence Intercomparison Reference (DFIR; *Rasmussen et al.*, 2012) wind shield. As reported in (*Notaros et al.*, 2016), the 2/3-scale DFIR was effective in reducing the ambient wind speeds by nearly a factor of 2-3 based on data from outside and inside the fence. The flow field in and around the DFIR has been simulated by (*Theriault et al.*, 2015) assuming steady ambient winds. They found that depending on the wind direction relative to the octagonal fence, weak vertical motions could be generated above the sensor areas. For 5 m/s speeds, the motions could range between -0.4 (down draft) to 0.2 m/s (up draft).

The instrument set-up was the same for the two sites (Greeley, Colorado and Huntsville, Alabama). Huntsville has a very different climate from Greeley, and its altitude is 212 m MSL as compared with 1.4 km MSL for Greeley. According to the Köppen–Trewartha climate classification system (*Trewartha and Horn,* 1980), this labels Greeley as a semiarid-type climate, whereas Huntsville is a humid subtropical-type climate (*Belda et al.,* 2014).

The MPS is an optical array probe (OAP) that uses the technique introduced by Knollenberg (1970, 1976, 1980) and measures drop diameter in the range from 0.05-3.1 mm. A 64 element photo-diode array is illuminated with a 660 nm collimated laser beam. Droplets passing through the laser cast a shadow on the array and the decrease in light intensity on the diodes is monitored with the signal processing electronics. A two dimensional image is captured by recording the light level of each diode during the period that the array is shadowed. The fall velocity is derived using two methods. One uses the same approach as described by (Montero-Martinez et al., 2009) where the fall velocity is calculated from the product of the true air speed clock and ratio of the image height -to-width. Note that "width" is the horizontal dimension parallel to the array and "height" is along the vertical. The second method computes the fall velocity from the maximum horizontal dimension (spherical drop shape assumption) divided by the amount of time that the image is on the array, a time measured with a 2 MHz clock. In order to be comparable to the results of (Montero-Martinez et al., 2009), their approach is implemented here for sizes > 250 µm. The fall velocity of smaller, slower moving droplets, is measured using the second technique.

The limitations and uncertainties associated with OAP measurements have been well documented (*Korolev et al.,* 1991; 1998; *Baumgardner et al.,* 2017). There are a number of potential artifacts that arise when making measurements with optical array probes (*Baumgardner et al.,* 2017): droplet breakup on the probe tips that form satellite droplets, multiple droplets imaged simultaneously, and out-of-focus drops whose images are usually larger than the actual drop (*Korolev,* 2007). The measured images have been analyzed to remove satellite droplets whose interarrival times are usually too short to be natural drops, multiple drops are detected by shape analysis and removed, and out-of-focus drops are detected and size corrected using the technique described by (*Korolev* 2007). The sizing and fall speed errors primarily depend on the digitization error (\pm 25 µm). The fall speed accuracy according to the manufacturer (DMT) is <10% for 0.25 mm and <1% for sizes greater than 1 mm, limited primarily by the accuracy in droplet sizing.

The 3rd generation 2DVD is described in detail by (*Schoenhuber et al.*, 2007; 2008) and its accuracy of size and fall speed measurement has been well documented (e.g., *Thurai et al.*, 2007; 2009; *Huang et al.*, 2008; *Bernauer et al.*, 2015). Considering the horizontal pixel resolution of 170 µm and other factors (such as "mis-matched" drops), the effective sizing range is D> 0.7 mm. To clarify the "mis-matched" drop problem: it is very difficult to match a drop detected in the top light-beam plane of the 2DVD to the corresponding drop in the bottom plane for tiny drops resulting in erroneous fall speeds. The fall velocity accuracy is determined primarily by the accuracy of calibrating the distance between the two orthogonal light "sheets" or planes and is < 5% for fall velocity <10 m s⁻¹. In our application, we utilize the MPS for measurement of small drops with D < 1.2 mm. The measurements from the MPS are compared with those from the 2DVD in the overlap region of D ≈ 0.7–2.0 mm to ensure consistency of observations. The only fall velocity threshold used for the 2DVD is the lower limit set at 0.5 m s⁻¹ in accordance with the manufacturer guidelines for rain measurements.

2.1 Fall Speeds from Greeley, Colorado

We first consider a long duration (around 20 h) rain episode on 17 April 2015 which consisted of a wide variety of rain types/rates (mostly light stratiform < 8 mm h⁻¹) as described in Table 2 of (*Thurai et al.,* 2017). Two wind sensors at a height of 1 m were available to measure the winds outside and inside the DFIR. Average wind speeds were, respectively, < 1.5 m s⁻¹ inside the DFIR and < 4 m s⁻¹ outside with light gusts. These wind sensors were specific to the winter experiment described in (*Notaros et al.,* 2016) and were unavailable for the rain measurement campaign after May 2015.

Figure 1(a) shows the fall speeds versus D from the 2DVD (shown as contoured frequency of occurrence), along with mean and $\pm 1\sigma$ standard deviation from the MPS. Also shown is the (*Foote and du Toit 1969*) (henceforth FT fit) to the terminal fall speed

measurements of (*Gunn and Kinzer*, 1949) at sea level and after applying altitude corrections (*Beard*, 1976) for the elevation of 1.4 km MSL for Greeley. Panels (b,c) shows the histogram of fall speeds for diameter intervals (0.5 ± 0.1) and $(1\pm0.1 \text{ mm})$, and (0.7 ± 0.1) and $(1.5\pm0.1 \text{ mm})$, respectively. Panel (a) demonstrates the excellent "visual" agreement between the two instruments in the overlap size range (0.7-2 mm) which is quantified in Table 1. However, the altitude-adjusted FT fit is slightly higher than the measured values as shown in Table 1. Notable in Fig. 1a is the remarkable agreement in mean fall speeds between the FT fit and the MPS for D< 0.5 mm down to near the lower limit of the instrument (0.1 mm). Few measurements have been reported of fall speeds in this size range.

Table 1: Expected fall velocities for various diameter intervals (bin width of 0.2 mm) from (*Foote and du Toit*, 1969) with altitude adjustment, and the measured mean fall velocities with $\pm 1\sigma$ (standard deviation)

D range (mm)	Expected (m s ⁻¹)	MPS (m s ⁻¹⁾	2DVD (m s ⁻¹)
(Greeley)	at 1.4 km	Mean $\pm 1\sigma$	Mean $\pm 1\sigma$
0.6 to 0.8	2.6 to 3.5	$\textbf{2.6}\pm\textbf{0.6}$	2.5 ± 0.8
0.8 to 1.0	3.5 to 4.3	$\textbf{3.4}\pm\textbf{0.6}$	3.3 ± 0.9
1.0 to 1.2	4.3 to 4.9	4.2 ± 0.6	4.1 ± 0.9
1.2 to 1.4	4.9 to 5.5	4.9 ± 0.5	5.0 ± 0.8
1.4 to 1.6	5.5 to 6.1	5.6 ± 0.5	5.7 ± 0.7
1.6 to 1.8	6.1 to 6.6	6.1 ± 0.4	6.2 ± 0.7
1.8 to 2.0	6.6 to 7.0	$\textbf{6.7}\pm\textbf{0.4}$	6.6 ± 0.8
D range (mm)	Expected (m/s)	MPS (m/s)	2DVD (m/s)
(Huntsville)	at 0 km	Mean ± Std_dev	Mean \pm Std. dev
0.6 to 0.8	2.5 to 3.3	$\textbf{2.6} \pm \textbf{0.6}$	2.5 ± 0.7
0.8 to 1.0	3.3 to 4.0	$\textbf{3.4}\pm\textbf{0.5}$	3.3 ± 0.7
1.0 to 1.2	4.0 to 4.6	4.2 ± 0.6	4.1 ± 0.8
1.2 to 1.4	4.6 to 5.2	4.9 ± 0.4	4.9 ± 0.7
1.4 to 1.6	5.2 to 5.7	5.4 ± 0.4	5.4 ± 0.6
1.6 to 1.8	5.7 to 6.1	6.0 ± 0.3	5.8 ± 0.6
1.8 to 2.0	6.1 to 6.5	6.5 ± 0.4	6.3 ± 0.5

The histograms in Fig. 1(b,e) show good agreement between 2DVD and MPS for 1 mm and 1.5 mm drop sizes, respectively, with respect to the mode, symmetry, spectral width and lack of skewness in the distributions. For the 1 mm size histogram, the mean is 3.8 m s⁻¹ while the spectral width or standard deviation from MPS data is 0.6 m s⁻¹. The corresponding coefficient of variation (ratio of standard deviation to mean) is 15.7%. The finite bin width used (0.9-1.1 mm) causes a corresponding fall speed "spread" of around 0.6 m s⁻¹ which is clearly a significant contributor to the measured coefficient of

variation. Similar comments apply to the fall speed histogram for the 1.5 mm size shown in Fig. 1c. The definition of sub- or super-terminal fall speeds by (*Montero-Martinez et al.,* 2009) is based on fall speeds that are, respectively, less than 0.7 times the mean value or greater than 1.3 times the mean value (i.e., exceeding 30% threshold on either side of the mean terminal fall speed). From examining the 1 mm size fall speed histogram there is negligible evidence of occurrences with fall speeds < 2.66 m s⁻¹ (sub) or > 4.94 m s⁻¹ (super). Similar comment also applies for the 1.5 mm size based on the corresponding histogram.



<u>Figure 1.</u> (a) Fall velocity versus diameter (D). The contoured frequency of occurrence from 2DVD data is shown in color (log scale). The mean fall velocity and $\pm 1\sigma$ standard deviation bars are from MPS. The dark dashed line is from the fit to the laboratory data of Gunn and Kinzer (1949) and the purple line is the same except corrected for the altitude of Greeley, CO (1.4 km

MSL). (b) Relative frequency histograms of fall velocity for the 0.5 ± 0.1 mm and 1 ± 0.1 mm bins. (c) as in (b) except for the 0.7 ± 0.1 mm and 1.5 ± 0.1 mm bins.

The histogram from MPS for the 0.5 mm sizes shows positive skewness with mean of 1.8 m s⁻¹, spectral width of 0.65 m s⁻¹ and corresponding coefficient of variation nearly doubling to 35% (relative to the 1 mm size histogram). The finite bin width (0.4-0.6 mm) causes a corresponding fall speed "spread" of 0.4 m s⁻¹ which contributes to the measured coefficient of variation. Nevertheless, it is not possible to rule out the low frequency of occurrence of sub- or super-terminal fall speeds, respectively, less than 1.26 m s⁻¹ or exceeding 2.34 m s⁻¹ based on our data. Examination of the MPS-based fall speed histogram for the 0.7 mm size indicates negative skewness. As with the 0.5 mm drops it is not possible to rule out the occurrences of fall speeds < 1.8 m s⁻¹ or > 3.4 m s⁻¹, i.e., sub- or super-terminal fall speeds.

2.2 Fall Speeds from Huntsville, Alabama

The first Huntsville event occurred on 11 April 2016 and consisted of precipitation associated with the mesoscale vortex of a developing squall line that moved across northern Alabama between 1800 and 2300 UTC and produced over 25 mm of rainfall in the Huntsville area. Figure 2(a) shows the ambient 10-m height wind speeds (3 s and 5-min averaged) recorded at the site. Maximum speeds were less than 5 m s⁻¹ and wind gusts were light. As no direct *in situ* measurement of turbulence was available we use the approach by (*Garrett and Yuter*, 2014) who estimate the difference between the maximum wind speed, or gust, that was sampled every 3 s, and the average wind speed derived from successive 5 min intervals. The estimated turbulent intensity is proportional to $E = (Gusts - AverageWind)^2/2$. Figure 2(b) shows the *E* values which were small (maximum $E < 0.4 \text{ m}^2 \text{ s}^{-2}$) and indicative of low turbulence. Also, shown in Fig. 2(b) is the 2DVD-based time series of rainfall rate (R) averaged over 3 mins; the maximum R is around 10 mm h⁻¹.



<u>Figure 2</u>: (a) 3-s raw and 5-min averaged wind speeds at 10-m height. (b) turbulent intensity estimates E, and 3-min averaged R.

Figure 3(a) shows the fall velocity versus D comparison between the two instruments while panels (b,c) show the histograms for the 0.5 and 1 mm, and 0.7 and 1.5 mm sizes, respectively. Similar to the Greeley event, the mean fall speed agreement between both instruments in the overlap region is excellent (see Table 1) and consistent with the FT fit to the Gunn-Kinzer laboratory data. As in Fig. 1(a), the MPS data in Fig. 3(a) is in excellent agreement with FT fit for sizes < 0.5 mm.

The 0.5 and 1 mm histogram shapes in Fig. 3(b) are quite similar to the Greeley case shown in Fig. 1(b). The mean and standard deviations from the MPS data for the 0.5 and 1 mm bins are, respectively, $[2 \pm 0.62]$ and $[3.88 \pm 0.44]$ m s⁻¹. The values for the 0.7 and 1.5 mm bins are, respectively, $[2.6 \pm 0.6]$ and $[5.4 \pm 0.4]$ m s⁻¹. There is negligible evidence of sub- or super-terminal fall speed occurrences based on the 1 and 1.5 mm histograms. The comments made earlier with respect to Fig. 1(b,c) of the Greeley event for the 0.5 and 0.7 mm histograms are also applicable here, i.e., we cannot rule out the occasional occurrences of sub- or super-terminal fall speeds based on our data.



<u>Figure 3</u>. (a) as in Fig. 1(a) except for 11 April 2016 event. The dashed line is fit to Gunn-Kinzer at sea level. (b,c) as in Fig. 1(b,c) except for 11 April 2016 event.

The second case considered is from 30 November 2016 wherein a supercell passed over the instrumented site from 0300-0330 UTC producing about 15 mins later a long-lived EF-2 tornado. Strong winds were recorded at the site with 5-min averaged speeds reaching 10-12 m s⁻¹ between 0320-0330 and E values in the range to 7-8 m² s⁻² indicating strong turbulence (Fig. 4a,b). The rain rates peaked at 70 mm h⁻¹ during this time (Fig. 4b). About 3 h later several squall-line type storm cells passed over the site from 0700-0900 UTC again with strong winds but considerably lower E values 2-4 m² s⁻² and maximum R of 80 mm h⁻¹. After 1000 UTC the E values were much smaller (< 0.5 m² s⁻²) indicating calm conditions. The peak R is also smaller at 30 mm h⁻¹ at 1000 UTC.

Figure 4 panels (c), (d) and (e) show the mean and $\pm 1\sigma$ of the fall speeds from the 2DVD for the 1.3, 2 and 3 mm drop sizes, respectively. The MPS data are not shown

here since during this event it was located outside the DFIR on its turntable and we did not want to confuse the wind-effects between the two instruments. It is clear from Fig. 4(c) that during the supercell passage (0300-0330 UTC) the mean fall speed for 1.3 mm drops decreases (from 5 to 3.5 m s⁻¹) and the standard deviation increases (from 0.5 to 1.5 m s⁻¹). The histogram shapes also show increasing negative skewness (not shown). The same trend can be seen for the subsequent squall-line rain cell passage from 0700-0900 UTC. Similar trends are noted in panels (d) and and less so in panel (e).



<u>Figure 4</u>. (a) as in Fig. 2(a) except for 30 Nov 2016 event. (b) as in Fig. 2(b). (c) mean and $\pm 1\sigma$ standard deviation of fall speeds from 2DVD for 1.3 ± 0.1 mm sizes. (d,e) as in (c) except for 2 ± 0.1 and 3 ± 0.1 mm sizes, respectively.

To expand on this observed correlation, Fig. 5 shows scatterplots of the mean fall speed and standard deviation versus E for the 1.3 mm drops (panels a,b), while panels (c,d) and (e,f) show the same but for the 2 and 3 mm drops, respectively. The mean fall speed decreases with increasing *E* nearly linearly for $E > 1 \text{ m}^2 \text{ s}^{-2}$ but less so for the 3 mm size drops (Stout et al., 1995). This decrease relative to Gunn-Kinzer terminal fall speeds is termed as "sub-terminal" and our data is in general agreement with (Montero-Martinez and Garcia-Garcia 2016) who found an increase in the numbers of subterminal drops with sizes between 1-2 mm under windy conditions using a 2D-Precipitation probe with resolution of 200 µm (similar to 2DVD) but without a wind fence. The standard deviation of fall speeds (σ_f) versus *E* is shown in panels 5 (b,d,f). When E>1 m² s⁻², the σ_f is nearly constant at 1.5 m s⁻¹ for both 1.3 and 2 mm drop sizes and constant at 1 m s⁻¹ for the 3 mm size. For E < 1, the σ_f is more variable and essentially uncorrelated with E. From the discussion related to Fig. 1(b,c) and 3(b,c), σ_f values exceeding approximately 0.5 m s⁻¹ can be attributed to physical, not instrumental or finite bin width effects (see, also, Table 1). Thus, the fall speed distributions are considerably broadened when $E>1 \text{ m}^2 \text{ s}^2$ due to increasing turbulence levels which is again consistent with the findings of (Montero-Martinez and Garcia-Garcia, 2016) as well as those of (Garett and Yuter, 2014). The latter observations, however, were of graupel fall speeds in winter precipitation using a multi-angle snowflake camera (Garrett et al., 2012).



<u>Figure 5.</u> (a,b) mean fall speed and standard deviation, respectively, versus E for 1.3 mm sizes. (c,d) same but for 2 mm sizes.(e,f) same but for 3 mm.

3 Discussion and Conclusions

We have reported on raindrop fall speed distributions using a high resolution (50 μ m) droplet spectrometer (MPS) collocated with moderate resolution (170 μ m) 2DVD (with both instruments inside a DFIR wind shield) to cover the entire size range (from 0.1 mm onwards) expected in natural rain. Turbulence intensity (*E*) was derived from wind/gust

data at 10-m height following (*Garrett and Yuter*, 2014). For low turbulent intensities ($E < 0.4 \text{ m}^2 \text{ s}^{-2}$), in the overlap region of the two instruments (0.7-2 mm), the mean fall speeds were in excellent agreement with each other for both the Greeley, CO and Huntsville, AL sites giving high confidence in the quality of the measurements. For D<0.5 mm and down to 0.1 mm, the mean fall speeds from MPS from both sites were in remarkable agreement with the (*Foote and du Toit*, 1969) fit to the laboratory data of (*Gunn and Kinzer*, 1949). In the overlap region, the mean fall speeds from the two instruments were in excellent agreement with the FT fit for the Huntsville site (no altitude adjustment required) and good agreement for the Greeley site (after adjustment for altitude of 1.4 km). For D>2 mm, the mean fall speeds from 2DVD were in excellent agreement with the FT fit at both sites.

Our histograms of fall speeds for 1 and 1.5 mm sizes under low turbulence intensity conditions ($E < 0.4 \text{ m}^2 \text{ s}^2$) from both MPS and 2DVD were in good agreement and did not show any evidence of either sub- or super-terminal speeds, rather the histograms were symmetric with mean close to the Gunn-Kinzer terminal velocity with no significant broadening over that ascribed to instrument and/or finite bin width effects. (Note: sub-terminal implies fall speeds < 0.7 times the terminal fall speed whereas super-terminal implies > 1.3 times terminal value; Montero-Martinez et al., 2009). However, for the 0.5 and 0.7 mm sizes, from the histogram of fall speeds using the MPS under the same conditions occasional occurrences of both sub- and super-terminal fall speeds, after accounting for instrumental and finite bin width effects, cannot be ruled out.

The only comparable earlier study is by (*Montero-Martinez et al.*, 2009) who used collocated 2D-cloud and precipitation probes (2D-C, 2D-P) but restricted their data to calm wind conditions. Their main conclusion was that the distribution of the ratio of the measured fall speed to the terminal fall speed for 0.44 mm size, while having a mode at 1 m s⁻¹ was strongly positively skewed with tails extending to 5 m s⁻¹ especially at high rain rates. In our data for the 0.5 and 0.7 mm sizes shown in Fig. 1(b,c) and 3(b,c), no such strong positive skewness was observed in the fall speed histograms, and the corresponding ratio of MPS-measured fall speeds to terminal values does not exceed 1.5 to 2.

Another study by *Larsen et al.,* (2014) appears to confirm the ubiquitous existence of super-terminal fall speeds for sizes < 1 mm using different instruments one of which was a 2DVD similar to the one used in this study. However, it is well-known that "mismatched" drops cause erroneous fall speed estimates from 2DVD for drops <0.5 mm (*Schoenhuber et al.,* 2008; Appendix in *Huang et al.,* 2010; *Bernauer et al.,* 2015). It is not clear if (*Larsen et al.,* 2014) accounted for this problem in their analysis. In addition, their 2DVD was not located within a DFIR-like wind shield.

In a later study using only the 2D-P probe, (*Montero-Martinez and Garcia-Garcia*, 2016) found sub-terminal fall speeds and broadened distributions under windy conditions for 1-2 mm sizes in general agreement with our results using the 2DVD. *Stout et al.*, (1995) simulated the motion of drops subject to non-linear drag in isotropic turbulence and determined that there would be a significant reduction of the average drop settling velocity (relative to terminal velocity) of greater that 35% for drops around 2 mm size when the ratio of *rms* velocity fluctuations (due to turbulence) relative to drop terminal velocity is around 0.8. Whereas we did not have a direct measure of the *rms* velocity fluctuations, the proxy for turbulence intensity (*E*) related to wind gusts during supercell passage (very large *E* around 7 m² s⁻²) and two squall-line passages (moderate *E* between 2-5 m² s⁻²) clearly showed a significant reduction in mean fall speeds of 25-30% relative to terminal speed for 1.3 and 2 mm sizes (and less so for 3 mm drops), with significant broadening of the fall speed distributions relative to calm conditions by nearly a factor of 1.5 to 2.

While our dataset is limited to three events they cover a wide range of rain rates, wind conditions and two different climatologies. One caveat is that the response of the DFIR wind shield to ambient winds in terms of producing subtle vertical air motions near the sensor area is yet to be evaluated as future work. Analysis of further events with direct measurement of turbulent intensity, for example using a 3D-sonic anemometer at the height of the sensor, would be needed to generalize our findings.

Data Availability

Data used in this paper can be accessed from:

ftp://lab.chill.colostate.edu/pub/kennedy/merhata/Bringi_et_al_2017_GRL_datasets/

Competing interests

VNB and MT declare they have no conflict of interest. DB is employed by Droplet Measurements Technologies, Inc. (Longmont, Colorado, USA) who manufacture the Meteorological Particle Spectrometer used in this study.

Acknowledgements

Two of the authors (VNB and MT) acknowledge support from the U.S. National Science Foundation via grant AGS-1431127. The assistance of Dr. Patrick Gatlin of NASA/MSFC is gratefully acknowledged. Prof. Kevin Knupp and Mr. Carter Hulsey of the University of Alabama in Huntsville processed the wind data.

References

- Atlas, D., R. C. Srivastava, and R. S. Sekhon (1973). Doppler radar characteristics of precipitation at vertical incidence, *Rev. Geophys.*, *11*, 1–35, doi:https://doi.org/10.1029/RG011i001p00001
- Barthazy, E., S. Göke, R. Schefold, and D. Högl (2004), An optical array instrument for shape and fall velocity measurements of hydrometeors, *J. Atmos. Oceanic Technol.*, 21, 1400–1416, doi:https://doi.org/10.1175/1520-0426(2004)021<1400:AOAIFS>2.0.CO;2.
- Baumgardner, D., S. Abel, D. Axisa, R. Cotton, J. Crosier, P. Field, C. Gurganus, A. Heymsfield, A. Korolev, M. Krämer, P. Lawson, G. McFarquhar, J. Z Ulanowski, J. Shik Um, 2016: Chapter 9: Cloud Ice Properties In Situ Measurement Challenges, AMS Monograph on Ice Formation and Evolution in Clouds and Precipitation: Measurement and Modeling Challenges, Eds. D. Baumgardner, G. McFarquhar, A. Heymsfield, Boston, MA.
- Beard, K. V. (1976), Terminal velocity and shape of cloud and precipitation drops aloft, *J. Atmos. Sci., 33*, 851–864, doi:https://doi.org/10.1175/1520-0469(1976)033<0851:TVASOC>2.0.CO;2
- Beard, K. V., and H. R. Pruppacher (1969), A determination of the terminal velocity and drag of small water drops by means of a wind tunnel, *J. Atmos. Sci., 26*, 1066–1072, doi: <u>https://doi.org/10.1175/1520-0469(1969)026<1066:ADOTTV>2.0.CO;2</u>.
- Belda, M., E. Holtanová, T. Halenka, and J. Kalvová (2014), Climate classification revisited: From Köppen to Trewartha. *Climate Res.*, *59*, 1–13, doi:https://doi.org/10.3354/cr01204.

Bernauer, F., K. Hürkamp, W. Rühm, and J. Tschiersch (2015), On the consistency of 2-D video disdrometers in measuring microphysical parameters of solid precipitation, *Atmos. Meas. Tech., 8*, 3251-3261, doi: https://doi.org/10.5194/amt-8-3251-2015

- Foote, G.B. and P.S. Du Toit (1969), Terminal Velocity of Raindrops Aloft. *J. Appl. Meteor.*, *8*, 249–253, https://doi.org/10.1175/1520-0450(1969)008<0249:TVORA>2.0.CO;2
- Garrett, T. J., and S. E. Yuter (2014), Observed influence of riming, temperature, and turbulence on the fallspeed of solid precipitation, *Geophys. Res. Lett.*, *41*, 6515–6522, doi:10.1002/2014GL061016.

Garrett, T. J., Fallgatter, C., Shkurko, K., and Howlett, D. (2012), Fall speed measurement and high-resolution multi-angle photography of hydrometeors in free fall, *Atmos. Meas. Tech., 5*, 2625-2633, doi:10.5194/amt-5-2625-2012

Gunn, R. and G.D. Kinzer (1949), The terminal velocity of fall for water droplets in stagnant air, *J. Meteor., 6*, 243–248, https://doi.org/10.1175/1520-0469(1949)006<0243:TTVOFF>2.0.CO;2

- Huang, G., V.N. Bringi, and M. Thurai (2008), Orientation Angle Distributions of Drops after an 80-m Fall Using a 2D Video Disdrometer, *J. Atmos. Oceanic Technol., 25*,1717–1723, https://doi.org/10.1175/2008JTECHA1075.1
- Huang, G., V.N. Bringi, R. Cifelli, D. Hudak, and W.A. Petersen (2010), A Methodology to Derive Radar Reflectivity–Liquid Equivalent Snow Rate Relations Using C-Band Radar and a 2D Video Disdrometer, *J. Atmos. Oceanic Technol.*, 27, 637– 651, https://doi.org/10.1175/2009JTECHA1284.1
- Joe, P., and R. List (1987), Testing and performance of two-dimensional optical array spectrometer with grey scale, *J. Atmos. Oceanic. Technol., 4*, 139-150, https://doi.org/10.1175/1520-0426(1987)004<0139:TAPOTD>2.0.CO;2
- Knollenberg, R. (1970), The Optical Array: An alternative to scattering or extinction for airborne particle size determination, *J. Appl. Meteorol.*, *9*, 86–103, doi:https://doi.org/10.1175/1520-0450(1970)009<0086:TOAAAT>2.0.CO;2.
- Knollenberg, R. (1976), Three new instruments for cloud physics measurements: The 2–D spectrometer probe, the forward scattering spectrometer probe and the active scattering aerosol spectrometer, in International Conference on Cloud Physics, American Meteorological Society, 554–561,.
- Knollenberg, R. (1981), Clouds, Their Formation, Optical Properties and Effects, chap.
 Techniques for probing cloud microstructure, Academic Press, edited by P.V.
 Hobbs and A. Deepak. 495 pp
- Korolev, A. V., Kuznetsov, S. V., Makarov, Y. E., and Novikov, V. S. (1991), Evaluation of Measurements of Particle Size and Sample Area from Optical Array Probes, J. Atmos. Oceanic Tech., 8, 514–522, https://doi.org/10.1175/1520-0426(1991)008<0514:EOMOPS>2.0.CO;2
- Korolev, A. V., J. W. Strapp, and G. A. Isaac (1998), Evaluation of the Accuracy of PMS Optical Array Probes, *Journal of Atmospheric and Oceanic Technology*, 15, 708–720, https://doi.org/10.1175/1520-0426(1998)015<0708:EOTAOP>2.0.CO;2
- Korolev, A. V. (2007), Reconstruction of the Sizes of Spherical Particles from Their Shadow Images. Part I: Theoretical Considerations, *Journal of Atmospheric and Oceanic Technology*, 24, 376–389, https://doi.org/10.1175/JTECH1980.1
- Larsen, M.L., A.B. Kostinski, and A.R. Jameson (2014), Further evidence for super terminal drops, *Geophysical Research Letters*, *41*, 2014GL061397.
- List, R., N.R. Donaldson, and R.E. Stewart (1987), Temporal Evolution of Drop Spectra to Collisional Equilibrium in Steady and Pulsating Rain, *J. Atmos. Sci.,* 44, 362–372, https://doi.org/10.1175/1520-0469(1987)044<0362:TEODST>2.0.CO;2

- Löffler-Mang, M. and J. Joss (2000), An Optical Disdrometer for Measuring Size and Velocity of Hydrometeors, *J. Atmos. Oceanic Technol.*, *17*, 130–139, https://doi.org/10.1175/1520-0426(2000)017<0130:AODFMS>2.0.CO;2
- Montero-Martinez, G. and F. Garcia-Garcia (2016), On the behavior of raindrop fall speed due to wind, Quarterly *Journal of the Royal Meteorological Society, 142*, 2794, DOI: 10.1002/qj.2794.
- Montero-Martinez, G., A. B. Kostinski, R. A. Shaw, and F. Garcia-Garcia (2009), Do all raindrops fall at terminal speed?, *Geophysical Research Letters*, *36*, 246 L11818, doi:10.1029/2008GL037111.
- Notaroš, B., V. N. Bringi, C. Kleinkort, P. Kennedy, G-J Huang, M. Thurai, A. J. Newman, W. Bang and G. Lee (2016), Accurate Characterization of Winter Precipitation Using Multi-Angle Snowflake Camera, Visual Hull, Advanced Scattering Methods and Polarimetric Radar, *Atmosphere*, 7(6), 81; doi:10.3390/atmos7060081
- Rasmussen, R., B. Baker, J. Kochendorfer, T. Meyers, S. Landolt, A.P. Fischer, J. Black, J.M. Thériault, P. Kucera, D. Gochis, C. Smith, R. Nitu, M. Hall, K. Ikeda, Gutmann (2012), How Well Are We Measuring Snow: and Ε. The Precipitation NOAA/FAA/NCAR Winter Test Bed, Bull. Amer. Meteor. Soc., 93, 811-829, https://doi.org/10.1175/BAMS-D-11-00052.1

Rosewell, C.J. (1986), Rainfall Kinetic Energy in Eastern Australia, *J. Climate Appl. Meteor., 25*, 1695–1701, https://doi.org/10.1175/1520-0450(1986)025<1695:RKEIEA>2.0.CO;2

- Schönhuber, M., Günter Lammer, Randeu W.L. (2007), Advances in Geosciences, 10, pp. 85-90, 2007, https://doi.org/10.5194/adgeo-10-85-2007.
- Schönhuber, M., G. Lammar, and W. L. Randeu (2008), "The 2D-video-distrometer", Chapter 1 in "Precipitation: Advances in Measurement, Estimation and Prediction", S. C. Michaelides, Ed., Springer, 3–31.
- Sekhon, R.S. and R.C. Srivastava (1971), Doppler Radar Observations of Drop-Size Distributions in a Thunderstorm, *J. Atmos. Sci.*, 28, 983–994, https://doi.org/10.1175/1520-0469(1971)028<0983:DROODS>2.0.CO;2
- Stout, J.E., S.P. Arva, and E.L. Genikhovich (1995), The Effect of Nonlinear Drag on the Motion and Settling Velocity of Heavy Particles, *J. Atmos. Sci., 52*, 3836–3848, https://doi.org/10.1175/1520-0469(1995)052<3836:TEONDO>2.0.CO;2
- Testik, F.Y. and M.K. Rahman (2016), High-Speed Optical Disdrometer for Rainfall Microphysical Observations, *J. Atmos. Oceanic Technol.*, 33, 231–243, https://doi.org/10.1175/JTECH-D-15-0098.1
- Thériault, J.M., R. Rasmussen, E. Petro, J. Trépanier, M. Colli, and L.G. Lanza (2015), Impact of Wind Direction, Wind Speed, and Particle Characteristics on the

Collection Efficiency of the Double Fence Intercomparison Reference, *J. Appl. Meteor. Climatol., 54*, 1918–1930, https://doi.org/10.1175/JAMC-D-15-0034.1

Thurai, M. and V. N. Bringi (2005), Drop axis ratios from a 2D video disdrometer, *J. Atmos. Oceanic Technol.*, 22, 966–978, https://doi.org/10.1175/JTECH1767.1

- M. Thurai, V. N. Bringi, M. Szakáll, S. K. Mitra, K. V. Beard, and S. Borrmann (2009), Drop Shapes and Axis Ratio Distributions: Comparison between 2D Video Disdrometer and Wind-Tunnel Measurements, Journal of Atmospheric and Oceanic Technology, 26 (7), 1427–1432, https://doi.org/10.1175/2009JTECHA1244.1
- Thurai, M., V. N. Bringi, W. A. Petersen, P. N. Gatlin (2013), Drop shapes and fall speeds in rain: two contrasting examples, *J. Appl. Meteor. Climatol.*, *52*, 2567–2581, https://doi.org/10.1175/JAMC-D-12-085.1
- Thurai, M., P. Gatlin, V. N. Bringi, W. Petersen, P. Kennedy, B. Notaroš, and L. Carey (2017), Toward completing the raindrops size spectrum: Case studies involving 2D-video disdrometer, droplet spectrometer, and polarimetric radar measurements, *J. Appl. Meteor. Climatol.*, 56, 877–896, https://doi.org/10.1175/JAMC-D-16-0304.1
- Trewartha, G. T., and L. H. Horn (1980), Introduction to Climate, 5th ed. McGraw Hill, 416 pp.
- Yu, C.-K., Hsieh, P.-R., Yuter, S. E., Cheng, L.-W., Tsai, C.-L., Lin, C.-Y., and Chen, Y.: Measuring droplet fall speed with a high-speed camera: indoor accuracy and potential outdoor applications, *Atmos. Meas. Tech.*, 9, 1755-1766, https://doi.org/10.5194/amt-9-1755-2016, 2016.