



Testing and evaluation of a new airborne system for continuous N₂O, CO₂, CO, and H₂O measurements: the Frequent Calibration High-performance Airborne Observation System (FCHAOS)

Alexander Gvakharia¹, Eric A. Kort¹, Mackenzie L. Smith^{1,2}, and Stephen Conley² ¹Climate and Space Sciences and Engineering, University of Michigan, Ann Arbor, Michigan, USA ²Scientific Aviation, Boulder, Colorado, USA

Correspondence to: Alexander Gvakharia (agvak@umich.edu)

Abstract. We present the development and assessment of a new flight system that uses a commercially available continuouswave, tunable infrared laser direct absorption spectrometer to measure N_2O , CO_2 , CO, and H_2O . When the commercial system is operated in an off-the-shelf manner, we find a clear cabin pressure/altitude dependency for N_2O , CO_2 , and CO. The characteristics of this artifact make it difficult to reconcile with conventional calibration methods, so we present a novel procedure

- 5 employing a high-flow system with high-frequency, short-duration sampling of a known calibration gas. This approach corrects for cabin pressure dependency as well as other sources of drift in the analyzer while maintaining a ~90% duty cycle for 1 Hz sampling. Assessment and validation of the flight system with both extensive in-flight calibrations and comparisons with other flight-proven sensors demonstrate the validity of this method. In-flight 1σ precision is estimated at 0.05 ppb, 0.10 ppm, 1.00 ppb, and 10 ppm for N₂O, CO₂, CO, and H₂O respectively, and traceability to WMO standards is found to be 0.14 ppb, 0.34
- 10 ppm, and 2.33 ppb for N₂O, CO₂, and CO. We show the system is capable of precise, accurate 1 Hz airborne observations of N₂O, CO₂, CO, and H₂O and highlight flight data illustrating the value of this analyzer for studying N₂O emissions on ~100 km spatial scales.

1 Introduction

Continuous, 1 Hz airborne observations of atmospheric greenhouse gases and pollutants provide essential information for
direct quantification of emissions (Karion et al., 2015; Peischl et al., 2015; Smith et al., 2015; Kort et al., 2016), assessment
of modeled representations of emissions and transport (Wofsy, 2011; O'Shea et al., 2014), and validation of remote sensing
observations (Tanaka et al., 2016; Inoue et al., 2016; Frankenberg et al., 2016). Advances in the last decade have facilitated
widespread, high-precision, high-accuracy continuous airborne observations of CH₄, CO₂, CO, and H₂O (Chen et al., 2010;
Karion et al., 2013; Filges et al., 2015). These observations have proven particularly valuable for quantifying emissions from

20 individual, large emitting point sources (Conley et al., 2017; Mehrotra et al., 2017) as well as constraining emissions of highly heterogeneous processes on 10-100 km scales (Karion et al., 2015; Peischl et al., 2015; Smith et al., 2015; Kort et al., 2016). Continuous, 1 Hz airborne sampling of N₂O with high accuracy and precision has proven more elusive, with limited aircraft campaigns reporting continuous airborne N₂O (Kort et al., 2011; Wofsy, 2011; Xiang et al., 2013), systems being large and





challenging to operate with frequent attention to supplies of cryogens (Santoni et al., 2014), and newer systems showing large cabin pressure dependencies (Pitt et al., 2016).

 N_2O is a potent greenhouse gas with natural and anthropogenic sources, and is currently the single most impactful anthropogenic ozone-depleting substance actively emitted to the atmosphere (Ravishankara et al., 2009). Atmospheric emissions of

- 5 N₂O have been steadily rising over time (Myhre et al., 2013), but attempts to better quantify, understand, and constrain anthropogenic emissions have been hindered by high uncertainties in model estimates and limited observational constraints (Ciais et al., 2013; Davidson and Kanter, 2014). The poor understanding of N₂O emissions processes is attributable to a combination of high spatial and temporal variability (Monni et al., 2007) that is hard to observe and represent, and a lack of direct observational data of emissions sources (Brown et al., 2001). The largest source of anthropogenic N₂O, contributing 66% of global
- 10 N_2O emissions, is agricultural activity (Davidson and Kanter, 2014). Some of these emissions are a direct product of human activity, such as the fertilizer production process, which has grown to 100 Tg N yr⁻¹ since the development of the Haber-Bosch process in 1908 (Erisman et al., 2008). Other anthropogenic emissions, such as from applied fertilizer, are harder to observe and represent as environmental factors including soil moisture, temperature, and crop type all influence emissions (Dalal et al., 2003; Ruser et al., 2006; Griffis et al., 2017).
- A diverse range of approaches have been utilized in attempts to measure N₂O emissions (Denmead, 2008; Rapson and Dacres, 2014). Flux chambers can quantify emissions from areas on the order of square meters (Bouwman et al., 2002; Marinho et al., 2004; Turner et al., 2008; Chadwick et al., 2014). Given the heterogeneity in N₂O emission processes, extrapolation of limited flux chambers to accurately represent domains on the orders of 10-100 square km remains challenging (Pennock et al., 2005; Flechard et al., 2007). The eddy covariance approach deploys sensors on towers to estimate fluxes on a 1-10 km² scale
- 20 (Dalal et al., 2003; Pattey et al., 2007), but not beyond that range, thus encountering similar representation challenges as flux chambers. Bottom-up modeling of emissions processes (Del Grosso et al., 2006; Tian et al., 2015) can represent emissions at a range of scales. The models are typically trained and evaluated with data from flux-chambers and then simulate emissions at a continental to global scale. Evaluation of these representations then can happen at the larger scales, where top-down atmospheric inversions (Kort et al., 2008, 2011; Miller et al., 2012; Thompson et al., 2014; Chen et al., 2016; Griffis et al., 2016; Chen et al
- 25 2017; Nevison et al., 2018) have challenged modeled and inventoried emissions and often found large discrepancies exceeding 100% (Miller et al., 2012). To better understand these divergences as well as to properly assess the representation of fluxchamber and eddy covariance measurements, we need observational constraints at 10-100 square km spatial scales.

Continuous, 1 Hz airborne measurements can provide information at this critical spatial scale, in addition to providing observational constraints for large point sources (N_2O fertilizer production facilities present a potentially important source of N_2O

30 emissions). To get good, useful data, aircraft studies require instruments that have high precision, a fast response time, and are relatively robust to changes in the environment (Fried et al., 2008). Continuous-wave tunable infrared laser direct absorption spectrometers (CW-TILDAS) can satisfy those requirements and are an appropriate choice for airborne instrumentation (Rannik et al., 2015).

Mid-infrared laser spectrometers have been widely used in airborne studies. They often employ an in-flight calibration to correct for spectral drift that can occur over several hours of measurement (O'Shea et al., 2013; Santoni et al., 2014). Zero





5

air with no gases in the absorption spectrum can also be used to adjust the spectral baseline for more accurate measurements, particularly if the desired gas has a weak absorption feature (Yacovitch et al., 2014; Smith et al., 2015). One recent study to measure N_2O emissions with such an instrument reported their assessment of its performance and found artifacts in the data primarily due to changes in airplane cabin pressure (Pitt et al., 2016), significantly impacting the duty cycle of the analyzer and its utility during vertical profiles. To deploy a CW-TILDAS for N_2O observation as in Pitt et al. (2016), problems can arise if drifts occur on a timescale faster than the conventional calibration period of 0.5.1 hour. Also, at low flow rates (0.1 - 1 slpm)

drifts occur on a timescale faster than the conventional calibration period of 0.5-1 hour. Also, at low flow rates (0.1 - 1 slpm), N_2O can take a long time to equilibrate, and this can have a negative impact on the instrument's duty cycle (Santoni et al., 2014). The efficacy of airborne instrumentation for N_2O measurements would benefit from improvements to such limitations.

We present the Frequent Calibration High-performance Airborne Observation System (FCHAOS), utilizing a TILDAS instrument and a novel calibration technique, to make N₂O measurements that can be utilized for calculating facility emissions,

- 10 strument and a novel calibration technique, to make N₂O measurements that can be utilized for calculating facility emissions, mass balance fluxes, and regional inversions. Rather than relying on spectral zeros and infrequent in-flight calibrations to correct for drift on large time-scales, we use short, frequent calibration measurements to resolve both long-term spectral drift and short-term environmental effects. This research was part of the Fertilizer Emissions Airborne Study (FEAST) campaign in spring 2017 targeting N₂O and other greenhouse gas emissions in the southern Mississippi River Valley region of the USA. In
- 15 this manuscript we discuss the operation and set-up of the instrumentation involved in the airborne flight system. We discuss test flights done to assess the off-the-shelf operation and the associated flaws. We then present our solution to improve instrument performance with short, frequent calibrations and validation by in-flight calibrations and comparison with a flight-proven Picarro cavity ring-down spectrometer.

2 Instrumentation

20 2.1 CW-TILDAS description

The core of our system is an Aerodyne mini spectrometer. The spectrometer uses a mid-IR, continuous-wave, distributed feedback laser with a frequency of 2227 cm⁻¹ (nanoplus, Germany). The laser is mounted on a copper Peltier device which keeps the laser temperature stable at ~17 °C and is regulated by a thermoelectric chiller held at 23 °C (Oasis 3, Solid State Cooling, USA). This laser is optically aligned into a 0.5 L astigmatic mirror multipass absorption Herriott cell (McManus

- et al., 1995). The refraction pattern in the cell is optimized to produce a total path length of 76 meters before the beam exits the cell and is aligned into a photodetector. The cell itself is sealed and held at ~40 Torr. The space outside of the cell is subject to variations in external pressure. The laser's output frequency can be adjusted by ramping the current, sweeping across a frequency range of approximately 2227.4-2227.9 cm⁻¹. This range contains transition lines for H₂O, CO₂, CO, and N₂O, allowing the photodetector to measure the laser transmission intensity at each of these transitions (Nelson et al., 2002).
- The mole fractions of N_2O , CO_2 , CO_2 , CO_2 , and H_2O are reported using the TDLWintel software as described in Nelson et al. (2002) and Nelson et al. (2004). The retrieval uses the Beer-Lambert law, where the absorption intensity, path length, and molar absorptivity enable calculation of gas concentration. The absorption spectrum is fit in real-time with a Voigt density profile using the Levenberg-Marquardt algorithm, allowing retrievals at 1 Hz (Nelson et al., 2004). The exact frequencies





of the line transitions and absorption cross-sections are obtained from the HITRAN2012 database (Rothman et al., 2013). Pressure and temperature data acquired from sensors in the cell are used to account for broadening effects in the fit. Though initial measurements are made as wet molar fractions, TDLWintel uses a H_2O broadening coefficient to mitigate the effect of H_2O vapor, directly reporting dry molar fractions for N_2O , CO_2 , and CO (Lebegue et al., 2016; Pitt et al., 2016).

5 2.2 Set-up and payload

We integrated the FCHAOS system on a single-engine Mooney M20R aircraft from Scientific Aviation. Figure 1 shows the flow diagram for our system. The inlet line to the instrument is ~5 m PVDF Kynar tubing. The inlet line is rear-facing on the right wing to reduce liquid and particle contamination of the line, with the plane exhaust located on the left wing, minimizing exhaust contamination. A membrane disc filter (Pall, USA) is also used to block particulates from entering the cell. Using a

- 10 mass flow controller (MC-5SLPM-D, Alicat Scientific, USA), we set a flow rate of 1.5 slpm. The MFC is placed downstream of the filter to prevent damage due to rogue particulates. The instrument cell is pressurized on the ground to 40 Torr using a dry scroll pump (IDP-3, Agilent Technologies, USA) and a needle valve (SS-1RS4, Swagelok, USA) directly upstream of the pump for adjusting the target pressure given a defined mass flow rate. The use of mass flow control enables rapid switching between calibration gas and ambient air without inducing pressure fluctuations or pressure ringing in the cell. Two
- 15 2 L aluminum carbon-fiber-wrapped compressed air cylinders are securely strapped in the plane. These tanks are outfitted with stainless steel regulators (51-14B-590, Air Liquide, USA) and stored calibration gases. Two three-way solenoid valves (009-0294-900, Parker-Hannifin, USA) control the air flow between the tanks and the inlet line.

The additional payload is set up on the Mooney as described in Conley et al. (2014) and Conley et al. (2017). Temperature and relative humidity are recorded with a humidity probe (HMP60, Vaisala, Finland). A cavity ring-down spectrometer (G2301-

f, Picarro, USA) measures CH₄, CO₂, and H₂O as described in Crosson (2008). Ozone is measured with an ozone monitor (Model 202, 2B Technologies, USA). Wind speed and direction are calculated using a differential GPS method as in Conley et al. (2014). The Mooney aircraft is not pressurized, so the instrument experiences pressure variation as the aircraft profiles.

Lag time between when air enters an instrument's inlet line and when it is measured in the cell is determined by breathing close to the inlet tube and recording sharp rises in CO_2 and H_2O concentrations. For FEAST lag times were measured at 3 s and

25 5 s for the FCHAOS and Picarro G2301-f respectively, values confirmed in flight by comparing variability with temperature and RH data from the humidity probe. These lag times are used in post-processing to match avionics and GPS data with the co-located mole fraction concentrations from the FCHAOS and G2301-f. Though lag times will vary with altitude, given the flow-rates, inlet line volumes, and altitude range of the Mooney aircraft it is essentially constant for the data presented in this manuscript.








Figure 1. Schematic of FCHAOS, where air flows from the inlet line through the solenoid valves, past the filter to the mass flow controller (MFC), through the instrument cell, a needle valve, and finally the vacuum pump. When calibrating the solenoid valves are actuated to direct flow from each individual calibration tank into the cell directly.

2.3 Calibration

We performed pre-flight calibrations on the ground for both the FCHAOS and Picarro G2301-f using two air cylinders calibrated to a NOAA WMO greenhouse gas scale (X2007, X2004A, X2014A, X2006A for CO_2 , CH_4 , CO, and N_2O respectively) (WMO, 2015). Both cylinders had concentrations of CO_2 (Zhao et al., 1997; Zhao and Tans, 2006; Tans et al., 2017), CH_4

5 (Dlugokencky et al., 2005), CO (Novelli et al., 2003), and N₂O (Hall et al., 2007) near ambient atmospheric levels, with one as a high-span standard and the other as a low-span.

We sequentially sampled these cylinders for multiple cycles, and compared the measured concentration for each gas to the reported value on the WMO scale. We consider known values X_{true} against the measured values $X_{measured}$, and a linear fit provides the slope m and intercept b such that $X_{true} = m^* X_{measured} + b$.

We filled the two in-flight calibration tanks used with the FCHAOS for FEAST with a separate custom mixture that contained atmospheric levels of N_2O , CO_2 , and CO. We calibrated the concentrations using the WMO standard cylinders by sampling the target cylinders in between the WMO standards.

We assessed the stability in linearity of the instrument by performing calibrations separated by months before and after the FEAST campaign. Over the course of four months, the slopes for N_2O , CO_2 , and CO changed by 0.4%, 0.01%, and 0.5%.

- 15 The impact of any variation in linearity depends on the difference between ambient levels and calibration gas values. For the operation of FCHAOS, we use calibration gas with concentrations near ambient levels. Typical atmospheric ambient levels of N₂O are ~335 ppb, so with a calibration gas at ~330 ppb, the long-term variation due to linearity is 0.4% of 5 ppb, or 0.02 ppb, an uncertainty that is within our precision as reported in Sect. 4.1. For CO₂ and CO, which have ambient atmospheric levels of ~400 ppm and ~155 ppb, we use calibration gases with ~390 ppm and ~150 ppb, and the impacts due to variation in linearity
- are 0.01 ppm and 0.025 ppb, respectively. If zero air were used instead, the impact on N_2O would be on the order of 0.4% of 335 ppb, or 1.3 ppb, an order of magnitude larger, with similar impacts for CO_2 and CO. By using calibration gases close to ambient levels we eliminate our sensitivity to drift in this instrument's linearity and thus can use one gas target for in-flight calibration to correct only for intercept variability.





3 In-flight operation

3.1 Null Test

For an instrument to be well-suited for airborne observation, resistance to environmental effects is paramount. A "null test," where an instrument samples air with known concentrations in flight while subject to variation in cabin pressure, air temper-

- 5 ature, etc., can be useful in evaluating its robustness as shown in Chen et al. (2010) and Karion et al. (2013). We conducted two null tests using the FCHAOS, once during a test flight in Colorado, once during a research flight in our target region in the lower Mississippi River basin. Figure 2 shows N₂O, CO₂, and CO concentrations observed by the FCHAOS while sampling tank air during a vertical profile descent. As the altitude decreases, there is a clear dependence due to the cabin pressure changing similar to what was reported in Pitt et al. (2016). As mentioned in Sect. 2, though the cell is pressurized, the rest of the
- 10 instrument is not, and since the aircraft cabin is not pressurized, our system thus experiences any change in ambient pressure. Correcting or mitigating this cabin pressure artifact is necessary for the FCHAOS to be capable of accurate airborne in-situ sampling.




Figure 2. A null test demonstrates artifacts when operating the instrument in an off-the-shelf manner. Drift occurs in N_2O , CO_2 , and CO due to changes in cabin pressure that occur with changing aircraft altitude. Dry tank air is used for the null test so H_2O is not evaluated.

3.2 Frequent calibration correction

15

The cause of the cabin pressure dependence is not immediately evident. One possible explanation could be an optical fringe pattern in the absorption spectrum that moves with changing cabin pressure. Acceleration during altitude change could also create g-force or electrical (via engine surges) changes that propagate through the instrument system. Without needing to





pinpoint the cause, we know the time period of the artifact presents on the order of many minutes, with a typical aircraft climb rate of 500 ft/min. Thus a correction that occurs on a shorter time spacing could remedy the drift. To account for both spectral drift in the instrument that occurs on the order of hours and cabin pressure-related artifacts that emerge on the order of minutes, we developed an empirical correction procedure using frequent measurements of a calibration gas.

- 5 The procedure is as follows. Every 2 min, we activate the solenoid valve to sample tank air for 10 s. We determined the calibration frequency of 2 min through a sensitivity test using null test data. By adjusting the calibration frequency and measuring the precision, we found similar 1σ uncertainties at 1 min and 2 min frequencies, but an increase in uncertainty at 4 min and beyond, making 2 min good for reducing gas consumption while maintaining high precision. We allow 5 s of flush time, leaving 5 s of measurement time. We determined the flush time duration of 5 s by sampling tank air in a lab setting at the appropriate
- 10 flow-rate and cell pressure as in-flight operation and measuring equilibration time. We calculate the average measured mole fraction of N₂O, CO₂, and CO in these 5 s (we omitted H₂O from this correction as the cabin pressure dependence does not seem to affect H₂O, more in Sect. 4). For each species we then interpolated in time between each measured calibration gas value and subtracted the known "true" value from this interpolation, giving us correction as a function of time. We then subtract this calibration curve from the raw data. Figure 3 shows both raw CO₂ data and the correction we derive using the frequent
- 15 calibration method from one of our flights. As mentioned above, the gas was on for 10 s, along with 5 s of post-calibration time removed to account for equilibration back to ambient sampling, resulting in a loss of 15 s of atmospheric observations every 120 s for an 87.5% duty cycle. As mentioned in Sect. 2.3, the calibration cylinder concentrations are near atmospheric values. As seen in Santoni et al. (2014), N₂O can take a long time to equilibrate between measurement sources due to its propensity to stick to tubing. Thus, choosing calibration values close to ambient is critical for maintaining short flush times. This also holds
- 20 for CO_2 , though less so for CO.








Figure 3. Raw CO₂ (black) measured by the FCHAOS for an entire flight, with frequent low dips due to calibrations. The blue dashed line indicates the "true" value of the calibration gas, the blue solid line shows the calibration curve obtained by interpolating between each calibration instance. The difference between the dashed and solid blue lines is used to correct for drift.

4 Calibration results and comparison with Picarro G2301-f

Figure 4 shows measurements from two null tests, one on April 26, 2017 in Colorado and one on May 2, 2017 in the Mississippi River Valley, the same null test as from Fig. 2. For each null test, the figure shows both the raw N_2O , CO, and CO_2 measurements and the corrected data following our calibration, along with the aircraft altitude. Our calibration method accounts for the

- 5 clear cabin pressure/altitude dependence. During a null test the FCHAOS samples tank air uninterrupted, rather than making a calibration measurement every 2 min as in the frequent calibration procedure described in Sect. 3.2. Thus, we average 5 s of data from every 120 s to simulate the normal operation mode. Even after correction there is some residual coherent variability evident at the 15 min mark of the null test shown in the bottom 2 rows of Fig. 4, but this potential feature remains still within our instrument precision.
- Given the repeatable, smooth nature of the cabin pressure artifact, it is possible to use just the cabin pressure data to empirically correct for the artifact, without running frequent calibrations. This method does not account for long-term spectral drift however or traceability, compromising accuracy. Additionally, for flights conducted in regions at a different elevation than the one in FEAST, the pressure-correction-only method would require a new vertical profile null test, which can impact gas consumption and flight hour usage.
- Figure 5 compares the raw CO_2 data from the Picarro G2301-f and FCHAOS during a research flight along with altitude, and a second comparison once the FCHAOS data is corrected. The difference between the two instruments is shown in the top





2 panels. The most significant discrepancies occur during the vertical profile section of the flight. Following calibration, the deviation during profiling is eliminated, and the 1σ uncertainty in the difference is reduced from 1.15 ppm to 0.28 ppm.

For the FEAST campaign, in post-processing it became evident that a persistent offset of 0.60 ppm existed for CO₂ between the Picarro and FCHAOS. On multiple subsequent deployments of these analyzers we have not found such offset. We believe

5 the origin of this offset to be related to regulator contamination of a calibration gas cylinder and/or tubing used in conjunction with the regulator. For the CO_2 comparisons in this manuscript, we have corrected for this bias.








Figure 4. Top two rows show FCHAOS data from a null test on April 26, 2017, bottom two rows shows data from a null test on May 2, 2017, the same seen in Fig. 2. Rows 1 and 3 show N₂O, CO, and CO₂ during the null test before any calibration, rows 2 and 4 show the gas data following the frequent calibration correction. The procedure removes cabin pressure dependence and calibrates for linear drift. Black horizontal lines show mean and 1σ uncertainty.





5




Figure 5. Picarro G2301-f and uncalibrated FCHAOS CO_2 time series on left, Picarro G2301-f and calibrated FCHAOS CO_2 on right. The calibration procedure corrects for any artifacts in the FCHAOS data correlated with aircraft altitude.

The raw H₂O measurements exhibit good agreement between FCHAOS and the Picarro G2301-f. The H₂O data was not calibrated or adjusted in any way, as there appeared to be minimal, if any, impact from cabin pressure variance. Figure 6 shows a histogram of the differences in Picarro G2301-f and FCHAOS H₂O and CO₂ (following calibration) for over 40 hours of research flight time. Figure 7 shows the differences as a function of time for all flight data. For H₂O, we find a mean difference between the two instruments of 170 ppm, a median of 180 ppm, and 1 σ of 340 ppm, shown in the figures as solid and dashed lines. In-flight 1 σ precision for H₂O from the Picarro G2301-f has been reported as 100 ppm (Crosson, 2008), while the inflight 1 σ precision for the FCHAOS was found to be 10 ppm. If a moving fringe is indeed the culprit for the cabin pressure sensitivity, it is possible that it does not manifest for H₂O, which has the lowest transition frequency and highest laser intensity,

likely resulting in the best signal-to-noise compared to N₂O, CO₂, and CO. The width of the fringe may be narrower than the

10 absorption band, and does not impact H_2O as much as it does the other gases.








Figure 6. Histogram of difference between H_2O and CO_2 concentrations from the Picarro G2301-f and FCHAOS. FCHAOS CO_2 has been calibrated, while H_2O has not. For H_2O , mean of 0.017% or 170 ppm, median of 0.018% or 180 ppm, 1 σ of 0.034% or 340 ppm, where Picarro G2301-f precision is 100 ppm. For CO_2 , mean of 0 ppm, median of 0.01 ppm, 1 σ of 0.44 ppm.








Figure 7. Difference as function of flight time in Picarro G2301-f and FCHAOS H₂O and CO₂ for all research flights. Colors separate flight days, grey lines indicate mean and 1σ uncertainty. Largest deviations occur when sampling in the immediate near-field of large point sources where some mismatched lag times contribute to deviations.

4.1 **Precision and Accuracy**

To assess the FCHAOS precision, we consider flight data during a null test when the altitude did not significantly change. We find 1 s precisions of ± 0.05 ppb, ± 0.10 ppm, ± 1.00 ppb, and ± 10 ppm for N₂O, CO₂, CO₂, and H₂O respectively. This is about a factor of 2 greater than the performance on the ground in a lab setting, with 1σ precisions of 0.02 ppb, 0.05 ppm, 0.50 ppb, and 7 ppm.

5

In addition to the frequent calibrations every two minutes, a second cylinder is sampled every hour for 25 s as a "check gas" to test the traceability of the in-flight system. The last 5 s of each check gas period is used to calculate a mean value for each species. Figure 8 shows each instance of N₂O, CO₂, and CO check gas sampling, along with histograms for the difference from the known value. The time series show the last 5 s of each check gas period, along with a horizontal line indicating the

10 known value of the air tank calibrated with the WMO standards as in Sect. 2.3. Note that the "check gas" and "calibration gas" cylinders were switched halfway through the campaign due to gas consumption, as reflected by the horizontal line. Looking at the difference of each check gas period from the known value, we find median offsets of 0.17 ppb, 0.08 ppm, and 0.29 ppb for N₂O, CO₂, and CO respectively, representative of possible bias between the flight system and the WMO scale. The 1σ





values for the check gas points are 0.13 ppb, 0.34 ppm, and 2.33 ppb for N_2O , CO_2 , and CO, representative of traceability of individual 1 s observations to the WMO scale. Table 1 summarizes the precision and accuracy for the four gases, though we were unable to measure H_2O traceability because we calibrated with dry tank air.

Table 1. Precision and accuracy for N₂O, CO₂, CO, and H₂O.

	N ₂ O (ppb)	CO ₂ (ppm)	CO (ppb)	H ₂ O (ppm)
1σ Precision	0.05	0.10	1.00	10
Accuracy (median offset)	0.17	0.08	0.29	NA
Accuracy (1 σ check gas)	0.14	0.34	2.33	NA




Figure 8. Top row: the last 5 s of each check gas period, black horizontal line indicating the value of the sampled gas traced to the WMO scale. Vertical lines separate the individual research flights. Bottom row: histograms of difference between known check gas value and last 5 s of measured check gas value, with solid grey lines indicating median and dashed lines showing 1σ uncertainty.

5 Applications

5 Continuous airborne N₂O observations can be useful for quantifying fluxes and estimating emissions on a facility-to-regional scale. Mass balances techniques, which have been utilized to estimate emissions of other atmospheric gases as in Karion et al. (2013), Smith et al. (2015), Peischl et al. (2015), and Kort et al. (2016), could similarly be applied for N₂O. Figure 9 shows the path flown during a research flight on May 6, 2017, with measured N₂O mole fraction in color, white arrows indicating wind direction and speed, and blue and black arrows showing the direction of the flight route and the upwind and





5

downwind transects. The bottom right panel of the figure shows N_2O from this flight as a function of latitude with the upwind and downwind transects in blue and black, while the top right panel shows the difference in N_2O between the downwind and upwind at each latitude. There is a distinct enhancement in the downwind transect relative to the upwind transect in the lower latitudes, from about 31.5° N to 32° N. This enhancement disappears at higher latitudes and the N_2O measurement tracks well between upwind and downwind transects, even with a substantial latitudinal gradient. This flight illustrates the ability of this instrument to accurately measure small variations and link to local emissions (to the south) or larger scale gradients (to the north). Future analyses of this data can involve mass balance flux quantification and/or regional model comparisons, both to

quantify emissions and link to driving factors such as soil moisture or crop type. As a fast-response sensor, FCHAOS can also be used for point source quantifications, as first explained in Conley et al.

(2017) and further analyzed in Mehrotra et al. (2017) and Vaughn et al. (2017). During FEAST, we circled several fertilizer plants with significant N₂O emissions, and future analyses can leverage these observations to better quantify emissions from the large point sources.




Figure 9. Left panel: flight path with N_2O signal and wind direction (white arrows). Blue and black arrows show the direction of the planes route and indicate upwind and downwind transects. Bottom right panel: N_2O signal as a function of latitude with upwind and downwind transects colored by blue and black, respectively. Top right panel: Difference in N_2O between downwind and upwind transects as a function of latitude.

6 Conclusions

We present a continuous-wave, mid-IR laser spectrometer system that can measure continuous 1 Hz airborne mole fractions
of N₂O, CO₂, CO, and H₂O. The commercial analyzer, when operated off-the-shelf, exhibits a dependence of N₂O, CO₂, and CO on cabin pressure. We correct for this artifact by employing a new calibration procedure with mass flow control at a high flow rate enabling high-frequency, short-duration calibrations. While modern systems conventionally use pressure control and





5

infrequent, long-duration zeros, our method expands on these previous approaches and opens up uses for the instrument in ways that have not yet been realized. We solve the inability of other systems to operate with large changes in cabin pressure by mitigating the cabin pressure effect while maintaining a ~90% duty cycle. In-flight 1 σ precisions are estimated to be ±0.05 ppb, ±0.10 ppm, ±1.00 ppb, and ±10 ppm for N₂O, CO₂, CO, and H₂O, with traceability to WMO observations estimated at 0.14 ppb, 0.34 ppm, and 2.33 ppb for N₂O, CO₂, and CO. We then validate our method by comparing FCHAOS data to CO₂ and H₂O measurements from a flight-proven cavity ring-down spectrometer, seeing excellent agreement. This flight-proven system can provide key insights into N₂O emissions processes by providing observational support for facility-quantification, for mass-balance flux estimates, and for inverse modeling. As presented, this system can be utilized for precise, accurate, continuous 1 Hz airborne observations of N₂O, CO₂, CO, and H₂O.

10 *Data availability.* Data collected as part of the FEAST campaign are presently available upon request. Upon manuscript acceptance data will be published in the University of Michigan's Deep Blue archive.

Competing interests. The authors declare they have no competing interests.

Acknowledgements. We thank Scientific Aviation pilots for their efforts in helping collect this data and Aerodyne Research Inc. for useful discussions. This material is based partly upon work supported by the National Science Foundation under Grant No. 1650682.





References

- Bouwman, A. F., Boumans, L. J. M., and Batjes, N. H.: Emissions of N2O and NO from fertilized fields: Summary of available measurement data, Global Biogeochemical Cycles, 16, 6–1–6–13, https://doi.org/10.1029/2001GB001811, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2001GB001811, 2002.
- 5 Brown, L., Armstrong Brown, S., Jarvis, S. C., Syed, B., Goulding, K. W. T., Phillips, V. R., Sneath, R. W., and Pain, B. F.: An inventory of nitrous oxide emissions from agriculture in the UK using the IPCC methodology: emission estimate, uncertainty and sensitivity analysis, Atmospheric Environment, 35, 1439–1449, https://doi.org/10.1016/S1352-2310(00)00361-7, 2001.
 - Chadwick, D., Cardenas, L., Misselbrook, T., Smith, K., Rees, R., Watson, C., McGeough, K., Williams, J., Cloy, J., Thorman, R., et al.: Optimizing chamber methods for measuring nitrous oxide emissions from plot-based agricultural experiments, European Journal of Soil
- 10 Science, 65, 295–307, 2014.

30

- Chen, H., Winderlich, J., Gerbig, C., Hoefer, A., Rella, C. W., Crosson, E. R., Van Pelt, A. D., Steinbach, J., Kolle, O., Beck, V., Daube, B. C., Gottlieb, E. W., Chow, V. Y., Santoni, G. W., and Wofsy, S. C.: High-accuracy continuous airborne measurements of greenhouse gases (CO₂ and CH₄) using the cavity ring-down spectroscopy (CRDS) technique, Atmospheric Measurement Techniques, 3, 375–386, https://doi.org/10.5194/amt-3-375-2010, https://www.atmos-meas-tech.net/3/375/2010/, 2010.
- 15 Chen, Z., Griffis, T. J., Millet, D. B., Wood, J. D., Lee, X., Baker, J. M., Xiao, K., Turner, P. A., Chen, M., Zobitz, J., and Wells, K. C.: Partitioning N2O emissions within the U.S. Corn Belt using an inverse modeling approach, Global Biogeochemical Cycles, 30, 1192– 1205, https://doi.org/10.1002/2015GB005313, http://dx.doi.org/10.1002/2015GB005313, 2015GB005313, 2016.
 - Ciais, P., Chris, S., Govindasamy, B., Bopp, L., Brovkin, V., Canadell, J., Chhabra, A., Defries, R., Galloway, J., and Heimann, M.: Carbon and other biogeochemical cycles, pp. 465–570, Cambridge University Press, 2013.
- 20 Conley, S., Faloona, I., Mehrotra, S., Suard, M., Lenschow, D. H., Sweeney, C., Herndon, S., Schwietzke, S., Pétron, G., Pifer, J., Kort, E. A., and Schnell, R.: Application of Gauss's theorem to quantify localized surface emissions from airborne measurements of wind and trace gases, Atmospheric Measurement Techniques, 10, 3345–3358, https://doi.org/10.5194/amt-10-3345-2017, https://www.atmos-meas-tech. net/10/3345/2017/, 2017.

Conley, S. A., Faloona, I. C., Lenschow, D. H., Karion, A., and Sweeney, C.: A Low-Cost System for Measuring Horizontal Winds from

- 25 Single-Engine Aircraft, Journal of Atmospheric and Oceanic Technology, 31, 1312–1320, https://doi.org/10.1175/JTECH-D-13-00143.1, https://doi.org/10.1175/JTECH-D-13-00143.1, 2014.
 - Crosson, E.: A cavity ring-down analyzer for measuring atmospheric levels of methane, carbon dioxide, and water vapor, Applied Physics B, 92, 403–408, https://doi.org/10.1007/s00340-008-3135-y, https://doi.org/10.1007/s00340-008-3135-y, 2008.

Dalal, R. C., Wang, W., Robertson, G. P., and Parton, W. J.: Nitrous oxide emission from Australian agricultural lands and mitigation options: a review, Australian Journal of Soil Research, 41, 165, https://doi.org/10.1071/sr02064, https://doi.org/10.1071/sr02064, 2003.

- Davidson, E. A. and Kanter, D.: Inventories and scenarios of nitrous oxide emissions, Environmental Research Letters, 9, 105012, http: //stacks.iop.org/1748-9326/9/i=10/a=105012, 2014.
 - Del Grosso, S., J Parton, W., Mosier, A., K Walsh, M., S Ojima, D., and E Thornton, P.: DAYCENT National-Scale Simulations of Nitrous Oxide Emissions from Cropped Soils in the United States, Journal of Environmental Quality, 35, 1451–60, 2006.
- Denmead, O.: Approaches to measuring fluxes of methane and nitrous oxide between landscapes and the atmosphere, vol. 309, 2008.
 Dlugokencky, E. J., Myers, R. C., Lang, P. M., Masarie, K. A., Crotwell, A. M., Thoning, K. W., Hall, B. D., Elkins, J. W., and Steele,
 L. P.: Conversion of NOAA atmospheric dry air CH4 mole fractions to a gravimetrically prepared standard scale, Journal of Geo-





physical Research: Atmospheres, 110, https://doi.org/10.1029/2005JD006035, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2005JD006035, 2005.

- Erisman, J., Sutton, M., Galloway, J., Klimont, Z., and Winiwarter, W.: How a century of ammonia synthesis changed the world, Nature Geoscience, 1, 636–639, https://doi.org/10.1038/ngeo325, http://pure.iiasa.ac.at/id/eprint/8475/, 2008.
- 5 Filges, A., Gerbig, C., Chen, H., Franke, H., Klaus, C., and Jordan, A.: The IAGOS-core greenhouse gas package: a measurement system for continuous airborne observations of CO2, CH4, H2O and CO, Tellus B: Chemical and Physical Meteorology, 67, 27989, https://doi.org/10.3402/tellusb.v67.27989, https://doi.org/10.3402/tellusb.v67.27989, 2015.
 - Flechard, C., Ambus, P., Skiba, U., Rees, R., Hensen, A., van Amstel, A., van den Pol-van Dasselaar, A., Soussana, J.-F., Jones, M., Clifton-Brown, J., Raschi, A., Horvath, L., Neftel, A., Jocher, M., Ammann, C., Leifeld, J., Fuhrer, J., Calanca, P., Thalman, E., Pilegaard, K.,
- Marco, C. D., Campbell, C., Nemitz, E., Hargreaves, K., Levy, P., Ball, B., Jones, S., van de Bulk, W., Groot, T., Blom, M., Domingues, R., Kasper, G., Allard, V., Ceschia, E., Cellier, P., Laville, P., Henault, C., Bizouard, F., Abdalla, M., Williams, M., Baronti, S., Berretti, F., and Grosz, B.: Effects of climate and management intensity on nitrous oxide emissions in grassland systems across Europe, Agriculture, Ecosystems & Environment, 121, 135 152, https://doi.org/https://doi.org/10.1016/j.agee.2006.12.024, http://www.sciencedirect.com/science/article/pii/S0167880906004385, the Greenhouse Gas Balance of Grasslands in Europe, 2007.
- 15 Frankenberg, C., Kulawik, S. S., Wofsy, S. C., Chevallier, F., Daube, B., Kort, E. A., O'Dell, C., Olsen, E. T., and Osterman, G.: Using airborne HIAPER Pole-to-Pole Observations (HIPPO) to evaluate model and remote sensing estimates of atmospheric carbon dioxide, Atmospheric Chemistry and Physics, 16, 7867–7878, http://proxy.lib.umich.edu/login?url=https://search-proquest-com.proxy.lib.umich. edu/docview/1803050742?accountid=14667, copyright - Copyright Copernicus GmbH 2016; Last updated - 2018-01-23, 2016.
- Fried, A., Diskin, G., Weibring, P., Richter, D., Walega, J., Sachse, G., Slate, T., Rana, M., and Podolske, J.: Tunable infrared laser instruments
 for airborne atmospheric studies, Applied Physics B, 92, 409–417, https://doi.org/10.1007/s00340-008-3136-x, https://doi.org/10.1007/s00340-008-3136-x, 2008.
 - Griffis, T. J., Chen, Z., Baker, J. M., Wood, J. D., Millet, D. B., Lee, X., Venterea, R. T., and Turner, P. A.: Nitrous oxide emissions are enhanced in a warmer and wetter world, Proceedings of the National Academy of Sciences, 114, 12081–12085, https://doi.org/10.1073/pnas.1704552114, http://www.pnas.org/content/114/45/12081, 2017.
- 25 Hall, B. D., Dutton, G. S., and Elkins, J. W.: The NOAA nitrous oxide standard scale for atmospheric observations, Journal of Geophysical Research: Atmospheres, 112, https://doi.org/10.1029/2006JD007954, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/ 2006JD007954, 2007.
 - Inoue, M., Morino, I., Uchino, O., Nakatsuru, T., Yoshida, Y., Yokota, T., Wunch, D., Wennberg, P. O., Roehl, C. M., Griffith, D. W. T., Velazco, V. A., Deutscher, N. M., Warneke, T., Notholt, J., Robinson, J., Sherlock, V., Hase, F., Blumenstock, T., Rettinger, M., Sussmann,
- 30 R., Kyrö, E., Kivi, R., Shiomi, K., Kawakami, S., De Mazière, M., Arnold, S. G., Feist, D. G., Barrow, E. A., Barney, J., Dubey, M., Schneider, M., Iraci, L. T., Podolske, J. R., Hillyard, P. W., Machida, T., Sawa, Y., Tsuboi, K., Matsueda, H., Sweeney, C., Tans, P. P., Andrews, A. E., Biraud, S. C., Fukuyama, Y., Pittman, J. V., Kort, E. A., and Tanaka, T.: Bias corrections of GOSAT SWIR XCO₂ and XCH₄ with TCCON data and their evaluation using aircraft measurement data, Atmospheric Measurement Techniques, 9, 3491–3512, https://doi.org/10.5194/amt-9-3491-2016, https://www.atmos-meas-tech.net/9/3491/2016/, 2016.
- 35 Karion, A., Sweeney, C., Wolter, S., Newberger, T., Chen, H., Andrews, A., Kofler, J., Neff, D., and Tans, P.: Long-term greenhouse gas measurements from aircraft, Atmospheric Measurement Techniques, 6, 511–526, https://doi.org/10.5194/amt-6-511-2013, https://www. atmos-meas-tech.net/6/511/2013/, 2013.





- Karion, A., Sweeney, C., Kort, E. A., Shepson, P. B., Brewer, A., Cambaliza, M., Conley, S. A., Davis, K., Deng, A., Hardesty, M., Herndon, S. C., Lauvaux, T., Lavoie, T., Lyon, D., Newberger, T., Pétron, G., Rella, C., Smith, M., Wolter, S., Yacovitch, T. I., and Tans, P.: Aircraft-Based Estimate of Total Methane Emissions from the Barnett Shale Region, Environmental Science & Technology, 49, 8124–8131, https://doi.org/10.1021/acs.est.5b00217, https://doi.org/10.1021/acs.est.5b00217, pMID: 26148550, 2015.
- 5 Kort, E. A., Eluszkiewicz, J., Stephens, B. B., Miller, J. B., Gerbig, C., Nehrkorn, T., Daube, B. C., Kaplan, J. O., Houweling, S., and Wofsy, S. C.: Emissions of CH4 and N2O over the United States and Canada based on a receptor-oriented modeling framework and COBRA-NA atmospheric observations, Geophysical Research Letters, 35, https://doi.org/10.1029/2008GL034031, https://agupubs.onlinelibrary.wiley. com/doi/abs/10.1029/2008GL034031, 2008.
 - Kort, E. A., Patra, P. K., Ishijima, K., Daube, B. C., Jiménez, R., Elkin, J., Hurst, D., Moore, F. L., Sweeney, C., and Wofsy,
- S. C.: Tropospheric distribution and variability of N2O: Evidence for strong tropical emissions, Geophysical Research Letters, 38, https://doi.org/10.1029/2011GL047612, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2011GL047612, 2011.
 - Kort, E. A., Smith, M. L., Murray, L. T., Gvakharia, A., Brandt, A. R., Peischl, J., Ryerson, T. B., Sweeney, C., and Travis, K.: Fugitive emissions from the Bakken shale illustrate role of shale production in global ethane shift, Geophysical Research Letters, 43, 4617–4623, https://doi.org/10.1002/2016GL068703, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1002/2016GL068703, 2016.
- 15 Lebegue, B., Schmidt, M., Ramonet, M., Wastine, B., Yver Kwok, C., Laurent, O., Belviso, S., Guemri, A., Philippon, C., Smith, J., et al.: Comparison of nitrous oxide (N 2 O) analyzers for high-precision measurements of atmospheric mole fractions, Atmospheric Measurement Techniques, 9, 1221–1238, 2016.
- Marinho, E. V. A., DeLaune, R. D., and Lindau, C. W.: Nitrous Oxide Flux from Soybeans Grown on Mississippi Alluvial Soil, Communications in Soil Science and Plant Analysis, 35, 1–8, https://doi.org/10.1081/CSS-120027630, https://doi.org/10.1081/CSS-120027630, 2004.
 - McManus, J. B., Kebabian, P. L., and Zahniser, M. S.: Astigmatic mirror multipass absorption cells for long-path-length spectroscopy, Appl. Opt., 34, 3336–3348, https://doi.org/10.1364/AO.34.003336, http://ao.osa.org/abstract.cfm?URI=ao-34-18-3336, 1995.

Mehrotra, S., Faloona, I., Suard, M., Conley, S., and Fischer, M. L.: Airborne Methane Emission Measurements for Selected Oil and Gas Facilities Across California, Environ. Sci. Technol., 51, 12981–12987, 2017.

- 25 Miller, S. M., Kort, E. A., Hirsch, A. I., Dlugokencky, E. J., Andrews, A. E., Xu, X., Tian, H., Nehrkorn, T., Eluszkiewicz, J., Michalak, A. M., and Wofsy, S. C.: Regional sources of nitrous oxide over the United States: Seasonal variation and spatial distribution, Journal of Geophysical Research: Atmospheres, 117, https://doi.org/10.1029/2011JD016951, https://agupubs.onlinelibrary.wiley.com/doi/abs/10. 1029/2011JD016951, 2012.
 - Monni, S., Perälä, P., and Regina, K.: Uncertainty in Agricultural CH4 AND N2O Emissions from Finland Possibilities to Increase
- 30 Accuracy in Emission Estimates, Mitigation and Adaptation Strategies for Global Change, 12, 545–571, https://doi.org/10.1007/s11027-006-4584-4, https://doi.org/10.1007/s11027-006-4584-4, 2007.
 - Myhre, G., Shindell, D., Bréon, F.-M., Collins, W., Fuglestvedt, J., Huang, J., Koch, D., Lamarque, J.-F., Lee, D., Mendoza, B., Nakajima, T., Robock, A., Stephens, G., Takemura, T., and Zhang, H.: Anthropogenic and natural radiative forcing, in: Climate Change 2013: The Physical Science Basis. Contribution of Working Group I to the Fifth Assessment Report of the Intergovernmental Panel on Climate
- 35 Change, edited by Stocker, T. F., Qin, D., Plattner, G.-K., Tignor, M., Allen, S. K., Doschung, J., Nauels, A., Xia, Y., Bex, V., and Midgley, P. M., pp. 659–740, Cambridge University Press, Cambridge, UK, https://doi.org/10.1017/CBO9781107415324.018, 2013.





Nelson, D., Shorter, J., McManus, J., and Zahniser, M.: Sub-part-per-billion detection of nitric oxide in air using a thermoelectrically cooled mid-infrared quantum cascade laser spectrometer, Applied Physics B, 75, 343–350, https://doi.org/10.1007/s00340-002-0979-4, https: //doi.org/10.1007/s00340-002-0979-4, 2002.

Nelson, D. D., McManus, B., Urbanski, S., Herndon, S., and Zahniser, M. S.: High precision measurements of atmospheric nitrous oxide and

- 5 methane using thermoelectrically cooled mid-infrared quantum cascade lasers and detectors, Spectrochimica Acta Part A: Molecular and Bioctroscopy, 60, 3325 – 3335, https://doi.org/https://doi.org/10.1016/j.saa.2004.01.033, http://www.sciencedirect.com/science/article/pii/ S138614250400109X, 2004.
 - Nevison, C., Andrews, A., Thoning, K., Dlugokencky, E., Sweeney, C., Miller, S., Saikawa, E., Benmergui, J., Fischer, M., Mountain, M., and Nehrkorn, T.: Nitrous Oxide Emissions Estimated With the CarbonTracker-Lagrange North American Regional Inversion Framework,
- 10 Global Biogeochemical Cycles, 32, 463–485, https://doi.org/10.1002/2017GB005759, https://agupubs.onlinelibrary.wiley.com/doi/abs/ 10.1002/2017GB005759, 2018.
 - Novelli, P. C., Masarie, K. A., Lang, P. M., Hall, B. D., Myers, R. C., and Elkins, J. W.: Reanalysis of tropospheric CO trends: Effects of the 1997-1998 wildfires, Journal of Geophysical Research (Atmospheres), 108, 4464, https://doi.org/10.1029/2002JD003031, 2003.
- O'Shea, S. J., Bauguitte, S. J.-B., Gallagher, M. W., Lowry, D., and Percival, C. J.: Development of a cavity-enhanced absorption spectrometer
 for airborne measurements of CH₄ and CO₂, Atmospheric Measurement Techniques, 6, 1095–1109, https://doi.org/10.5194/amt-6-1095-2013, https://www.atmos-meas-tech.net/6/1095/2013/, 2013.
 - O'Shea, S. J., Allen, G., Gallagher, M. W., Bower, K., Illingworth, S. M., Muller, J. B. A., Jones, B. T., Percival, C. J., Bauguitte, S. J.-B., Cain, M., Warwick, N., Quiquet, A., Skiba, U., Drewer, J., Dinsmore, K., Nisbet, E. G., Lowry, D., Fisher, R. E., France, J. L., Aurela, M., Lohila, A., Hayman, G., George, C., Clark, D. B., Manning, A. J., Friend, A. D., and Pyle, J.: Methane and carbon dioxide fluxes and their
- 20 regional scalability for the European Arctic wetlands during the MAMM project in summer 2012, Atmospheric Chemistry and Physics, 14, 13 159–13 174, https://doi.org/10.5194/acp-14-13159-2014, https://www.atmos-chem-phys.net/14/13159/2014/, 2014.
 - Pattey, E., Edwards, G., Desjardins, R., Pennock, D., Smith, W., Grant, B., and MacPherson, J.: Tools for quantifying N2O emissions from agroecosystems, Agricultural and Forest Meteorology, 142, 103 – 119, https://doi.org/https://doi.org/10.1016/j.agrformet.2006.05.013, http://www.sciencedirect.com/science/article/pii/S0168192306002899, the Contribution of Agriculture to the State of Climate, 2007.
- 25 Peischl, J., Ryerson, T. B., Aikin, K. C., Gouw, J. A., Gilman, J. B., Holloway, J. S., Lerner, B. M., Nadkarni, R., Neuman, J. A., Nowak, J. B., Trainer, M., Warneke, C., and Parrish, D. D.: Quantifying atmospheric methane emissions from the Haynesville, Fayetteville, and northeastern Marcellus shale gas production regions, Journal of Geophysical Research: Atmospheres, 120, 2119–2139, https://doi.org/10.1002/2014JD022697, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1002/2014JD022697, 2015.
- Pennock, D., Farrell, R., Desjardins, R., Pattey, E., and MacPherson, J. I.: Upscaling chamber-based measurements of N2O emissions at snowmelt, Canadian Journal of Soil Science, 85, 113–125, https://doi.org/10.4141/S04-040, https://doi.org/10.4141/S04-040, 2005.
- Pitt, J. R., Le Breton, M., Allen, G., Percival, C. J., Gallagher, M. W., Bauguitte, S. J.-B., O'Shea, S. J., Muller, J. B. A., Zahniser, M. S., Pyle, J., and Palmer, P. I.: The development and evaluation of airborne in situ N₂O and CH₄ sampling using a quantum cascade laser absorption spectrometer (QCLAS), Atmospheric Measurement Techniques, 9, 63–77, https://doi.org/10.5194/amt-9-63-2016, https://www.atmos-meas-tech.net/9/63/2016/, 2016.
- 35 Rannik, U., Haapanala, S., Shurpali, N. J., Mammarella, I., Lind, S., Hyvonen, N., Peltola, O., Zahniser, M., Martikainen, P. J., and Vesala, T.: Intercomparison of fast response commercial gas analysers for nitrous oxide flux measurements under field conditions, Biogeosciences, 12, 415–432, https://doi.org/10.5194/bg-12-415-2015, https://www.biogeosciences.net/12/415/2015/, 2015.





Rapson, T. D. and Dacres, H.: Analytical techniques for measuring nitrous oxide, TrAC Trends in Analytical Chemistry, 54, 65 – 74, https://doi.org/https://doi.org/10.1016/j.trac.2013.11.004, http://www.sciencedirect.com/science/article/pii/S0165993613002574, 2014.

Ravishankara, A. R., Daniel, J. S., and Portmann, R. W.: Nitrous Oxide (N2O): The Dominant Ozone-Depleting Substance Emitted in the 21st Century, Science, 326, 123–125, https://doi.org/10.1126/science.1176985, http://science.sciencemag.org/content/326/5949/123, 2009.

- 5 Rothman, L. S., Gordon, I. E., Babikov, Y., Barbe, A., Chris Benner, D., Bernath, P. F., Birk, M., Bizzocchi, L., Boudon, V., Brown, L. R., Campargue, A., Chance, K., Cohen, E. A., Coudert, L. H., Devi, V. M., Drouin, B. J., Fayt, A., Flaud, J.-M., Gamache, R. R., Harrison, J. J., Hartmann, J.-M., Hill, C., Hodges, J. T., Jacquemart, D., Jolly, A., Lamouroux, J., Le Roy, R. J., Li, G., Long, D. A., Lyulin, O. M., Mackie, C. J., Massie, S. T., Mikhailenko, S., Müller, H. S. P., Naumenko, O. V., Nikitin, A. V., Orphal, J., Perevalov, V., Perrin, A., Polovtseva, E. R., Richard, C., Smith, M. A. H., Starikova, E., Sung, K., Tashkun, S., Tennyson, J., Toon, G. C., Tyuterev, V. G., and
- 10 Wagner, G.: The HITRAN2012 molecular spectroscopic database, Journal of Quantitiative Spectroscopy and Radiative Transfer, 130, 4–50, https://doi.org/10.1016/j.jqsrt.2013.07.002, 2013.
 - Ruser, R., Flessa, H., Russow, R., Schmidt, G., Buegger, F., and Munch, J.: Emission of N2O, N2 and CO2 from soil fertilized with nitrate: effect of compaction, soil moisture and rewetting, Soil Biology and Biochemistry, 38, 263 – 274, https://doi.org/https://doi.org/10.1016/j.soilbio.2005.05.005, http://www.sciencedirect.com/science/article/pii/S0038071705001975,
- 15 2006.
- Santoni, G. W., Daube, B. C., Kort, E. A., Jiménez, R., Park, S., Pittman, J. V., Gottlieb, E., Xiang, B., Zahniser, M. S., Nelson, D. D., Mc-Manus, J. B., Peischl, J., Ryerson, T. B., Holloway, J. S., Andrews, A. E., Sweeney, C., Hall, B., Hintsa, E. J., Moore, F. L., Elkins, J. W., Hurst, D. F., Stephens, B. B., Bent, J., and Wofsy, S. C.: Evaluation of the airborne quantum cascade laser spectrometer (QCLS) measurements of the carbon and greenhouse gas suite CO₂, CH₄, N₂O, and CO during the CalNex and HIPPO campaigns, Atmospheric Mea-
- 20 surement Techniques, 7, 1509–1526, https://doi.org/10.5194/amt-7-1509-2014, https://www.atmos-meas-tech.net/7/1509/2014/, 2014.
 Smith, M. L., Kort, E. A., Karion, A., Sweeney, C., Herndon, S. C., and Yacovitch, T. I.: Airborne Ethane Observations in the Barnett Shale: Quantification of Ethane Flux and Attribution of Methane Emissions, Environmental Science & Technology, 49, 8158–8166, https://doi.org/10.1021/acs.est.5b00219, https://doi.org/10.1021/acs.est.5b00219, pMID: 26148554, 2015.
- Tanaka, T., Yates, E., Iraci, L. T., Johnson, M. S., Gore, W., Tadić, J. M., Loewenstein, M., Kuze, A., Frankenberg, C., Butz, A., and Yoshida,
- 25 Y.: Two-Year Comparison of Airborne Measurements of CO2 and CH4 With GOSAT at Railroad Valley, Nevada, IEEE Transactions on Geoscience and Remote Sensing, 54, 4367–4375, 2016.
 - Tans, P. P., Crotwell, A. M., and Thoning, K. W.: Abundances of isotopologues and calibration of CO₂ greenhouse gas measurements, Atmospheric Measurement Techniques, 10, 2669–2685, https://doi.org/10.5194/amt-10-2669-2017, https://www.atmos-meas-tech.net/10/ 2669/2017/, 2017.
- 30 Thompson, R. L., Chevallier, F., Crotwell, A. M., Dutton, G., Langenfelds, R. L., Prinn, R. G., Weiss, R. F., Tohjima, Y., Nakazawa, T., Krummel, P. B., Steele, L. P., Fraser, P., O'Doherty, S., Ishijima, K., and Aoki, S.: Nitrous oxide emissions 1999 to 2009 from a global atmospheric inversion, Atmospheric Chemistry and Physics, 14, 1801–1817, https://doi.org/10.5194/acp-14-1801-2014, https://www.atmos-chem-phys.net/14/1801/2014/, 2014.

Tian, H., Chen, G., Lu, C., Xu, X., Ren, W., Zhang, B., Banger, K., Tao, B., Pan, S., Liu, M., Zhang, C., Bruhwiler, L., and Wofsy, S.:

35 Global methane and nitrous oxide emissions from terrestrial ecosystems due to multiple environmental changes, Ecosystem Health and Sustainability, 1, 1–20, https://doi.org/10.1890/EHS14-0015.1, https://esajournals.onlinelibrary.wiley.com/doi/abs/10.1890/EHS14-0015. 1, 2015.





- Turner, D. A., Chen, D., Galbally, I. E., Leuning, R., Edis, R. B., Li, Y., Kelly, K., and Phillips, F.: Spatial variability of nitrous oxide emissions from an Australian irrigated dairy pasture, Plant and Soil, 309, 77-88, https://doi.org/10.1007/s11104-008-9639-8, https://doi. org/10.1007/s11104-008-9639-8, 2008.
- Vaughn, T. L., Bell, C. S., Yacovitch, T. I., Roscioli, J. R., Herndon, S. C., Conley, S., Schwietzke, S., Heath, G. A., Pétron, G., and
- 5 Zimmerle, D.: Comparing facility-level methane emission rate estimates at natural gas gathering and boosting stations, Elem Sci Anth, 5, 71, https://doi.org/10.1525/elementa.257, https://doi.org/10.1525/elementa.257, 2017.
 - WMO, W.: 18th WMO/IAEA Meeting on Carbon Dioxide, Other Greenhouse Gases and Related Tracers Measurement Techniques (GGMT-2015), GAW Report- No. 229, 2015.
 - Wofsy, S. C.: HIAPER Pole-to-Pole Observations (HIPPO): fine-grained, global-scale measurements of climatically important atmospheric
- 10 gases and aerosols, Philosophical Transactions of the Royal Society of London A: Mathematical, Physical and Engineering Sciences, 369, 2073-2086, https://doi.org/10.1098/rsta.2010.0313, http://rsta.royalsocietypublishing.org/content/369/1943/2073, 2011.
 - Xiang, B., Miller, S. M., Kort, E. A., Santoni, G. W., Daube, B. C., Commane, R., Angevine, W. M., Ryerson, T. B., Trainer, M. K., Andrews, A. E., Nehrkorn, T., Tian, H., and Wofsy, S. C.: Nitrous oxide (N2O) emissions from California based on 2010 CalNex airborne measurements, Journal of Geophysical Research: Atmospheres, 118, 2809-2820, https://doi.org/10.1002/jgrd.50189, https://doi.org/1 //agupubs.onlinelibrary.wiley.com/doi/abs/10.1002/jgrd.50189, 2013.
- Yacovitch, T. I., Herndon, S. C., Roscioli, J. R., Floerchinger, C., McGovern, R. M., Agnese, M., Pétron, G., Kofler, J., Sweeney, C., Karion, A., Conley, S. A., Kort, E. A., Nähle, L., Fischer, M., Hildebrandt, L., Koeth, J., McManus, J. B., Nelson, D. D., Zahniser, M. S., and Kolb, C. E.: Demonstration of an Ethane Spectrometer for Methane Source Identification, Environmental Science & Technology, 48, 8028-8034, https://doi.org/10.1021/es501475q, http://dx.doi.org/10.1021/es501475q, pMID: 24945706, 2014.
- Zhao, C. L. and Tans, P. P.: Estimating uncertainty of the WMO mole fraction scale for carbon dioxide in air, Journal of Geo-20 physical Research: Atmospheres, 111, https://doi.org/10.1029/2005JD006003, https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/ 2005JD006003, 2006.
 - Zhao, C. L., Tans, P. P., and Thoning, K. W.: A high precision manometric system for absolute calibrations of CO2 in dry air, Journal of Geophysical Research: Atmospheres, 102, 5885–5894, https://doi.org/10.1029/96JD03764, https://agupubs.onlinelibrary.wiley.com/doi/ abs/10.1029/96JD03764, 1997.

25

15