Atmos. Meas. Tech. Discuss., doi:10.5194/amt-2018-459-AC1, 2019 © Author(s) 2019. This work is distributed under the Creative Commons Attribution 4.0 License.



AMTD

Interactive comment

Interactive comment on "Simultaneous measurement of NO and NO₂ by dual-channel cavity ring down spectroscopy technique" by Renzhi Hu et al.

Renzhi Hu et al.

rzhu@aiofm.ac.cn

Received and published: 26 March 2019

Thanks for the reviewer's questions. The manuscript will be revised following the reviewer's suggestions.

1. Could authors provide more test data on-road measurements of vehicle NO2/NOx emissions? And if possible, the on-road intercomparsions will be meaningful for the validation of the method and instrument.

Reply: The intercomparsion between the CRDS instrument with NO analyzer for NO measurements and the intercomparsion between the CRDS instrument with CEAS

Printer-friendly version

Discussion paper



instrument for NO2 measurements have been done to valid the accuracy of the instrument in the paper, so we don't provide other data on road measurements of vehicle NO2/NOx emissions. Based on the reviewer's suggestions, we performed another measurement of vehicle emissions on road. NO analyzer (42i), O3 analyzer (49i) and the CRDS instruments were placed in a car and were powered by three batteries. Ambient air was pumped through an inlet fixed on the roof of the car and then was divided into three lines to the instruments, respectively. Fig. 1 illustrates the 4-hour drive around Hefei, the drive track involve highway, urban and suburban area and is colored with respect to the measured NO and NO2. Vehicle speeds varied greatly on the three different road types and vehicle speed is around 100km/h on highway. Influenced by the vehicle emissions, the NOx plumes on urban roads are higher than those on suburban roads and highway. Fig.2 shows the time series of NO2,NO and O3.O3 and NO showed a significant negative correlation and O3 can be titrated by NO quickly. Fig.3 shows the NO data measured by CRDS and CL analyzer (42i), (a) is the raw data for the CRDS instrument and (b) is the data with time resolution of is 1 min for the CRDS instrument. The good agreement between the two instruments proves that the CRDS instrument can be applied for fast vehicle NOx emissions.

It will be helpful if someone can review and make some corrections the English writing. page 1, line 23: "Too much NOx are" too much is how much? "are" to "is" page 2,line 55 "too much high"

Reply: Since the questions above are about the English expression and grammar mistakes, the revisions will be done in the final version.

page 15, table 1: it will be better to convert the detection limits of all different measurements to an unified unit such as "ppt/1s(1sigma)

Reply: The suggestion will be followed in the revised manuscript.

Interactive comment on Atmos. Meas. Tech. Discuss., doi:10.5194/amt-2018-459, 2019.

AMTD

Interactive comment

Printer-friendly version

Discussion paper



AMTD

Interactive comment




Fig.1.The 4-h drive around Hefei, China, colored by the measured NO (a) and $NO_2(b)$ concentrations, respectively.

Printer-friendly version

Discussion paper



Fig. 1.

AMTD

Interactive comment




Fig.2. Results of the NO₂ NO and O₃ concentrations around Hefei, China.

Printer-friendly version


Discussion paper



Fig. 2.

AMTD

Interactive comment



CRDS instrument; (b) is the data with time resolution of is 1 min for the CRDS instrument.

Printer-friendly version

Discussion paper



Fig. 3.