

We thank both reviewers for reading our manuscript so carefully and for their very useful comments which helped us improve the manuscript.

Please find below our point to point replies in blue as well the text changes we made to the manuscript marked in **bold**. The line numbers refer to the revised manuscript without track changes. A red-lined version of the manuscript is also attached after the replies.

Anonymous Referee #1

The paper presents the measurement of latent and sensible heat flux profiles in the convective boundary layer (CBL) derived from temperature, humidity and wind data from three co-located lidar systems. The profiles are derived from a 45 min time period in a well-developed CBL and show the expected shape demonstrating primarily the capability of the method. The paper fits in AMT's scope. The method and data are well described, the results are convincing and the text is very well written. I recommend the paper for publication in AMT with minor revisions.

We thank the reviewer for his/her positive general comment.

Minor revisions:

L95: From my own experience, I still believe the main challenge for PRR measurements is not the low cross section but the system stability in combination with a relatively weak temperature dependence of the ratio of the PRR signals. Hence, neither laser power nor detector efficiency is key for success, but system stability. I'd appreciate a comment on this.

We agree that these are also important points and added corresponding text.

Changes:

L96 "This was challenging because of the relatively low backscatter cross-section of the inelastic Raman backscatter processes **combined with low temperature sensitivity**. Key for the achievement were powerful ultraviolet lasers in combination with more efficient receiver designs. **Furthermore, the calibration function of TRRL systems must be stable which means that technical solutions had to be implemented so that neither the laser wavelength nor the optical properties of the receiver components vary.**"

L118: Please specify what type of calibration function has been used.

Happy to do, done.

Changes: L122 "**The second-order logarithmical function suggested by Behrendt and Reichart (2000) was used as calibration function.**"

L151: Please specify how many standard deviations were used in this study to flag outliers.

It is four. We have clarified this.

Changes: L157 “This means that histograms of the data in each height were calculated for the selected period and then all data outside of ~~several~~ **four** standard deviations from the median were removed.”

L159: This is not an interpolation but a fit to the data. Change wording.

The reviewer is right, changed

Changes: L165 “...are ~~linearly interpolated~~ **used** over the selected period to obtain mean **linear trends profiles**...”

L160: S* is a matrix rather than a profile. Change wording.

OK, done.

Changes: L165 “Trend profiles” changed to “trends”

L180: Why is N height dependent?

Because of the despiking routine which removes a few data points.

Changes: We added L185 “**N(z) is not the same for all heights z because the despiking routine removes a few data points.**”

L185: Since “error” is not further used in this sense here, I don’t see the need for this clarification in parenthesis. “Error” rather appears at several other locations in the text to refer to measurement error of both systematic and random nature (L78, L171, L310, L324, L591).

We agreed.

Changes: We deleted the two sentences in parenthesis, see L191.

L226: “The most...” this phrase is not clear and should be reworded.

We agree and rewrote this sentence,

Changes: L230 “The most suitable choice ~~of for the~~ **number of** lags is a factor of 2.5 larger than the integral time scale.”

L231 and L240: “uncertainty variance” is not a good term. It is rather uncertainty expressed as a variance.

We agree and changed the wording.

Changes: L235 “The representativeness uncertainty ~~variance~~ or sampling uncertainty **variance** of the flux **expressed as a variance** is...” and L244 “An upper limit ~~of the square~~ of the representativeness uncertainty **variance** can...”

L305: I would assume that all eddies contain energy and hence don’t understand why the authors refer to “energy-containing” eddies. Please comment.

Indeed, the reviewer is correct. We rewrote this sentence to explain better what we mean.

Changes: L309 "~~The integral scale is a measure of the typical energy containing eddy size in the temporal domain.~~ The integral scale is a measure of the mean horizontal size of the eddies in the temporal domain during the measurement period (see, e.g., Lenschow et al. 2000, for details)."

L329: adopt the terminology from section 3.3, i.e. "vertical divergence of ...".

Thanks! Clarified.

Changes: L333 "...for **the vertical divergence of the sensible heat flux divergence**"

Figures 1 and 2: Fonts of the axis labels are too small. Technical corrections:

Thanks. Changes: We increased the font sizes of the plots in Figs. 1 and 2.

L165: perfect instead of prefect.

Thanks, corrected (L170).

L227: is instead of it

Thanks, corrected (L231)

L291: add a comma after "buoyancy"

Thanks, corrected. (L295)

Anonymous Referee #3

This study presents one case study of measurement of sensible (H) and latent (L) heat flux profiles during the HOPE campaign, using a Raman lidar with a Doppler wind lidar (for H profiles) and a water-vapor differential absorption lidar with a Doppler wind lidar (for L profiles). The methodology is clearly presented and the study fits in the scope of AMT.

I recommend the paper for publication in AMT with minor revisions.

We thank the reviewer for his/her positive general comment.

Minor revision suggested:

Since this study presents the results from one case study only, I think this needs to be clarified in the manuscript, probably in the Abstract is OK.

OK, done.

Changes: L15 "The **case study uses a measurement example is** from the HOPE campaign-..."

Page 4, lines 98-99: "An overview of the instruments and methodology is given in Section 2. The results are presented and discussed in section 3. Finally, a summary and an outlook are given." I think there is something wrong here as the Methodology is not in Section 2, but in Section 3; the Results are presented in Section 4 and not in Section 3; the Summary is in Section 5.

Thanks! Corrected.

Changes: L101 and 102 “An overview of the instruments ~~and methodology~~ is given in Section 2. **The methodology is described in Section 3.** The results are presented and discussed in Section 4. Finally, a summary and an outlook are given.”

Page 5, Section 3. Do you also need a subsection for the Latent heat flux analysis?

Good point. Since the methodology for L is the same as for H we decided to add “latent heat flux” in the section title and added a few words explaining this.

Changes: Titel changed to “3.1 Sensible **and latent** heat flux analyses” (L153), sentence added (L154) “**In the following, we explain the method with the sensible heat flux as example; the measurement of the latent heat flux works in an analogous way.**”

Page 5, lines 130-131: You sometimes refer to the water-vapor differential absorption lidar as to WVDIAL (here for instance) and some other times as to DIAL. Please be consistent thorough the manuscript.

Thanks, corrected. Changes: Only “WVDIAL” used throughout the text.

Fig 5) The tick and thin error bars are difficult to differentiate, both on the screen and when printing out the page. Please find another way to present them.

Thanks for pointing this out. We changed it.

Changes: We now plot the thin error bars in pale colors in Fig 5. Same in Fig. 3 b for consistency.

Label of Fig. 5) "Sensible heat flux H and the latent heat flux L derived from the lidar data." I would clarify in the caption of the figure what combination of instrument was used to compute H and L profiles.

Good idea, done.

Changes: L607 “Sensible heat flux H and the latent heat flux L derived from the lidar data. **The temperature and vertical wind fluctuations for determining H were obtained from UV rotational Raman lidar and coherent Doppler lidar measurements, respectively. For L, humidity fluctuations measured with a water vapor DIAL were combined with vertical wind fluctuations measured with Doppler lidar...**”

Observation of sensible and latent heat flux profiles with lidar

Andreas Behrendt¹, Volker Wulfmeyer¹, Christoph Senff^{2,3}, Shravan Kumar Muppa^{1,4}, Florian Späth¹, Diego Lange¹, Norbert Kalthoff⁵, Andreas Wieser⁵

¹Institute of Physics and Meteorology, University of Hohenheim, Stuttgart, Germany

5 ²Cooperative Institute for Research in Environmental Sciences (CIRES), University of Colorado, Boulder, USA

³NOAA Earth System Research Laboratory/Chemical Sciences Division, Boulder, CO, USA

⁴now with University of Bayreuth, Bayreuth, Germany

⁵Institute of Meteorology and Climate Research, Karlsruhe Institute of Technology (KIT), Eggenstein-Leopoldshafen, Germany

10 *Correspondence to:* Andreas Behrendt (andreas.behrendt@uni-hohenheim.de)

Abstract. We present the first measurement of the sensible heat flux (H) profile in the convective boundary layer (CBL) derived from the covariance of collocated vertical-pointing temperature rotational Raman lidar and Doppler wind lidar measurements. The uncertainties of the H measurements due to instrumental noise and limited sampling are also derived and discussed. Simultaneous measurements of the latent heat flux profile (L) and other turbulent variables were obtained with the combination of water-vapor [differential absorption lidar \(WVDIAL\)](#) and Doppler lidar. The [case study uses a](#) measurement example ~~is~~ from the HOPE campaign, which took place in western Germany in 2013 and presents a cloud-free well-developed quasi-stationary CBL. The mean boundary layer height z_i was at 1230 m above ground level. The results show – as expected – positive values of H in the middle of the CBL. A maximum of (182 ± 32) W/m², with the second number for the noise uncertainty, is found at $0.5 z_i$. At about $0.7 z_i$, H changes sign to negative values above. The entrainment flux was (-62 ± 27) W/m². The mean sensible heat flux divergence in the observed part of the CBL above $0.3 z_i$ was -0.28 W/m³, which corresponds to a warming of 0.83 K/h. The L profile shows a slight positive mean flux divergence of 0.12 W/m³ and an entrainment flux of (214 ± 36) W/m². The combination of H and L profiles in combination with variance and other turbulent parameters is very valuable for the evaluation of large-eddy simulation (LES) results and the further improvement and validation of turbulence parameterization schemes.

25 1 Introduction

The energy reaching the earth surface in form of solar radiation during daytime is partly reflected as outgoing radiation, partly conducted into the ground, and partly transported into the atmosphere by turbulent eddies of various scales forming the convective boundary layer (CBL) during daytime (LeMone, 2002). The latter energy flux partitions into sensible heat flux H and latent heat flux L . The understanding of H and L profiles is decisive for correct atmospheric simulations with models since these profiles rule the heat and water budgets, the distribution of humidity and temperature, and thus the atmospheric stability and furthermore the formation of clouds and precipitation.

The variance of humidity and temperature at the CBL top determines clouds formation (Moeng and Sullivan 1994). Weckwerth et al. 1996 found strong variability in the moisture structure in the CBL due to the presence of horizontal convective rolls. The coherent perturbations of temperature and moisture in these rolls influence the formation of deep convection (Weckwerth et al. 1999). Also, surface flux partitioning is an important parameter for studying convection initiation (e.g., Gantner and Kalthoff 2010; Adler et al. 2011; Behrendt et al. 2011; Kalthoff et al. 2011) and land-atmosphere feedback (Santanello et al. 2018). Clearly, not only the mean structure of moisture in the CBL is important but also the variance profiles due to their contribution to the variance budget (Lenschow et al. 1980). At the same time, variations in the humidity structure also influence precipitation patterns (Dierer et al. 2009).

It is difficult to parameterize these sub-grid scale moisture variations in cloud, convection, and turbulence resolving models (Moeng and Sullivan 1994). Shallow cumulus parameterizations (e.g., Bretherton and Park 2009; Neggers et al. 2009; Berg et al. 2013) are used in mesoscale models which do not resolve the turbulent eddies to approximate their effects. These schemes are decisive for the correct simulation of clouds and precipitation. To verify these parametrizations in weather prediction models, not only monitoring of the mean CBL thermodynamic structure (e.g., Milovac et al. 2016), but also measurements of higher-order moments of turbulent fluctuations of the thermodynamic variables (like variances, skewness, kurtosis) and their covariances (like H and L) are highly desirable (e.g., Ayotte et al. 1996, Heinze et al. 2017). Preferably, these parameters should be collected continuously in time and simultaneously throughout the CBL.

It is clear that in situ-measurements performed from airborne platforms (e.g. Grunwald et al. 1996; Grunwald et al. 1998; Bange et al. 2002) can only sample the atmosphere stepwise. Recently unmanned aerial vehicle systems were used for the estimation of water vapor fluxes in the CBL (Thomas et al., 2012). However, in-situ measurements systems cannot obtain the total vertical profile simultaneously and continuously over longer measurement periods though it is very important to derive the flux divergence.

In recent years, it has been demonstrated that lidar, a laser remote sensing technique covering the CBL, is capable of not only determining mean profiles and gradients in the daytime CBL, the interfacial layer, and the lower free troposphere above but also higher-order-moment profiles of turbulent fluctuations. In recent year, this was demonstrated for more and more variables: vertical wind (e.g., Frehlich et al 1998; Lenschow et al. 2000; Lothon et al. 2006, 2009; Hogan et al. 2009; O'Connor et al. 2010, Lenschow et al. 2012), humidity (Kiemle et al 1997; Wulfmeyer et al. 1999a; Lenschow et al. 2000, Couvreux et al. 2005, 2007; Wulfmeyer et al. 2010; Turner et al. 2014a,b; Muppa et al. 2016; Di Girolamo et al., 2017), aerosol backscatter (Pal et al. 2010), and – most recently – also temperature (Behrendt et al. 2015, Di Girolamo et al., 2017). Consequently, large-eddy-simulation (LES) models can be evaluated with the synergy of temperature, humidity and wind lidar systems (Heinze et al. 2017) and new parametrizations can be developed (Wulfmeyer et al. 2016, Wulfmeyer et al. 2018).

First measurements of virtual heat flux with a remote sensing technique, were presented by Peters et al. (1985) by combining a sodar for vertical wind measurements and a radio acoustic sounding system (RASS) for virtual temperature measurements reaching heights up to 188 m above ground. With the combination of a radar wind profiler and a RASS, the range of virtual heat flux measurements could later be extended up to a few hundred meters (Angevine et al., 1993a) and comparisons with

aircraft measurements were made for the average of a 7-day period reaching up to $0.8 z_i$, with z_i being the CBL height (Angevine et al., 1993b). Since RASS measures the virtual temperature and not the physical temperature (Matuura et al. 1986), the measured virtual heat flux depends also on humidity fluctuations. For model comparisons, however, separate measurements of H and L are preferable.

70 First L measurements in the CBL with remote sensing techniques were achieved by Senff et al. (1994) with a combination of water vapor differential absorption lidar (WVDIAL) and RASS. Heights between 400 and 700 m above ground level (AGL) could be investigated. Wulfmeyer (1999b) used the same combination of techniques at a site located at the coast of the island Gotland, Sweden, reaching at that site with about the same range even heights beyond z_i . The first lidar-only flux measurements were made by Giez et al. (1999) by combining ~~water vapor~~ WVDIAL and Doppler lidar for L profiling. Because the range of
75 Doppler lidar is larger than the range of RASS, the authors extended with this approach the range of lidar L profiles to about 1300 m AGL. The same combination of lidar systems was also applied by Linne et al. (2007). Kiemle et al. (2007, 2011) operated the technique from an airborne platform over flat and complex terrain, respectively. The first water-vapor flux profiling using a Raman lidar and a Doppler lidar was demonstrated in Wulfmeyer et al. (2018) showing a good performance with respect to statistical errors.

80 While all the above mentioned measurements were made in the CBL - which means in daytime - Rao et al. (2002) presented nighttime water vapor Raman lidar measurements in combination with sodar measurements estimating L profiles in the nocturnal urban boundary layer under unstable conditions.

Lidar flux measurements of other trace gases than water vapor were discussed, e.g., by Senff et al. (1996) who combined an ozone DIAL and a RASS for measuring turbulent ozone fluxes, and by Gibert et al. (2011) who combined a CO_2 DIAL and
85 Doppler lidar for measuring turbulent CO_2 fluxes. Profiles of turbulent aerosol particle mass fluxes in the CBL were measured by Engelmann et al. (2008) with a combination of aerosol Raman lidar and Doppler lidar.

While there has been great progress for measuring all these different types of fluxes in the atmospheric boundary layer in recent years, profiles of H – highly desirable for model verification – were not available till date due to the lack of suitable remote sensing temperature measurements with high temporal and spatial resolution in the daytime CBL. In the following, we
90 will show that this gap has been closed with temperature rotational Raman lidar (TRRL). This technique (see, e.g., Behrendt 2005 for an overview) provides the physical temperature of the atmosphere independent of assumptions on the atmospheric state (like hydrostatic equilibrium) and other parameters like humidity or aerosol particle density. In contrast to the virtual heat flux measurements obtained with RASS, TRRL provides data of the heat flux and not the virtual heat flux the latter of which is entangled with L . In recent years, the TRRL technique achieved precise measurements not only at night but also in daytime
95 reaching heights up to the CBL top and above into the lower free troposphere (e.g., Radlach 2008, Hammann et al. 2015; Behrendt et al. 2015, Di Girolamo et al. 2017, Lange et al. 2019). This was challenging because of the relatively low backscatter cross-section of the inelastic Raman backscatter processes combined with low temperature sensitivity. Key for the achievement were powerful ultraviolet lasers in combination with more efficient receiver designs. Furthermore, the calibration function of

TRRL systems must be stable which means that technical solutions had to be implemented so that neither the laser wavelength nor the optical properties of the receiver components vary.

An overview of the instruments ~~and methodology~~ is given in Section 2. The methodology is described in Section 3. The results are presented and discussed in Section 3.4. Finally, a summary and an outlook are given.

2. Instruments

2.1 Temperature Rotational Raman Lidar

105 Rotational Raman lidar makes use of Raman signals of atmospheric molecules (mainly N₂ and O₂) of different temperature dependency (Cooney 1972, Behrendt 2005). From the ratio of the atmospheric backscatter signals, a measurement signal is obtained which depends on atmospheric temperature. The rotational Raman lidar of the University of Hohenheim was designed with the focus on high-resolution measurements during daytime (Radlach et al. 2008, Hammann et al. 2015, Hammann and Behrendt 2015). As laser transmitter, a frequency-tripled injection-seeded Nd:YAG laser is used which emits 200-mJ laser pulses at 355 nm with a repetition rate of 50 Hz. A Pellin-Broca prism refracts the other laser wavelengths out of the optical path, which makes the system eye-safe from short distances onward. The whole lidar is housed in a truck so that it can be moved easily to field campaigns. A two-mirror scanner allows for 3-dimensional observations. For the measurements discussed here, this scanner was pointing vertically. The backscatter signals of the atmosphere are collected with a telescope with a 40-cm primary mirror and then separated with interference filters into four channels: the elastic channel, two rotational Raman channels, and a water vapor Raman channel. The first three of these channels are mounted in a cascade, which makes the signal separation very efficient (Behrendt and Reichardt 2000, Behrendt et al. 2002, 2004). The water vapor Raman channel was not yet in operation for the measurements discussed here, but the beamsplitter for this channel was already in place. Photomultipliers collect the four signals and give electric signals, which are analysed with a combined photon-counting and analogue transient recorder (LICEL GmbH). A temporal resolution of 10 s and a range resolution of 3.75 m were selected for the raw data of all channels. For the temperature measurements, the two rotational Raman signals were first smoothed with a gliding average of 108.75 m, then the ratio of the signals was calculated. For the temperature calibration, data of a radiosonde launched at the lidar site were used. -The second-order logarithmical function suggested by Behrendt and Reichart (2000) was used as calibration function. Since the strong daytime photon-counting signals were influenced by deadtime effects in the ranges discussed in this study, we used only analogue signals.

125 2.2 Doppler Wind Lidar

Doppler lidar measures the radial wind velocity via the Doppler shift of laser radiation scattered in the atmosphere (e.g., Werner 2005). In this study, we used data of the heterodyne Doppler lidar Wind-Tracer WTX of Lockheed Martin Coherent

Technologies, USA, operated by the Karlsruhe Institute of Technology (KIT) (Träumner et al., 2014). The lidar transmitter is a Er:YAG laser that emits laser pulses at a wavelength of 1.6 μm using a pulse repetition frequency of 750 Hz with 2.7 mJ pulse energy. The lidar can be operated in different scan patterns. Vertical stare mode yields vertical velocity w with a time resolution of typically 1 s from about 375 m AGL to the top of the boundary layer and partly above, depending mainly on the aerosol concentration. The effective range-gate resolution was about 60 m.

2.3 Water Vapour Differential Absorption Lidar

In the following, we also introduce briefly the water-vapor differential absorption lidar (WVDIAL) of University of Hohenheim (UHOH) because we show for comparison latent heat flux profiles. WVDIAL provides absolute humidity profiles with high temporal and spatial resolution in the lower troposphere (Wulfmeyer and Bösenberg 1998). During the HOPE campaign (Macke et al. 2017), the scanning water vapour WVDIAL of University of Hohenheim (Wagner et al. 2013) was operated in vertical mode during clear sky conditions and in scanning mode during cloudy periods (Späth et al. 2016). The operational wavelength of the UHOH WVDIAL is near 818 nm. The laser transmitter was switched shot by shot between the online and offline frequencies. The backscatter signals were recorded for each laser shot (250 Hz) with a range resolution of 15 m. The measured absolute humidity has typical temporal and spatial resolutions of 1 s to 1 min and 15 m to 300 m, respectively, depending on the range of interest. Due to the instrument's high laser power (about 2 W) in combination with a very efficient receiver (0.8 m telescope), the data have low noise uncertainties up to the CBL top. When deriving absolute humidity from the UHOH WVDIAL data used in this study, 10 s averages and a gliding window length of 135 m for the Savitzky-Golay algorithm (Savitzky and Golay, 1964) were used resulting in a triangular weighting function with a full width at half maximum of about 60 m.

3 Methodology

3.1 Sensible and latent heat flux analyses

Lenschow et al. (2000) introduced a procedure for the estimation of higher-order moments of turbulent fluctuations that accounts for random instrumental noise. We follow this method for resolving the turbulent moments of temperature, vertical wind, and humidity for estimating instrument noise uncertainties. Further, important refinements were presented in Wulfmeyer et al. (2016) such as automated spike detection and the proper choice of lags used in the autocovariance analyses.

The flux profiles in the CBL were calculated using the eddy covariance method (see, e.g., Senff et al. 1994, Wulfmeyer 1999b). The data processing procedure is described in detail in Wulfmeyer et al. (2016). In the following, we explain the method with the sensible heat flux as example; the measurement of the latent heat flux works in an analogous way. First, temperature and wind data measured by the TRRL and Doppler lidar, respectively, were despiked. This means that histograms of the data in

each height were calculated for the selected period and then all data outside of ~~several~~four standard deviations from the median were removed. Other authors (Turner et al. 2014a,b) refined the despiking of noisy lidar data by considering also non-Gaussian distributions and asymmetric despiking thresholds on either side of the histogram, but we found that for the case shown here such further refinements do not change the results significantly. A despiking procedure is required because the lidar data analysis algorithms are non-linear and noise in the data may result in large (non-linear) outliers in some cases.

In a second step, the despiked temperature data were detrended using a linear fit at each height level. This procedure is required in order to focus on the turbulent fluctuations by removing influences of large-scale advection, synoptic processes, and the diurnal cycle. Detrending means that the time series of the scalar observations $s(z,t)$ with s being, e.g., temperature T or humidity q , z being height above ground, and t being time, are ~~linearly interpolated~~used over the selected period to obtain mean linear trends ~~profiles~~ $s^*(z,t)$ and that these trends were then subtracted from the instantaneous values $s(z,t)$ at each height to obtain the fluctuations

$$s'(z,t) = s(z,t) - s^*(z,t). \quad (1)$$

Consequently, the mean of these fluctuations becomes zero.

In case of the wind data $w(z,t)$, we decided to subtract only time-independent means in each height level of the vertical wind data in order to ensure fluctuations with ~~perfect~~perfect zero mean. Detrending alters the real atmospheric fluctuations quite significantly when the updrafts and downdrafts are not perfectly evenly distributed in the analysis period (which is in practice never the case due to the statistical nature of the thermals in the CBL).

In practice, both despiking and detrending has to be performed with caution in order not to eliminate real atmospheric features. This means that the time series of data should be investigated first and only quasi-stationary time series with small trends in the scalar (T or q), small biases in w , and a sufficient number of thermals are well suitable for the derivation of fluxes with low systematic errors. Typically, the time period for the analysis thus need to be at least 30 minutes.

Before the scalar and wind time series can be combined, one must ensure in a third step that the time and height for each data point are as close as possible. For this, we gridded the data to closest neighbours.

The correlation of the temperature fluctuations T' and the vertical wind fluctuations w' provides profiles of the eddy sensible heat flux according to

$$H(z) = \rho_a(z) c_p \overline{w'(z) T'(z)}, \quad (2)$$

with $\rho_a(z)$ for the air density at height z and c_p for the specific heat capacity of air.

For the lidar data, which are discrete in time, equation 2 results in

$$H(z) = \frac{\rho_a(z) c_p}{N(z)} \sum_{i=1}^{N(z)} w'_i(z) T'_i(z), \quad (3)$$

where i is the number of each data point and $N(z)$ is the total number of common data points in height z of T' and w' . $N(z)$ is not the same for all heights z because the despiking routine removes a few data points.

3.2 Uncertainties due to noise and representativeness

190 The instrumental noise uncertainty and the representativeness uncertainty play a major role when deriving the statistics of turbulent fluctuations in the atmosphere with noisy data (Lenschow et al. 1994; 2000). The noise uncertainty is due to the instrumental noise of the lidar data. The uncertainty due to sampling only a limited period of time covering a limited number of turbulent eddies is referred to as representativeness uncertainty or sampling uncertainty. ~~(We prefer the term “uncertainty” over “error” to stress that the results vary in a statistical sense; we prefer to use error for the difference of the measured value to the true value, which is unknown.)~~

195 Fortunately, when $H(z)$ is calculated with the lidar data with equation 3, the noise contributions of the vertical wind and temperature fluctuations, $w'_{i,n}(z)$ and $T'_{i,n}(z)$, do not cause a bias in the covariance and – unlike for the variances – no subtraction of an instrumental noise term is required.

This can be understood by splitting the fluctuations in an atmospheric part and in a noise part according to

$$200 \quad w'_i(z) = w'_{i,a}(z) + w'_{i,n}(z) \quad (4)$$

$$\text{and} \quad T'_i(z) = T'_{i,a}(z) + T'_{i,n}(z). \quad (5)$$

Inserting equations 4 and 5 in equation 3 yields

$$H(z) = \frac{\rho_a(z) c_p}{N(z)} \sum_{i=1}^{N(z)} \left(w'_{i,a}(z) T'_{i,a}(z) + w'_{i,a}(z) T'_{i,n}(z) + w'_{i,n}(z) T'_{i,a}(z) + w'_{i,n}(z) T'_{i,n}(z) \right) \quad (6)$$

and hence

$$205 \quad H(z) = \frac{\rho_a(z) c_p}{N(z)} \sum_{i=1}^{N(z)} w'_{i,a}(z) T'_{i,a}(z) \quad (7)$$

because $w'_{i,n}(z)$ and $T'_{i,n}(z)$ are uncorrelated with each other as well as with the atmospheric fluctuations.

But even though there is no noise term to be subtracted when determining fluxes from noisy data, of course, there still remains an uncertainty of the flux value due to noise: Because the real atmospheric data set is always of finite length, the noise terms do not cancel fully. This noise uncertainty of the covariance of the fluctuations of a scalar s (e.g. T or q) and the vertical wind w can be estimated by applying Gaussian error propagation to equation 7 giving (Wulfmeyer et al. 2016)

$$210 \quad \sigma_{w's'}(z) \cong \sqrt{\frac{s'_a(z)^2 \sigma_w(z)^2 + w'_a(z)^2 \sigma_{s'}(z)^2}{N(z)}} \quad (8)$$

with $\sigma_{w'}(z)^2$ and $\sigma_{s'}(z)^2$ for the noise variances of the scalar and the vertical wind at height z , respectively. Furthermore, the noise uncertainties of the fluctuations are equal to the noise uncertainties of the original (non-detrended) data sets, $\sigma_{w'}(z)^2 = \sigma_w(z)^2$ and $\sigma_{s'}(z)^2 = \sigma_s(z)^2$ (assuming that the noise uncertainty in the trend determination can be neglected); nevertheless, we keep in the following the notation with primes for clarity as we are dealing with fluctuations here. Equation 8 can be further approximated and rearranged so that the relative noise of the covariance is expressed with the relative noise variances according to

$$\frac{\sigma_{w's'}}{w's'} \cong \sqrt{\frac{1}{N r^2} \left(\frac{\sigma_{s'}^2}{s_a'^2} + \frac{\sigma_{w'}^2}{w_a'^2} \right)} \quad (9)$$

where r is the correlation coefficient between atmospheric vertical wind fluctuations and atmospheric scalar fluctuations given by

$$r = \frac{\overline{w' s'}}{\sqrt{\overline{w_a'^2} \overline{s_a'^2}}} \quad (10)$$

Please note that we omit the height dependence for simplicity in equation 9 and the following equations. Consequently, it follows for the noise uncertainty of the sensible heat flux

$$\frac{\sigma_H}{H} \cong \sqrt{\frac{1}{N r^2} \left(\frac{\sigma_{T'}^2}{T_a'^2} + \frac{\sigma_{w'}^2}{w_a'^2} \right)} \quad (11)$$

It is important to note that we find the variances of the atmospheric fluctuations of temperature and vertical wind in equation 11 but not the variances of the total fluctuations (which include both the atmospheric and noise fluctuations).

In order to identify these atmospheric variances of the temperature and vertical wind fluctuations, we use the method of Lenschow et al. (2000) to separate the noise variance from the total variance: The atmospheric variance σ_a^2 is obtained from the total variance σ_{tot}^2 by subtracting the noise variance σ_n^2 :

$$\sigma_a^2 = \sigma_{tot}^2 - \sigma_n^2 \quad (12)$$

σ_n^2 is determined from an autocovariance analysis of the high-resolution time series of the lidar data. The autocovariance at zero lag is the sum of the atmospheric and noise variances. While the atmospheric fluctuations are correlated in time, the random instrumental noise fluctuations are not. Consequently, one can separate the atmospheric variance from the noise variance by extrapolating the fit of the autocovariance function (also called “structure function”) to lag zero. The most suitable choice of for the number of lags is a factor of 2.5 larger than the integral time scale τ (Wulfmeyer et al. 2016).

After the noise uncertainty profiles have been determined from the variance analysis for both the temperature and vertical wind measurements, $\sigma_{T'}$ and $\sigma_{w'}$ are used for calculating the noise uncertainty of the fluxes with equation 12.

240 The representativeness uncertainty ~~variance~~ or sampling uncertainty ~~variance~~ of the flux expressed as a variance is the square of the difference of the mean flux $\langle F \rangle$ measured in the sampled time period and the real mean flux \overline{F} which would be determined in an infinitely long measurement period:

$$\sigma_F^2 = \langle (\overline{F} - \langle F \rangle)^2 \rangle. \quad (13)$$

This uncertainty can be estimated for $T \gg \tau_{ws}$ with (Lenschow et al. 1994)

$$\sigma_F = \sqrt{2 \left(1 + \frac{1}{r^2} \right)^2 \frac{\tau_{ws}}{T} \overline{F}^2} \quad (14)$$

245 where τ_{ws} is the integral time scale of the vertical flux of the scalar s , T is the length of the measurement period and r is again the correlation coefficient of s' and w' . (Note that Lenschow et al. (1994) call this type of uncertainty “random error” which must not be confused with the noise uncertainty due to random noise.)

An upper limit of the ~~square of the~~ representativeness uncertainty ~~variance~~ can be obtained from the minimum of the integral time scales of vertical wind τ_w and the integral time scale of the scalar τ_s via (Lenschow and Kristensen, 1985)

$$250 \quad \sigma_F = \sqrt{\frac{4}{r^2} \frac{\min(\tau_w, \tau_s)}{T} \overline{F}^2}. \quad (15)$$

Thus, it follows for the sensible heat flux

$$\sigma_{H, \text{sampling}} = \frac{2H}{r} \sqrt{\frac{\min(\tau_w, \tau_s)}{T}}. \quad (16)$$

3.3 Flux divergence and tendency

255 The vertical divergence of the sensible heat flux can be related to a temperature tendency via

$$\frac{1}{\rho_a c_p} \frac{\partial H}{\partial z} = \frac{\partial (w' T')}{\partial z} = - \left(\frac{\partial \overline{\theta}}{\partial t} \right)_{\text{FluxDiv}}. \quad (17)$$

The temperature tendency term on the right hand side of Eq. 17 is just a fraction of the total tendency, namely the contribution of the vertical flux divergence to the total tendency. We indicate this relation by the subscript FluxDiv. The tendency contributions of advection, radiative cooling etc. are not included and need to be determined separately.

260 With the lidar data, we obtain the fluxes in the lower part of the CBL and at the CBL top simultaneously. Thus, we get the temperature trend due to flux divergence in the observed part of the CBL with

$$\left(\frac{\partial \bar{\theta}}{\partial t}\right)_{\text{FluxDiv}} = -\frac{1}{\rho_a c_p} \frac{H(z_i) - H(z_{\text{bottom}})}{z_i - z_{\text{bottom}}} \quad (18)$$

where z_{bottom} stands for the lowest observed height of the CBL.

In a similar way, the divergence of the latent heat flux is related to the moisture tendency in the CBL via

$$265 \quad \frac{1}{L_v} \frac{\partial L}{\partial z} = \frac{\partial(w'q')}{\partial z} = -\left(\frac{\partial \bar{q}}{\partial t}\right)_{\text{FluxDiv}}. \quad (19)$$

with L_v for the latent heat of vaporization and thus we use for the lidar data

$$\left(\frac{\partial \bar{q}}{\partial t}\right)_{\text{FluxDiv}} = -\frac{1}{L_v} \frac{L(z_i) - L(z_{\text{bottom}})}{z_i - z_{\text{bottom}}}. \quad (20)$$

4 Results and discussion

4.1 Meteorological conditions

270 The data used in this study were collected during the HOPE campaign (Macke et al. 2017). HOPE stands for the HD(CP)² Observational Prototype Experiment. HD(CP)² (High Definition Clouds and Precipitation for advancing Climate Prediction) was a German research initiative aiming at a reduction in the uncertainty of climate-change predictions by means of better understanding and simulating cloud and precipitation processes. The HOPE domain was located near the Research Center Jülich in Western Germany. During the HOPE period in April and May 2013, three so-called supersites were set up forming a
 275 triangle with side lengths of about 4 km. At the site near the village of Hambach, the University of Hohenheim (UHOH) set up its scanning rotational Raman temperature lidar (TRRL) and its scanning water vapour differential absorption lidar (WVDIAL). The Karlsruhe Institute of Technology (KIT) brought its so-called KITcube (Kalthoff et al. 2013) with – among a suite of other instruments – a scanning Doppler wind lidar and a surface energy balance station.

In this study, we use data collected on 24 April 2013, the HOPE intensive observation period (IOP) 6. The HOPE domain was
 280 under the influence of an anticyclone located over central Europe on this day (see also Behrendt et al. 2015; Muppa et al. 2016). At the lidar site, the CBL was well developed by 1000 UTC (Muppa et al. 2016). We selected the period from 1105 to 1150 UTC around solar noon at 1132 UTC for the analysis of fluxes. Similar periods have been used regarding separate

analyses of higher-order moments of the turbulent wind, temperature and humidity fluctuations (Behrendt et al. 2015; Mauer et al. 2016; Muppa et al. 2016, Wulfmeyer et al. 2016).

285 As discussed in Behrendt et al. (2015), the mean of the instantaneous CBL heights z_i in the observation period was 1230 m above ground level (a.g.l.). This value is used in the following for the normalized height scale z/z_i . The standard deviation of the instantaneous CBL heights was 33 m; the absolute minimum and maximum were 1125 and 1323 m a.g.l., i.e., the instantaneous CBL heights were within 200 m. At the ground, sensible heat flux H_0 was 192 W m^{-2} and thus lower than the latent heat flux L_0 of 255 W m^{-2} measured with the KITcube energy balance station at the lidar site.

290 4.2 Lidar time series

Fig 1 shows the fluctuations of temperature, humidity, and vertical wind $T'(z,t)$, $q'(z,t)$, and $w'(z,t)$, respectively, measured with the three lidar systems on 24 April 2013 in the 45-minute period between 1105 and 1150 UTC. We found that this period is long enough to provide results with low uncertainties. It should be noted that these data include both atmospheric fluctuations and instrumental noise (compare Eqs. 4 and 5). While the first are correlated in time, the latter are not. It can already be seen
295 here, that the noise in the temperature data is higher than in the humidity and vertical wind data. Nevertheless, the correlated atmospheric fluctuations stand out from the noise in all three plots.

It is interesting to compare now the simultaneous fluctuations of temperature, humidity, and wind with each other. Updrafts are generally, but not always, related to warmer and moister air, while downdrafts are generally, but not always, cooler and dryer. This illustrates the CBL dynamics, which are mainly driven by buoyancy, but also its complexity.

300 The products of vertical wind fluctuations with temperature and humidity fluctuations, respectively, are shown in Fig. 2. Positive instantaneous latent heat flux values are dominant throughout the CBL while the instantaneous sensible heat flux values are dominantly positive in the lower half of the CBL but negative in the upper half.

For completeness, Fig 2 also shows the product of temperature and humidity fluctuations. The data show – apart from noise – partly positive and partly negative values. Positive values indicate that warmer air was moister while cooler air was drier in
305 the CBL. The fact that there are also negative data points reveals that also cooler and moister as well as warmer and dryer fluctuations appeared simultaneously here.

4.3 Integral scales and variances

For the variance data and noise uncertainties presented here, 20 data points of the structure function were used for the fit giving with 10-s resolution of the data a period of 200 s. This is a reasonable number because the first zero crossing of the autocovariance function τ_0 is found at 2.5-times the integral scale (Behrendt et al. 2015, Wulfmeyer et al. 2016) which is
310 mostly between 40 and 120 s in this case (see Fig. 3a). The integral scales were determined according to Eq. 42 of Wulfmeyer et al. (2016). We found that it is not a problem to use a few more lags (even beyond the zero crossing) in order to get a stable

fit. ~~The integral scale is a measure of the typical energy containing eddy size in the temporal domain.~~ The integral scale is a measure of the mean horizontal size of the eddies in the temporal domain during the measurement period (see, e.g., Lenschow et al., 2000, for details).

315 Interestingly, this scale is usually different for different variables. In addition, by comparing the temporal resolution of the lidar measurements with the profile of the integral scale, we can make sure that the temporal resolution is high enough throughout the profile to resolve the major part of the turbulent fluctuations.

The temperature variance profile shows in this case the typical peak near the CBL top in this case (Fig. 3b). The value at z_i was $(0.46 \pm 0.08 \pm 0.13) \text{ K}^2$ with the first error for the sampling uncertainty and the second for the noise uncertainty, respectively.

320 The humidity variance has a more complex structure here with a double peak near z_i (see also Muppa et al. 2016). The peak at $0.9 z_i$ was $(0.17 \pm 0.04 \pm 0.01) (\text{g/m}^3)^2$ while the upper peak at $1.1 z_i$ was $(0.58 \pm 0.11 \pm 0.10) (\text{g/m}^3)^2$. Also the vertical wind variance shows a secondary peak at z_i in this case while the maximum is found, like typically, in the middle CBL. The maximum vertical wind variance appeared at $0.6 z_i$ and was $(1.67 \pm 0.40 \pm 0.03) (\text{m/s})^2$.

4.4 Correlation coefficients, heat flux profiles, and tendencies

325 The correlation coefficients (Eq. 10) of the lidar data (Fig. 1) are shown in Fig. 4. Fig. 5 shows the sensible heat flux profile $H(z)$ derived with the data shown in Fig. 1 via Eq. 3 together with the latent heat flux profile $L(z)$. While positive values are found for $H(z)$ in the lower and middle CBL, negative values are found in the upper CBL as well as in the lower free troposphere. The upward sensible heat flux in the lower and middle CBL is related to upward energy flux from the surface into the CBL while the negative values above show the downward energy flux into the CBL by entrainment. The sign of the correlation coefficient r of w' and T' is just the same as the sign of H at the same height. The values of r lie between -1 and 1 with the exception of two data points between 1000 and 1100 m. These outliers are due to the statistical uncertainty of the data since the temperature variance is close to zero here. r is larger than 0.5 from 400 to about 600 m with a decreasing tendency with height. The maximum H was $(182 \pm 112 \pm 32) \text{ W/m}^2$ and appears at $0.5 z_i$, again with the first error for the sampling uncertainty and the second for the noise uncertainty, respectively. At about $0.7 z_i$, H and r change signs to negative values

330 above. We estimated the entrainment flux near z_i by averaging the measurements between 0.95 and $1.05 z_i$ and obtained a value of $(-62 \pm 27 \pm 42) \text{ W/m}^2$. At our lowest measurement points between 400 and 500 m (corresponding to 0.3 to $0.4 z_i$) we found a mean sensible heat flux of $(156 \pm 34 \pm 8) \text{ W/m}^2$. Taking these representative values at the lower and upper parts of our measurement range in the CBL, we obtain -0.28 W/m^3 for the vertical divergence of the sensible heat flux ~~divergence~~. This corresponds (Eq. 18) to a temperature tendency term of $2.3 \cdot 10^{-4} \text{ K/s}$ or 0.83 K/h .

340 Fig. 5 also shows the latent heat flux profile $L(z)$ derived with the lidar data for comparison. The values are positive throughout the CBL as being typical. So are also the values of the correlation coefficients of moisture and vertical wind fluctuations (Fig. 4). This is because both upward moisture transport from the surface into the CBL and downward entrainment of dry air from the lower free troposphere into the CBL are related to positive values. Taking again representative values for the latent heat flux at the lower and upper parts of the boundary layer, we can determine the latent heat flux divergence and furthermore the

345 water-vapor tendency (Wulfmeyer 1999b). Between 400 and 500 m (corresponding to 0.3 to 0.4 z_i), we found a latent heat flux of $(95 \pm 37 \pm 5)$ W/m². The entrainment flux near z_i was $(190 \pm 63 \pm 39)$ W/m² (obtained again from 0.95 and 1.05 z_i , but with the outlier at 1275 m excluded). Over the range of the measurements, we thus get a latent heat flux divergence of 0.12 W/m³ which corresponds to a tendency of the absolute humidity due to the interplay of evapotranspiration and entrainment of $-5.3 \cdot 10^{-5}$ (g/m³)/s or -0.19 (g/m³)/h.

350 5. Summary and conclusions

We have presented the first measurements of sensible heat flux profiles $H(z)$ in the daytime convective boundary layer made with ground-based remote sensing. The temperature fluctuations were obtained from UV rotational Raman lidar measurements while the vertical wind measurements were made with a coherent Doppler lidar. A cloud-free 45-minute analysis period of the HOPE campaign served as case study. The results show a typical profile of $H(z)$ with positive values in the lower and middle
355 CBL, namely, up to a value of $(182 \pm 112 \pm 32)$ W/m² with the second and third number being the sampling uncertainty and noise uncertainty, respectively, found at 0.5 z_i . In the upper CBL as well as in the lower free troposphere around z_i , we found negative values of H of about $(-62 \pm 27 \pm 42)$ W/m². With the profile of $H(z)$, we obtained -0.28 W/m³ for the sensible heat flux divergence in the CBL which corresponds to a warming tendency term of 0.83 K/h. Furthermore, we presented a simultaneously measured profile of the latent heat flux measured with a combination of the same Doppler lidar and a ~~water~~
360 ~~vapour~~ WVDIAL. The results showed an entrainment drying CBL. Furthermore, the variance profiles of vertical wind as well as of the temperature and moisture fluctuations are shown. Given the feasibility of determining all these critical turbulent CBL variables together with lidar, we foresee that operating such instruments during field campaign or even continuously in automated mode will provide very valuable data for model verifications and testing turbulence parametrizations because these flux profiles rule the distribution of humidity and temperature and thus the atmospheric stability and furthermore the formation
365 of clouds and precipitation.

Data availability. The data are available from the author upon request.

370 **Author contributions.** AB, SKM, FS, DL, NK and AW collected and analyzed the lidar data; AB, VW and CS developed the codes, AB prepared the manuscript, which was improved by all co-authors.

Competing interests. The authors declare that they have no conflict of interest

Acknowledgements

- 375 This project was funded by the German Federal Ministry of Education and Research within the framework programme "Research for Sustainable Development (FONA)", www.fona.de, under the number 01LK1506C within the initiative HD(CP)² - High definition clouds and precipitation for advancing climate prediction.

References

- 380 Adler, B., Kalthoff, N., Gantner, L., 2011: Initiation of deep convection caused by land-surface inhomogeneities in West Africa: a modelled case study. *Meteorol. Atmos. Phys.*, 112, 15–27, DOI:10.1007/s00703-011-0126-z.
- Angevine, W. M., S. K. Avery, W. L. Ecklund, D. A. Carter, 1993a: Fluxes of Heat and Momentum Measured with a Boundary-Layer Wind Profiler Radar-Radio Acoustic Sounding System. *J. Appl. Meteor.*, 32, 73-80, DOI:10.1175/1520-0450(1993)032<0073:FOHAMM>2.0.CO;2
- 385 Angevine, W. M., S. Avery, and G. Kok, 1993b: Virtual heat flux measurements from a boundary-layer profiler-RASS compared to aircraft measurements. *J. Appl. Meteor.*, 32, 1901–1907, DOI:10.1175/1520-0450(1993)032<1901:VHFMA>2.0.CO;2.
- Ayotte, K. W., and Coauthors, 1996: An evaluation of neutral and convective planetary boundary-layer parameterizations relative to large eddy simulations. *Bound.-Layer Meteor.*, 79, 131–175.
- 390 Bange, J, Beyrich, F, Engelbart, D 2002 Airborne measurements of turbulent fluxes during LITFASS-98: Comparison with ground measurements and remote sensing in a case study *Theor. Appl. Climatol.* (2002) 73:35, DOI:10.1007/s00704-002-0692-6.
- Behrendt, A. and J. Reichardt, 2000: Atmospheric temperature profiling in the presence of clouds with a pure rotational Raman lidar by use of an interference-filter-based polychromator. *Appl. Opt.* 39 (9), 1372-1378. DOI:10.1364/AO.39.001372.
- 395 Behrendt, A., T. Nakamura, M. Onishi, R. Baumgart, and T. Tsuda, 2002: Combined Raman lidar for the measurement of atmospheric temperature, water vapor, particle extinction coefficient, and particle backscatter coefficient. *Appl. Opt.* 41 (36), 7657-7666, DOI:10.1364/AO.41.007657.
- Behrendt, A., T. Nakamura, and T. Tsuda, 2004: Combined temperature lidar for measurements in the troposphere, stratosphere, and mesosphere. *Appl. Optics* 43 (14), 2930-2939, DOI:10.1364/AO.43.002930.
- 400 Behrendt, A.: Temperature measurements with lidar, 2005: In: *Lidar: Range-Resolved Optical Remote Sensing of the Atmosphere*, edited by: Weitkamp, C., Springer, New York, 273–305.
- Behrendt, A., V. Wulfmeyer, A. Riede, G. Wagner, S. Pal, H. Bauer, M. Radlach, and F. Späth, 2009: 3-Dimensional observations of atmospheric humidity with a scanning differential absorption lidar. In Richard H. Picard, Klaus Schäfer, Adolfo Comeron et al. (Eds.), *Remote Sensing of Clouds and the Atmosphere XIV*, SPIE Conference Proceeding Vol. 7475, ISBN: 9780819477804, 2009, Art. No. 74750L, DOI:10.1117/12.835143.

- 405 Behrendt, A., Pal, S., Aoshima, F., Bender, M., Blyth, A., Corsmeier, U., Cuesta, J., Dick, G., Dorninger, M., Flamant, C., Di
Girolamo, P., Gorgas, T., Huang, Y., Kalthoff, N., Khodayar, S., Mannstein, H., Träumner, K., Wieser, A., and
Wulfmeyer, V, 2011: Observation of convection initiation processes with a suite of state-of-the-art research instruments
during COPS IOP8b, *Q. J. Roy. Meteor. Soc.*, 137, 81–100, doi:10.1002/qj.758.
- Behrendt A, Wulfmeyer V, Hammann E, Muppa SK, Pal S. 2015. Profiles of second to fourth-order moments of turbulent
410 temperature fluctuations in the convective boundary layer: First asurements with rotational Raman lidar. *Atmos. Chem.
Phys.* 15:5485–5500, DOI:10.5194/acp-15-5485-2015.
- Berg LK, Gustafson, WI, Kassianov, EI, and Deng, L.2013: Evaluation of a modified scheme for shallow convection:
Implementation of CuP and case studies. *Mon. Wea. Rev.*, 141, 134–147, DOI:10.1175/MWR-D-12-00136.1
- Bretherton C, Park S. 2009. A new moist turbulence parameterization in the community atmosphere model. *J. Clim.*, 22:3422–
415 3448, DOI:10.1175/2008JCLI2556.1.
- Cooney, J., 1972: Measurement of atmospheric temperature profiles by Raman backscatter, *Appl. Meteor.* **11**, 108-112.
- Couvreux, F., F. Guichard, J.-L. Redelsperger, C. Kiemle, V. Masson, J.-P. Lafore, and C. Flamant, 2005: Water-vapour
variability within a convective boundary-layer assessed by large-eddy simulations and IHOP_2002 observations. *Quart.
J. Roy. Meteor. Soc.*, 131, 2665–2693, DOI:10.1256/qj.04.167.
- 420 Couvreux, F., F. Guichard, V. Masson, and J.-L. Redelsperger, 2007: Negative water vapour skewness and dry tongues in the
convective boundary layer: Observations and large-eddy simulation budget analysis. *Bound.-Layer Meteor.*, 123, 269–
294, DOI:10.1007/s10546-006-9140-y.
- Di Girolamo, P., Marchese, R., Whiteman, D. N., and Demoz B. B.: Rotational Raman Lidar measurements of atmospheric
temperature in the UV, *Geophys. Res. Lett.*, 31, L01106, DOI:10.1029/2003GL018342, 2004.
- 425 Di Girolamo, P., M. Cacciani, D. Summa, A. Scoccione, B. De Rosa, A. Behrendt, V. Wulfmeyer, 2017: Characterisation of
boundary layer turbulent processes by the Raman lidar BASIL in the frame of HD(CP)2 Observational Prototype
Experiment, *Atmos. Chem. Phys.* 17, 745-767, DOI:10.5194/acp-17-745-2017.
- Dierer S, Arpagaus M, Seifert A, Avgoustoglou E, Dumitrache R, Grazzini F, Mercogliano P, Milelli M, Starosta K. 2009.
Deficiencies in quantitative precipitation forecasts: Sensitivity studies using the COSMO model. *Meteorol. Z.* **18**: 631–
430 645.
- Engelmann, R., Wandinger, U., Ansmann, A., Müller, D., Zeromskis, E., Althausen, D., Wehner, B., 20018: Lidar observations
of the vertical aerosol flux in the planetary boundary layer. *J. Atmos. Ocean. Tech.*, 25, 1296-1306.
- Frehlich, R., S. M. Hannon, and S. W. Henderson, 1998: Coherent Doppler lidar measurements of wind field statistics. *Bound.-
Layer Meteor.*, 86, 233–256, DOI:10.1023/A:1000676021745.
- 435 Gantner, L., Kalthoff, N., 2010: Sensitivity of a modelled life cycle of a mesoscale convective system to soil conditions over
West Africa. *Quart. J. Roy. Meteor. Soc.*, 136(S1), 471-482, DOI:10.1002/qj.425.
- Gibert F., G. Koch, K.J. Davis, J.Y. Beyon, T. Hilton, A. Andrews, P. Flamant and U.N. Singh: Can CO₂ turbulent flux be
measured by lidar? A preliminary study, *J. Atmos. Ocean. Technology*, 28, 365-377, 2011




- Giez, A., G. Ehret, R. L. Schwiesow, K. J. Davies, and D. H. Lenschow, 1999: Water vapor flux measurements from ground-based vertically pointed water vapor differential absorption and Doppler lidars. *J. Atmos. Oceanic Technol.*, 16, 237–250.
- 440
- Grunwald, J., Kalthoff, N., Corsmeier, U., Fiedler, F., 1996: Comparison of areally averaged turbulent fluxes over non-homogeneous terrain: results from the EFEDA. *Bound.-Lay. Meteor.*, 77, 105-134, <https://doi.org/10.1007/BF00119574>.
- 445
- Grunwald, J., Kalthoff, N., Fiedler, F., Corsmeier, U., 1998: Application of different flight strategies to determine areally averaged turbulent fluxes. *Contrib. Atmos. Phys.*, 71, 283-302.
- Hammann E, Behrendt A, Le Mounier F, Wulfmeyer V. 2015: Temperature profiling of the atmospheric boundary layer with rotational Raman lidar during the HD(CP)2 Observational Prototype Experiment. *Atmos. Chem. Phys.* **15**: 2867–2881, DOI: 10.5194/acp-15-2867-2015.
- 450
- Hammann, E. and A. Behrendt, 2015: Parametrization of optimum filter passbands for rotational Raman temperature measurements. *Opt. Express* 23 (24), 30767-30782. DOI:10.1364/OE.23.030767
- Heinze R, A. Dipankar, C. Carbajal Henken, C. Moseley, O. Sourdeval, S. Trömel, X. Xie, P. Adamidis, F. Ament, H. Baars, C. Barthlott, A. Behrendt, U. Blahak, S. Bley, S. Brdar, M. Brueck, S. Crewell, H. Deneke, P. Di Girolamo, R. Evaristo, J. Fischer, C. Frank, P. Friederichs, T. Göcke, K. Gorges, L. Hande, M. Hanke, A. Hansen, H.-C. Hege, C. Hoose, T. Jahns, N. Kalthoff, D. Klocke, S. Kneifel, P. Knippertz, A. Kuhn, T. van Laar, A. Macke, V. Maurer, B. Mayer, C. I. Meyer, S. K. Muppa, R. A. J. Neggers, E. Orlandi, F. Pantillon, B. Pospichal, N. Röber, L. Scheck, A. Seifert, P. Seifert, F. Senf, P. Siligam, C. Simmer, S. Steinke, B. Stevens, K. Wapler, M. Weniger, V. Wulfmeyer, G. Zängl, D. Zhang, and J. Quaas, 2017. Large-eddy simulations over Germany using ICON: A comprehensive evaluation. *Q.J.R. Meteorol. Soc.*, **143**:69–100, DOI: 10.1002/qj.2947.
- 455
- Hirsch, L, and Peters, G, 1998: Abilities and limitations of a radar-RASS wind profiler for the measurement of momentum flux in the planetary boundary layer *Meteorol Z.*, N.F, 7, 336-344
- 460
- Hogan, R. J., A. L. M. Grant, A. J. Illingworth, G. N. Pearson, and E. J. O'Connor, 2009: Vertical velocity variance and skewness in clear and cloud-topped boundary layers as revealed by Doppler lidar. *Quart. J. Roy. Meteor. Soc.*, 135, 635–643, doi:<https://doi.org/10.1002/qj.413>.
- 465
- Kalthoff, N., Kohler, M., Barthlott, C., Adler, B., Mobbs, S.D., Corsmeier, U., Träumner, K., Foken, T., Eigenmann, R., Krauss, L., Khodayar S., Di Girolamo, P., 2011: The dependence of convection-related parameters on surface and boundary-layer conditions over complex terrain. *Quart. J. Roy. Meteor. Soc.*, 137(S1), 70-80. DOI: 10.1002/qj.686.
- Kalthoff, N., Adler, B., Wieser, A., Kohler, M., Träumner, K., Handwerker, J., Corsmeier, U., Khodayar, S., Lambert, D., Kopmann, A., Kunka, N., Dick, G., Ramatschi, M., Wickert, J., Kottmeier, Ch., 2013: KITcube - a mobile observation platform for convection studies deployed during HyMeX. *Meteorol. Z.*, 22, 633-647. Doi:<https://doi.org/10.1127/0941-2948/2013/0542>
- 470



- Kiemle, C., and Coauthors, 2007: Latent heat flux profiles from collocated airborne water vapor and wind lidars during IHOP_2002. *J. Atmos. Oceanic Technol.*, 24, 627–639, doi:<https://doi.org/10.1175/JTECH1997.1>.
- 475 Kiemle, C., G. Ehret, A. Giez, K. Davis, D. Lenschow, and S. P. Oncley, 1997: Estimation of boundary layer humidity fluxes and statistics from airborne differential absorption lidar (DIAL). *J. Geophys. Res.*, 102, 29 189–29 203, doi:<https://doi.org/10.1029/97JD01112>.
- Kiemle, C., M. Wirth, A. Fix, S. Rahm, U. Corsmeier, and P. Di Girolamo, 2011: Latent heat flux measurements over complex terrain by airborne water vapour and wind lidars. *Quart. J. Roy. Meteor. Soc.*, 137, 190–203, doi:<https://doi.org/10.1002/qj.757>.
- 480 Lange, D., A. Behrendt, V. Wulfmeyer, 2019: Automated Turbulence-Resolution Thermodynamic Profiler for the Troposphere Based on Water Vapor and Temperature Raman Lidar, in preparation.
- LeMone, M., 2002: Convective boundary layer. *Encyclopedia of Atmospheric Sciences*, 1st ed. J. Holton and J. Curry, Eds., Academic Press, 250–257.
- Lenschow D. H., J. C. Wyngaard, W. T. Pennel, 1980: Mean-Field and Second-Moment Budgets in a Baroclinic, Convective
485 Boundary Layer. *Journal of the Atmospheric Sciences* 37, 1313-1326. DOI: 10.1175/1520-0469(1980)037<1313:MFASMB>2.0.CO;2
- Lenschow, D. H., and L. Kristensen, 1985: Uncorrelated noise in turbulence measurements. *J. Atmos. Oceanic Technol.*, 2, 68-81.
- Lenschow, D. H., J. Mann, and L. Kristensen, 1994: How long is long enough when measuring fluxes and other turbulence
490 statistics? *J. Atmos. Oceanic Technol.*, 11, 661–673, doi:[https://doi.org/10.1175/1520-0426\(1994\)011<0661:HLILEW>2.0.CO;2](https://doi.org/10.1175/1520-0426(1994)011<0661:HLILEW>2.0.CO;2).
- Lenschow, D. H., V. Wulfmeyer, and C. Senff, 2000: Measuring second-through fourth-order moments in noisy data. *J. Atmos. Oceanic Technol.*, 17, 1330–1347, doi:[https://doi.org/10.1175/1520-0426\(2000\)017<1330:MSTFOM>2.0.CO;2](https://doi.org/10.1175/1520-0426(2000)017<1330:MSTFOM>2.0.CO;2).
- Lenschow, D. H., M. Lothon, S. D. Mayor, P. P. Sullivan, and G. Canut, 2012: A comparison of higher-order vertical velocity
495 moments in the convective boundary layer from lidar with in situ measurements and large-eddy simulation. *Bound.-Layer Meteor.*, 143, 107–123, doi:<https://doi.org/10.1007/s10546-011-9615-3>.
- Linné, H., B. Hennemuth, J. Bösenberg, and K. Ertel, 2007: Water vapour flux profiles in the convective boundary layer. *Theor. Appl. Climatol.*, 87, 201–211.
- Lothon, M., D. H. Lenschow, and S. D. Mayor, 2006: Coherence and scale of vertical velocity in the convective boundary
500 layer from a Doppler lidar. *Bound.-Layer Meteor.*, 121, 521–536, doi:<https://doi.org/10.1007/s10546-006-9077-1>.
- Lothon, M., D. H. Lenschow, and S. D. Mayor, 2009: Doppler lidar measurements of vertical velocity spectra in the convective planetary boundary layer. *Bound.-Layer Meteor.*, 132, 205–226, doi:<https://doi.org/10.1007/s10546-009-9398-y>.
- Macke A, Seifert P, Baars H, Beekmans C, Behrendt A, Bohn B, Madhavan BL, Brüggemann B, Hammann E, Hirsikko A, Bühl J, Cacciani M, Corsmeier U, Crewell S, Damian T, Di Girolamo P, Graf A, Handwerker J, Kalisch J, Kalthoff N, Kinne
505 S, Kohler M, Linné H, Löhnert U, Metzendorf S, Muppa SK, Pfeiffer M, Pospichal B, Simmer C, Späth F, Riede A,


- Ruhtz T, Stelitano D, Scaccione A, Serikov I, Summa D, Träumner K, Wieser A, Wulfmeyer V. 2017. The HD(CP)2 Observational Prototype Experiment HOPE – an overview. *Atmos. Chem. Phys.*, DOI: 10.5194/acp-2016-990
- Matuura, M., Y. Masuda, H. Inuki, S. Kato, S. Fukao, T. Sato, and T. Tsuda, 1986: Radio acoustic measurement of temperature profile in the troposphere and stratosphere. *Nature*, 323, 426–428, doi:<https://doi.org/10.1038/323426a0>.
- 510 Maurer, V., Kalthoff, N., Wieser, A., Kohler, M., Mauder, M., Gantner, L., 2016: Observed spatiotemporal variability of boundary-layer turbulence over flat, heterogeneous terrain. *Atmos. Chem. Phys.*, 16, 1377-1400, <https://doi.org/10.5194/acp-16-1377-2016>.
- Milovac J, Warrach-Sagi K, Behrendt A, Spaeth F, Ingwersen J, Wulfmeyer V. 2016. Investigation of PBL schemes combining the WRF model simulations with scanning water vapor differential absorption lidar measurements. *J. Geophys. Res.*
- 515 **121**: 624–649, doi: 10.1002/2015JD023927.
- Moeng CH, and Sullivan PP. 1994. A comparison of shear- and buoyancy-driven planetary boundary layer flows. *J. Atmos. Sci.***51**: 999–1022.
- Muppa SK, Behrendt A, Späth F, Wulfmeyer V, Metzendorf S, Riede A. 2016. Turbulent humidity fluctuations in the convective boundary layer: Case studies using water vapour differential absorption lidar measurements. *Bound.-Layer Meteorol.* **158**: 43–66.
- 520 *Meteorol.* **158**: 43–66.
- Neggers, RAJ. 2009. A dual mass flux framework for boundary layer convection. Part II: clouds. *J Atmos Sci***66**(6):1489–1506.
- O'Connor EJ, Illingworth AJ, Brooks IM, Westbrook CD, Hogan RJ, Davies F, Brooks BJ (2010) A method for estimating the turbulent kinetic energy dissipation rate from a vertically pointing Doppler lidar, and independent evaluation from
- 525 balloon-borne in situ measurements. *J Atmos Ocean Technol* 27:1652–1664.
- Osman, M.K., D.D. Turner, T. Heus, and V. Wulfmeyer, 2019: Validating the Water Vapor Variance Similarity Relationship in the Interfacial Layer Using Observations and Large-eddy Simulations. Submitted for publication in *J. Geophys. Res. Atm.*
- Pal, S., A. Behrendt, and V. Wulfmeyer, 2010: Elastic-backscatter-lidar-based characterization of the convective boundary layer and investigation of related statistics. *Ann. Geophys.*, 28, 825–847, doi:<https://doi.org/10.5194/angeo-28-825-2010>.
- 530 *Ann. Geophys.*, 28, 825–847, doi:<https://doi.org/10.5194/angeo-28-825-2010>.
- Peters, G., H. Hinzpeter, and G. Baumann, 1985: Measurements of heat flux in the atmospheric boundary layer by sodar and RASS. *Radio Sci.*, 20, 1555–1564.
- Radlach, M., Behrendt, A., and Wulfmeyer, V.: Scanning rotational Raman lidar at 355 nm for the measurement of tropospheric temperature fields, *Atmos. Chem. Phys.*, 8, 159–169, doi:10.5194/acp-8-159-2008, 2008.
- 535 *Atmos. Chem. Phys.*, 8, 159–169, doi:10.5194/acp-8-159-2008, 2008.
- Rao, M., S. Casadio, G. Fiocco, M. Cacciani, A. Di Sarra, D. Fuá, P. Castracane, 2001: Estimation Of Atmospheric Water Vapour Flux Profiles In The Nocturnal Unstable Urban Boundary Layer With Doppler Sodar And Raman Lidar. *Boundary-Layer Meteorology* 102, 39-62. DOI:10.1023/A:1012794731389.

- Santanello, J. A., P. A. Dirmeyer, C. R. Ferguson, K. L. Findell, A. B. Tawfik, A. Berg, M. Ek, P. Gentine, B. P. Guillod, C. van Heerwaarden, J. Roundy, and V. Wulfmeyer, 2018: Land-Atmosphere Interactions: The LoCo Perspective. *Bull. Amer. Meteor. Soc.* 99, 1253-1272, DOI:10.1175/BAMS-D-17-0001.1.
- Savitzky A, Golay MJE (1964) Smoothing and differentiation of data by simplified least squares procedures. *Anal Chem* 36:1627-1639
- Senff, C., J. Bösenberg, and G. Peters, 1994: Measurement of water vapor flux profiles in the convective boundary layer with lidar and radar-RASS. *J. Atmos. Oceanic Technol.*, 11, 85–93.
- Senff, C., J. Bösenberg, G. Peters, and T. Schaberl, 1996: Remote sensing of turbulent ozone fluxes and the ozone budget in the convective boundary layer with DIAL and radar-RASS: A case study. *Contrib. Atmos. Phys.*, 69, 161–176.
- Späth, F., A. Behrendt, S. K. Muppa, S. Metzendorf, A. Riede, and V. Wulfmeyer, 2016: 3D water vapor field in the atmospheric boundary layer observed with scanning differential absorption lidar. *Atmos. Meas. Tech.* 9, 1701-1720. DOI:10.5194/amt-9-1701-2016
- Thomas, R. M., Lehmann, K., Nguyen, H., Jackson, D. L., Wolfe, D., and Ramanathan, V., 2012: Measurement of turbulent water vapor fluxes using a lightweight unmanned aerial vehicle system, *Atmos. Meas. Tech.*, 5, 243-257, DOI:10.5194/amt-5-243-2012.
- Träumner K, Damian Th, Stawiarski Ch, Wieser, A, 2014: Turbulent structures and coherence in the atmospheric surface layer. accepted in *Boundary-Layer Meteorol* DOI 10.1007/s10546-014-9967-6.
- Turner, D. D., R. A. Ferrare, V. Wulfmeyer, and A. J. Scarino, 2014a: Aircraft evaluation of ground-based Raman lidar water vapor turbulence profiles in convective mixed layers. *J. Atmos. Oceanic Technol.*, 31, 1078–1088, doi:<https://doi.org/10.1175/JTECH-D-13-00075.1>.
- Turner, D. D., V. Wulfmeyer, L. K. Berg, and J. H. Schween, 2014b: Water vapor turbulence profiles in stationary continental convective mixed layers. *J. Geophys. Res. Atmos.*, 119, 11 151–11 165, doi:<https://doi.org/10.1002/2014JD022202>.
- Wagner, G., V. Wulfmeyer, F. Späth, A. Behrendt, and M. Schiller, 2013: Performance and specifications of a pulsed high-power single-frequency Ti:Sapphire laser for water-vapor differential absorption lidar. *Appl. Opt.* 52 (11), 2454-2469. DOI:10.1364/AO.52.002454.
- Weckwerth T., J. W. Wilson, R. M. Wakimoto, 1996. Thermodynamic variability within the convective boundary layer due to horizontal convective rolls. *Mon. Wea. Rev.* 124:769–784.
- Weckwerth T., T. W. Horst, J. W. Wilson, 1999: An observational study of the evolution of horizontal convective rolls. *Mon Weather Rev.* 127: 2160–2179
- Werner, C., 2005: Doppler wind lidar. In: C. Weitkamp (Ed.), *Lidar – Range-Resolved Optical Remote Sensing of the Atmosphere*, Springer.
- Wulfmeyer, V. and J. Bösenberg, 1998: Ground-based differential absorption lidar for water-vapor profiling: Assessment of accuracy, resolution, and meteorological applications. *Appl. Opt.* 37 (18), 3825-3844, DOI:10.1364/AO.37.003825.




- Wulfmeyer, V., 1999a: Investigations of humidity skewness and variance profiles in the convective boundary layer and comparison of the latter with large eddy simulation results. *J. Atmos. Sci.*, 56, 1077–1087, DOI:10.1175/1520-0469(1999)056<1077:IOHSAV>2.0.CO;2.
- 575 Wulfmeyer, V., 1999b: Investigation of turbulent processes in the lower troposphere with water vapor DIAL and radar-RASS. *J. Atmos. Sci.*, 56, 1055–1076, DOI:10.1175/1520-0469(1999)056<1055:IOTPIT>2.0.CO;2.
- Wulfmeyer, V., S. Pal, D. D. Turner, and E. Wagner, 2010: Can water vapour Raman lidar resolve profiles of turbulent variables in the convective boundary layer? *Bound.-Layer Meteor.*, 136, 253–284, DOI:10.1007/s10546-010-9494-z.
- Wulfmeyer V, Muppa SK, Behrendt A, Hammann E, Späth F, Sorbjan Z, Turner D, Hardesty R. 2016. Determination of the convective boundary layer entrainment fluxes, dissipation rates and the molecular destruction of variances: Theoretical description and a strategy for its confirmation with a novel lidar system synergy. *J. Atmos. Sci.* **73**: 667–692, DOI:10.1175/JAS-D-14-0392.1.
- 580
- Wulfmeyer V, Turner DD, Baker B, Banta R, Behrendt A, Bonin T, Brewer WA, Buban M, Choukulkar A, Dumas E, Hardesty RM, Heus T, Ingwersen J, Lange D, Lee T, Metzendorf S, Muppa SK, Meyers T, Newsom R, Osman M, Raasch S, Santanello J, Senff C, Späth F, Wagner T, Weckwerth W. 2018. A new research approach for observing and characterizing land-atmosphere feedback. *Bull. Amer. Meteorol. Soc.* 99, 1639-1667, DOI:10.1175/BAMS-D-17-0009.1.
- 585









595 Figure 1: Time–height cross-sections of the measurements of the detrended and despiked fluctuations of (a) temperature T' , (b) vertical velocity w' , and (c) absolute humidity q' measured with rotational Raman lidar, Doppler lidar, and water vapour DIAL on 24 April 2013 in the 45-minute period between 1105 and 1150 UTC.











Figure 2: Time–height cross-sections of the fluctuation products (a) $w' T'$, (b) $w' q'$, and (c) $T' q'$.





615 Figure 3: (a) Integral time scales of the atmospheric temperature fluctuations (RRL, red), atmospheric fluctuations of absolute humidity (WVDIAL, blue), and atmospheric fluctuations of the vertical wind (DL, green). The dashed line shows the mean CBL height determined with the RRL backscatter data at 1230 m AGL. Thin error bars **in pale colors** show the sampling uncertainties. (b) Same as (a) but for the variances. Thick error bars show the uncertainties due to instrumental noise.




Figure 4: Profiles of the correlation coefficients of the lidar data





Figure 5: Sensible heat flux H and the latent heat flux L derived from the lidar data. The temperature and vertical wind fluctuations for determining H were obtained from UV rotational Raman lidar and coherent Doppler lidar measurements, respectively. For L , humidity fluctuations measured with a water vapor DIAL were combined with vertical wind fluctuations measured with Doppler lidar. Thick error bars show the uncertainties due to instrumental noise; thin error bars in pale colors show the sampling uncertainties.

620

625

