



Evaluation of equivalent black carbon (EBC) source appointment using observations from Switzerland between 2008 and 2018

Stuart K. Grange^{1,2}, Hanspeter Löttscher³, Andrea Fischer¹, Lukas Emmenegger¹, and Christoph Hueglin¹

¹Empa, Swiss Federal Laboratories for Materials Science and Technology, Überlandstrasse 129, 8600 Dübendorf, Switzerland

²Wolfson Atmospheric Chemistry Laboratories, University of York, York, YO10 5DD, United Kingdom

³Amt für Natur und Umwelt Graubünden, Gürtelstrasse 89, 7001 Chur, Switzerland

Correspondence to: Stuart K. Grange (stuart.grange@empa.ch)

Abstract.

Black carbon (BC) or soot is a constituent of particulate matter (PM) which is relevant for negative human health and climate effects, and despite the lack of legal limits, it is recognised as an important atmospheric pollutant to monitor, understand, and control. Aethalometers are instruments which continuously monitor BC by measuring absorption at a number of distinct
5 wavelengths. If collocated elemental carbon (EC) observations are used to transform these values into BC mass, by convention, the result is named equivalent black carbon (EBC). BC emitted by different combustion processes have different optical absorption characteristics and this can be used to apportion EBC mass into traffic (EBC_{TR}) and woodburning (EBC_{WB}) components with a data processing technique known as the aethalometer model. The aethalometer model was applied to six EBC monitoring sites across Switzerland (using data between 2008 and 2018) and was evaluated by investigating diurnal cycles,
10 model coefficients, and ambient temperature dependence of the two EBC components. For one monitoring site, San Vittore, the aethalometer model failed to produce plausible outputs. The reason for this failure was likely due to a high load of freshly emitted wood smoke during the winter which should be thought of as a third distinct emission source. After model evaluation, the trend analysis indicated that EBC_{TR} concentrations at the remaining five locations significantly decreased between 2008 and 2018 illustrating the successful widespread installation of diesel particulate filters (DPF) within the vehicle fleet. EBC_{WB}
15 also demonstrated significant decreases in most monitoring locations, but not at a monitoring site south of the Alps with a high PM load sourced from biomass burning. This indicated that the management of woodburning has been ineffective at reducing BC emissions and concentrations for this, likely representative location. The EBC/PM_{2.5} ratios suggested that EBC contributes 6–13 % of the PM_{2.5} mass in Switzerland which is important for soot and PM source management. The aethalometer model is a useful data analysis procedure, but can fail under certain conditions, thus, careful evaluation is required to ensure the method
20 is robust and suitable in other locations.



1 Introduction

1.1 Black carbon

Atmospheric particulate matter (PM) has a variety of components, one of which is black carbon (BC) which is commonly referred to as soot. BC is strongly light absorbing (hence the name), is generally found in the fine PM fraction ($\leq \text{PM}_{2.5}$), and is generated by the incomplete combustion of fuels (Hansen et al., 1984; Vignati et al., 2010). Biomass burning, internal combustion engines (especially those which are fuelled by diesel), and industrial processes can all be BC emission sources (Bond et al., 2004; Jacobson, 2001). There are no known BC generation or degradation processes in the atmosphere and because the only removal mechanisms for BC are wet and dry deposition, BC has a lifetime between several days to weeks in the atmosphere. These attributes make BC a reliable tracer for combustion processes.

BC is an important atmospheric pollutant to consider in its own sense however (Anenberg et al., 2012). BC is believed to have a positive (warming) climate forcing effect due to the absorption of radiation and the reduction of albedo, especially when deposited on snow and ice (Ramanathan and Carmichael, 2008; Weinhold, 2012; Bond et al., 2013). BC is harmful to human health and there is evidence that BC is a particularly potent PM component when considering deleterious health effects due to the aerosol's large surface area to mass ratio, tendency to be enriched with harmful organic compounds, and ability to penetrate deep into the lungs (Janssen et al., 2011; De Prins et al., 2014; Laeremans et al., 2018). The International Agency for Research on Cancer (IARC) has also classed soot as a Group 1 carcinogen indicating there is clear evidence that soot causes cancer in humans (International Agency for Research on Cancer, 2019). It is however, difficult to tease apart the health effects of BC alone from PM as a whole (Jacobson, 2001; European Environment Agency, 2013). These features have made BC an important pollutant to monitor, understand, manage, and control despite not currently having legal limits imposed in Europe and elsewhere (Reche et al., 2011; European Environment Agency, 2016).

1.2 Aethalometers and the aethalometer model

BC is measured, sampled, or monitored in a variety of ways but the most widespread is done by aethalometers (Hansen et al., 1984). Aethalometers are described in depth elsewhere, however, briefly they are optical instruments which sample air continuously and deposit the PM onto filter material. The loaded filter is illuminated, the light attenuation is measured as an optical absorption, and the increase in attenuation over time is logged and used to calculate BC concentrations with empirical coefficients. The quartz filter material used by aethalometers can reach saturation, so the instruments employ a filter-tape system where the filter material is advanced if saturation occurs, or when a threshold of elapsed time has passed. Continuously depositing aerosol onto a filter causes artefacts known as filter-scattering and filter-shadowing effects, but there are standard algorithms to compensate for these effects, some of which are applied on-board by the instrument as part of the measurement cycle (Magee Scientific, 2016).

Modern aethalometers used in ambient air quality monitoring networks are multi-wavelength models measuring absorption between the near-ultraviolet (UV) to the near-infrared (IR) range, but at distinct wavelengths within this range. If the wavelength range is wide enough, analysis of the spectral dependence can be explored. BC sourced from different families of combustion



processes demonstrate different absorption dependence at different wavelengths. Most notably, woodburning particles, *i.e.* wood smoke, generally contains a rich organic component which is very effective at absorbing light in the UV range while diesel soot shows a weaker spectral dependence (Kirchstetter et al., 2004) (Fig. 1). The different spectral dependences between these sources can be leveraged with a data processing technique called the aethalometer model, first reported by Sandradewi et al. (2008) but used many times since in many locations; for examples, see Sandradewi et al. (2008); Favez et al. (2009); Herich et al. (2011); Fuller et al. (2014). In routine aethalometer use, only the 880 nm absorption wavelength is used with a fixed coefficient (called a mass absorption coefficient) which is the strict definition of BC. Therefore, the aethalometer model simply uses information which is generally discarded in most monitoring applications and the barrier for entry to the method is low.




Figure 1. Demonstration of different aethalometer absorption dependence on wavelengths for two monitoring sites in Switzerland with distinct aerosol characteristics. Data have been filtered to a single observation (hourly) to show the dependence on the dominating sources.

10 1.3 Black carbon nomenclature note

The nomenclature and vocabulary used for BC is diverse and can lead to confusion (Andreae and Gelencsér, 2006; Petzold et al., 2013). Here, we refer to BC determined by optical measurement techniques, *i.e.* by aethalometers and transformed with the use of collocated elemental carbon (EC) observations, as equivalent black carbon (EBC). This definition has been recommended by the Global Atmospheric Watch (Tarasova, 2012). When EBC is apportioned into its traffic and woodburning components, the TR and WB subscript notation is used respectively, *i.e.*, EBC_{TR} and EBC_{WB} . If total EBC needs to be used for clarity against the EBC components, EBC_{TOT} is used. This notation is consistent with Zotter et al. (2017) which this



work somewhat extends. When discussing emissions of soot, BC is still used however, because EBC is only a measurement definition and does not refer to the pollutant.

1.4 Objectives

The primary objective of this work is to apply the aethalometer model data transformation technique to apportion long-term (up to ten years) EBC time series from six Swiss monitoring sites into two components: a traffic and a woodburning component (EBC_{TR} and EBC_{WB}) and evaluate the method's performance. The suitability and limitations of the aethalometer model as a technique to employ before trend analysis will be discussed. A data set is presented where the aethalometer model fails to apportion the two EBC components correctly. This is done to demonstrate the features which will be present if the aethalometer model is inadequate for a particular application, and it outlines that although the aethalometer model is a useful technique, but is not a panacea. The second objective is to expose the EBC_{TR} and EBC_{WB} components to a trend analysis and give explanations for the features observed in the Swiss time series.

2 Methods

2.1 Data

Absorption observations measured by aethalometers for six monitoring sites in Switzerland were analysed (Table 1; Fig. 2). The monitoring sites were either part of the federal monitoring network (National Air Pollution Monitoring Network; NABEL) or networks run by the Swiss Cantonal authorities (states) (Federal Office for the Environment, 2014). Sites were classified as either urban traffic, urban background, rural, or rural mountain according to their surrounds. Four of the sites were located on the Swiss plateau (where the majority of the human population is located) but Rigi-Seebodenalp, despite being located on the plateau is at altitude (1031 metres; Figure 2). Two monitoring sites, Magadino-Cadenazzo and San Vittore are located south of the Alps in valleys where residential woodburning is much more common than on the Swiss plateau due to its rural nature (Alfarra et al., 2007; Szidat et al., 2007).

Table 1. Information about the six equivalent black carbon (EBC) monitoring sites in Switzerland which were used in this study.

Site	Site name	Local ID	Site type	Start date	End date	Days online	Latitude	Longitude	Elevation (m)
ch0031a	Bern-Bollwerk	BER	Urban traffic	2013-12-11	2018-12-31	1846	46.951	7.441	536
ch0010a	Zürich-Kaserne	ZUE	Urban background	2009-04-02	2018-12-31	3560	47.378	8.530	409
ch0002r	Payerne	PAY	Rural	2008-03-04	2018-12-31	3954	46.813	6.944	489
ch0033a	Magadino-Cadenazzo	MAG	Rural	2008-03-13	2018-12-31	3945	46.160	8.934	203
ch2001e	San Vittore	SVI	Rural	2013-10-04	2018-12-31	1914	46.239	9.105	298
ch0005r	Rigi-Seebodenalp	RIG	Rural mountain	2013-01-25	2018-12-31	2166	47.067	8.463	1031

The absorption observations were measured by two models of multi-wavelength aethalometers manufactured by Magee Scientific. The two models were the AE31 and AE33 which measure adsorption at seven wavelengths: 370, 470, 520, 590,




Figure 2. Switzerland’s six equivalent black carbon (EBC) monitoring sites and their site classifications. Solid black areas are significant water bodies and shading represents the terrain and elevation. The boundaries of Switzerland and the lakes were extracted from OpenStreetMap (OpenStreetMap contributors, 2019) and the heights were derived from Switzerland’s digital height model (Swiss Federal Office of Topography (swisstopo), 2010).

660, 880, and 950 nm. The AE31 is an earlier generation instrument discontinued in 2016 (Magee Scientific, 2017) while the AE33 aethalometer replaced the AE31 and is currently manufactured (Magee Scientific, 2019). These two aethalometer models share the same measurement principle, however the newer AE33 uses a “dual-spot” approach to allow for a superior method to compensate for filter loading effects (Drinovec et al., 2015). The differences between the AE31 and AE33 technologies mean that the algorithms which compensate or correct for filter shadowing effects and filter loading effects are different. For the full description of the compensation procedures, see Weingartner et al. (2003); Drinovec et al. (2015). Quartz filters were used by the aethalometers and therefore, a multiple light scattering factor (denoted as C) of 2.14 was used (Weingartner et al., 2003). There were thirteen distinct aethalometers used in the monitoring network which were irregularly cycled among the monitoring sites as part of the networks’ maintenance procedures (Table 2). All aethalometers were operated with $PM_{2.5}$ sample inlets.

10 Data from the aethalometers for five of the six Swiss EBC monitoring sites were queried from the NABEL monitoring network’s database while the remaining site’s observations, San Vittore, were provided directly by the Graubünden canton’s environmental department (Amt für Natur und Umwelt). All absorption observations had been compensated for the filter loading and shadowing effects with the instrument model’s respective algorithms before this analysis was undertaken (Weingartner



Table 2. Aethalometer instruments' locations between 2007 and 2018. Dates have been rounded to the nearest hour and those end dates which are missing shows the instrument was on site to the end of the analysis period (the end of 2018).

Site	Site name	Local ID	Start date	End date	Instrument ID
ch0031a	Bern-Bollwerk	BER	2013-12-10 16:00:00	2014-03-13 10:00:00	AE33-S02-00136
ch0031a	Bern-Bollwerk	BER	2014-03-13 09:00:00	2014-03-14 16:00:00	AE33-S01-00092
ch0031a	Bern-Bollwerk	BER	2014-03-14 15:00:00	2016-07-27 11:00:00	AE31-768:0701
ch0031a	Bern-Bollwerk	BER	2016-07-27 15:00:00	2016-10-26 10:00:00	AE31-718:0605
ch0031a	Bern-Bollwerk	BER	2016-10-26 10:00:00	2017-07-06 11:00:00	AE31-768:0701
ch0031a	Bern-Bollwerk	BER	2017-07-06 10:00:00	2018-03-22 12:00:00	AE31-719:0605
ch0031a	Bern-Bollwerk	BER	2018-03-22 11:00:00	2018-11-29 12:00:00	AE31-768:0701
ch0031a	Bern-Bollwerk	BER	2018-11-29 10:00:00		AE33-S07-00736
ch0010a	Zürich-Kaserne	ZUE	2009-04-02 10:00:00	2009-10-08 11:00:00	AE31-769:0701
ch0010a	Zürich-Kaserne	ZUE	2009-10-08 10:00:00	2011-07-25 14:00:00	AE31-768:0701
ch0010a	Zürich-Kaserne	ZUE	2011-07-25 13:00:00	2012-08-31 14:00:00	AE31-719:0605
ch0010a	Zürich-Kaserne	ZUE	2012-08-31 10:00:00	2013-06-05 13:00:00	AE31-768:0701
ch0010a	Zürich-Kaserne	ZUE	2013-06-05 12:00:00	2014-04-10 11:00:00	AE31-718:0605
ch0010a	Zürich-Kaserne	ZUE	2014-04-10 10:00:00		AE33-S01-00092
ch0002r	Payerne	PAY	2008-03-04 15:00:00	2008-05-14 09:00:00	AE31-768:0701
ch0002r	Payerne	PAY	2008-05-21 09:00:00	2008-10-02 16:00:00	AE31-768:0701
ch0002r	Payerne	PAY	2008-10-02 15:00:00	2013-04-04 12:00:00	AE31-718:0605
ch0002r	Payerne	PAY	2013-04-04 11:00:00	2013-06-27 13:00:00	AE31-719:0605
ch0002r	Payerne	PAY	2013-06-27 12:00:00	2015-09-16 12:00:00	AE31-769:0701
ch0002r	Payerne	PAY	2015-09-16 12:00:00	2016-06-08 16:00:00	AE31-719:0605
ch0002r	Payerne	PAY	2016-06-08 10:00:00		AE33-S04-00430
ch0033a	Magadino-Cadenazzo	MAG	2008-03-13 12:00:00	2008-06-17 12:00:00	AE31-769:0701
ch0033a	Magadino-Cadenazzo	MAG	2008-07-03 13:00:00	2008-08-28 10:00:00	AE31-769:0701
ch0033a	Magadino-Cadenazzo	MAG	2008-08-28 11:00:00	2008-12-05 11:00:00	AE31-719:0605
ch0033a	Magadino-Cadenazzo	MAG	2008-12-18 11:00:00	2010-03-25 12:00:00	AE31-719:0605
ch0033a	Magadino-Cadenazzo	MAG	2010-03-25 11:00:00	2013-06-12 13:00:00	AE31-769:0701
ch0033a	Magadino-Cadenazzo	MAG	2013-06-12 13:00:00	2013-12-18 13:00:00	AE31-768:0701
ch0033a	Magadino-Cadenazzo	MAG	2013-12-18 14:00:00	2014-07-17 11:00:00	AE31-719:0605
ch0033a	Magadino-Cadenazzo	MAG	2014-06-12 09:00:00	2016-01-21 11:00:00	AE31-718:0605
ch0033a	Magadino-Cadenazzo	MAG	2016-01-21 10:00:00	2016-12-21 10:00:00	AE31-769:0701
ch0033a	Magadino-Cadenazzo	MAG	2016-12-21 10:00:00	2017-05-24 11:00:00	AE33-S00-00060
ch0033a	Magadino-Cadenazzo	MAG	2017-05-24 10:00:00		AE33-S04-00429
ch2001e	San Vittore	SVI	2013-10-04 00:00:00		AE33-S02-00133
ch0005r	Rigi-Seebodenalp	RIG	2013-01-22 14:00:00	2013-05-30 13:00:00	AE33-S00-00049
ch0005r	Rigi-Seebodenalp	RIG	2013-05-30 10:00:00	2015-11-12 12:00:00	AE33-S00-00060
ch0005r	Rigi-Seebodenalp	RIG	2015-11-12 11:00:00		AE33-S02-00136



et al., 2003; Drinovec et al., 2015). Generally, the observations were stored as hourly means, but for the data which was at higher resolution (10 and 30 minute means), observations were aggregated to create a consistently hourly time series which was used for analysis. Overall, the analysis covered a period between March 2008 to the end of 2018, but the start date of aethalometer operation varied among the different monitoring sites (Table 1; Table 2).

5 The method employed to transform absorption observations to EBC requires elemental carbon (EC) concentrations. EC was determined by the standard EN16909 thermal optical transmission (TOT) method using the EUSAAR2 temperature protocol (European Committee for Standardization (CEN), 2017). Unlike the continuous observations which the aethalometers provided, EC concentrations were available as daily samples and ranged from being sampled between every fourth to twelfth day. When using aethalometer and EC data together, the aethalometer observations were aggregated (as arithmetic means) to daily
10 resolution to ensure the observations spanned the same time period and duration. The EC samples were also collected with $PM_{2.5}$ inlets. $PM_{2.5}$ observations for the monitoring sites were required to calculate the EBC/ $PM_{2.5}$ ratios. These data were accessed with the **saqgetr** R package which gives access to the European Commission's AirBase and Air Quality e-Reporting (AQER) repositories in a convenient way (European Environment Agency, 2014, 2019; Grange, 2019b). Only validated data were kept for analysis.

15 2.2 Source apportionment

The absorption measures from the aethalometers were apportioned into two components: the traffic fraction (EBC_{TR}) and the woodburning fraction (EBC_{WB}) with the aethalometer model (Sandradewi et al., 2008). The aethalometer model is based on the principle that EBC emitted from woodburning activities has an enhanced absorption in the UV range relative to EBC sourced from the combustion of fossil fuels. A critical component of applying the aethalometer model to produce valid outputs
20 is the selection of the Ångström exponents (which are the slopes of exponential regression models), usually denoted by α (Harrison et al., 2013). Fortunately, in Switzerland, the Ångström exponents for woodburning and traffic sources have been determined robustly using ^{14}C observations of the EC fraction across Switzerland between 2005 and 2012 (Zotter et al., 2017). Here we use 0.9 and 1.68 for α_{TR} and α_{WB} respectively, as reported by Zotter et al. (2017).

Mass absorption cross section (MAC) coefficients are required to transform optical absorption observations to EBC mass
25 (Magee Scientific, 2016). The instrument manufacturers use fixed MAC values on-board to calculate BC mass (for example the A33's factory MAC values are displayed in Table A1), but any given MAC value is a function PM size and morphology which will change depending on the PM source (Zotter et al., 2017). For the trend analysis reported here, the MAC values for absorption at the 950 nm wavelength (used for the IR input to the aethalometer model) were calculated with rolling simple least squares linear regression models between absorption and the mass of EC in the $PM_{2.5}$ fraction. A least squares estimator
30 was used because EC was determined with a reference method, and is accepted without uncertainty. The window was 180 days (with centre alignment), and this logic was implemented with the **zoo** R package (Zeileis and Grothendieck, 2005).

Once the Ångström exponents were chosen and the MAC values calculated, the aethalometer model was applied to the absorption observations at hourly resolution and the R function used for this transformation is available (Grange, 2019a). Based on the absorption at 470 and 950 nm (UV and IR spectra respectively), this resulted in three EBC mass variables for



each valid absorption observation: EBC_{WB} , EBC_{TR} , and EBC_{TOT} . A flow diagram which represents the data processing steps can be found in Figure A2.

2.3 Trend tests

Formal trend tests were performed on the EBC components with the Theil-Sen slope estimator, a robust, non-parametric estimator provided by the **openair** R package (Carslaw and Ropkins, 2012). Before the trend was tested, the observations were aggregated to monthly resolution and deseasonalised with loess models to extract the trend component (R Core Team, 2019). Autocorrelation was taken into account resulting in conservative slope estimations and all trend tests were conducted at the 0.05 significance level.

3 Results and discussion

3.1 Model coefficients evaluation

3.1.1 Mass absorption cross section (MAC) coefficients

The MAC values which were empirically derived using least squares regression models (using EC and absorption at 950 nm) with a 180-day rolling window showed substantial variability (Fig. 3). This suggests that the use of fixed or static MAC values are questionable for trend analysis applications. The sites' MAC values at 950 nm generally had a range of $10\text{m}^2\text{g}^{-1}$ during the analysis period despite the irregular cycling of different instruments among the sites (Table 2). For perspective, compare this range with the factory MAC values displayed in Table A1. A seasonal pattern was present in the MAC values where summertime absorption measures were higher than those in wintertime which represent a change of average aerosol characteristics during the year which is to be expected. The range of the seasonality was generally less than $3\text{m}^2\text{g}^{-1}$.

The MAC values for Rigi-Seebodenalp were atypical and showed a substantial decrease between 2013 and 2016 (Fig. 3). During this period, the same aethalometer was operating at the monitoring location (Table 2; Fig. A1). The MAC value is an empirical coefficient which represents aerosol composition and it is very unlikely that Rigi-Seebodenalp's aerosol characteristics altered dramatically between 2013 and 2016, therefore the observed decrease in the MAC value was almost certainly an instrument artefact, perhaps a slow degradation in sensitivity. Indeed, the decrease in the MAC value stopped when the instrument was replaced in late-2015 and remained low for the rest of the monitoring period (Fig. A1). This instrument-derived feature was only uncovered due to the presence of collocated EC observations, but due to a lack of additional data, we do not wish to speculate further on what was the cause for this decline in the MAC coefficient.

The rolling least squares regression procedure presented here ensures that the changes in MAC over time is compensated for before EBC mass is calculated with the aethalometer model. The changes or drift in the MAC values, especially for Rigi-Seebodenalp, are not propagated into the EBC masses using this method. Therefore, this approach is recommended over using fixed MAC values if EC time series are available and trend analysis is to be undertaken with several years of aethalometer observations.




Figure 3. Mass absorption cross section (MAC) coefficients for 950 nm for different monitoring sites as calculated by rolling simple linear regression models with windows of 180 days (alignment of the window was the centre of the period).

3.1.2 Ångström exponents (α)

A critical input for the aethalometer model is the α values used for the traffic and woodburning sourced EBC (Harrison et al., 2013). The α values used here were previously derived from comparing ^{14}C and EC observations (Section 2.2; Zotter et al. (2017)), but to validate if the values were sensible for the sites analysed, α was calculated for each hourly absorption observation and their distributions investigated.

The distributions of the calculated α values were consistent with those reported by Zotter et al. (2017) which were 0.9 and 1.68 for α_{TR} and α_{WB} respectively. Figure 4 shows the α distributions for three of the monitoring sites along a continuum of increasing woodburning activity (from left to right). The distributions for α at each of the monitoring sites peaked at 1.2, the value used for α_{TR} in the aethalometer model. However, as the monitoring sites' were exposed to a progressively higher woodburning PM load, the distribution become positively skewed. Magadino-Cadenazzo for example, a site which is exposed to wood smoke, has a tail which extends beyond 1.68 while the urban traffic Bern-Bollwerk site's α distribution contains only a



small component at, and beyond, the α_{WB} value of 1.68. Therefore, the features of the α distributions can be rather informative for diagnostic purposes.




Figure 4. Counts of binned Ångström exponents (α) for three equivalent black carbon (EBC) monitoring sites' hourly absorption observations in Switzerland between 2014 and 2018.

San Vittore's calculated α were unique because they displayed a bimodal distribution which was not present at the other monitoring sites (Fig. 4). The presence of the bimodal distribution indicates that San Vittore is exposed to an additional source that the other monitoring sites are not. Although this extra BC source is unknown, we speculate that it is very likely to be freshly emitted wood smoke which has been emitted nearby the monitoring location and rapidly transported to the monitoring site before chemical processing has had the opportunity to act on the aerosol. The importance of this feature is discussed further in Section 3.3. An additional check on the observations was performed in the form of a three-factor receptor model with the multilinear engine (ME-2) as implemented by the EPA PMF tool (Norris et al., 2014; Brown et al., 2015). However, in this case the factor analysis was unable to resolve the three sources and did not offer any additional contribution to the data analysis.

3.2 Diurnal cycles

Diurnal plots were used to validate if the two components' behaviour were consistent with what is expected of their emission source behaviour after the EBC fractions were calculated with the aethalometer model and the model's coefficients evaluated (Fig. 5). With the exception of Rigi-Seebodenalp, an elevated rural mountain site, both the traffic and woodburning components' diurnal cycles could be readily understood in terms of source activity influencing the monitoring sites. This gives support to the plausibility of the aethalometer model's source apportionment ability.

Bern-Bollwerk, an urban traffic site displayed a clear morning rush hour peak for EBC_{TR} with a decline in concentrations in the late morning, followed by a smaller increase in the afternoon/evening rush hour (Fig. 5). This traffic-forced pattern was also present at Payerne and Zürich-Kaserne, rural and urban background sites, respectively, but at lower concentrations. Magadino-Cadenazzo also displayed a clear twin-peak EBC_{TR} diurnal cycle. Here however, the evening peak had approximately the same




Figure 5. Mean hourly equivalent black carbon (EBC) components for the six monitoring sites. Note the different scales on the y -axes.

concentration as the morning peak which was not observed at the other monitoring locations. The strong evening peak was only observed at winter at Magadino-Cadenazzo, This feature was most likely driven by very stable and stagnant atmospheric conditions in the morning and evening because this monitoring site (and surrounding population centres), is located in a deep valley where the day length is short at these times of the year due to confining terrain. This is confirmed by mean bivariate polar plots for Magadino-Cadenazzo where elevated EBC_{WB} concentrations were found when wind speeds were very low ($\leq 2\text{ms}^{-1}$) while EBC_{TR} sources were identified for a diverse range of wind speeds and directions (Fig. 6).

For most monitoring sites, the EBC_{WB} components displayed elevated concentrations in the late evening with a decline in the early morning, consistent with domestic heating demands (Grange et al., 2013). In most cases, this evening peak was followed by decrease and a lesser morning increase in EBC_{WB} , likely due to the reignition of woodburning appliances in the morning. However, at the Bern-Bollwerk urban traffic site, the morning EBC_{WB} peak was reminiscent of the EBC_{TR} peak, indicating a slight contamination of EBC_{WB} by EBC_{TR} which the aethalometer model was unable to separate. Magadino-




Figure 6. Mean polar plots of equivalent black carbon (EBC) components for Magadino-Cadenazzo between 2011 and 2018.

Cadenazzo, the rural monitoring location which is exposed to a high load of woodburning PM, the diurnal cycle was very clear and strong.

Rigi-Seebodenalp's EBC diurnal cycles were different than the other monitoring locations (Fig. 5). This monitoring site is located at an elevation of 1031 metres, is isolated from any significant local emissions, and is intermittently in the boundary layer and therefore, at times is not influenced by surface source activities (Grange et al., 2018). These site attributes resulted in EBC diurnal cycles being driven primarily by boundary layer evolution rather than local source strength and activities. When the convective boundary layer grew in vertical extent and exceeded the site's elevation, EBC was mixed to the site, but when the stratified nocturnal boundary layer decoupled the site from surface-based emissions, concentrations remained low (Fig. 5). This feature was clearer for EBC_{TR} than EBC_{WB} .

10 3.3 Aethalometer model failure

San Vittore is a small settlement located in the Mesolcina Valley in the south of Switzerland (Fig. 2), an area which experiences high concentrations of PM and BC from residential woodburning. The diurnal plots for San Vittore demonstrate, on average, negative mass contributions for EBC_{TR} when EBC_{WB} concentrations were high in the evening (averages shown in Fig. 5). This is an implausible situation and indicates the failure of the aethalometer model to correctly apportion the traffic and woodburning EBC sources. When the time series of the EBC_{TR} and EBC_{WB} are plotted, the negative contributions are very clear during the colder months, November to December (Fig. 7).

These negative contributions can be managed to some extent by altering the woodburning Ångström exponent (α_{WB}), but only with justification. In the case of San Vittore, the α_{WB} was increased to ≈ 2.0 (a very high value) in an attempt to eradicate




Figure 7. EBC_{TR} and EBC_{WB} hourly time series between 2014 and 2018 at San Vittore using two values for α_{WB} . The α_{WB} of 1.68 was used for the analysis but showed negative contributions of EBC_{TR} when EBC_{WB} concentrations were high and using an α_{WB} of 2.0 showed implausible EBC_{TR} concentrations at this site.

the negative EBC_{TR} mass contributions (Fig. 7). This solution only partially resolves the negative EBC_{TR} concentrations, but also results in the EBC_{TR} being estimated at implausibly high concentrations for this location. This is most evident during the cooler periods where EBC_{WB} concentrations are high due to a heavy burden of wood smoke, but EBC_{TR} concentrations are also high and based on San Vittore's characteristics, we concluded that the aethalometer model is unable to separate the two
5 EBC components in this time series.

The San Vittore example represents a very clear example of when the aethalometer model fails and the results cannot be used further for data analysis. The aethalometer model fails in this example because the monitoring site is exposed to freshly emitted wood smoke from the near-by residential properties. Woodburning aerosol which has not been exposed to any or very little atmospheric ageing has different special properties than those exposed to atmospheric processing (Jimenez et al., 2009)
10 (which was indicated in Fig. 4) and is the explanation for the aethalometer model failure. The aethalometer model's two-source approach is most likely insufficient for the freshly emitted wood smoke which may need to be treated as a third distinct source. A receptor modelling approach (such as PMF) may be a technique which could resolve these three sources, but an investigation



of this was outside of the scope of this study. Observations from the San Vittore site were excluded from any further analysis but have been presented to demonstrate that although the aethalometer model can be a useful technique, it is pragmatic and is not appropriate in all cases.

3.4 EBC dependence on air temperature

5 BC emissions from traffic and woodburning sources are not only different in respect to their timing as discussed in Section 3.2, but also by their dependence on ambient air temperature. Although vehicle emissions of PM are known to be temperature dependent (Jamriska et al., 2008; Weilenmann et al., 2009), this effect can be expected to be less pronounced when compared to residential heating emissions which have a quite distinct “heating threshold temperature” where emissions will increase as the air temperature decreases further to meet an increasing space heating energy demand. Additionally, in warmer periods,
10 there is very little or no emissions of BC from residential heating.

These different source patterns were clearly demonstrated for the Swiss EBC monitoring sites with Magadino-Cadenazzo EBC_{WB} concentrations being negative correlated with air temperature, and with increases in mean EBC_{WB} concentrations once air temperatures were below 12°C (Fig. 8). Temperatures of 17°C and above resulted in EBC_{WB} being less than 0.15 µg m⁻³ at the same location. Payerne’s EBC components showed similar patterns to Magadino-Cadenazzo while the
15 sites which were influenced more by traffic emissions, Bern-Bollwerk and Zürich-Kaserne still demonstrated a greater ambient temperature dependence for EBC_{WB} than EBC_{TR} despite EBC_{TR} concentrations being higher for most temperatures.

Due to Rigi-Seebodenalp’s elevated location, the patterns observed are different than at the other monitoring sites, in particular as temperature increased so did EBC_{TR} concentrations (Fig. 8). This was a result of mixing of traffic sourced pollutants to the monitoring location and shows that Rigi-Seebodenalp is influenced more by traffic emissions than those originating from
20 woodburning activities which was also suggested by Fig. 5.

3.5 Trend analysis

After the aethalometer model split EBC into the two components, EBC_{TR} was found to be significantly decreasing across all monitoring sites in Switzerland between 2008 and 2018, with the exception of the rural mountain monitoring site, Rigi-Seebodenalp (Fig. 9). Bern-Bollwerk, an urban traffic site was the most polluted EBC monitoring site (Table A2) and saw the
25 greatest reduction in EBC_{TR} with a decrease of -0.13 µg m⁻³ year⁻¹. Magadino-Cadenazzo, Payerne, and Zürich-Kaserne demonstrated modest significantly decreasing EBC_{TR} trends ranging from -0.028 to -0.059 µg m⁻³ year⁻¹ (Fig. 9).

These EBC_{TR} trends can be interpreted as successful management of BC emissions from vehicular internal combustion engines. There were no obvious breakpoints in the trend components, but the widespread installation of diesel particle filters (DPF) for the (late) Euro 4 and 5 emission standards (beginning in 2000) and the elimination of older diesel-fuelled vehicles
30 are most likely the main drivers for the reductions in concentrations of EBC_{TR} (Gill et al., 2011; Reşitoğlu et al., 2015). The efficacy of DPFs for trapping soot post-combustion chamber has offset the high proportion of diesel passenger vehicles in the European fleet which peaked in 2010 at over 50 % (Schiermeier, 2015; International Council on Clean Transportation Europe, 2015; Zachariadis, 2016; ACEA, 2018). However, the diesel market share for passenger vehicles sharply declined in the wake




Figure 8. EBC_{TR} and EBC_{WB} dependence on air temperature for five equivalent black carbon (EBC) monitoring sites in Switzerland.

of the Volkswagen emission scandal (“dieselgate”) after 2015, and this market change may also be a contributory factor in the EBC_{TR} trends observed after about 2016.

EBC_{WB} trends were different than those observed for EBC_{TR} , even when comparing the same monitoring sites (Fig. 9). The urban monitoring locations, Bern-Bollwerk and Zürich-Kaserne demonstrated significantly decreasing EBC_{WB} trends but at a smaller magnitude when compared to the EBC_{TR} components at the same sites. Payerne’s EBC_{WB} concentrations were also found to be decreasing significantly, but at a minute rate ($-0.005 \mu\text{g m}^{-3} \text{ year}^{-1}$). Critically, the monitoring site which experiences the greatest woodburning PM load, Magadino-Cadenazzo south of the Alps (Fig. 2), showed no significant trend in the EBC_{WB} component (Fig. 9). This is in contrast to the traffic-sourced BC and indicated that efforts to reduce PM emissions from woodburning activities have not been successful in communities south of the Alps. The same conclusion was found when PM_{10} observations were previously analysed at the same monitoring site (Grange et al., 2018).

Figure 5 and 8 suggest that Rigi-Seebodenalp’s isolation from localised BC sources made the site distinct from the other EBC monitoring sites in Switzerland. The trends for Rigi-Seebodenalp were also distinct and showed no significant trend in both the EBC_{TR} and EBC_{WB} components (Fig. 9).




Figure 9. Deseasonalised trends of EBC_{TR} and EBC_{WB} at five EBC monitoring sites in Switzerland between 2008 and 2018. Asterisks (*) in the panels indicate if the trend was statistically significant and dashed lines show the trend tests' 95 % confidence interval.

3.6 EBC/PM_{2.5} ratios

BC is almost exclusively an anthropogenic pollutant with generally minor and intermittent contributions from “naturally” caused combustion processes. It is therefore useful to explore what effect a complete eradication of the BC emission sources would have on air quality. The seasonal EBC/PM_{2.5} ratios for the five Swiss EBC monitoring sites are shown in Fig. 10 and shows that the ratios were variable among the monitoring sites and seasons. Bern-Bollwerk, the urban traffic site had the highest EBC/PM_{2.5} ratio while Payerne and Rigi-Seebodenalp had the lowest. Again, Fig. 10 gave plausibility to the aethalometer model's source apportionment abilities because features such as EBC_{WB} having very low contributions in the summer for most sites, even for the biomass burning dominated Magadino-Cadenazzo location. However, as suggested by Fig. 5, Bern-Bollwerk's EBC_{WB} contribution to PM_{2.5} were most likely too high, indicating that that the aethalometer model was unable to fully separate the two EBC_{TR} and EBC_{WB} fractions completely for this particular monitoring site.

On first inspection, the EBC_{TOT} contribution to PM_{2.5} mass seems modest, ranging from 6–13 % depending on site and season. Compare these values to the largest European urban areas, Paris and London, where their BC/PM_{2.5} ratios have been reported (at single heavily trafficked locations) as 43 ± 20 % and ≈ 50 % respectively (Ruellan and Cachier, 2001; Grange et al., 2016). If BC was perfectly controlled at the source of emission, Switzerland could achieve a 6–13 % reduction of PM_{2.5}




Figure 10. Seasonal equivalent black carbon (EBC)/PM_{2.5} ratios for five monitoring sites in Switzerland between 2014 and 2018.

concentrations to aid with the compliance with the annual and daily limits set for PM_{2.5}, most notably Switzerland's tight annual 10 µg m⁻³ year⁻¹ limit introduced in 2018.

The discussion above is focused on the contribution of EBC to PM. In addition, BC should be reduced to the lowest possible level because of its classification as a Group 1 carcinogen by the International Agency for Research on Cancer (IARC; entered as soot) (International Agency for Research on Cancer, 2019). The reduction of soot emissions also has co-benefits for reducing climate warming effects and this can also be used for motivation for the implementation of soot control at the source.



4 Conclusions

Using aethalometers for EBC monitoring allows for the application of the aethalometer model to split EBC into EBC_{TR} and EBC_{WB} components. The aethalometer model is a useful and pragmatic data processing technique, but it requires evaluation before using the model's outputs for further data analysis activities. Based on the results presented using Swiss aethalometer observations from six sites between 2008 and 2018, these recommendations can be offered to other data users:

- Values used for the mass absorption cross section (MAC) coefficients and the Ångström exponents (α) should be checked with the observational record which is being analysed to ensure they are plausible for use with the particular data set. EC observations are however required for the calculation of MACs and therefore, the expansion of monitoring networks to include regular EC samples is recommended for better exploitation of aethalometer absorption data.
- Evaluate the calculated EBC_{TR} and EBC_{WB} by investigating the presence of negative mass contributions, their diurnal cycles, and ambient temperature dependence to ensure these features are consistent with what is known about the sites' PM load and relevant physical and chemical atmospheric processes.
- If available, put the EBC_{TR} and EBC_{WB} in context by using PM mass concentrations.

These recommendations will help those who are interesting in applying the aethalometer model which has a rather low barrier to entry.

Despite the failure of the aethalometer model to produce value outputs for one of the six monitoring sites analysed, EBC_{TR} and EBC_{WB} were successfully analysed separately at five locations, and different trends were observed for the two EBC components. EBC_{TR} concentrations significantly decreased across all monitoring sites between 2008 and 2018 with the exception of an isolated rural mountain monitoring location at a maximum rate of $-0.13 \mu\text{g m}^{-3} \text{ year}^{-1}$. It is likely that the EBC_{TR} trends were primarily driven by the widespread installation of effective DPF throughout the in-service heavy- and light-duty vehicle fleet. Trends of EBC_{WB} were more variable and despite some significantly decreasing trends of some monitoring sites, a site known to be heavily burdened by wood smoke showed no significant trend over the 2008 and 2018 monitoring period. This is evidence of ineffective management of reducing BC and PM emissions from domestic wood burning which has been noted in the past. The $EBC/PM_{2.5}$ ratios for the five monitoring sites showed location and seasonal variability, and the EBC contribution to $PM_{2.5}$ was between 6 and 13 %. This $EBC/PM_{2.5}$ ratio is low when compared to other heavily trafficked sites in Paris and London, but is important to know for an air quality management perspective. The aethalometer model is a pragmatic and useful data processing technique, but full evaluation is needed to ensure the results are suitable for further data analysis.

Code and data availability. The data sources used in this work are described and referenced in the text. Observations for the Bern-Bollwerk and San Vitore monitoring sites (which are not currently public accessible) are available from the authors on reasonable request.



Author contributions. SKG and CH developed the research questions and conducted the data analysis. HP and AF collected and supplied additional data. SKG and CH prepared the manuscript with input from LE.

Competing interests. The authors declare no competing interest.

Acknowledgements. This work was financially supported by the Swiss Federal Office for the Environment (FOEN). SKG is also supported
5 by the Natural Environment Research Council (NERC) while holding associate status at the University of York. The authors thank the COST Action CA16109 COLOSSAL (Chemical On-Line cOmpoSition and Source Apportionment of fine aerosoL) for motivating this research.



Table A1. Factory mass absorption cross section (MAC) coefficients for the AE33 aethalometer (Magee Scientific, 2016).

Wavelength (nm)	MAC value ($\text{m}^2 \text{g}^{-1}$)	Notes
370	18.47	
470	14.54	
520	13.14	
590	11.58	
660	10.35	
880	7.77	The definition of black carbon (BC)
950	7.19	

Table A2. Summary statistics for daily equivalent black carbon (EBC) at five monitoring sites in Switzerland between 2008 and 2018.

Site name	Site type	EBC _{TOT} ($\mu\text{g m}^{-3}$)	EBC _{TR} ($\mu\text{g m}^{-3}$)	EBC _{WB} ($\mu\text{g m}^{-3}$)
Bern-Bollwerk	Urban traffic	1.37 (95% CI [1.34, 1.39])	0.83 (95% CI [0.82, 0.85])	0.53 (95% CI [0.52, 0.55])
Zürich-Kaserne	Urban background	0.77 (95% CI [0.76, 0.79])	0.54 (95% CI [0.53, 0.55])	0.23 (95% CI [0.23, 0.24])
Payerne	Rural	0.49 (95% CI [0.48, 0.50])	0.29 (95% CI [0.28, 0.29])	0.20 (95% CI [0.20, 0.21])
Magadino-Cadenazzo	Rural	0.90 (95% CI [0.87, 0.93])	0.39 (95% CI [0.38, 0.41])	0.50 (95% CI [0.48, 0.52])
Rigi-Seebodenalp	Rural mountain	0.24 (95% CI [0.23, 0.25])	0.15 (95% CI [0.15, 0.16])	0.09 (95% CI [0.09, 0.10])




Figure A1. Mass absorption cross section/mass absorption coefficients (MAC) values for 950 nm at Rigi-Seebodenalp and coded by the aethalometers which were operating at the monitoring site.




Figure A2. A flow chart of the data processing steps required to apply the aethalometer model.



References

- ACEA: Share of Diesel in New Passenger Cars, <https://www.acea.be/statistics/article/Share-of-diesel-in-new-passenger-cars>, European Automobile Manufacturers' Association, 2018.
- Alfarra, M. R., Prevot, A. S. H., Szidat, S., Sandradewi, J., Weimer, S., Lanz, V. A., Schreiber, D., Mohr, M., and Baltensperger, U.: Identification of the Mass Spectral Signature of Organic Aerosols from Wood Burning Emissions, *Environmental Science & Technology*, 41, 5770–5777, <https://doi.org/10.1021/es062289b>, <http://dx.doi.org/10.1021/es062289b>, 2007.
- Andreae, M. O. and Gelencsér, A.: Black carbon or brown carbon? The nature of light-absorbing carbonaceous aerosols, *Atmospheric Chemistry and Physics*, 6, 3131–3148, <https://www.atmos-chem-phys.net/6/3131/2006/>, 2006.
- Anenberg, Susan, C., Joel, S., Drew, S., Markus, A., Greg, F., Zbigniew, K., Greet, J.-M., Luca, P., Rita, V. D., Elisabetta, V., Lisa, E., Muller Nicholas, Z., Jason, W. J., Martin, W., Volodymyr, D., Kevin, H. W., Johan, K., Frank, R., and Veerabhadran, R.: Global Air Quality and Health Co-benefits of Mitigating Near-Term Climate Change through Methane and Black Carbon Emission Controls, *Environmental Health Perspectives*, 120, 831–839, <https://doi.org/10.1289/ehp.1104301>, <https://doi.org/10.1289/ehp.1104301>, 2012.
- Bond, T. C., Streets, D. G., Yarber, K. F., Nelson, S. M., Woo, J.-H., and Klimont, Z.: A technology-based global inventory of black and organic carbon emissions from combustion, *Journal of Geophysical Research: Atmospheres*, 109, <https://doi.org/10.1029/2003JD003697>, <https://agupubs.onlinelibrary.wiley.com/doi/abs/10.1029/2003JD003697>, 2004.
- Bond, T. C., Doherty, S. J., Fahey, D. W., Forster, P. M., Berntsen, T., DeAngelo, B. J., Flanner, M. G., Ghan, S., Kärcher, B., and Koch, D.: Bounding the role of black carbon in the climate system: A scientific assessment, *Journal of Geophysical Research: Atmospheres*, 118, 5380–5552, 2013.
- Brown, S. G., Eberly, S., Paatero, P., and Norris, G. A.: Methods for estimating uncertainty in PMF solutions: Examples with ambient air and water quality data and guidance on reporting PMF results, *Science of The Total Environment*, 518-519, 626–635, <http://www.sciencedirect.com/science/article/pii/S004896971500025X>, 2015.
- Carslaw, D. C. and Ropkins, K.: *openair* — An R package for air quality data analysis, *Environmental Modelling & Software*, 27–28, 52–61, <http://www.sciencedirect.com/science/article/pii/S1364815211002064>, 2012.
- De Prins, S., Dons, E., Van Poppel, M., Int Panis, L., Van de Mierop, E., Nelen, V., Cox, B., Nawrot, T. S., Teughels, C., Schoeters, G., and Koppen, G.: Airway oxidative stress and inflammation markers in exhaled breath from children are linked with exposure to black carbon, *Environment International*, 73, 440–446, <http://www.sciencedirect.com/science/article/pii/S0160412014002013>, 2014.
- Drinovec, L., Močnik, G., Zotter, P., Prévôt, A. S. H., Ruckstuhl, C., Coz, E., Rupakheti, M., Sciare, J., Müller, T., Wiedensohler, A., and Hansen, A. D. A.: The “dual-spot” Aethalometer: an improved measurement of aerosol black carbon with real-time loading compensation, *Atmospheric Measurement Techniques*, 8, 1965–1979, <https://www.atmos-meas-tech.net/8/1965/2015/>, 2015.
- European Committee for Standardization (CEN): CEN EN 16909: Ambient air—Measurement of elemental carbon (EC) and organic carbon (OC) deposited on filters, 2017.
- European Environment Agency: Status of black carbon monitoring in ambient air in Europe, <https://www.eea.europa.eu/publications/status-of-black-carbon-monitoring>, EEA Technical report. No 18/2013, 2013.
- European Environment Agency: AirBase – The European air quality database (Version 8), <https://www.eea.europa.eu/data-and-maps/data/airbase-the-european-air-quality-database-8>, 2014.
- European Environment Agency: Black carbon: Better monitoring needed to assess health and climate change impacts, <https://www.eea.europa.eu/highlights/black-carbon-better-monitoring-needed>, news. Published 10 Dec 2013; Last modified 21 Jun 2016, 2016.



- European Environment Agency: Download of air quality data. Download service for E1a and E2a data, <http://discomap.eea.europa.eu/map/fme/AirQualityExport.htm>, 2019.
- Favez, O., Cachier, H., Sciare, J., Sarda-Estève, R., and Martinon, L.: Evidence for a significant contribution of wood burning aerosols to PM_{2.5} during the winter season in Paris, France, *Atmospheric Environment*, 43, 3640–3644, <http://www.sciencedirect.com/science/article/pii/S1352231009003690>, 2009.
- 5
- Federal Office for the Environment: Messstationen des NABEL — Stations de mesure NABEL, <https://www.bafu.admin.ch/dam/bafu/en/dokumente/luft/fachinfo-daten/nabel-messstationen.pdf.download.pdf/nabel-messstationen.pdf>, Technischer Bericht NABEL 2013, 2014.
- Fuller, G. W., Tremper, A. H., Baker, T. D., Yttri, K. E., and Butterfield, D.: Contribution of wood burning to PM₁₀ in London, *Atmospheric Environment*, 47, 87–94, <http://www.sciencedirect.com/science/article/pii/S1352231013009825>, 2014.
- 10
- Gill, S. S., Chatha, G. S., and Tsolakis, A.: Analysis of reformed EGR on the performance of a diesel particulate filter, *International Journal of Hydrogen Energy*, 36, 10 089–10 099, <http://www.sciencedirect.com/science/article/pii/S0360319911011876>, 2011.
- Grange, S. K.: R function to calculate equivalent black carbon (EBC) components with the aethalometer model, <https://gist.github.com/skgrange/a458a5f7eafc1efe594e99dc20ff8da3>, GitHub Gist, 2019a.
- Grange, S. K.: **saqgetr**: Import Air Quality Monitoring Data in a Fast and Easy Way, <https://cran.r-project.org/web/packages/saqgetr/index.html>, r package, 2019b.
- 15
- Grange, S. K., Salmond, J. A., Trompetter, W. J., Davy, P. K., and Ancelet, T.: Effect of atmospheric stability on the impact of domestic wood combustion to air quality of a small urban township in winter, *Atmospheric Environment*, 70, 28–38, <https://doi.org/http://dx.doi.org/10.1016/j.atmosenv.2012.12.047>, <http://www.sciencedirect.com/science/article/pii/S1352231013000411>, 2013.
- 20
- Grange, S. K., Lewis, A. C., and Carslaw, D. C.: Source apportionment advances using polar plots of bivariate correlation and regression statistics, *Atmospheric Environment*, 145, 128–134, <http://www.sciencedirect.com/science/article/pii/S1352231016307166>, 2016.
- Grange, S. K., Carslaw, D. C., Lewis, A. C., Boleti, E., and Hueglin, C.: Random forest meteorological normalisation models for Swiss PM₁₀ trend analysis, *Atmospheric Chemistry and Physics*, 18, 6223–6239, <https://doi.org/https://doi.org/10.5194/acp-18-6223-2018>, <https://www.atmos-chem-phys.net/18/6223/2018/>, 2018.
- 25
- Hansen, A., Rosen, H., and Novakov, T.: The aethalometer – An instrument for the real-time measurement of optical absorption by aerosol particles, *Science of The Total Environment*, 36, 191 – 196, [https://doi.org/10.1016/0048-9697\(84\)90265-1](https://doi.org/10.1016/0048-9697(84)90265-1), <http://www.sciencedirect.com/science/article/B6V78-48YVWBR-Y/2/7805001daabd183d7d8d14a4a7207771>, 1984.
- Harrison, R. M., Beddows, D. C., Jones, A. M., Calvo, A., Alves, C., and Pio, C.: An evaluation of some issues regarding the use of aethalometers to measure woodsmoke concentrations, *Atmospheric Environment*, 80, 540–548, <http://www.sciencedirect.com/science/article/pii/S1352231013006353>, 2013.
- 30
- Herich, H., Hueglin, C., and Buchmann, B.: A 2.5 year’s source apportionment study of black carbon from wood burning and fossil fuel combustion at urban and rural sites in Switzerland, *Atmospheric Measurement Techniques*, 4, 1409–1420, <https://www.atmos-meas-tech.net/4/1409/2011/>, 2011.
- International Agency for Research on Cancer: List of Classifications, <https://monographs.iarc.fr/list-of-classifications>, Agents classified by the IARC Monographs, Volumes 1–124, 2019.
- 35
- International Council on Clean Transportation Europe: European vehicle market statistics, 2015/2016, <http://www.theicct.org/european-vehicle-market-statistics-2015-2016>, Pocketbook, 2015.



- Jacobson, M. Z.: Strong radiative heating due to the mixing state of black carbon in atmospheric aerosols, *Nature*, 409, 695–697, <https://doi.org/10.1038/35055518>, 2001.
- Jamriska, M., Morawska, L., and Mergersen, K.: The effect of temperature and humidity on size segregated traffic exhaust particle emissions, *Atmospheric Environment*, 42, 2369–2382, <http://www.sciencedirect.com/science/article/pii/S135223100701151X>, 2008.
- 5 Janssen, Nicole, A. H., Gerard, H., Milena, S.-L., Paul, F., van Bree Leendert, ten Brink Harry, Menno, K., Atkinson Richard, W., Ross, A. H., Bert, B., and Cassee Flemming, R.: Black Carbon as an Additional Indicator of the Adverse Health Effects of Airborne Particles Compared with PM₁₀ and PM_{2.5}, *Environmental Health Perspectives*, 119, 1691–1699, <https://doi.org/10.1289/ehp.1003369>, <https://doi.org/10.1289/ehp.1003369>, 2011.
- Jimenez, J. L., Canagaratna, M. R., Donahue, N. M., Prevot, A. S. H., Zhang, Q., Kroll, J. H., DeCarlo, P. F., Allan, J. D., Coe, H., Ng, N. L.,
10 Aiken, A. C., Docherty, K. S., Ulbrich, I. M., Grieshop, A. P., Robinson, A. L., Duplissy, J., Smith, J. D., Wilson, K. R., Lanz, V. A., Hueglin, C., Sun, Y. L., Tian, J., Laaksonen, A., Raatikainen, T., Rautiainen, J., Vaattovaara, P., Ehn, M., Kulmala, M., Tomlinson, J. M., Collins, D. R., Cubison, M. J., Dunlea, J., Huffman, J. A., Onasch, T. B., Alfarra, M. R., Williams, P. I., Bower, K., Kondo, Y., Schneider, J., Drewnick, F., Borrmann, S., Weimer, S., Demerjian, K., Salcedo, D., Cottrell, L., Griffin, R., Takami, A., Miyoshi, T., Hatakeyama, S., Shimono, A., Sun, J. Y., Zhang, Y. M., Dzepina, K., Kimmel, J. R., Sueper, D., Jayne, J. T., Herndon, S. C., Trimborn, A. M., Williams,
15 L. R., Wood, E. C., Middlebrook, A. M., Kolb, C. E., Baltensperger, U., and Worsnop, D. R.: Evolution of Organic Aerosols in the Atmosphere, *Science*, 326, 1525, <http://science.sciencemag.org/content/326/5959/1525.abstract>, 2009.
- Kirchstetter, T. W., Novakov, T., and Hobbs, P. V.: Evidence that the spectral dependence of light absorption by aerosols is affected by organic carbon, *Journal of Geophysical Research*, 109, <https://doi.org/10.1029/2004jd004999>, <https://doi.org/10.1029/2004JD004999>, 2004.
- Laeremans, M., Dons, E., Avila-Palencia, I., Carrasco-Turigas, G., Orjuela-Mendoza, J. P., Anaya-Boig, E., Cole-Hunter, T., De Nazelle,
20 A., Nieuwenhuijsen, M., and Standaert, A.: Black carbon reduces the beneficial effect of physical activity on lung function, *Medicine & Science in Sports & Exercise*, 50, 2018.
- Magee Scientific: Aethalometer Model AE33 User Manual, version 1.54. March 2016, 2016.
- Magee Scientific: Discontinuation / Model AE31-22, <https://mageesci.com/discontinuation-model-ae31-22/>, 2017.
- Magee Scientific: AE33 Aethalometer, <https://mageesci.com/our-products/ae33/>, 2019.
- 25 Norris, G., Duvall, R., Brown, S., and Bai, S.: EPA Positive Matrix Factorization (PMF) 5.0 Fundamentals and User Guide, <https://www.epa.gov/air-research/epa-positive-matrix-factorization-50-fundamentals-and-user-guide>, U.S. Environmental Protection Agency, EPA/600/R-14/108, April 2014, 2014.
- OpenStreetMap contributors: OpenStreetMap, <http://www.openstreetmap.org>, 2019.
- Petzold, A., Ogren, J. A., Fiebig, M., Laj, P., Li, S.-M., Baltensperger, U., Holzer-Popp, T., Kinne, S., Pappalardo, G., Sugimoto, N., Wehrli,
30 C., Wiedensohler, A., and Zhang, X.-Y.: Recommendations for reporting “black carbon” measurements, *Atmospheric Chemistry and Physics*, 13, 8365–8379, <https://www.atmos-chem-phys.net/13/8365/2013/>, 2013.
- R Core Team: R: A Language and Environment for Statistical Computing, R Foundation for Statistical Computing, Vienna, Austria, <https://www.R-project.org/>, 2019.
- Ramanathan, V. and Carmichael, G.: Global and regional climate changes due to black carbon, *Nature Geoscience*, 1, 221–227, <http://dx.doi.org/10.1038/ngeo156>, 2008.
35
- Reche, C., Querol, X., Alastuey, A., Viana, M., Pey, J., Moreno, T., Rodríguez, S., González, Y., Fernández Camacho, R., de la Rosa, J., Dall’Osto, M., Prévôt, A. S. H., Hueglin, C., Harrison, R. M., and Quincey, P.: New considerations for PM, Black Carbon and particle



- number concentration for air quality monitoring across different European cities, *Atmospheric Chemistry and Physics*, 11, 6207–6227, <https://doi.org/10.5194/acp-11-6207-2011>, <http://www.atmos-chem-phys.net/11/6207/2011/>, 2011.
- Reşitoğlu, İ. A., Altinişik, K., and Keskin, A.: The pollutant emissions from diesel-engine vehicles and exhaust aftertreatment systems, *Clean Technologies and Environmental Policy*, 17, 15–27, <https://doi.org/10.1007/s10098-014-0793-9>, 2015.
- 5 Ruellan, S. and Cachier, H.: Characterisation of fresh particulate vehicular exhausts near a Paris high flow road, *Atmospheric Environment*, 35, 453–468, <http://www.sciencedirect.com/science/article/pii/S1352231000001102>, 2001.
- Sandradewi, J., Prévôt, A., Weingartner, E., Schmidhauser, R., Gysel, M., and Baltensperger, U.: A study of wood burning and traffic aerosols in an Alpine valley using a multi-wavelength Aethalometer, *Atmospheric Environment*, 42, 101 – 112, <https://doi.org/10.1016/j.atmosenv.2007.09.034>, <https://www.sciencedirect.com/science/article/pii/S1352231007008072>, 2008.
- 10 Sandradewi, J., Prévôt, A. S. H., Szidat, S., Perron, N., Alfarra, M. R., Lanz, V. A., Weingartner, E., and Baltensperger, U.: Using Aerosol Light Absorption Measurements for the Quantitative Determination of Wood Burning and Traffic Emission Contributions to Particulate Matter, *Environmental Science and Technology*, 42, 3316–3323, <https://doi.org/10.1021/es702253m>, <https://doi.org/10.1021/es702253m>, 2008.
- Schiermeier, Q.: The science behind the Volkswagen emissions scandal, *Nature News*, <https://www.nature.com/news/the-science-behind-the-volkswagen-emissions-scandal-1.18426>, 2015.
- 15 Swiss Federal Office of Topography (swisstopo): The digital height model of Switzerland with a 200m grid (DHM25/200m), https://shop.swisstopo.admin.ch/en/products/height_models/dhm25200, 2010.
- Szidat, S., Prévôt, A. S. H., Sandradewi, J., Alfarra, M. R., Sýnal, H.-A., Wacker, L., and Baltensperger, U.: Dominant impact of residential wood burning on particulate matter in Alpine valleys during winter, *Geophysical Research Letters*, 34, L05 820, <http://dx.doi.org/10.1029/2006GL028325>, 2007.
- 20 Tarasova, O.: Position of the GAW Scientific Advisory Group on the use of Black Carbon terminology, https://projects.nilu.no/ccc/tfmm/malta_2012/day1/8_GAW_BC-TFMM.pptx, 13th annual TFMM meeting, 17–19 April 2012, Gozo, Malta., 2012.
- Vignati, E., Karl, M., Krol, M., Wilson, J., Stier, P., and Cavalli, F.: Sources of uncertainties in modelling black carbon at the global scale, *Atmospheric Chemistry and Physics*, 10, 2595–2611, <https://www.atmos-chem-phys.net/10/2595/2010/>, 2010.
- 25 Weilenmann, M., Favez, J.-Y., and Alvarez, R.: Cold-start emissions of modern passenger cars at different low ambient temperatures and their evolution over vehicle legislation categories, *Atmospheric Environment*, 43, 2419–2429, <http://www.sciencedirect.com/science/article/pii/S1352231009001174>, 2009.
- Weingartner, E., Saathoff, H., Schnaiter, M., Streit, N., Bitnar, B., and Baltensperger, U.: Absorption of light by soot particles: determination of the absorption coefficient by means of aethalometers, *Journal of Aerosol Science*, 34, 1445 – 1463, [https://doi.org/10.1016/S0021-8502\(03\)00359-8](https://doi.org/10.1016/S0021-8502(03)00359-8), <http://www.sciencedirect.com/science/article/B6V6B-498TSCY-2/2/d009f1a109bb1ab60855660763bb9023>, 2003.
- 30 Weinhold, B.: Global Bang for the Buck: Cutting Black Carbon and Methane Benefits Both Health and Climate, 2012.
- Zachariadis, T.: After ‘dieselgate’: Regulations or economic incentives for a successful environmental policy?, *Atmospheric Environment*, 138, 1–3, <http://www.sciencedirect.com/science/article/pii/S1352231016303430>, 2016.
- Zeileis, A. and Grothendieck, G.: **zoo**: S3 Infrastructure for Regular and Irregular Time Series, *Journal of Statistical Software*, 14, 1–27, <http://www.jstatsoft.org/v14/i06/>, 2005.
- 35 Zotter, P., Herich, H., Gysel, M., El-Haddad, I., Zhang, Y., Močnik, G., Hüglin, C., Baltensperger, U., Szidat, S., and Prévôt, A. S. H.: Evaluation of the absorption Ångström exponents for traffic and wood burning in the Aethalometer-based source apportionment using



radiocarbon measurements of ambient aerosol, Atmospheric Chemistry and Physics, 17, 4229–4249, <https://www.atmos-chem-phys.net/17/4229/2017/>, 2017.