

On-line SPME derivatization for the sensitive determination of multi-oxygenated volatile compounds in air

5 Esther Borrás¹, Luis Antonio Tortajada-Genaro², Milagro Ródenas¹, Teresa Vera¹, Thomas Speak³, Paul Seakins³, Marvin D. Shaw⁴, Alastair C. Lewis⁴, Amalia Muñoz¹

¹ Fundación Centro de Estudios Ambientales del Mediterráneo (CEAM), 46980 Paterna, Valencia, Spain

² Departamento de Química-Instituto IDM. Universitat Politècnica de València, 46022, Valencia, Spain.

10 ³ University of Leeds, LS2 9JT, Leeds, UK.

⁴ National Centre for Atmospheric Science, University of York, York YO10 5DD, UK.

Correspondence to: Amalia Muñoz (amalia@ceam.es)

Abstract. Multi-oxygenated volatile organic compounds are important markers of air pollution and precursors of ozone and secondary aerosols in both polluted and remote environments. Herein, their accurate determination was enhanced. The approach was based on an automated system for active sampling and on-fiber derivatization coupled with GC-MS technique. The method capability was determined for different compound families, such as aldehydes, ketones, α -dicarbonyls, hydroxy-aldehydes, hydroxy-ketones and, carboxylic acids. A good accuracy (<7%) was demonstrated from the results compared to Fourier-transform infrared spectroscopy (FTIR). Detection limits (LOD) of 6 - 100 pptV were achieved with a time resolution lower than 20 min. The developed method was successfully applied to the determination of multi-oxygenated compounds in air samples collected during an intercomparison campaign (EUROCHAMP-2020 project). Also, its capability and accuracy for atmospheric monitoring was demonstrated in an isoprene ozonolysis experiment. Both were carried out in the high-volume outdoor atmospheric simulation chambers (EUPHORE, 200 m³).

25 In summary, our developed technique offers near-real-time monitoring with direct sampling, which is an advantage in terms of handling and labour time for a proper quantification of trace-levels of atmospheric multi-oxygenated compounds.

1 Introduction

The interest in the assessment of multi-oxygenated volatile organic compounds, so called OVOCs, has increased significantly in recent years. These compounds exist naturally in the environment but mainly come from the photo-oxidation of hydrocarbons in the atmosphere (Mellouki et al., 2015). They play an important role in secondary organic aerosol (SOA) and ozone formation, can potentially influence climate change and cause negative health effects on humans (Atkinson and Arey, 2003). Their tropospheric concentrations are highly variable, generally at trace levels, thus adding more complexity to their determination (Gomez-Alvarez et al., 2012). Moreover, OVOCs are polar and volatile, a fact that negatively affects their determination. Given their crucial role in tropospheric chemistry, there is an urgent need for sensitive and reliable techniques.

Several technologies have been proposed for the determination of OVOCs, including Fourier transform infrared spectroscopy (FTIR), proton transfer mass spectrometry (PTR-MS), selected-ion flow-tube mass spectrometry (SIFT-MS), broadband cavity enhanced absorption spectroscopy (BBCEAS), cavity-enhanced differential optical absorption spectroscopy (CE-DOAS) (Thalman et al., 2015). Atmospheric pressure interface time-of-flight chemical ionization mass spectrometers (APITOF-CIMS) has been recently proposed for the detection of OVOCs. Nevertheless, CIMS data present overlapping ions and large uncertainties in quantification of the wide variety of species have been detected (Riva et al., 2019). Moreover, some off-line methods, generally based on chromatographic techniques, have been applied (Legreid et al., 2007). They incorporate intensive sample pre-concentration steps by passing through high volumes of air. The sampling systems are denuders, bags, lab-on-a chip devices, impingers and different types of solid-phase cartridges (Ras et al., 2009). In the recent years, solid phase microextraction (SPME) has demonstrated an extraordinary potential for the sampling of volatile compounds, supporting a more accurate determination of multi-oxygenated compounds (Zhu et al., 2015). The advantages of SPME are low cost per sample, reusability, high selective sampling for target analytes, high sensitivity, without solvent extraction - meeting the requirement of green chemistry -, high reproducibility, quite fast and it can be automated (Chen and Pawliszyn, 2004; Gómez-Alvarez, 2007; Baimatova et al., 2016).

Because of high volatility and polarity of OVOCs, their latter quantification is quite complex and usually it is necessary to derivatize prior to chromatographic analysis. Derivatization enhances chromatographic behavior or detectability and it enables a resolved separation of species which are not directly amenable to analysis due to inadequate volatility or stability (Edler et al., 2002). The main reagents for carbonyl determination include dinitrophenyl hydrazine (DNPH) – normally used in conjunction with high-performance liquid chromatography (HPLC) analysis – (Van Leeuwen et al., 2004) and O-(2,3,4,5,6-pentafluorophenyl) methylhydroxylamine (PFBHA) that is usually applied in conjunction with gas chromatography (GC) (Yu et al., 1995). Silylant reagents such as N,O-bis(trimethylsilyl)trifluoroacetamide (BSTFA) or N-methyl-n-(trimethylsilyl) trifluoroacetamide (MSTFA) were employed for hydroxyl or carboxylic functional groups derivatization (Borras and Tortajada-Genaro, 2012; Jaoui et al., 2012). These types of derivatization are performed after sampling and are followed by lengthy and aggressive sample treatment, which could potentially alter the sample

composition. Moreover, some of them were questioned due to interferences with water vapor, ozone or nitrogen dioxide (Mellouki et al., 2015).

The key to making major improvements in derivatization methodologies may lie in performing simple and automated sample preparation prior to analysis (Pang et al., 2013). In this way, PFBHA derivatization combined with SPME provides several exceptional advantages for carbonyl compounds (Bourdin and Desauziers 2014). After the sampling, derivatization takes place immediately on-fiber and the derivatives are thermally desorbed, avoiding dilution by solvents and sample alteration. However, previous studies were carried out at concentrations of analytes considerably higher (hundreds of ppbV) than those that would be present in atmospheric conditions. In addition, the decrease of fiber efficiency due to deterioration or depletion of the polymeric phase, was also observed. Another problem is the competition among analytes and the consequent reduction of reaction yields (Larroque et al., 2006).

These facts have led us (1) to explore on-line variations in the SPME derivatization which could lead to improving its performance and (2) to conduct experiments aimed at evaluating the quantification approach for atmospheric studies. Therefore, a method based on active sampling with SPME fibers and quantitative GC-MS determination of OVOCs had been developed. The research aim was to investigate on-line derivatization for decreasing the sampling times, reaching an effective capture and a complete conversion, and reducing competition between analytes. In order to evaluate the performances, the simultaneous determination of OVOCs in air samples was examined at the EUPHORE chamber facility, a highly instrumented, large-scale outdoor simulation chamber (Borras et al., 2015).

2 Experimental

2.1 Reagents

The derivatization reagents: O-(2,3,4,5,6-pentafluorobenzyl) hydroxylamine (PFBHA) (99%); N,O-bis(trimethylsilyl)trifluoroacetamide (BSTFA), N-trimethylsilyl-N-methyl trifluoroacetamide (MSTFA) and trimethylchlorosilane (TMCs) as catalyst purchased from Sigma–Aldrich (Madrid, Spain) were used directly in this study without any further purification. Methylglyoxal at 30% in water (MGLY), glyoxal (GLY), glutaraldehyde, methyl vinyl ketone (MVK), methacrolein, glycolaldehyde, hydroxyacetone, succinic acid and benzaldehyde were supplied by Fluka (Madrid, Spain). Other α -dicarbonyl compounds, such as 4-oxo-2-pentenal and E-butenedial, were synthesized (provided by Leeds University, Organic Chemistry Department).

2.2 Automated active SPME sampling coupled to GC-MS system

This methodology was carried out in four steps. The first one was the chemical modification of the fiber with PFBHA (carbonyl reagent). The second proposed step was the sampling on a cell of multi-oxygenated compounds for “on-fiber derivatization” of carbonyl compounds. The third step was the chemical modification of the fiber with MSTFA plus TMCs (hydroxyl or carboxylic compounds reagent). Finally, derivatized OVOCs on SPME were injected on GC for thermal

desorption and their analysis by mass spectrometry. These steps were carried out by an automated procedure achieved with a Combi Pal autosampler (CTC Analytics, Zwingen, Switzerland) controlled by Cycle Composer software and equipped with SPME sampling adaptors, sample trays, and a temperature-controlled agitator tray. Figure 1 shows a scheme of multi-step derivatization protocol.




Fig.1 Scheme of sampling and on-fiber derivatization steps.

For the development of our proposed methodology, a sampling system with an inert sampling line and a cell was designed. Sampling line was of sulfinert® material and it was heated at 80°C to avoid losses of sticky OVOCs compounds. The sampling cell of 5 x 4 x 4 cm was made of stainless steel. The air passed through, in a turbulent regime at 10 L min⁻¹, which corresponds to 50 cm s⁻¹, to guarantee air velocity higher than 10 cm s⁻¹, defined by some authors as a certain critical value (Gómez Alvarez et al., 2012; Augusto et al., 2001). Moreover, the sampling cell was installed just below the simulator chamber but at laboratory conditions, i.e. without the influence of solar radiation and under controlled temperature at 20°C, critical parameters for SPME sampling (Gomez-Alvarez, 2007).

The SPME selected fiber was polydimethylsiloxane/divinylbenzene (PDMS/DVB) coating, a stable flex fiber, with a needle size 23 gauge and, coating thickness of 65 µm (Sigma Aldrich, USA). This type of fiber was chosen because of its high affinity to PFBHA (Zhu et al., 2015). A robotic injection system (PAL Auto Sampler, Agilent Technologies, USA) was used. The protocol started with the conditioning of SPME fiber in the GC injector port (30 min at 200°C). By doing so, every analysis also constitutes pre-conditioning for the following sampling step avoiding fiber contamination. Secondly, a PFBHA derivatization solution (87 mg of PFBHA in 2 mL pure) was prepared and located in a reagent tray position 1. Thirdly, PFBHA headspace vapor was generated in an incubation cell under optimized conditions of temperature, agitation time and speed, and adsorption time. Fourthly, SPME doped with PFBHA was located in the sampling cell where air is passed through during a selected sampling time. Fifthly, pure MSTFA plus catalyst (40 µL plus 10 µL of TMCs) was prepared and located in a reagent tray position 2. Silylant reagent head space vapor was also generated in an incubation cell under

temperature, agitation time and speed, and adsorption time optimized conditions. Finally, the sample was analyzed by GC-MS. The chemical reactions involved in these derivatization steps are shown in Figure SI.1.

125 **2.3 Chromatographic conditions**

The sample was thermally desorbed in a GC port of an Agilent GC-MS (Santa Clara, USA) equipped with a HP-5MS column of 30 m × 0.25 mm I.D × 0.25 mm film (Agilent, Santa Clara, USA). The chromatograph was programmed at 80 °C for 2 min, then ramped at a rate of 12 °C min⁻¹ to 240 °C, 100 °C min⁻¹ to 280 °C. The injection port was held at 250 °C and the transfer line from GC to MS was held at 300 °C. Samples were injected in splitless mode, using helium as carrier at flow
130 of 1 mL min⁻¹. The EI-voltage was 70 eV, the ion source temperature was set at 200 °C and the quadrupole temperature was set at 100 °C. Full scan mode was used (m/z 50-650) to identify the most abundant ions of multi-oxygenated compounds. The selected ion chromatograms of the most abundant ions were used to quantify them.

2.4 Smog chamber facilities and reference methods

135 The on-line SPME-GC-MS optimization was carried out in the high-volume outdoor smog chambers EUPHORE (European PHOtoREactor) (Valencia, Spain). These chambers consist of two half-spherical fluoropolymeric bags, each one of 200 m³, with integrated measuring systems for monitoring pressure, humidity, temperature, precursor species, and reaction products. Pressure, relative humidity and temperature were measured using a pressure sensor (Air-DB-VOC, Sirsa, Madrid, Spain) and a dew point hydrometer (TS-2, Walz, Effeltrich, Germany). Also, a serenius 50 Ozone Monitor (Ecotech, Melbourne,
140 Australia) was also used (Borrás and Tortajada-Genaro, 2012).

The OVOCs compounds were determined by two techniques. First, samples for on-line SPME-GC-MS technique were taken during 6 h at sampling frequency of 20 min (10 L min⁻¹, sampling time: 5 min). Second, a White-type mirror system (path length of 553.5 m) coupled to a FTIR with MCT detector (NICOLET 670, Thermo Scientific, USA) was used. Spectra were collected at 1 cm⁻¹ resolution by averaging 300 scans (sampling time: 5 min). The quantification was based on aldehydic C-
145 H stretching for methylglyoxal, within the spectral region of 2750–3000 cm⁻¹ and C-C and CH₂ bands for isoprene, methyl vinyl ketone and methacrolein in 900 – 1047 cm⁻¹ by using ANIR software (Ródenas, 2008).

For the optimization of the on-line SPME-GC-MS methodology, methylglyoxal, glyoxal, glutaraldehyde, methyl vinyl ketone, methacrolein, benzaldehyde, glycoldehyde, hydroxyacetone, succinic acid, 4-oxo-2-pentenal and E-butenedial - selected carbonyl, α -dicarbonyl, hydroxyl-carbonyl compounds and carboxylic acids - were injected in the smog chamber
150 using an impinger. A stream of hot air (> 150 °C) produced by a hot gun enabled their volatilization and the transference inside the chamber at a flow of 10 L min⁻¹. Moreover, our technique was applied in an intercomparison campaign and in the monitoring of isoprene ozonolysis. Reactants and products are diluted during experiments and to determine the correct concentration values, they must be corrected. The dilution rate in the chamber was calculated from the decay of SF₆ by FTIR areas in the IR range of 762-956 cm⁻¹. The specific dilution process was determined by FTIR adding 120 $\mu\text{g m}^{-3}$ of SF₆ as a
155 non-reactive tracer (value of $1.1 \times 10^{-5} \text{ s}^{-1}$) to the reaction mixtures at the start of the experiments.

Mili-Q water was added by a sprayer system (dried cleaned air at 2 bar) into EUPHORE chamber. Dew point system was used to confirm relative humidity values.

Intercomparison study. A large intercomparison campaign of oxygenated organic compounds measurements was held at EUPHORE from mid-May to 1st June 2018 (Muñoz et al., 2019, Ródenas et al, In preparation). Taking advantage of it, our
160 proposed SPME-GC-MS plus derivatization technique was compared towards a number of instruments: four on-line instruments together with one off-line analytical method. The on-line techniques were on-line SPME-GC-MS plus derivatization, FTIR, two proton transfer time of flight mass spectrometer (PTR-ToF-MS), and a selected-ion flow-tube mass spectrometry (SIFT-MS). The off-line techniques were DNPH cartridges analyzed by LC-MS. These techniques and methodologies were operated by University of York, University of Leeds, Forschungszentrum Jülich and Fundación CEAM.
165 A detailed summary of techniques and institutions is in Table SI.1

Measurement of OVOCs at unknown concentrations were done under different relative humidity conditions (0-50% RH). After overnight cleaning, all instruments sampled background air for 1 h. After that, OVOCs were added into the simulation chamber. I.e, methacrolein, acetone, 2-butanone, hydroxyacetone, glycolaldehyde, formaldehyde, benzaldehyde, acetaldehyde, methyl vinyl ketone, glyoxal and methylglyoxal were added in a range of 40 – 60 ppbV. Samples were taken
170 during 1 h followed by the addition of water to increase the relative humidity up to 50%. Subsequently samples were taken during a 30 min period and the gas mixture was diluted within 1 h down to 50% of the initial concentration. This protocol was repeated twice.

Ozonolysis of isoprene. The ozonolysis experiment consisted in adding Isoprene, 220 ppbV - 160 μL - were fed to the photoreactor via heated air stream. O_3 was added at 23 ppbV min^{-1} from an O_2 5.0 of purity using a UV lamp, until reach 215
175 ppbV. CO was added as OH radical scavenger (230 ppm of CO, 5000 ppmV at 10L min^{-1}). Later, all the reactants were mixed for 10 min and all the instrumentation and techniques took samples during almost 6 h throughout the experiment.

3. Results and discussion

3.1 Set-up experiments of on-fiber PFBHA derivatization

The first challenge was an effective on-fiber derivatization of the carbonyl compounds to oxime products based on a
180 substitution reaction by PFBHA. For assay development, methylglyoxal was selected as model compound and a synthetic air mixture was generated at the EUPHORE smog chamber at 50 ppbV (confirmed by FTIR). Complete factorial designs were performed to study the variable effect (Table 1).

185

Table 1. Optimization experiments of on-fiber PFBHA derivatization

<i>Step</i>	<i>Variable</i>	<i>Conditions Range</i>	<i>Selected value</i>
Headspace generation	PFBHA concentration	10 – 170 g L ⁻¹	87 mg L ⁻¹
	Loading temperature	20 – 50 °C	50 °C
	Agitation time	1– 10 min	3 min
	Agitation speed	200 – 500 rpm	500 rpm
Reagent adsorption	Adsorption time	1– 10 min	4 min
On-fiber derivatization	Sampling flow	5 – 20 L min ⁻¹	10 L min ⁻¹
	Sampling time	1 – 10 min	5 min
	Incubation Time	0 – 10 min	0 min
Desorption	Time	1-15 min	10 min
	Temperature	150 – 250°C	250°C

190 The generation of PFBHA reagent vapor in a headspace mode was studied, varying reagent amount, temperature, agitation time and speed. The selection criteria were (1) maximum oxime signal; (2) minimal artifacts for the reagent depletion; (3) minimal standard deviation between replicates. Results showed that the signal saturation was achieved at PFBHA solution of 87 mg L⁻¹. In fact, higher PFBHA concentrations reduced the derivatization capacity and increased the interfering peaks as it was previously described by Yu et al., 2017. Regarding the incubation temperature, the oxime formation lightly improved
195 when incubation temperature cell increased. The best values were reported at 50 °C. The modification of agitation time and speed factors were tested also leded an improvement of reaction yield and reproducibility. Once an effective generation of the derivatizing reagent in the headspace was achieved, the fiber exposition was evaluated. The chosen adsorption time was 4 min, in accordance with previous studies (Gómez-Alvarez et al., 2012).

The next experiments were aimed at the on-fiber derivatization of carbonyl compounds. Sampling flow of 10 L min⁻¹ during
200 5 min and no-incubation time produced maximum capture of analyte at fast sampling rate. Finally, derivatized compounds were desorbed and directly transferred to the GC-MS. Injector desorption conditions (10 min at 250°C) assured totally desorption, calculated from peak areas of methylglyoxal derivatives (13.9 min, 14.2 min, 14.4 min, and 14.5 min) being also negligible the presence of underivatized chromatographic peak of methylglyoxal (retention time 7.65 min). Thus, the on-line SPME PFBHA-derivatization was completed for up to 95% methylglyoxal in a reduced time (total time 18 min) and low
205 reagent consumption (0.17 mg per assay). Also, memory effect on sampling cell was evaluated, including a blank derivatized sampled included on sampling sequence. No compounds were observed, confirming the absence of memory effect.

The reusability of PDMS/DVB fibers was tested, performing replicate experiments (> 50 assays). Since reproducible responses were registered, on-fiber derivatization is a cost-effective approach for the detection of OVOCs in air samples.

210 3.2 Determination of carbonyl and α -dicarbonyl compounds after on-fiber PFBHA derivatization

The multiplexed automated on-fiber derivatization was approached, studying the methodology for a mixture of eight carbonyl compounds, including aldehydes, ketones, aromatic aldehydes and α -dicarbonyls. Then, the air sample contained the selected compounds: methylglyoxal, glyoxal, glutaraldehyde, methyl vinyl ketone, methacrolein, benzaldehyde, 4-oxo-2-pentenal and E-butenedial.

215 The chromatograms obtained from air mixtures confirmed the correct on-fiber derivatization and later chromatographic separation process. The chromatographic oxime peaks of each carbonyl compounds and its corresponding mass spectra are reported in Figure SI.2 and SI.3. The identification of derivatives was based on the molecular ion in the EI mass spectra. The m/z fragments were 265 for both methacrolein and methyl vinyl ketone; 301, 448, 462, 490, 488, and 476, for benzaldehyde, glyoxal, methylglyoxal, glutaraldehyde, 4-oxo-2-pentenal and, E-butenedial, respectively. Also, several fragments were
 220 examined, such as ions with m/z = M-30, M-181, and M-211, resulting from loss of NO, C₆F₅CH₂, C₆F₅-CH₂NO, respectively. Table 2 summarizes the main chromatographic features for the specific oximes formed.

Table 2. Description of chromatographic peaks detected after the on-fiber derivatization using PFBHA as reagent for the carbonyl and α -dicarbonyl compounds selected.

<i>r.t</i> (min)	<i>Compound</i>	<i>Main m/z fragments</i>	<i>r.t of other oxime peaks (min)</i>
7.2	Methacrolein	84,181,235,265	7.3
7.5	Methyl vinyl ketone	181,235,265	7.6
11.9	Benzaldehyde	90,120,181,271,301	12.0
14.0	Glyoxal	181,267,418,448	14.1
14.8	Methylglyoxal	181,251,432,462	13.8, 14.2, 14.7
15.8	E-4-oxo-2-pentenal	181,307,458,488	15.6, 15.7, 16.0, 16.1, 16.2, 16.3, 16.4
16.0	Glutaraldehyde	181,279,309,460,490	-
16.1	E-butenedial	181,293,474	15.9, 16.0, 16.2

r.t = retention time

225

The number of underivatized compounds was negligible (< 1.5 %) and the number of PFBHA interference residue peaks was reduced and perfectly resolved (resolution > 1.5). The calculated recoveries ranged from 91% (glutaraldehyde) to 99.7% (methylglyoxal) as shown in Table SI. 2. Therefore, the suitability of the developed method was demonstrated for a wide

range of compounds, considering organic functionalities, molecular sizes, boiling temperatures and reactivities. Therefore, our method avoided the main limitation of SPME-based methods for multiplexed purposes. Often, the simultaneous determination of several analyte families led to a wide range of recoveries, because these methods are highly sensitive to interferences and experimental conditions, such as sampling time, analyte concentrations, passive or active systems, reagent concentration, temperature, operator handling, etc (Koziel and Novak 2002).

The effect of humidity was examined because several techniques such as PTRMS-TOF or CEAS showed an erroneous determination for air samples with high water content, depending on the applied data evaluation routine (Talman et al., 2015). Air mixtures of the model organic compounds were prepared and mixed with water vapor. Statistical test demonstrated that the humidity effect was negligible (test t, p values < 0.005).

3.3 Analytical performances of on-fiber PFBHA derivatization

OVOCs air mixtures at different concentrations were analyzed - ranged from 5 pptV to 100 ppbV -. As a selective separation was achieved, appropriate calibration curves were obtained. The regression coefficients were 0.990-0.998.

The evaluation of sensitivity was performed analyzing blank samples and serial dilutions of standard air mixtures (dilution factor 1:10). Detection limits (LOD) were calculated as 3 times the standard deviation of blank samples at the retention time corresponding of each compound (Table 3). The estimated detection limits ranged from 6 pptV (glyoxal) to 100 pptV (methacrolein), equivalent to 14 to 237 ng m⁻³. Quantification limits (LOQ) were calculated as 10 times the standard deviation of blank samples at the retention time corresponding of each compound. The limits were from 20 pptV (glyoxal) to 330 pptV (methacrolein). The LOD values were compared to those reported in previously published papers. For glyoxal, mist chamber (Cofer scrubber) obtained LOD of 2.7 pptV (Spaulding et al., 2002); DOAS system 2 pptV, CEAS systems 19 pptV (Pang et al., 2013) or 75 pptV in Pang et al., 2014. For methylglyoxal, other studies obtained LOD 170 pptV using CEAS systems (Pang et al., 2013), 185 pptV in Pang et al., 2014 or 89 pptV using PTR-ToF-MS (Michoud et al., 2018), being our detection limit of 97 pptV. The detection limit of our technique is comparable with most spectrometric methods and improves the values for small molecules such as glyoxal and methylglyoxal. This result is particularly relevant because these α -dicarbonyl compounds play a key role on SOA formation in the atmosphere. Although this research was performed in a high-volume simulation chamber (200 m³), the detection limits were below to typical concentrations of these compounds observed in ambient air.

Method precision was estimated from replicate experiments at 1, 10, 25, 50 and 100 ppbV (n=5). The percentage of relative standard deviation (RSD) was 0.2 – 7%. Other techniques reported higher errors, in Pang et al., 2013, the error was 22% using microfluidic lab-on-a-chip derivatization methodology. On the other hand, in Pang et al., 2014 the reproducibility was 6.6% for glyoxal and 7.5% for methylglyoxal using the same methodology. Therefore, we can conclude that our method presented comparable, even better, results.

Table 3. Analytical performances for the determination of carbonyl and α -dicarbonyl compounds.

<i>Compound</i>	<i>Molecular Formula</i>	<i>Linear Range (ppbV)</i>	<i>LOD (pptV)</i>	<i>LOQ (pptV)</i>	<i>RSD (%)</i>
Methacrolein	C ₄ H ₆ O	5 - 50	100	300	7
Methylvinylketone	C ₄ H ₆ O	10 - 100	70	200	6
Benzaldehyde	C ₇ H ₆ O	5 - 100	8	30	3
Glyoxal	C ₂ H ₂ O ₂	1 - 25	6	20	0.2
Methylglyoxal	C ₃ H ₄ O ₂	5 - 50	9	300	3
E-4-oxo-2-pentenal	C ₅ H ₆ O ₂	0.9 - 20	9	30	1.5
Glutaraldehyde	C ₅ H ₈ O ₂	5 - 50	50	170	5
E-Butenedial	C ₄ H ₄ O ₂	0.05 - 20	50	150	2

265

3.4 Extension to on-fiber PFBHA plus MSTFA derivatization

The on-line derivatization of hydroxyl or carboxylic groups, directly or after the described process for carbonyl groups, was studied based on a silylation reaction. For that, MSTFA was chosen as silylant. Besides previously selected ketones and aldehydes, hydroxyacetone, glycolaldehyde and succinic acid were selected as hydroxyl-carbonyl and carboxylic acid model compounds, due to their atmospheric relevance (Pospisilova et al., 2020; Mellouki et al., 2015). The derivatization sequence studied implied adsorption of PFBHA, sample loading and MSTFA plus catalyst adsorption. Thus, the oximes (-C=O groups) were generated before the formation of silanes (-OH and -COOH groups) Alternatively, BSTFA was tested as a silylant reagent, but the chromatograms showed more residual peaks and lower response for product peaks. These data suggested that short chain or branched compounds were hindered by steric impediment, as it was observed in solution derivatization (Borrás and Tortajada-Genaro, 2012).

270

The main experimental variables of MSTFA-based method were optimized from the corresponding chromatographic peaks (Table SI.3). Together with the molecular ions and PFBHA-associated fragments, the main ions were $m/z = M-15$ and $M-73$ resulting from loss of CH₃ and Si(CH₃)₃. The results indicated that the direct loading of vaporized reagent and catalyst (TMCS) was an effective way to transform PFBHA-products formed on the PDMS/DVB fiber. The absence of memory column effects and low number of artefacts were observed. Also, a successful thermal desorption of PFBHA-MSTFA products was achieved given the quantitative recoveries (> 95%).

280

Regarding the analytical performances, the LOD was 0.08 – 0.15 ppbV, the linear range was 5-150 ppbV and reproducibility, expressed as standard deviation, was 2-4 % (see Table 4). In conclusion, double derivatization treatment allowed the proper determination of OVOCs, independently of the functionalized group (-C=O, -OH and/or -COOH), even carbonyl compounds with α -hydrogen.

285

Table 4. Analytical performances for the determination of hydroxyl-carbonyl and carboxylic acid model compounds.

<i>Compound</i>	<i>Molecular Formula</i>	<i>Linear Range (ppbV)</i>	<i>LOD (pptV)</i>	<i>LOQ (pptV)</i>	<i>RSD (%)</i>
Hydroxyacetone	C ₃ H ₆ O ₂	5 - 150	150	400	4
Glycolaldehyde	C ₂ H ₄ O ₂	5 - 150	20	100	3
Succinic acid	C ₄ H ₆ O ₄	5 - 150	8	50	1

3.5 Validation in an intercomparison study

290 An intercomparison campaign for the measurement of small multi-oxygenated compounds was carried out at EUPHORE atmospheric simulator. The study included the variation of OVOCs concentration and the impact that the presence of potential interferants, such as high humidity, and dilution steps can induce in the methodologies evaluated in this work (see Table SI.1).

From the different OVOCs, we selected methylglyoxal since was previously used as OVOC model (see section 3.1). Figure 295 2 shows the average concentration in each step. Some techniques (spectroscopic and off-line) presented large interferences. The methodologies provided consistent results of methylglyoxal quantification. As can be observed, the results from SPME-GC-MS plus derivatization technique were in great agreement with the theoretical values - a known quantity of compound was introduced into EUPHORE chamber - and with the results obtained by other techniques, both optical and mass spectroscopic methodologies. In fact, we can affirm that it does not present interferences with relative humidity lower than 300 60%. For that, a Test T for paired samples was performed with a result of $\alpha < 0.5$ for our proposed methodology, confirming that high humidity did not significantly affect our measurements.




Fig. 2. Average concentration of methylglyoxal provided by on-line SPME-GC-MS, FTIR and Ionicon-PTR-ToF-MS (from Jülich). The dashed line indicates the theoretical value, according to the quantity injected into the chamber, and the steps show this adjusted value with the dilution of the chamber (according to SF₆ values). Errors from SPME and FTIR include precision and accuracy; PTR-ToF-MS error consider 3σ of precision (did not include accuracy).

The intercomparison included OVOCs identified as main degradation products of biogenic pollutants (Aschmann and Atkinson, 1994; Iannone et al., 2010). Figure 3 shows the determined concentration levels of methacrolein and methyl vinyl ketone in a mixture containing both compounds. As previously observed, the results from SPME-GC-MS plus derivatization technique agreed with the theoretical values from chamber dilutions. Regarding other techniques, the concentrations were comparable to SIFT-MS, FTIR and DNPH cartridges analyzed by LC-MS. However, PTR-ToF-MS cannot discriminate between the structural isomers of both carbonyl compounds. In this case, the sum of MVK and MACR are measured due to PTR-MS methods are not selective. Both compounds have different sensitivity factor imposing an additional inaccuracy on the data, for more details see Ródenas et al., in preparation, 2021. On the contrary, on-line SPME-GC-MS approach can be used for a reliable monitoring of both MVK and MACR in atmospheric reactions.




Fig. 3. Average concentration of methacrolein (panel a) and methyl vinyl ketone (panel b) for all compared techniques: On-line SPME-GC-MS, FTIR, DNPH-LC-MS, Ionicon-PTR-ToF-MS, SIFT-MS and, KORE-PTR-ToF-MS. Errors from SPME, FTIR and DNPH-LC-MS include precision and accuracy; Ionicon-PTR-ToF-MS, SIFT-MS and KORE-PTR-ToF-MS errors consider 3σ of precision (did not include accuracy).

3.6 Application to monitoring of an ozonolysis reaction

The ozonolysis of isoprene, one of main biogenic compound emitted to the atmosphere, was studied at the EUPHORE atmospheric simulator. On-line SPME-GC-MS plus PFBHA derivatization and MSTFA derivatization was applied for tracing the formation of the multi-oxygenated compounds. Figure 4a shows the decay of isoprene and ozone and the major

degradation product (formaldehyde) formation. The degradation rate of isoprene and ozone was fitted to first order decay as previously described in Karl et al., 2004. Regarding to minor products, the OVOCs determined were 2-butanone, methacrolein, methyl vinyl ketone, glycolaldehyde, hydroxyacetone, glyoxal and methylglyoxal. Some of them are plotted on Figure 4b. The results fitted to a standard growing for degradation products. In case of 2-butanone, the formation was fast and, after 1 h, a decay by chemical degradation was registered. The maximum concentrations were (23.6 ± 1.2) ppbV, (25.4 ± 1.3) ppbV, (4.2 ± 0.2) ppbV, (4.1 ± 0.2) ppbV, (3.8 ± 0.2) ppbV, (2.1 ± 0.1) ppbV, and (2.2 ± 0.1) ppbV, for 2-butanone, methacrolein, methyl vinyl ketone, glycolaldehyde, hydroxyacetone, glyoxal and methylglyoxal, respectively. Other OVOCs such as methyl vinyl ketone were also detected. A total of seven OVOCs were identified and quantified in the isoprene ozonolysis, in good accordance with previous studies (Karl et al., 2004; Wennberg et al., 2018).




Fig. 4. Concentration profiles obtained from ozonolysis of isoprene at the high-volume atmospheric simulation chamber. Reagents and main product determined by FTIR (panel a). Main multi-oxygenated organic compounds determined by on-line SPME-GCMS (panel b). $[\text{Isoprene}]_0 = 220$ ppV; $[\text{Ozone}]_0 = 215$ ppbV; $[\text{CO scavenger}] = 230$ ppmV; Reaction volume = 200 m^3 .

Therefore, our proposed on-line SPME-GC-MS plus derivatization enabled the accurate sensitive atmospheric monitoring of secondary pollutants. This technique will support their relevance since the ozonolysis of biogenic VOCs such as isoprene gives multifunctional oxygenated organic compounds that participate in the formation of aerosols. SOA formation during the atmospheric oxidation of biogenic organic compounds is estimated at $20\text{-}380 \text{ Tg r}^{-1}$ globally, influencing on human health and on climate (Mellouki et al., 2015).

350 4. Conclusions

The oxygenated volatile organic compounds play an important role in the atmosphere, even at low concentrations, so their reliable determination is challenging. On-line SPME-GC-MS double derivatization has demonstrated an efficient approach for alcohols, aldehydes, ketones, carboxylic acids and their combinations, independently on molecular size or structure. Compared to other techniques, such as FTIR, PTR-ToF-MS among others, this approach provides discontinuous data (20
355 min). However, on-line SPME-GC-MS method shows excellent analytical performances such as LOD (6-100 pptV), reproducibility (0.2-7%), selectivity (high resolution), cost-effectiveness and high-throughput. It is important to highlight the advantages compared to other chromatographic techniques, derived from an automated format, such as null solvent consumption, low reagent amounts, hands-off preparation, reusability of SPME fiber, robustness and high precision.

Demonstrated for the ozonolysis of isoprene, the number of potential applications is extraordinarily wide. On-line SPME-
360 GC-MS double derivatization methodology could support a better understanding of atmospheric chemistry processes and an accurate monitoring of their atmospheric levels. This technology is particularly useful in atmospheric simulation chambers for air chemistry studies. A relevant example is the research of OVOCs as secondary organic aerosols (SOA) and ozone precursors. This information should help a better assessment of their impact on human health and climate change. Moreover, after an adequate adaptation for mobile laboratories, the monitoring of atmospheric OVOCs levels is feasible.

365

Data availability. The experimental data will be available via the EUROCHAMP-2020(<https://data.eurochamp.org/data-access/chamber-experiments/>), data center as well as upon request to the contact author.

Special issue statement. This article is part of the special issue “Simulation chambers as tools in atmospheric research (AMT/ACP/GMD inter-journal SI).

370

Acknowledges

This project/work has received funding from the European Union's Horizon 2020 research and innovation programme through the EUROCHAMP-2020 Infrastructure Activity under grant agreement N° 730997 and from IMAGINA- Prometeo project (PROMETEO/2019/110 from Generalitat Valenciana) F. CEAM is partly funded by the GVA. We especially want to
375 thank Ralf Tillmann, Sergej Wedel and David Reimer, for the measurements made with PTRMS by Forschungszentrum Jülich (FZJ) institution.

References

- Aschmann, S.M., Atkinson, R. Formation Yields of Methyl Vinyl Ketone and Methacrolein from the Gas-Phase Reaction of O₃ with Isoprene. *Environ. Sci. Technol.* 28, 8, 1539-1542, <https://doi.org/10.1021/es00057a025>., 1994.
- 380 Atkinson, R., Arey, J. Gas-phase tropospheric chemistry of biogenic volatile organic compounds: A review. *Atmos. Environ.* 37(1) 197-219, [https://doi.org/10.1016/S1352-2310\(03\)00391-1](https://doi.org/10.1016/S1352-2310(03)00391-1), 2003.

- Augusto, F., Koziel, J., Pawliszyn, J. Design and Validation of Portable SPME Devices for Rapid Field Air Sampling and Diffusion-Based Calibration. *Anal. Chem.* 73, 3, 481-486, <https://doi.org/10.1021/ac000629k>, 2001.
- 385 Baimatova, N., Kenessov, B., Koziel, J.A., Carlsen, L., Bektassov, M., Demyanenko, O.P. Simple and accurate quantification of BTEX in ambient air by SPME and GC-MS. *Talanta*, 154, 1, 46-52, <https://doi.org/10.1016/j.talanta.2016.03.050>, 2016.
- Borrás, E., Tortajada-Genaro, L.A. Determination of oxygenated compounds in secondary organic aerosol from isoprene and toluene smog chamber experiments. *Intern. J. Environ. Anal. Chem.* 92, 1, 110-124, <https://doi.org/10.1080/03067319.2011.572164>, 2012.
- 390 Borrás, E., Tortajada-Genaro, L., Ródenas, M., Vera, T., Coscollá, C., Yusá, V., Muñoz, A. Gas-Phase and Particulate Products from the Atmospheric Degradation of the Organothiophosphorus Insecticide Chlorpyrifos-methyl. *Chemosphere*. 38, 888-894, <https://doi.org/10.1016/j.chemosphere.2014.11.067>, 2015.
- Bourdin, D., Desauziers, V. Development of SPME on-fiber derivatization for the sampling of formaldehyde and other carbonyl compounds in indoor air. *Anal. Bioanal. Chem.* 406, 1, 317-28, <https://doi.org/10.1007/s00216-013-7460-6>, 2014.
- 395 Chen, Y., Pawliszyn, J. Solid-Phase Microextraction Field Sampler. *Anal. Chem.* 76, 22, 6823-6828, <https://doi.org/10.1021/ac0490806>, 2004.
- Edler, M., Metze, D., Jakubowski, N., Linscheid, M. Quantification of silylated organic compounds using gas chromatography coupled to ICP-MS. *J. Anal. Atom. Spectrom.* 17, 1209-1212, <https://doi.org/10.1039/B207227K>, 2002.
- 400 Gómez-Alvarez, E. Characterisation of absorptive sampling with SPME fibres in the EUPHORE photoreactor. *Talanta*, 72, 1757-1766, <https://doi.org/10.1016/j.talanta.2007.02.013>, 2007.
- Gómez-Alvarez, E., Vázquez, M., Gligorovski, S., Wortham, H., Valcárcel, M. Characterisation and calibration of active sampling Solid Phase Microextraction applied to sensitive determination of gaseous carbonyls. *Talanta*, 88, 15, 252-258, <https://doi.org/10.1016/j.talanta.2011.10.039>, 2012.
- 405 Iannone, R., Koppmann, R., Rudolph, J. Stable carbon kinetic isotope effects for the production of methacrolein and methyl vinyl ketone from the gas-phase reactions of isoprene with ozone and hydroxyl radicals. *Atmos. Environ.* 44, 4135-4141, <https://doi.org/10.1016/j.atmosenv.2010.07.046>, 2010.
- Jaoui, M., Kleindienst, T.E., Offenberg, J.H., Lewandowski, M., Lonneman, W.A. SOA formation from the atmospheric oxidation of 2-methyl-3-buten-2-ol and its implications for PM_{2.5}. *Atmos. Chem. Phys.*, 12, 2173-2188, <https://doi.org/10.5194/acp-12-2173-2012>, 2012.
- 410 Karl, M., Brauers, T., Dorn, H.P., Holland, F., Komenda, M., Poppe, D., Rohrer, F., Rupp, L., Schaub, A., Wahner, A. Kinetic Study of the OH-isoprene and O₃-isoprene reaction in the atmosphere simulation chamber, SAPHIR. *Geophysical Research Letters*, 31, L05117, <https://doi.org/10.1029/2003GL019189>, 2004.
- 415 Koziel, J.A., Novak, I. Sampling and sample-preparation strategies based on solid-phase microextraction for analysis of indoor air. *Trends in Anal. Chem.* 21, 12, 840-850, [https://doi.org/10.1016/S0165-9936\(02\)01204-9](https://doi.org/10.1016/S0165-9936(02)01204-9), 2002.
- Larroque, V., Desauziers, V., Mocho, P. Development of a solid phase microextraction (SPME) method for the sampling of VOC traces in indoor air. *J. Environ Monit.* 1, 106-11, <https://doi.org/10.1039/B511201J>, 2006.

- 420 Legreid, G., BalzaniLööv, J., Staehelin, J., Hueglin, C., Hill, M., Buchmann, B., Prevot, A.S.H., Reimann, S. Oxygenated volatile organic compounds (OVOCs) at an urban background site in Zürich (Europe): Seasonal variation and source allocation. *Atmos. Environ.* 41, 38, 8409-8423, <https://doi.org/10.1016/j.atmosenv.2007.07.026>, 2007.
- Mellouki, A., Wallington, T.J., Chen J. Atmospheric Chemistry of Oxygenated Volatile Organic Compounds: Impacts on Air Quality and Climate. *Chem. Rev.* 115, 10, 3984-4014, <https://doi.org/10.1021/cr500549n>, 2015.
- 425 Michoud, V., Sauvage, S., Léonardis, T., Fronval, I., Kukui, A., Locoge, N., Dusanter, S. Field measurements of methylglyoxal using proton transfer reaction time-of-flight mass spectrometry and comparison to the DNPH-HPLC-UV method. *Atmos. Meas. Tech.*, 11, 5729-5740. <https://doi.org/10.5194/amt-11-5729-2018>.
- 430 Muñoz, A., Ródenas, M., Borrás, E., Brennan, A., Dellen, J., Escalante, J.M., Gretien, A., Gómez, T., Herrmann, H., Kari, E., Michoud, V., Mutzel, A., Olariu, R., Seakins, P., Tillmann, R., Vera, T., Viertanen, A., Wedel, S. Intercomparison of instruments to measure OVOCs: assessment of performance under different relevant controlled conditions (EUPHORE chambers). *Geophysical Research Abstracts Vol. 21, EGU2019-17788*, 2019.
- Pang, X., Lewis, A.C., Ródenas, M. Microfluidic lab-on-a-chip derivatization for gaseous carbonyl analysis. *J. Chrom. A.* 1296, 28, 93-103, <https://doi.org/10.1016/j.chroma.2013.04.066>, 2013.
- 435 Pang, X., Lewis, A.C., Rickard, A.R., Baeza-Romero, M.T., Adams, T.J., Ball, S.M., Daniels, M.J.S., Goodall, I.C.A., Monks, P.S., Peppe, S., Ródenas, M., Sánchez, P., Muñoz, A. A smog chamber comparison of a microfluidic derivatisation measurement of gas-phase glyoxal and methylglyoxal with other analytical technique. *Atmos. Meas. Tech.* 7, 373-389, <https://doi.org/10.5194/amt-7-373-2014>, 2014.
- 440 Pospisilova, V., Lopez-Hilfiker, F.D., Bell, D.M., El Haddad, I., Mohr, C., Huang, W., Heikkinen, L., Xiao, M., Dommen, J., Prevot, A.S.H., Baltensperger, U., Slowik, J.G. On the fate of oxygenated organic molecules in atmospheric aerosol particles. *Sci. Adv.* 6, eaax8922, <https://doi.org/10.1126/sciadv.aax8922>, 2020.
- Ras, M.R., Borruill, F., Marcé, R.M. Sampling and preconcentration techniques for determination of volatile organic compounds in air samples. *Trends in Anal. Chem.* 28, 3, 347-361, <https://doi.org/10.1016/j.trac.2008.10.009>, 2009.
- 445 Riva, M., Rantala, P., Krechmer, J.E., Peräkylä, O., Zhang, Y., Heikkinen, L., Garmash, O., Yan, C., Kulmala, M., Worsnop, D., Ehn, M. Evaluating the performance of five different chemical ionization techniques for detecting gaseous oxygenated organic species. *Atmospheric Measurement Techniques*, vol. 12, no.4, pp. 2403-2421. <https://doi.org/10.5194/amt-12-2403-2019>, 2019.
- Ródenas, M. Improvements in Spectroscopy Data Processing: Faster Production and Better Reliability of Lab Data, INTROP Report, 2008. <http://www.ceam.es/GVAceam/archivos/MRodenasINTROPReport.pdf>, 2008.
- 450 Ródenas, M. Intercomparison of on-line and off-line techniques for the measurement of oxygenated organic compounds. In preparation.
- Spaulding, R.S., Talbot, R.W., Charles, M.J. Optimization of a Mist Chamber (Cofer Scrubber) for Sampling Water-Soluble Organics in Air. *Environ. Sci. Technol.* 36, 8, 1798-1808, <https://doi.org/10.1021/es011189x>, 2002.
- 455 Thalman, R., Baeza-Romero, M.T., Ball, S.M., Borrás, E., Daniels, M.J.S., Goodall, I.C.A., Henry, S.B., Karl, T., Keutsch, F.N., Kim, S., Mak, J., Monks, P.S., Muñoz, A., Orlando, J., Peppe, S., Rickard, A.R., Ródenas, M., Sánchez, P., Seco, R., Su, L., Tyndall, G., Vázquez, M., Vera, T., Waxman, E., Volkamer, R.. Instrument intercomparison of glyoxal, methyl glyoxal and NO₂ under simulated atmospheric conditions. *Atmos. Meas. Tech.*, 8, 1835-1862, <https://doi.org/10.5194/amt-8-1835-2015>, 2015.

- 460 van Leeuwen, S., Hendriksen, L., Karst, U. Determination of aldehydes and ketones using derivatization with 2,4-dinitrophenylhydrazine and liquid chromatography-atmospheric pressure photoionization-mass spectrometry. *J. Chrom. A* 1058, 1-2, 107-12, <https://doi.org/10.1016/j.chroma.2004.08.149>, 2004.
- 465 Wennberg, P.O., Bates, K.H., Crouse, J.D., Dodson, L.G., McVay, R.C., Mertens, L.A., Nguyen, T.B., Praske, E., Schwantes, R.H., Smarte, M.D., St Clair, J.M., Teng, A.P., Zhang, X., Seinfeld, J.H. Gas-phase reactions of isoprene and its major oxidation products. *Chemical reviews*, 118, 7, 3337-3390, <https://doi.org/10.1021/acs.chemrev.7b00439>, 2018.
- Yu, R., Duan, L., Jiang, J., Hao, J. An optimized two-step derivatization method for analyzing diethylene glycol ozonation products using gas chromatography and mass spectrometry. *J. Environ. Sci*, 53, 313-321, <https://doi.org/10.1016/j.jes.2016.02.021>, 2017.
- 470 Yu, J., Jeffries, H.E., Le Lacheur, R.M. Identifying Airborne Carbonyl Compounds in Isoprene Atmospheric Photooxidation Products by Their PFBHA Oximes Using Gas Chromatography/Ion Trap Mass Spectrometry. *Environ. Sci. Technol.* 29, 8, 1923-1932, <https://doi.org/10.1021/es00008a009>, 1995.
- Zhu, W., Koziel, J.A., Cai, L., Özsoy, H.D., van Leeuwen, J. Quantification of Carbonyl Compounds Generated from Ozone-Based Food Colorants Decomposition Using On-Fiber Derivatization-SPME-GC-MS. *Chromatography*, 2, 1-18, <https://doi.org/10.3390/chromatography2010001>. 2015.

475

480