

Response to Referee #3

Thank you for carefully reading the manuscript and providing useful suggestions to improve the paper. The replies to the referee comments are given below. The referee comments are highlighted in blue with our responses in black. Some comments concerning similar issues are grouped together. The sentences in the manuscript are between the quotation marks, with the modifications in the revised manuscript in red.

General

The paper contains smoke observations over Finland. But this aspect alone is, to my opinion, not sufficient to justify publication. Meanwhile there are so many smoke observations with lidar in the literature (see review of Adam et al., 2020) and even over the North Pole (Ohneiser et al., 2021). Therefore, the goals of the paper need to better emphasized: lidar-ceilometer observations and comparison with model results is probably one goal. Another goal is the careful analysis (some kind of a feasibility study) to what extent Vaisala ceilometers (and these huge ceilometer networks) can contribute to tropospheric smoke monitoring (even in terms of mass concentration profiling). The paper is worthwhile to be published, however only after significant improvement. Furthermore, the paper contains many speculative and questionable aspects. Their own AERONET approach to derive smoke conversion factors is unacceptable. So, there are many parts that need to be significantly improved.

Major revisions are required.

Details:

Abstract:

It should be clearly stated in the beginning: What is the main goal of the paper, what is new in this paper (in view of the numerous smoke observations with lidar in the literature, see review of Adam et al., 2020). First lidar smoke observations over Finland is not a convincing argument (or goal). Recently, TROPOS people even measured smoke over the North Pole (Engelmann et al., 2020, Ohneiser et al., 2021) ... with lidar aboard an ice breaker.

To my opinion, to combine lidar and ceilometer observations (and even to include modelling) is an attractive approach. And especially, if the main goal is: ... to demonstrate the usefulness of a Vaisala ceilometer to monitor smoke in the troposphere!

However, feel free to define your specific goals! This is just a suggestion. In this context, you can then easily present all your nice smoke results on changing depolarization ratios, on this unique smoke feature with larger lidar ratios at 532 than at 355 nm, and the comparison with model results for smoke.

Thank you for the suggestion.

We have changed the title of the manuscript to better communicate the main goal of our analysis:

“ Mass concentration estimates of long-range-transported Canadian biomass burning aerosols from a multi-wavelength Raman polarization lidar and a ceilometer in Finland

”

We made modifications in abstract in the revised version and emphasized the goal of the manuscript:

“ A quantitative comparison study for Raman lidar and ceilometer observations, and for model simulations of mass concentration estimates of smoke particles is presented. Layers of biomass burning aerosol particles were observed in the lower troposphere, at 2 to 5 km height on 4 to 6 June 2019, over Kuopio, Finland. These long-range-transported smoke particles originated from a Canadian wildfire event. The most pronounced smoke plume detected on 5 June was intensively investigated. Optical properties were retrieved from the multi-wavelength Raman polarization lidar Polly^{XT}. Particle linear depolarization ratios (PDR) of this plume were measured to be 0.08 ± 0.02 at 355 nm and 0.05 ± 0.01 at 532 nm, suggesting the presence of partly coated soot particles or particles that have mixed with a small amount of dust or other non-spherical aerosol type. The layer-mean PDR at 355 nm (532 nm) decreased during the day, from ~ 0.11 (0.06) in the morning to ~ 0.05 (0.04) in

the evening; this decrease with time could be linked to the particle aging and related changes in the smoke particle shape properties. Lidar ratios were derived as 47 ± 5 sr at 355 nm and 71 ± 5 sr at 532 nm. A complete ceilometer data processing for a Vaisala CL51 is presented, including the water vapor correction for high latitude for the first time, from sensor provided attenuated backscatter coefficient to particle mass concentration. Aerosol backscatter coefficients (BSCs) were measured at four wavelengths (355, 532, 1064 nm from Polly^{XT}, and 910 nm from CL51). Two methods, based on a combined lidar and sun-photometer approach, are applied for mass concentration estimations from both Polly^{XT} and the ceilometer CL51 observations. In the first method #1 we used converted BSCs at 532 nm (from measured BSCs) by corresponding measured backscatter-related Ångström exponent, whereas in the second method #2 we used measured BSCs at each wavelength independently. A difference of $\sim 12\%$ or $\sim 36\%$ was found between Polly^{XT} and CL51 estimated mass concentrations using method #1 or #2, showing the potential of mass concentration estimates from ceilometer. Ceilometer estimations have uncertainty of $\sim 50\%$ in the mass retrieval, but the potential of the data lies in the great spatial coverage of these instruments. The mass retrievals were compared with the Modern-Era Retrospective analysis for Research and Applications, version 2 (MERRA-2) meteorological and aerosol reanalysis. The inclusion of dust (as indicated by MERRA-2 data) in the retrieved mass concentration is negligible considering the uncertainties, which also shows that ceilometer observations for mass retrievals can be used even without exact knowledge on the composition of the smoke dominant aerosol plume in the troposphere.

“

Introduction:

P 2-3: The Introduction should be improved. You mention the Mueller1999 paper, then I would add the Mueller2005 paper as well because that paper is directly related to smoke observations (and lidar inversion application). Furthermore, you need to mention this Adam 2020 review paper!

In the next step, you may want to continue with network activities (before you introduce the ceilometer network aspect), and maybe, also CALIPSO observations. Again, with clear focus on smoke. There are these Baars2019 and Khaykin2018 papers as examples for network and space lidar activities. This would show the added value towards regional to global scale smoke characterization when using networks. This motivates, to my opinion, then the next step: to analyse to what extent the existing and exciting (European) ceilometer infrastructure could do in case of smoke monitoring... and so on.... All this would corroborate the importance of the paper. Are there some smoke observations with ceilometers in the literature (I am not sure)? If yes, should be cited. If not, that would be new point to be mentioned! One may also indicate similar approaches such as the ceilometer observations of volcanic aerosols (Eyjafjalla volcanic aerosol, Emeis and Flentje papers in 2010/2011?) to indicate the usefulness of modern ceilometers to detect aerosols (and not only clouds).

Feel free to define your own specific goals of the paper. It is not very clear to me at the moment what the goals are.

Thank you for the useful comment and detailed suggestions, we have enriched our introductions, and emphasized the goal of the manuscript:

“

...
Lidars provide quantitative range-resolved information of atmospheric aerosols. Multi-wavelength Raman lidar, together with its depolarization capability, provides comprehensive information on aerosol optical and microphysical properties (Müller et al., 1999, 2005), and allow the identification of the aerosol type using the intensive optical parameters (Groß et al., 2013; Illingworth et al., 2015). Ground-based lidar networks, such as EARLINET (European Aerosol Research Lidar Network, <https://www.earlinet.org>, last access: 3 May 2021, Pappalardo et al., 2014), PollyNET (Raman and polarization lidar network, <http://picasso.tropos.de>, last access: 3 May 2021, Baars et al., 2016), and MPLNET (Micropulse Lidar Network, <https://mplnet.gsfc.nasa.gov>, last access: 20 July 2021, Welton et al., 2001) have continued to provide observations of clouds and aerosols over large spatial scales. Adam et al. (2020) present a methodology for analysing the biomass burning events recorded in the EARLINET database, and provide a literature review of lidar-derived intensive parameters of biomass burning aerosols (46 reference values from 39 cited papers), including fresh and aged ones. Lidar observations

showed that biomass burning aerosols are medium- to high-absorbing particles with an almost spherical shape and small particle size, producing medium to high lidar ratios, low depolarization ratios and high Ångström exponents (Alados-Arboledas et al., 2011; Amiridis et al., 2009; Baars et al., 2012; Müller et al., 2007; Murayama et al., 2004; Nepomuceno Pereira et al., 2014).

Spaceborne lidars such as CALIOP (Cloud-Aerosol Lidar with Orthogonal Polarization) onboard the CALIPSO (Cloud-Aerosol Lidar and Infrared Pathfinder Satellite Observations) (Winker et al., 2009), and the ADM-Aeolus lidar of European Space Agency (ESA) (Stoffelen et al., 2005) are complementary to these network observations by providing 3-D aerosol distributions around the globe, which also contribute significantly to the monitoring and documentation of the transport of the smoke (Baars et al., 2021; Kim et al., 2009; Ohneiser et al., 2020).

Numerous studies have investigated the properties of smoke plumes transported from Canadian wildfires to Europe (Ansmann et al., 2018; Fiebig et al., 2003; Hu et al., 2019; Müller et al., 2005). For example, in 2017 a record-breaking Canadian wildfire smoke event was observed over European lidar stations. The arrival of biomass burning smoke layers from this event in August 2017 was first reported by Khaykin et al. (2018). Haarig et al. (2018) present night-time lidar observations of wildfire smoke aerosols during the event in both tropospheric and stratospheric layers over Leipzig, with lidar ratios of 40–45 sr (355 nm), 65–80 sr (532 nm), 80–95 sr (1064 nm), low depolarization ratio (<0.03 at 355, 532, 1064 nm) for plumes in the troposphere and higher depolarization ratio (0.22 at 355 nm, 0.18 at 532 nm, 0.04 at 1064 nm) for plumes in the stratosphere. Later on, Baars et al. (2019) reported six months observations (from August 2017 to January 2018) of such wildfire smoke aerosols during the episode with a network of 28 EARLINET ground-based lidars in Europe, showing the aerosol properties and the evolution of the smoke layer during the long-range transport. Recently, wildfire smoke layers were measured over the North Pole with a lidar aboard the icebreaker Polarstern during the MOSAiC (Multidisciplinary drifting Observatory for the Study of Arctic Climate) expedition (Engelmann et al., 2020; Ohneiser et al., 2021). However, the spatial resolution remains sparse, as advanced lidars are expensive. Similar observational records over Northern Europe are more scarce in the literature.

Several national weather services have built up ceilometer networks for cloud monitoring (e.g., <http://ceilometer.fmi.fi>, Hirsikko et al., 2014, E-Profile: <https://e-profile.eu>, last access: 21 April 2021) with unattended operation on a 24/7 basis. Information from the large number of ceilometers in these networks can fill the gaps between advanced lidar stations. Ceilometers are single-wavelength, eye-safe backscatter lidars, originally designed to determine cloud base heights. Studies (e.g., Wiegner and Geiß, 2012) show that ceilometers can also be used to retrieve the aerosol backscatter coefficient with high accuracy. However, the accuracy of the aerosol extinction coefficient retrieval is sensitive to the estimate of the unknown lidar ratio (LR). Ceilometers typically operate in the near-infrared (1064 nm or 910 nm) but the lidar ratios for different aerosol types have usually been observed and reported only at 532 and 355 nm. Only recently have lidar ratios at 1064 nm been measured by Raman lidar (Haarig et al., 2016).

Ceilometer measurements have been used in several aerosol studies even though the instruments were originally designed to measure cloud heights. From an Arctic station, Mielonen et al. (2013) reported ceilometer observations of biomass burning plume heights from the 2010 Russian wildfires in northern Finland. Ceilometer measurements of the German Weather Service (DWD) network (<http://www.dwd.de/ceilomap>, last access: 20 July 2021) were employed to follow the progression of the volcanic ash layer (Emeis et al., 2011), and to visualise the dispersion and temporal development of the North American smoke plumes (Trickl et al., 2015). Vaughan et al. (2018) showed how a dense network of lidars and ceilometers in UK tracked the evolution of Canadian forest fire smoke. Huff et al. (2021) demonstrated that ceilometers in the Unified Ceilometer Network (UCN, <https://alg.umbc.edu/ucn/>, last access: 20 July 2021) can verify and track smoke plume transport from a prescribed fire, in Maryland. Calibrated ceilometer profiles were also used as a tool to evaluate the aerosol forecasts by the European Centre for Medium-Range Weather Forecasts (ECMWF) Integrated Forecasting System aerosol module (IFS-AER) (Flentje et al., 2021). However, ceilometer studies in the literature often only provide information of layer heights and locations, mainly in terms of attenuated backscatter. In order to analyse to what extent the existing ceilometer infrastructure could do in case of smoke monitoring, we performed a comparison study using an advanced Raman lidar, a ceilometer, and model data.

On 4–6 June 2019, biomass burning aerosol layers were observed in the lower troposphere over Kuopio, Finland. These smoke particles originated from a Canadian wildfire event. In this study, we present observations of the smoke plume from a multi-wavelength Raman polarization lidar Polly^{XT} and a Vaisala CL51 ceilometer. A combined lidar–photometer approach is presented for estimating mass concentration as a good knowledge of the

aerosol mass concentration is required from the aviation safety point of view (Schumann et al., 2011). Based on this approach, we applied two methods in this study: method #1, measured backscatter coefficients were converted to backscatter coefficients at 532 nm by corresponding measured backscatter-related Ångström exponent, and then be applied to estimate the mass concentrations; method #2, mass concentrations were estimated from measured backscatter coefficients at each wavelength (355, 532, 1064 nm from PollyXT, and 910 nm from CL51) independently. This study reports, for the first time, a quantitative comparison study for Raman lidar and ceilometer observations of smoke particles. Moreover, we demonstrate the usefulness of a Vaisala ceilometer to monitor smoke in the troposphere; the potential for mass concentration retrieval from ceilometer observations is also discussed. In addition, the mass retrievals were compared with the Modern-Era Retrospective analysis for Research and Applications, version 2 (MERRA-2) meteorological and aerosol reanalysis.

“

Now some more detailed remarks:

P6, line 176: I do not believe that you can get the backscatter coefficient at 910 or 1064 nm with an uncertainty of less than 10%. The uncertainty in the reference value is too large. And a proper Rayleigh fit at these long wavelengths almost impossible. The uncertainty is certainly always in the range of 20-30% at 910 or 1064 nm for the backscatter coefficient.

Thank you for pointing it out, we have made modifications in the revised version.

“

The retrieval methods for deriving the backscatter coefficient from ceilometers are quite mature (Wiegner et al., 2014; Wiegner and Geiß, 2012). Under favourable conditions, a relative error of the backscatter coefficient on the order of 10 % seems feasible with a careful calibration by applying the forward integration. On the contrary, significant temporal averaging of ceilometer data is required for performing a Rayleigh calibration, as the detection of molecular signals is intrinsically very difficult. Binietoglou et al. (2011) propose a two-step approach, resulting promising agreement comparing to their lidar PEARL (Potenza EARLINET Raman lidar). The uncertainty of the backscatter coefficient could be in the range of 20–30 % using the backward integration. The advantage of the forward algorithm is that calibration is required only occasionally, and it is not affected by the low SNR in the upper troposphere. However, the accuracy in deriving extinction coefficients is limited due to the unknown LR at 910 or 1064 nm and its uncertainties. In particular the presence of multi-layered aerosol distributions (with different aerosol types) may introduce more uncertainties. In addition, the uncertainty due to the neglecting the water vapor increased with the distance from the chosen reference height. In this study, we applied the Klett method (Wiegner et al., 2014) by defining the reference height as close as to the layer of interest, so that the error propagation (due to uncertainties of LR and water vapor transmission) would be minimized for that layer.

“

And the conversion (backscatter to extinction) will introduce another 20-40% uncertainty in the case of smoke layers. The lidar ratio for smoke was found to be 50, 60, 70, 80, even 110 sr in smoke observation (see Adam et al, including the ACPD version and supplementary tables). So, using, e.g., 75 sr as smoke lidar ratio at 532 nm, and the range is from 50 to 100 sr, than the error is 33%. The uncertainties are probably similar for 910 nm.

P10, lines 288-289, please re-calculate the uncertainties by assuming 20% (BSC), 30% (LR), 20% (conversion factor from literature) and 20% (particle density), probably the uncertainty is 40-50%.

Thank you for the comment. We have re-calculated the uncertainties and made modifications in the manuscript; we also added a new Table 3 for the clarity as follows in the revised version.

In section 2.2 “Polly^{XT} lidar”:

“

The relative uncertainties are in the range of 5–10 % for backscatter coefficients and depolarization ratios at 355 and 532 nm (Ansmann et al., 1992b; Baars et al., 2012). The backscatter coefficients retrieval at 1064 nm may be possible with a relative uncertainty of 15 % using only elastic signal by assuming a proper lidar ratio. The lidar ratios at 355 and 532 nm are measured with a typical relative uncertainty of ~ 20 % when the inelastic

measurements are good enough. Higher uncertainties in lidar ratio at 1064 nm ($\sim 30\%$) should be considered (Haarig et al., 2018).

Table 3. Relative uncertainties in the input parameters and in the retrieved products (in bold). The uncertainty origins are given for input parameters and denoted as: R-Raman measurement available, E-only elastic measurement for the retrieval, L-literature, A-assumption. The uncertainty in the smoke mass density (ρ) was assumed as 20 % as in Ansmann et al. (2021). Different retrieval information (R or E) is available at each wavelength with a different system (Polly^{XT} or CL51), thus different uncertainties in the backscatter coefficients (β) and lidar ratio (LR) are considered. The uncertainty in the smoke volume-to-extinction conversion factor (c_v) was assumed as 10 % for both methods, as given in Ansmann et al. (2021). The relative uncertainties in the mass concentration (m), backscatter-related Ångström exponent (BAE), and converted backscatter coefficient (β_{conv}^{532}) are obtained by the error propagation applied to Eqs. 1-5.

		Polly ^{XT}		CL51		
	λ (nm)	532	355	1064	910	
	Uncertainty					
Common	$\Delta\rho/\rho$	0.20 (L)				
	$\Delta\beta/\beta$	0.10 (R)	0.10 (R)	0.15 (E)	0.20 (E)	
Method #1	$\Delta c_v/c_v$	0.10 (L)	-			
	if $\beta(532)$	$\Delta LR/LR$	0.20 (R)	-		
	available	$\Delta BAE/BAE^*$	-	0.14	0.12	0.24
		$\Delta\beta_{conv}^{532}/\beta_{conv}^{532}^{**}$	-	0.18	0.24	0.31
		$\Delta m/m$	0.32	0.36	0.40	0.45
	if $\beta(532)$	$\Delta LR/LR$	0.30 (A)	-		
	not available	$\Delta BAE/BAE^*$	-	0.30 (A)	0.30 (A)	0.30 (A)
		$\Delta\beta_{conv}^{532}/\beta_{conv}^{532}^{**}$	-	0.33	0.51	0.36
		$\Delta m/m$	-	0.67	0.52	0.54
Method #2	$\Delta c_v/c_v$	0.10 (A)	0.10 (A)	0.10 (A)	0.10 (A)	
	$\Delta LR/LR$	0.20 (R)	0.20 (R)	0.30 (L)	0.40 (A)	
	$\Delta m/m$	0.32	0.32	0.42	0.52	

* Wavelength pair of λ and 532, ** Converted backscatter coefficient at 532 nm from λ .

We have added discussions on uncertainty studies in the revised version:

In section 3.2.1 for the method #1:

In Table 3, the uncertainties in the input parameters and the estimated mass concentrations are listed. We assume an uncertainty of 20 % in the smoke mass density (Ansmann et al., 2021). The uncertainties in backscatter coefficients at different wavelengths and lidar ratio at 532 nm follow from the discussions in Sect. 2. The conversion factor and lidar ratio at 532 nm are required as input, with assumed uncertainties of 10 % (given in Ansmann et al., 2021) and 20 % (c.f., Sect. 2.2), respectively. The uncertainties in BAE between different wavelength pairs, and in β_{conv}^{532} were obtained by error propagations to Eqs. (3,4). Note that the standard deviations of BAE from our measurements (Table 2) show lower values than their uncertainties. Finally, after applying the law of error propagation to Eq. (5), we expect an overall uncertainty in the mass concentration estimates of 32–45 %. The highest uncertainty of 45 % was found when using the ceilometer method, mainly due to the higher uncertainty of 20 % in the backscatter coefficient retrieval.

However, the lidar measurements at 532 nm are not always collocated, especially for numerous ceilometer stations. For those cases, the lidar ratio at 532 nm and the BAEs (or colour ratios) should be assumed, thus with higher uncertainties. We can assume uncertainties of 30 % in lidar ratio at 532 nm and 30 % in BAEs for all

wavelength pairs, thus, the uncertainty for the estimated mass concentrations will be over 50 % (Table 2). For the smoke particles, extended overviews of observed wavelength dependencies of backscatter coefficients can be found in Burton et al. (2012) and Adam et al. (2020).

”

In section 3.2.2 for the method #2:

”

The uncertainties in the input parameters and the estimated mass concentrations of this method #2 are listed in Table 3. The uncertainties in the conversion factors from the standard deviation in Table 2 are very small due to the limited sample number, thus 0.10 was used as proposed in Ansmann et al. (2021). The uncertainties in backscatter coefficients and lidar ratios at each wavelength follow from the discussion in Sect. 2. Uncertainties in the lidar ratio at ceilometer wavelengths are much larger, particularly, as we applied the lidar ratio value measured at 1064 nm to the ceilometer wavelength of 910 nm. Thus, we assume an uncertainty of 40 % in the ceilometer lidar ratio. The overall uncertainties in the mass concentration estimates are of about 30–50 %, with the highest uncertainty of 52 % when using ceilometer measurements.

As can be seen in Table 3, when applying the method #2, the uncertainty in mass concentration estimations is slightly lower using measured BSCs at 355 nm, whereas higher uncertainties were found when using measured BSCs at 1064 and 910 nm. The main reason lies in the high uncertainties in lidar ratios at 1064 and 910 nm. Hence, when the lidar ratio can be measured or properly estimated, and the conversion factor can be estimated under the pure aerosol type condition, method #2 is recommended. Otherwise, method #1 can be applied by using properly estimated BAEs or colour ratios.

”

P7, lines 201 – 214: I speculate that there was an air mass transport from central Europe to Finland at heights below 3 km height (not presented), when I see the backward trajectory figure for the arrival height of 4 km. And this aged European haze widely determined the observed AOD over the field sites. You mention 500 nm AODs of 0.24-0.42 (as written on page 6). And for the smoke layer the 532 nm AOD was found to be 0.02 to 0.13 (page 7, Sect 3.1.). So the smoke impact was at least not dominating. This means that the AERONET observations cannot be used to derive smoke conversion factors. This point will be further discussed below.

P9, line 256: It makes no sense to me at all to use the actual AERONET data to derive smoke conversion factors. As mentioned, the AOD was obviously dominated by European pollution, so that the conversion factors reflect European fine mode haze properties. All the efforts to get proper conversion factors from AERONET (dust, smoke, marine, etc.) were done in regions with pure dust or marine or smoke conditions, etc. One should therefore use the conversion factors presented in this Ansmann 2020 paper, or you try to use the Polly multiwavelength information (inversion) to obtain the smoke volume concentration in the smoke layer together with the backscatter and extinction coefficients in these layers, and in this way the required smoke conversion parameters. Your conversion factor of 0.21 perfectly describes the conversion factor for urban haze. The smoke conversion factors are in the range from 0.12-0.15, and thus considerably lower.

Thank you for the comments.

The smoke layer AOD only present the partial smoke AOD for the smoke on 5 June, as the values are for the selected layer (SPoI), whereas there were several layers on those days. Unfortunately, the AERONET level 2 inversion products were not available on 5 June (when there was the SPoI – selected layer), we therefore used the AERONET data on 6 June for the factor estimate in the manuscript.

We have added one new section 3.2.1 using the “Method #1”, where we applied the Ångström exponent to convert the measure backscatter coefficients to 532 nm, and used the conversion factor of 0.13 factor from literature (Ansmann et al. 2021).

We performed more analysis for the second day 6 June (when we used the AERONET factor), and we found that there could be pollution contamination on 6 June, indicated from both back trajectory and CALIPSO observations. We have added this possible inappropriate issue in the revised version.

The method used in the original manuscript is referred as method #2. The possible mixing with pollution in method #2 is now acknowledged in the revised version, and we agree with the reviewer that this is an important source of uncertainty in our analysis. However, although our observations have uncertainties, this method #2 would be the optimal way to estimate aerosol mass when good quality observations are available. Thus, we would like to keep it in the manuscript so that the readers can find information on all the possible ways to do the retrieval in the same paper.

In the revised version two methods are presented, and results from both methods are discussed. We made significant improvement concerning the mass concentration estimations (section 3.2 and 3.3) in the revised version. We didn't copy all the modifications in this reply file, please check these sections (3.2 and 3.3) in the revised version of manuscript.

3.2 Mass concentration estimation

3.2.1 Method #1: based on BAE & the conversion factor from literature

3.2.2 Method #2: BSC at each wavelength & conversion factors from site

3.3 Comparison with MERRA-2 model - wildfire smoke and dust aerosol mixture

We introduce two methods in section 3.2 "Mass concentration estimation":

" This approach was applied to both Polly^{XT} and CL51 data to estimate the mass concentration profiles for biomass burning aerosols in the SPoI. Adapting from the methods describe by Ansmann et al. (2021), we applied two methods in this study:

Method #1: Mass concentrations were estimated from the measured backscatter coefficients which were converted to 532 nm, using the corresponding measured backscatter-related Ångström exponent. The volume-to-extinction conversion factors at 532 nm from literature was applied (currently the only available wavelength for the smoke factor in the literature).

Method #2: Mass concentrations were estimated from measured backscatter coefficients at each wavelength of 355, 532, 1064 and 910 nm. The volume-to-extinction conversion factors were evaluated at corresponding wavelengths using AERONET data.

In this study, we assume that both methods can be applied appropriately, and the limitations and sources of uncertainties of method #2 will be discussed in Sect. 3.2.2. The recommendation on the chosen method will be discussed later.

"

We have modified the tables concerning two methods:

Table 2. Parameters required for the mass concentration retrieval using two methods. The smoke mass density and lidar ratio at 532 nm are common parameters required for both methods #1 and #2.

	Parameter	Wavelength	Value	References
Common	Smoke mass density (g cm ⁻³)	-	1.3	Ansmann et al. (2021)
	Lidar ratio (sr)	532	71 ± 5	This study
Method #1	Smoke volume-to-extinction conversion factor c_v (10 ⁻⁶ m)	532	0.13 ± 0.01	Ansmann et al. (2021)
	Backscatter-related Ångström exponent	355/532	2.5 ± 0.2	This study
		1064/532	2.2 ± 0.3	
		910/532	1.8 ± 0.2	
Method #2	Lidar ratio (sr)	355	47 ± 5	This study
		1064	82 ± 22	
		910	82 ± 22*	
	Fine-mode volume-to-extinction conversion factor c_v (10 ⁻⁶ m)	355	0.100 ± 0.002	This study
		532	0.211 ± 0.003	(Possible pollution contamination)
		910	0.620 ± 0.002	
		1064	0.902 ± 0.004	

* LR values measured at 1064 nm are used for LR at 910 nm.

Table 4. Parameters required for the mass concentration retrieval, considering fine dust and smoke mixture.

	Smoke		Fine dust	
Mass density (g cm ⁻³)	1.3	(Ansmann et al., 2021)	2.6	(Ansmann et al., 2012)
Depolarization ratio at 532 nm	0.03	(Haarig et al., 2018)	0.16	(Sakai et al., 2010)
Lidar ratio at 532 nm (sr)	71	this study	40	(Ansmann et al., 2019)
Volume-to-extinction conversion factor c_v (532 nm) (10 ⁻⁶ m)	method #1 method #2	0.13 0.21	(Ansmann et al., 2021) this study	0.22 0.22
				(Ansmann et al., 2019)

The goal of this method #2 is describe at the beginning of section 3.2.2. It requires measurement at only one wavelength, which would be useful for other ceilometer station where there is no lidar measurements at 532 nm.

The method #1 is recommended when the measurements at 532 nm are additionally available, or the BAE (or backscatter colour ratio) can be reasonably assumed. Nevertheless, here we suggest a second method, in which mass concentrations were estimated from measured backscatter coefficients at several wavelengths independently, and the measurement at one single wavelength (e.g., for elastic lidars and ceilometers) is required as input for each estimate. This method #2 is recommended in the regions with the pure aerosol type (dust, smoke, marine, etc) condition, where the conversion factor can be evaluated with high accuracy. The mass estimations of the SPoI from measured backscatter coefficients at each wavelength are compared in this section.

“

We have added discussions on the estimated conversion factor, and point out the uncertainties in the factor used in this method #2. We also show the possible pollution contamination for the factor.

“

The estimated conversion factor value at 532 nm of $0.211 \pm 0.003 \times 10^{-6}$ m is higher than what we used in the previous section, with the difference ($\Delta c_v = 0.08 \times 10^{-6}$ m) larger than the uncertainty. This value is higher than the values for both fresh and aged smoke observations (from 0.13 ± 0.01 to $0.17 \pm 0.02 \times 10^{-6}$ m) at several AERONET stations reported in Ansmann et al. (2021). However, Ansmann et al. (2012) also applied a high value of $0.24 \pm 0.02 \times 10^{-6}$ m for the mass concentration retrieval of smoke aerosols (fine mode) when studying lofted layers containing desert dust and biomass burning smoke. It is hard to distinguish between smoke and urban haze aerosols, as they are often small (with size up to about 1 μm in radius) and quasi-spherical aerosols. Further, the characteristic conversion factors are in the similar value range. For examples, Ansmann et al., (2011) reported a conversion factor of $0.18 \pm 0.02 \times 10^{-6}$ m for the central European haze; Mamali et al., (2018) found a factor of $0.14 \pm 0.02 \times 10^{-6}$ m for continental/pollution particles over Cyprus; Mamouri et al., (2017) computed a factor of $0.30 \pm 0.08 \times 10^{-6}$ m for continental aerosol pollution over Germany.

Air mass sources of aerosols on 6 June were investigated by the backward trajectory analysis (HYSPLIT model). It shows that some of the particles were coming from the forest fire in Canada region, while part of them were transported from Poland where urban haze could have been with smoke aerosols (e.g., Fig. 6). The aerosol subtype products (version 4.20) from CALIPSO when the orbit passing over Poland on 3 June (orbit from UTC 11:44 to 11:58) and 4 June (orbit from UTC 01:18 to 01:31) indicate the presence of polluted continental/smoke and polluted dust.

Consequently, it is possible that European pollution was mixed with Canadian smoke aerosols on 6 June in the fine-mode particles. Hence, the retrieved conversion factors cannot perfectly describe the smoke. However, in this section we still assume these factors reflect the smoke, so as to do the comparison analysis of estimated mass concentration from Polly^{XT} and CL51.




Figure 6. Five-day backward trajectories from the HYSPLIT model (a) in Frequency option, and (b) in Ensemble option, ending at 6h UTC on 6 June 2019 for Kuopio, Finland. The end location of the air mass is at 1.5 km agl in the range-transported plume.

”

P10, lines 295-300, this is a ‘pure’ speculation about dust (only fine-mode dust, no coarse mode dust), is my feeling. On the other hand, the enhanced depolarization ratio can easily be explained by non-spherical smoke. Already small deviations from the ideal spherical shape causes depolarization as Gialitaki et al., ACP, 2020 shows.

P10, lines 301-318, These paragraphs do not make any sense. I would remove this part. It is pure speculation. Sure, you may have fine dust, but without the presence of any coarse dust? Is that possible? And again, non-spherical smoke is a convincing argument for the enhanced depol values.

P11, L319-334. All this should be removed, just speculation, simply not convincing! Impossible, to accept that as a reviewer!

Thank you for the suggestions. We have changed this section as “3.3 Comparison with MERRA-2 model - wildfire smoke and dust aerosol mixture”.

The motivation for this analysis came from the MERRA-2 simulation results which indicated the presence of dust in the smoke plume. Therefore, we had to check how the inclusion of dust in our retrievals would affect the correspondence with the simulated mass profiles. The main conclusion from this exercise is that the mass retrievals are not that sensitive to aerosol types, which is good news for ceilometer retrievals as we are not able to consider mixed aerosol layers with ceilometer data only. Therefore, we feel that this discussion is a valuable addition to the manuscript and we would like to keep it. We added AIRS “Dust score” as additional dust information.

In section 3:

”

The backward trajectory analysis was performed using the HYSPLIT model. The analysis shows that particles in the SPOI had travelled about seven days from the forest fire sources (MODIS, 2019) in western Canada to North Europe (Fig. 4). The AIRS dust score map (<https://airs.jpl.nasa.gov/map/>, last access: 1 July 2021) also showed some dust presence in North America on 30 May.

”

We have clarified this in section 3.3:

“


The mass concentrations from MERRA-2 model data are used for the comparison with the lidar retrievals. An interesting feature in the MERRA-2 simulation results is the presence of dust in the SPoI. The contribution of dust to the total AOD is very low (much lower than the carbon optical depth), indicating that the dust particles are in the fine mode. However, the dust contribution to the total mass concentration is non-negligible. Low values of lidar-derived depolarization ratio suggest no significant presence of non-spherical particles, but in principle, a small amount of dust could be mixed with the smoke. It is possible that there are biomass burning aerosols and fine dust aerosols in the SPoI, as only fine dust particles should be able to remain long enough in the atmosphere to be transported from North America to Kuopio. Furthermore, the air masses in SPoI passed by the area in North America where dust was present (shown by the AIRS data).

...

In order to check how the inclusion of dust (as indicated by MERRA-2) would affect the mass concentration estimations, we assume that there were wildfire smoke and fine dust aerosol mixture in the SPoI. The POLIPHON (Polarization lidar photometer networking) method (Mamouri and Ansmann, 2014, 2017) was applied to separate fine dust (particles with radius < 500 nm) and biomass burning aerosols for the SPoI.

”

Our NASA colleagues V. Buchard and A.S. Darmenov provide the re-analysed MERRA-2 data for this manuscript, suggesting the fine dust presence. Thus, we mainly consider the fine dust and smoke mixture in the manuscript. In order to check if our conclusion is still valid when there is coarse mode dust mixture, we have also performed analysis considering coarse mode dust mixture. In the following figure, we estimate the mass concentrations by considering coarse mode dust (dc, dashed lines) mixture or fine mode dust (df, dotted lines). The total mass concentration is higher (of ~20–30 %) when considering coarse mode dust, but still within the uncertainty range. We didn't add this figure in the manuscript, but we have added discussions as follows in the revised version.



”

For the example given in Fig. 8, the fine dust contributes ~ 13 % to the extinction in the SPoI, whereas its mass concentration contributes ~ 32 % (method #1) or ~ 23 % (method #2) to the total mass concentration. However, the derived total mass concentration considering a fine dust and smoke mixture is only ~ 18 % (method #1) or ~ 4 % (method #2) higher than one assuming smoke particles only. The inclusion of a dust mixture results in slightly higher estimated mass concentration values, with a difference negligible considering the uncertainties. We have also performed POLIPHON considering coarse mode dust mixture; higher (~20–30 %) total mass concentrations were retrieved but still within the uncertainty range. The aged smoke aerosols may also introduce enhanced depolarization ratios. If we use a bigger value (e.g., 0.05) instead of 0.03 as the smoke depolarization ratio in POLIPHON, the dust impacts on the mass concentration estimations are even smaller. Hence, the mass estimations of the SPoI considering only smoke are good enough even if the plume contains small amount of dust.

Similar conclusion can also be applied to ceilometer observations. It is not possible to perform the aerosol separation using ceilometer data alone, as no depolarization information is available at this wavelength. For this instrument, only one aerosol type should always be assumed in the layer of interest, which then imparts an additional bias when estimating the mass concentration. However, we have shown in this section that ceilometer

observations for mass retrievals can be used even without exact knowledge on the composition of the smoke plume in the troposphere.

”

To continue: Surface (in situ) observation cannot be used when discussing lofted layers. And the in situ measured aerosol values are most probably enhanced because of the advected central European haze. So, the final paragraph in Sect. 3 (before Sect. 3.1) makes no sense, and should be skipped.

Thank you for the suggestion. We used in situ measurements to show that the increase in the aerosol mass concentration and absorption and scattering coefficients at the ground level was observed only after 6 June, after the deposition of the aerosol particles from this layer to the ground. The in situ measurements also demonstrated a high black carbon content and an increase in the brown carbon fraction at the ground level, indicating aerosol of biomass burning origin on 6th, when we used the AERONET factor.

But we agree with the referee that those in situ measurements don't offer much information in this paper, and we have removed all related parts (one paragraph in section 2.1, the final paragraph in Sect. 3, some sentence in the conclusion, and the figure of in situ measurements) in the revised version.

P8, line 234: Sedimentation of large particles is not a good argument here. Smoke particles always show a pronounced accumulation mode, so difference in falling speed is low, when coarse mode particles are absent. Particle aging is more likely. Smoke aging process mainly occur in the first 36-48 hours after emission, and afterwards aging is slow. At the end of this aging process, the particles are usually spherical or almost spherical in shape. Particles show an almost perfect core-shell structure (coating, OC material) and the shell is often liquid at lower heights. And the probability that smoke particle are glassy (not perfectly round) increase with decreasing temperature. That could also be a reason that you saw a decreasing trend in the depolarization values with decreasing height.

Thank you for the comment. We made modifications in the revised version:

”

The smoke particles caused **slightly enhanced** particle linear depolarization ratios (PDR) at 355 nm (532 nm) with a mean value of 0.08 ± 0.02 (0.05 ± 0.01) in the smoke layer, suggesting the presence of partly coated soot particles or particles that have mixed with a small amount of dust or other non-spherical aerosol type. The layer-mean PDR at 355 nm (532 nm) decreased during the day, from ~ 0.11 (0.06) in the morning to ~ 0.05 (0.04) in the evening. **The decrease of the PDR with time could be linked to the particle aging and related changed in the smoke particle shape properties, as stated by Baars et al. (2019).** The relative humidity (RH) profiles from GDAS1 data showed low values in the lower atmosphere (<60 % below 6 km) before 15h UTC, and even lower RH (<40 %) at the SPoI altitude. RH slightly increased in the evening. The signal in the 407 nm Raman-shifted channel was used to determine the water vapor mixing ratio profile during night-time, showing that the layer-mean RH changed from ~ 27 % at 19 h to ~ 38 % at 23 h, which was associated with the advection of a moister air mass with a water vapor mixing ratio close to $1-3$ g kg⁻¹. The smoke particles were dry, and then captured water vapor in the atmosphere during the evening. **The decreasing temperature and increasing RH also increase the probability that smoke particles become glassy.** The depolarization ratios of **aged** biomass burning aerosols (originating from Canada and/or North America) reported in the literature (Table 1) **range from 0.01 to 0.11** (0.01 to 0.08) at 532 nm (355 nm). More information of the aged smoke from other regions can be found in the literature review by Adam et al. (2020, see the Supplement).

”

Figure 6: If you include a 40 or 50% uncertainty bar to the mass concentration values, you do not need to speculate about any dust contribution!

We agree, so we have removed the Fig.6c as it shows only few information. We have added a new subfigure to show the difference on the estimated mass concentrations.

In general, I miss uncertainty bars in Figures 6 and 7. Not many, but at least one or two per lidar and ceilometer profile!

We have added the uncertainty bars.

Now we need conclusions: One conclusion should deal with the question: What is now the value of the ceilometer? The ceilometer is able to detect smoke layers even in the middle to upper troposphere? With what overall uncertainty? What about mass retrieval from ceilometer observations? Possible? Yes or no? Conversion factors for 910 nm are not available. How to proceed? ..with 910/532 nm smoke backscatter color ratios? ..to convert 910 backscatter into 532 nm backscatter for which smoke conversion factors are available.

Thank you for the very useful suggestions. We have added the colour ratio (or backscatter-related Ångström exponent) method as a new method #1 as a sub-section. Please check our previous replies. In the conclusions we have also emphasized our goal and replied to the referee's questions.

“

Two methods, based on a combined lidar and sun-photometer approach (based on AERONET products), were applied to both Polly^{XT} and CL51 data for estimating mass concentrations: method #1, measured backscatter coefficients were converted to backscatter coefficients at 532 nm by corresponding measured backscatter-related Ångström exponent, and then be applied to estimate the mass concentrations; method #2, mass concentrations were estimated from measured backscatter coefficients at each wavelength (355, 532, 1064 nm from Polly^{XT}, and 910 nm from CL51) independently. A difference of ~ 12 % or ~ 36 % was found between Polly^{XT} and CL51 estimated mass concentrations using method #1 or #2, showing that ceilometers are potential tools for mass concentration retrievals with ~ 50 % uncertainty, but with great spatial coverage. The retrieved mass concentration profiles were also compared with MERRA-2 aerosol profiles, where we considered and analysed two scenarios in the SPOI – 1) only smoke particles and 2) mixture of fine dust and smoke aerosols, and reported with the corresponding uncertainties. The inclusion of dust in the retrieved mass concentration is negligible considering the uncertainties; which indicates that ceilometer observations for mass retrievals can be used even without exact knowledge on the composition of the smoke dominant aerosol plume in the troposphere. We demonstrated the potential of the Vaisala CL51 ceilometer to contribute to atmospheric aerosol research in the vertical profile (e.g., to monitor smoke in the troposphere), from sensor-provided attenuated backscatter coefficient to particle mass concentration.

”