

Validation of Aeolus Level 2B wind products using wind profilers, ground-based Doppler wind lidars, and radiosondes in Japan

Hironori Iwai¹, Makoto Aoki¹, Mitsuru Oshiro¹, and Shoken Ishii²

¹Radio Research Institute, National Institute of Information and Communications Technology, 4-2-1 Nukuikita, Koganei,
5 Tokyo 184-8795, Japan

²Department of Aeronautics and Astronautics, Tokyo Metropolitan University, 6-6 Asahigaoka, Hino, Tokyo 191-0065,
Japan

Correspondence to: Hironori Iwai (iwai@nict.go.jp)

Abstract. The first space-based Doppler wind lidar (DWL) on board the Aeolus satellite was launched by the European
10 Space Agency (ESA) on 22 August 2018 to obtain global profiles of horizontal line-of-sight (HLOS) wind speed. In this
study, the Rayleigh-clear and Mie-cloudy winds for periods of baseline 2B02 (from 1 October to 18 December 2018) and
2B10 (from 28 June to 31 December 2019 and from 20 April to 8 October 2020) were validated using 33 wind profilers
(WPRs) installed all over Japan, two ground-based coherent Doppler wind lidars (CDWLs), and 18 GPS-radiosondes (GPS-
RSs). In particular, vertical and seasonal analyses were performed and discussed using WPR data. During the baseline 2B02
15 period, a positive bias was found to be in the ranges of 0.5 to 1.7 m s⁻¹ for Rayleigh-clear winds and 1.6 to 2.4 m s⁻¹ for Mie-
cloudy winds using the three independent reference instruments. The statistical comparisons for the baseline 2B10 period
showed smaller biases, -0.8 to 0.5 m s⁻¹ for the Rayleigh-clear and -0.7 to 0.2 m s⁻¹ for the Mie-cloudy winds. The vertical
analysis using WPR data showed that the systematic error was slightly positive in all altitude ranges up to 11 km during the
baseline 2B02 period. During the baseline 2B10 period, the systematic errors of Rayleigh-clear and Mie-cloudy winds were
20 improved in all altitude ranges up to 11 km as compared with the baseline 2B02. Immediately after the launch of Aeolus,
both Rayleigh-clear and Mie-cloudy biases were small. Within the baseline 2B02, the Rayleigh-clear and Mie-cloudy biases
showed a positive trend. For the baseline 2B10, the Rayleigh-clear wind bias was generally negative at all months except
August 2020, and Mie-cloudy wind bias gradually fluctuated. Both Rayleigh-clear and Mie-cloudy biases did not show a
marked seasonal trend and approached zero towards September 2020. The dependence of the Rayleigh-clear wind bias on
25 the scattering ratio was investigated, showing that there was no significant bias dependence on the scattering ratio during the
baseline 2B02 and 2B10 periods. Without the estimated representativeness error associated with the comparisons using WPR
observations, the Aeolus random error was determined to be 6.7 (5.1) and 6.4 (4.8) m s⁻¹ for Rayleigh-clear (Mie-cloudy)
winds during the baseline 2B02 and 2B10 periods, respectively. The main reason for the large Aeolus random errors is the
lower laser energy compared to the anticipated 80 mJ. Additionally, the large representativeness error of the WPRs is
30 probably related to the larger Aeolus random error. Using the CDWLs, the Aeolus random error estimates were in the range
of 4.5 to 5.3 (2.9 to 3.2) and 4.8 to 5.2 (3.3 to 3.4) m s⁻¹ for Rayleigh-clear (Mie-cloudy) winds during the baseline 2B02 and
2B10 periods, respectively. By taking the GPS-RS representativeness error into account, the Aeolus random error was

determined to be 4.0 (3.2) and 3.0 (2.9) m s⁻¹ for Rayleigh-clear (Mie-cloudy) winds during the baseline 2B02 and 2B10 periods, respectively.

35

1 Introduction

Accurate numerical weather prediction (NWP) is useful for commercial activities such as agriculture, fisheries, construction, transportation, and energy development, and for daily life. Since wind is one of the fundamental meteorological variables describing the atmospheric state, it is very important to understand the evolution and structure of winds for NWP.

40 Measurement of the three-dimensional global wind field is crucial for NWP and furthermore also for air quality monitoring and forecasting, climate studies, and various meteorological studies. The wind observations obtained by the global meteorological observing system, which contains radiosondes, wind profilers (WPRs), and aircrafts, are routinely assimilated in NWP models. The radiosondes, WPRs, and aircrafts during takeoff and landing provide accurate and precise vertical wind profiles. However, the observational coverage is limited from the global perspective. Satellite-borne
45 microwave scatterometers and radiometers can estimate ocean surface vector winds using microwave return from the ocean roughness. Although these instruments well capture mesoscale wind field at the ocean surface, they do not provide any profiling information. Atmospheric motion vectors (AMVs) can be retrieved from cloud and water vapour motions derived from geostationary and polar-orbit satellite images (e.g., Bormann et al., 2003). AMVs have a large coverage area and high temporal and horizontal resolutions, but the limited accuracy of AMV winds is mainly caused by significant systematic and
50 correlated errors due to uncertainties of their height assignment (e.g., Folger and Weissmann, 2014).

A space-based Doppler wind lidar (DWL) is a powerful remote sensing instrument for global wind profiling. The European Space Agency (ESA) launched on 22 August 2018 the first space-based DWL on board the Aeolus satellite, for obtaining global wind profiles (Kanitz et al., 2019; Reitebuch et al., 2020a). Aeolus carries a single payload, named Atmospheric Laser Doppler Instrument (ALADIN). ALADIN uses a single-frequency UV laser and a direct-detection system and provides
55 profiles of a single line-of-sight (LOS) wind speed on a global scale from the ground up to about 30 km in the stratosphere (ESA, 1999; Stoffelen et al., 2005, 2020; Reitebuch, 2012; Kanitz et al., 2019). The main purpose of Aeolus is to provide global wind profiles with vertical resolution and wind observation accuracy that meet for the World Meteorological Organization (WMO) observation requirements to improve NWP and to fill the gap of the current global wind observation systems. Its other main purposes are to contribute to research on the energy balance, atmospheric circulation, precipitation
60 system, southern vibration phenomenon, stratosphere/troposphere exchange (ESA, 1999; Ingmann and Straume, 2016).

The new remote sensing technology and retrieval algorithm requires a careful assessment of the quality and validity of the generated data products before releasing them to the user community. ESA released an Announcement of Opportunity (AO) in 2007 and 2014 calling for calibration and validation (CAL/VAL) proposals for Aeolus. The CAL/VAL activities include a full assessment of all aspects of the DWL wind measurement performance and stability. The National Institute of

65 Information and Communications Technology (NICT) has applied to contribute to CAL/VAL activities for Aeolus in East
Asia and the Western Pacific region. Continuous validation of horizontal LOS (HLOS) wind speed after calibration
processes is important in order to contribute to the L2C product, which results from the background assimilation of the
Aeolus HLOS winds in the European Centre for Medium-Range Weather Forecasts (ECMWF) operational prediction model.
The purposes of the project are to contribute to reducing uncertainty in Aeolus wind measurements, to validate processes for
70 improving HLOS wind speed measured by Aeolus, and to assess the quality of wind data.

The aim of this paper is therefore to validate the quality of the Aeolus HLOS winds over Japan by using measurements from
WPRs, ground-based coherent Doppler wind lidars (CDWLs), and GPS-radiosondes (GPS-RSS). The paper is organized as
follows. First, an overview of Aeolus and ALADIN is provided. Section 3 describes the WPR, CDWL, and GPS-RS
instrument setups and measurement procedures. The procedure of matching the Aeolus measurements with the reference
75 instruments' measurements is also described in Sect. 3. The intercomparison and statistical methods are addressed in Sect. 4.
Section 5 presents statistical comparisons between the Aeolus measurements and the WPR, CDWL, and GPS-RS
measurements. In Sect. 6, the main findings are summarized.

2 Overview of Aeolus and ALADIN

80 Aeolus flies in a sun-synchronous polar orbit (inclination 97°) at an altitude of about 320 km, with a period of about 90 min
and a seven-day repeat cycle. The typical ground tracks of Aeolus over Japan are shown in Fig. 1. The red and blue lines
represent the Aeolus ground tracks for ascending and descending orbits, respectively. The principal components of ALADIN
are two fully redundant diode-pumped single-frequency continuous-wave neodymium-doped yttrium-aluminium-garnet
(Nd:YAG) lasers and two diode-pumped Q-switched Nd:YAG lasers (Flight Model A (FM-A) and FM-B) with power
85 amplifiers, a 1.5-m-diameter afocal Cassegrain telescope, a direct-detection receiver, and signal processing devices. The
single-frequency Q-switched Nd:YAG lasers with a 1064.4 nm operating wavelength emit about 250 mJ output energy with
a 20 ns pulse width (full width at half maximum) operating at a pulse repetition frequency (PRF) of 50.5 Hz. Nonlinear
lithium triborate crystals are used to generate the UV laser pulses with a 354.8 nm operating wavelength. The single-
frequency Q-switched UV laser emits about 60 mJ output energy at the PRF of 50.5 Hz (Lux et al., 2020a) and a laser beam
90 divergence of $20 \mu\text{rad}$. The laser pulses are directed downward to Earth at an off-nadir angle of 35° and enter at an incident
angle of about 37.6° at the sea and land surfaces due to Earth's curvature. The FM-A laser was used until the middle of June
2019, and the FM-B laser has been used since 28 June 2019. The direct-detection receiver consists of the Cassegrain
telescope, three interferometers, and two accumulation charge-coupled devices (ACCDs). The signal backscattered by
moving atmospheric molecules (Rayleigh scattering) and aerosol and cloud particles (Mie scattering) is collected by the
afocal Cassegrain telescope. Two of the three interferometers use the double-edge technique using two Fabry–Perot
95 interferometers (Chanin et al., 1989; Flesia and Korb, 1999; Flesia and Hirt, 2000; Gentry et al., 2000), which is mainly




Figure 1. Map showing the locations of WPRs (black squares), Kobe CDWL (magenta circle), and Okinawa CDWL (yellow circle). Red and blue lines represent the typical Aeolus ground tracks for ascending and descending orbits, respectively.

sensitive to atmospheric molecules (Rayleigh channel). The other one uses a spectrometer based on a Fizeau interferometer (Schillinger et al., 2003; Morançais et al., 2004), which is sensitive to aerosol and cloud particles (Mie channel). The signals for Rayleigh and Mie channels are imaged on each ACCD after passing through relay optics (Weiler et al., 2021a). The signals imaged on the two ACCDs are converted to electrical signals and stored.

In this study, we used three different periods during the processor baseline 2B02 and 2B10 periods to assess L2B data products: 1 October 2018 to 15 May 2019 (2B02), 28 June to 31 December 2019 (2B10) and 20 April to 8 October 2020 (2B10). The first period with baseline 2B02 was within the commissioning phase, which was from the launch of Aeolus to the end of January 2019. The L2B data products with the 2B10 baseline include a bias correction for ALADIN's telescope primary (M1) mirror temperature variation (Rennie and Isaksen, 2020; Weiler et al. 2021b) and have been available for new observations since April 2020. A hot pixel correction has also been improved in the 2B10 baseline processor version. The L2B winds from 28 June to 31 December 2019 are a homogeneous reprocessed dataset using also the 2B10 processor version. We mainly discuss the measurement performance of Aeolus for Rayleigh-clear and Mie-cloudy winds during the baseline 2B02 and 2B10 periods. The baseline 2B10 period is composed of the M1 mirror and hot pixel bias corrected observations and the reprocessed data set. Rayleigh-clear winds refer to wind observations in an aerosol-free atmosphere. Mie-cloudy winds refer to winds acquired from Mie backscattered signals induced by aerosols and clouds (Witschas et al., 2020). The quality of the Aeolus wind data is indicated by validity flags. The validity flag (de Kloe et al., 2016) considers

the validity of the products. Several different technical, instrumental, and retrieving checks account for this flag, for example checking for signal and background radiation levels. It has the value 1 (valid) or 0 (not valid). We only used Aeolus products with a validity flag of 1. We also used HLOS estimated errors (theoretical) of the L2B data products. The estimated error is a theoretical value, which is estimated on the basis of measured signal levels as well as the temperature and pressure sensitivities of the Rayleigh channel response (Dabas et al., 2008).

3 Overview of reference instruments

3.1 Wind profilers

In April 2001, the Japan Meteorological Agency (JMA) started the operation of a wind profiler (WPR) network, Wind profiler Network and Data Acquisition System (WINDAS; Ishihara et al., 2006). WINDAS consists of 33 1.3-GHz-band wind profilers as of August 2021 (black squares in Fig. 1). The specifications of WPR are listed in Table 1. WINDAS can operate continuously, acquiring vertical profiles of horizontal wind speed, wind direction, vertical velocity, and signal-to-noise ratio (SNR) over the wind profilers using five beams (one vertical beam and four oblique beams). The horizontal wind

Table 1. Specifications of WPRs.

Transmitter	
Frequency (GHz)	1.35
Peak power (kW)	4.8
Pulse repetition frequency (kHz)	5, 10, 15, 20 10 (Operation)
Pulse width (μ s)	0.67, 1.33, 2, 2.66, 4
Beam width (degree)	3.9
Beam elevation angle (degree)	76, 90
Beam azimuth angle (degree)	0, 90, 180, 270
Number of beams	5
Receiver	
Antenna	Active phased array antenna
Observation altitude range (m)	294 to 11,600
Range resolution (m)	100, 150, 200, 300, 400, 600
Vertical resolution (m)	291 (Operation)
Temporal resolution for wind measurement (min)	1
Temporal resolution for averaging (min)	10

speed and wind direction are calculated from radial wind speeds by the four-beam method under strict data quality control (Adachi et al., 2005). WINDAS provides a profile of wind data with high accuracy. In operational mode, the temporal and vertical resolutions of WINDAS data are 10 min and 291 m, respectively. The minimum and maximum detection heights are 294 m and 11.6 km above the wind profiler, respectively. There are 40 range bins for one wind profile. The wind measurement accuracy of the WPRs was evaluated by comparisons with winds forecasted by the NWP model and radiosondes (Tada 2001). From the comparisons, the wind measurement accuracy of the WPRs was comparable to that from radiosonde observations. The random error (root mean square error) σ_{WPR} of zonal winds was determined to be about 3 m s⁻¹. The comparison of wind data between Aeolus and the WPRs is useful for assessing wind measurement performance and the spatiotemporal variation in the wind field.

130

135 Considering the different spatial and temporal resolutions of the WPRs and the Aeolus, data matching procedures are necessary before comparing the data obtained by the two sensors. First, the WPR data and Aeolus data need to be matched in both space and time. To achieve geographical matching, the distance between the mean positions of an Aeolus measurement and the WPR was set to be less than 100 km. To achieve temporal synchronization, we used averages of WPR wind data from 30 min before to 30 min after the passage of Aeolus. There is also a difference in the vertical resolution between

140 Aeolus measurements and WPR measurements. The horizontal wind speed and wind direction measured by the WPRs were averaged to the Aeolus bin by using the top and bottom altitudes given in the Aeolus L2B data product. After temporal and spatial collocation, the Aeolus L2B wind product closest to each WPR measurement was adopted for comparison. The horizontal wind speed and wind direction measured by the WPRs during the periods from 1 October 2018 to 15 May 2019 (baseline 2B02) and from 28 June to 31 December 2019 and from 20 April to 8 October 2020 (baseline 2B10) were used to

145 compare Aeolus HLOS wind data.

3.2 Coherent Doppler wind lidars

NICT has installed 1.54- μ m CDWLs (WINDCUBE 400S manufactured by LEOSPHERE; Cariou et al., 2006) in Kobe (34.66°N, 135.16°E; magenta circle in Fig. 1) and Okinawa (26.50°N, 127.84°E; yellow circle in Fig. 1). The specifications of the CDWLs are listed in Table 2. The CDWL in Kobe was placed on the rooftop of a building managed by Kobe City. The CDWL in Okinawa was placed on the fifth floor (25.1 m MSL) of the steel tower in Okinawa Electromagnetic Technology Center of NICT (hereafter, NICT Okinawa). In this experiment, their range bins had a length of 150 m with the center of the first bin at 300 m. With 159 range bins per beam, adjacent range bins were overlapped by 83.1 m and the maximum range was about 13.4 km depending on the aerosol load and/or cirrus clouds present. The vertical profiles of

150 horizontal wind speed and wind direction were acquired by the Doppler beam swinging (DBS; Röttger and Larsen, 1990) technique from four inclined beams (north, east, south, and west) with an elevation angle of 70°. The Doppler velocity spectra for all range bins of each beam were obtained 100,000 times on average. Since the PRF was 10 kHz, the accumulation time of each beam was 10 s. The Doppler wind speed at each bin was estimated from the averaged Doppler-

Table 2. Specifications of CDWLs.

Transmitter	
Wavelength (μm) / Frequency (THz)	1.543 / 194
Average power (W)	1.8
Pulse repetition frequency (kHz)	10
Pulse width (ns)	800
Laser beam elevation angle (degree)	-10 to +190
Laser beam azimuth angle (degree)	0 to 360
Number of beams	5
Receiver	
Telescope diameter with 2-axis scanning device (m)	0.12
Observation altitude range (m)	300 to 13,400
Range resolution (m)	150
Temporal resolution for wind measurement (s)	10
Temporal resolution for averaging (min)	60

shifted frequency spectra using the maximum likelihood estimator (Levin 1965). We evaluated the bias and random error for wind measurements of the CDWLs using the methods described by Iwai et al. (2013). Bias was estimated at 0.02 m s^{-1} using measurements from a stationary hard target for single LOS measurements. Random errors were 0.02 to 0.10 m s^{-1} from -10 to -30 dB wideband SNR and the CDWLs operated near a theoretical Cramer–Rao lower bound (Aoki et al., 2016; Rye and Hardesty, 1993). On the basis of the comparison with collocated radiosonde data, the systematic error and random error (root mean square error) σ_{CDWL} of horizontal wind speed acquired by the DBS technique were determined to be about 0.2 and 2 m s^{-1} , respectively (Aoki et al., 2015). Therefore, the CDWL measurements act as a reference owing to their low systematic and random errors that result from the coherent measurement principle of the system. As for the WPR data, the CDWL data and Aeolus data need to be matched in both space and time. To achieve geographical matching, the distance between the mean position of an Aeolus measurement and the CDWL should be less than 100 km . As mentioned earlier, we averaged Doppler velocity spectra for all range bins of each beam from 30 min before to 30 min after the passage of Aeolus, and then the vertical profiles of horizontal wind speed and wind direction were acquired by the DBS technique. As with the WPR, the horizontal wind speed and wind direction measured by the CDWLs were averaged to the Aeolus bin. In Okinawa, the vertical profiles of horizontal wind speed and wind direction measured during the periods from $18 \text{ October } 2018$ to $11 \text{ May } 2019$ (baseline 2B02) and from 28 June to $31 \text{ December } 2019$ and from 20 April to $8 \text{ October } 2020$ (baseline 2B10) were obtained to compare Aeolus HLOS wind data. In Kobe, the vertical profiles of horizontal wind speed and wind

175 direction measured during the periods from 16 October 2018 to 15 May 2019 (baseline 2B02) and from 3 September to 31
 180 December 2019 and from 20 April to 15 July 2020 (baseline 2B10) were obtained to compare Aeolus HLOS wind data.

3.3 Radiosondes

Twelve GPS-radiosondes (GPS-RSs) of type RS41-SGP produced by Vaisala were launched from NICT Okinawa (26.50°N,
 180 127.84°E; yellow circle in Fig. 1) from October to December 2018 (baseline 2B02). The specifications of the RS41-SGP are
 listed in Table 3. From September to December 2019 (baseline 2B10), six GPS-RSs were also launched from NICT Okinawa.
 An overview of the 18 obtained validation cases is given in Table 4. The GPS-RSs transmit observed data every 2 s to an
 MW41 ground receiver unit. The observed data are processed using Vaisala proprietary software (DigiCORA version). The
 vertical resolution is about 10 m at the typical ascending speed of 5 m s⁻¹. The horizontal wind speed and direction are
 185 calculated using changes in the GPS location. According to the estimated Global Climate Observing System Reference
 Upper-Air Network (GRUAN), the measurement uncertainties of the horizontal wind speed σ_{GPS-RS} and direction are
 assumed to be 0.7 m s⁻¹ and 1°, respectively (Dirksen et al., 2014). Although the measurement uncertainties are derived from
 the radiosonde of type RS92 and not RS41, there is no significant difference in the uncertainty as both radiosonde types use
 the same technique to obtain wind speed and direction (Jensen et al., 2016; Kawai et al., 2017). Since the GPS-RS wind data
 190 are obtained by direct in situ measurements, the GPS-RS observations are generally very accurate and the instrument errors
 are small. The GPS-RS measurements are suitable for use as a reference data set for the validation of Aeolus HLOS winds.

Table 3. Specifications of GPS-RSs of type RS41-SGP.

Wind speed	
Resolution (m s ⁻¹)	0.1
Velocity measurement uncertainty (m s ⁻¹)	0.7
Maximum reported wind speed (m s ⁻¹)	160
Wind direction	
Resolution (degree)	0.1
Directional measurement uncertainty (degree)	1
Wind direction range (degree)	0 to 360
Geopotential height	
Resolution (gpm)	0.1
Measurement range (gpm)	Surface to 40,000
Accuracy (gpm)	10.0

Furthermore, the observation errors can be assumed to be uncorrelated between different GPS-RSs. However, other errors arise due to the GPS-RS drift during its ascent. The averaged ascent time of the GPS-RSs was about 45 min when they reached an altitude of 25 km. The GPS-RSs launched from NICT Okinawa drifted by a horizontal distance of up to about 120 km. These values were considered when defining collocation criteria for comparisons of Aeolus and GPS-RS measurements. In this study, the GPS-RS measurements that were within 120 km horizontal distance and 60 min temporal difference from the Aeolus measurements were used for the validation. As with the WPR, the horizontal wind speed and wind direction measured by the GPS-RSs were averaged to the Aeolus bin.

Table 4. Overview of Aeolus validation cases obtained with GPS-RS launched at NICT Okinawa for baselines 2B02 and 2B10. The baseline, date, GPS-RS launch time, and Aeolus overpass time are given. The last column indicates whether Aeolus had an ascending or a descending orbit.

Baseline	Date	GPS-RS launch time (UTC)	Aeolus overpass time (UTC)	Aeolus orbit type
2B02	1 Nov 2018	21:21	21:35	Descending
	8 Nov 2018	21:20	21:35	Descending
	10 Nov 2018	09:08	09:22	Ascending
	15 Nov 2018	21:19	21:35	Descending
	24 Nov 2018	09:07	09:22	Ascending
	29 Nov 2018	21:20	21:34	Descending
	1 Dec 2018	09:07	09:22	Ascending
	6 Dec 2018	21:20	21:35	Descending
	8 Dec 2018	09:07	09:22	Ascending
	13 Dec 2018	21:20	21:34	Descending
	15 Dec 2018	09:07	09:21	Ascending
	20 Dec 2018	21:20	21:35	Descending
2B10	19 Sep 2019	22:06	21:35	Descending
	7 Nov 2019	21:20	21:35	Descending
	9 Nov 2019	09:07	09:22	Ascending
	23 Nov 2019	09:07	09:22	Ascending
	19 Dec 2019	21:20	21:34	Descending
	21 Dec 2019	09:07	09:22	Ascending

200 4 Intercomparison and statistical methods

All valid averaged wind speeds ($WS_{i=WPR,CDWL,GPS-RS}$) and directions ($wd_{i=WPR,CDWL,GPS-RS}$) measured by the WPRs, CDWLs, and GPS-RSs are projected onto the HLOS wind speed of Aeolus ($HLOS_{i=WPR,CDWL,GPS-RS}$) by means of the Aeolus azimuth angle φ_{Aeolus} , which is obtained from L2B data product, according to the following equation (Witschas et al., 2020):

$$205 \quad HLOS_i = \cos(\varphi_{Aeolus} - wd_i) \cdot ws_i . \quad (1)$$

To validate the quality of Aeolus HLOS winds ($HLOS_{Aeolus}$), the difference from the corresponding WPR, CDWL, and GPS-RS winds projected onto the Aeolus viewing direction ($HLOS_{WPR/CDWL/GPS-RS}$) is calculated according to

$$HLOS_{diff} = HLOS_{Aeolus} - HLOS_{WPR/CDWL/GPS-RS} . \quad (2)$$

210 Following Witschas et al. (2020), the difference between Aeolus HLOS winds and WPR HLOS winds ($HLOS_{diff}$) can be used to verify the thresholds for the estimated HLOS error provided in the Aeolus L2B data product during the baseline 2B02 and 2B10 periods as shown in Figs. 2 and 3, respectively. For the Rayleigh-clear winds (Figs. 2a and 3a), the lowest estimated HLOS errors are 2.3 m s^{-1} during both, baseline 2B02 and 2B10 periods. The HLOS differences remain reasonably constant until an estimated HLOS error of about 8 m s^{-1} and then increases with increasing estimated HLOS error.




Figure 2. Dependence of wind speed difference between the Aeolus HLOS and WPR HLOS winds on the estimated HLOS error given in the L2B product for (a) Rayleigh-clear winds and (b) Mie-cloudy winds for baseline 2B02. The areas on the right of the vertical dashed lines indicate the data with estimated errors larger than 8 m s^{-1} (Rayleigh) and 5 m s^{-1} (Mie), which are considered to be invalid observations.

The Mie-cloudy winds (Figs. 2b and 3b) show estimated HLOS errors of as little as 0.2 and 0.4 m s⁻¹ during the baseline
 215 2B02 and 2B10 periods, respectively. The HLOS differences are reasonably constant up to an estimated error of about 5 m
 s⁻¹ and then show a considerable increase for larger estimated HLOS errors. Therefore, only Rayleigh-clear winds with
 estimated HLOS errors smaller than 8 m s⁻¹ and Mie-cloudy winds with estimated HLOS errors smaller than 5 m s⁻¹ are
 used for the validation. These estimated HLOS error thresholds are consistent with recommendations of the Aeolus
 CAL/VAL teams (Rennie and Isaksen, 2020) and those adopted in other validation studies (e.g., Baars et al., 2020, Belova et
 220 al., 2021; Lux et al., 2020; Martin et al., 2021).

To evaluate the results of comparison between Aeolus HLOS winds and reference instruments' HLOS winds, we use mean
 differences (BIAS) and the standard deviation (STD) of the differences as:

$$\text{BIAS} = \frac{1}{N} \sum_{i=1}^N \text{HLOS}_{diff}(i), \quad (3)$$

$$\text{STD} = \sqrt{\frac{1}{N-1} \sum_{i=1}^N (\text{HLOS}_{diff}(i) - \text{BIAS})^2}, \quad (4)$$

225 where N is the number of available data points. In addition to the STD, the scaled median absolute deviation (scaled MAD)
 is calculated as

$$\text{scaled MAD} = 1.4826 \times \text{median} \left(\left| \text{HLOS}_{diff}(i) - \text{median}(\text{HLOS}_{diff}(i)) \right| \right). \quad (5)$$

MAD is used as a very robust measure for the variability of the Aeolus HLOS winds because it is less sensitive to outliers
 than the STD (Lux et al., 2020b; Witschas et al., 2020; Baars et al., 2020; Rennie and Isaksen, 2020; Martin et al., 2021).




Figure 3. Same as Fig. 2 but for baseline 2B10.

230 When a data set follows a normal distribution, the MAD value multiplied by 1.4826 (scaled MAD) is identical to the STD (Ruppert and Matteson, 2015). By assuming independence between Aeolus measurements and reference instruments' measurements, the total variance of the difference between them (squared scaled MAD) (σ_{val}^2) is the sum of the variance resulting from the Aeolus random error (σ_{Aeolus}^2) and the variance resulting from reference instruments' random error ($\sigma_{i=WPR,CDWL,GPS-RS}^2$). Thus, the Aeolus random error σ_{Aeolus} is calculated as

$$235 \quad \sigma_{Aeolus} = \sqrt{\sigma_{val}^2 - \sigma_i^2}, \quad (6)$$

where σ_{WPR} , σ_{CDWL} , and σ_{GPS-RS} are assumed to be 3, 2, and 0.7 m s⁻¹, respectively (see Section 3.1, 3.2, and 3.3). Note that this estimation of σ_{Aeolus} includes the representativeness error due to the spatial and temporal mismatch between Aeolus and reference instruments' measurements. In addition to the BIAS, STD, and scaled MAD, the correlation coefficient (R) between Aeolus HLOS winds and reference instruments' HLOS winds, and the slopes and intercepts of the linear regression lines are used to evaluate the results of comparison.

5 Results

5.1 Comparison of Aeolus and WPR wind data

5.1.1 Overall intercomparison

245 Scatterplots of Aeolus HLOS wind speed against WPR HLOS wind speed for Rayleigh-clear winds and Mie-cloudy winds during the baseline 2B02 and 2B10 periods are presented in Figs. 4 and 5, respectively. Summaries of the statistical parameters retrieved from the scatter plot analyses for the baseline 2B02 and 2B10 are given in Tables 5 and 6, respectively. During the baseline 2B02 period, the numbers of data pairs for Rayleigh-clear and Mie-cloudy winds plotted against WPR winds are 3053 and 2687, respectively. During the baseline 2B10 period, 8443 and 6050 data pairs are provided for
 250 Rayleigh-clear and Mie-cloudy wind validation, respectively, about 2.5 times the numbers during the baseline 2B02 period. The increased number of data pairs can be explained by there being about twice as many periods for the baseline 2B10. The laser energy decrease in the FM-A laser during the baseline 2B02 period led to fewer Rayleigh-clear winds that can be used for the comparison. Since 5 March 2019, Aeolus Mie-cloudy winds have been processed with a smaller horizontal averaging length of down to 10 km, also leading to more Mie-cloudy winds that can be used for comparison during the baseline 2B10
 255 period. The range-bin settings of Aeolus were changed on several occasions (Rennie and Isaksen, 2020). The number and resolution of the bins in the lower troposphere increased after 21 October 2019. Therefore, the number of available Rayleigh-clear and Mie-cloudy winds for the comparison increased during the baseline 2B10 period.

During the baseline 2B02 and 2B10 periods, the linear trend between the Rayleigh-clear (Mie-cloudy) winds and WPR winds is clearly seen for all data and both orbit phases (Figs. 4 and 5). Although the Rayleigh-clear winds for all data and both orbit phases exhibit a positive bias between 1.63 and 1.76 m s^{-1} during the baseline 2B02 period (Figs. 4a–c), no significant wind-speed-dependent bias is apparent. However, the systematic errors (biases) obtained in this study are higher than those of 0.7 m s^{-1} stipulated in the mission requirements (Ingmann and Straume, 2016). The slopes of the linear regression line of Rayleigh-clear versus WPR winds are 0.98, 0.96, and 0.90 for all data, the ascending orbit, and the descending orbit, respectively. High correlation coefficients are also found: 0.95 for all data, 0.88 for the ascending orbit, and 0.84 for the descending orbit. That is, the slopes of the fit are not significantly different from 1 and the correlation coefficients exceed 0.8. The random error represented by the scaled MAD is determined to be 7.21 to 7.49 m s^{-1} for the Rayleigh-clear winds. Lux et al. (2020b) compared the Rayleigh-clear winds measured along the Aeolus LOS with LOS winds measured with the ALADIN Airborne Demonstrator (A2D) during the WindVal III validation campaign carried out in central Europe from 17 November to 5 December 2018 (i.e., during the baseline 2B02 period). They reported a bias of 2.56 m s^{-1} with a scaled MAD of 3.57 m s^{-1} , corresponding to HLOS values of 4.25 and 5.93 m s^{-1} , respectively. It is note that the WindVal III flights were conducted for probing the ascending orbit. Witschas et al. (2020) reported a bias of 2.11 m s^{-1} with




Figure 4. Aeolus HLOS wind speed plotted against the WPR HLOS wind speed for (a, b, c) Rayleigh-clear winds and (d, e, f) Mie-cloudy winds for (a, d) all data and (b, e) ascending and (c, f) descending orbits for baseline 2B02. Corresponding least-square line fits are indicated by the thick solid lines. The fit results are shown in the insets. The $x = y$ line is represented by the dashed line.

a scaled MAD of 3.97 m s^{-1} for Rayleigh-clear winds during the same campaign (WindVal III) using an airborne $2 \mu\text{m}$ CDWL. They also reported that the slope of the linear regression line and the correlation coefficient were 0.99 and 0.95, respectively. Thus, the bias, slope, and correlation coefficient of Rayleigh-clear versus WPR winds are consistent with those derived from other Aeolus validation campaigns, but the scaled MAD is significantly larger. The scaled MAD leads to a large σ_{Aeolus} (6.56 to 6.86 m s^{-1}). The Aeolus random error of Rayleigh-clear winds is significantly larger than the 2.5 m s^{-1} stipulated in the mission requirements at 2 to 16 km altitude (Ingmann and Straume, 2016). Witschas et al. (2020) estimated a σ_{Aeolus} of 3.9 m s^{-1} for Rayleigh-clear winds by excluding the $2 \mu\text{m}$ CDWL measurement error during the commissioning phase. This discrepancy is probably related to the large representativeness error due to the large sampling volume of the WPR.

During the baseline 2B10 period, the biases of Rayleigh-clear winds are slightly negative (-0.82 , -1.11 , and -0.51 m s^{-1}) for all data and both orbit phases (Figs. 5a–c). The absolute values of the biases during the baseline 2B10 period are about half of those during the baseline 2B02 period. The slightly negative biases are generally consistent with those reported by Guo et al. (2021), who compared the Rayleigh-clear winds with winds measured with the radar wind profiler network in China from 20 April to 20 July 2020. The slopes of the linear regression line (correlation coefficients) of Rayleigh-clear versus WPR winds are 0.94 (0.90), 0.91 (0.83), and 0.92 (0.82) for all data, the ascending orbit, and the descending orbit, respectively.




Figure 5. Same as Fig. 4 but for baseline 2B10.

These values are almost the same as those of the baseline 2B02 and agree well with those reported by Guo et al. (2021). The scaled MADs (7.06 to 7.19 m s⁻¹) are marginally smaller than those of the baseline 2B02. Although the random error is significantly large, these results indicate that the Aeolus Rayleigh-clear winds are broadly consistent with WPR winds over Japan.

The same statistics are shown for the Mie-cloudy winds in Figs. 4d–f and 5d–f. The biases of Mie-cloudy versus WPR winds are positive for all data and both orbit phases (2.42, 2.60, and 2.24 m s⁻¹) during the baseline 2B02 period (Figs. 4d–f). The biases are beyond the mission requirements of Aeolus and slightly larger than the Rayleigh-clear bias (Figs. 4a–c). The slopes of the linear regression line (correlation coefficients) are 0.98 (0.95), 0.96 (0.90), and 0.94 (0.89) for all data, the ascending orbit, and the descending orbit, respectively. As with the Rayleigh-clear winds, the slopes of the fit are not significantly different from 1 and correlation coefficients exceed 0.8. The scaled MAD is determined to be 5.75–5.96 m s⁻¹ and slightly smaller than that of the Rayleigh-clear winds. Witschas et al. (2020) reported a bias of 2.26 m s⁻¹ with a scaled MAD of 2.22 m s⁻¹ for Mie-cloudy winds during the WindVal III validation campaign. The slope of the linear regression line (correlation coefficient) was 0.96 (0.92). Therefore, the bias, slope, and correlation coefficient of Mie-cloudy versus WPR winds derived in this study are almost the same as the results of Witschas et al. (2020), but the random error is significantly larger. The scaled MAD leads to a large σ_{Aeolus} (4.91 to 5.14 m s⁻¹). Witschas et al. (2020) estimated a σ_{Aeolus} of 2.0 m s⁻¹ for Mie-cloudy winds by excluding the 2 μ m CDWL measurement error during the commissioning phase. Again, the discrepancies may be caused by the larger representativeness error due to the large sampling volume of the WPR.

The same statistics are shown for the baseline 2B10 in Figs. 5d–f. For all data, the slope of the linear regression line and the correlation coefficient for the Mie-cloudy winds are 0.96 and 0.93, respectively. These values are almost the same as those of the Rayleigh-clear winds. The slopes of the linear regression line (correlation coefficient) are 0.93 (0.90) and 0.95 (0.86)

Table 5. Statistical comparison of Aeolus HLOS winds and WPR HLOS winds for baseline 2B02.

Statistical parameter	Rayleigh-clear			Mie-cloudy		
	All data	Ascending	Descending	All data	Ascending	Descending
N points	3053	1603	1450	2687	1301	1386
BIAS (m s ⁻¹)	1.69	1.63	1.76	2.42	2.60	2.24
STD (m s ⁻¹)	8.08	8.16	7.99	6.83	7.12	6.55
Scaled MAD (m s ⁻¹)	7.35	7.49	7.21	5.94	5.75	5.96
σ_{Aeolus} (m s ⁻¹)	6.71	6.86	6.56	5.12	4.91	5.14
Correlation	0.95	0.88	0.84	0.95	0.90	0.89
Slope	0.98	0.96	0.90	0.98	0.96	0.94
Intercept (m s ⁻¹)	1.75	2.46	-0.23	2.44	3.22	1.35

for ascending and descending orbits, respectively. These results indicate that the performance of Aeolus for Mie-cloudy winds is reliable over Japan. The biases of Mie-cloudy versus WPR winds are slightly negative for all data and both orbit phases (-0.51 , -0.73 , and -0.29 m s^{-1}), but these values are smaller than those of the Rayleigh-clear winds. As with the Rayleigh-clear winds, the absolute bias is slightly larger for the ascending orbit than for the descending orbit. The small bias, slope close to 1, and high correlation coefficient agree well with those reported by Guo et al. (2021). The scaled MADs are relatively large (5.56 to 5.66 m s^{-1}), but the values are smaller than those of the Rayleigh-clear winds.

To summarize, the systematic and random errors of Rayleigh-clear (Mie-cloudy) versus WPR winds for the baseline 2B10 are improved as compared with those for the baseline 2B02. In contrast to the baseline 2B02, the systematic error of Mie-cloudy winds is superior to that of Rayleigh-clear winds during the baseline 2B10 period. During the baseline 2B02 period, the systematic error is significantly larger than the strict mission requirement of 0.7 m s^{-1} specified for Aeolus HLOS winds. During the baseline 2B10 period, both Rayleigh-clear and Mie-cloudy winds generally meet the mission requirements on systematic errors. The reduced bias of the baseline 2B10 period compared to the baseline 2B02 is most likely due to the M1 mirror bias correction (Rennie and Isaksen, 2020; Weiler et al. 2021b) and the improvement of the hot pixel correction.

However, the Aeolus random error of Rayleigh-clear and Mie-cloudy winds is considerably larger than the required precision of 2.5 m s^{-1} in the free troposphere during the baseline 2B02 and 2B10 periods. The main reason for not yet achieving the mission requirement for random errors is the lower laser energy compared to the anticipated 80 mJ (Reitebuch et al. 2020a and 2020b). Additionally, the large representativeness error due to the large sampling volume of the WPR is probably related to the larger Aeolus random error. Although, from the statistical comparisons, there is no significant difference between the ascending and descending orbits with respect to the Rayleigh-clear and Mie-cloudy winds during the

Table 6. Same as Table 5 but for baseline 2B10.

Statistical parameter	Rayleigh-clear			Mie-cloudy		
	All data	Ascending	Descending	All data	Ascending	Descending
N points	8443	4294	4149	6050	3085	2965
BIAS (m s^{-1})	-0.82	-1.11	-0.51	-0.51	-0.73	-0.29
STD (m s^{-1})	7.89	7.94	7.83	6.47	6.14	6.79
Scaled MAD (m s^{-1})	7.08	7.06	7.19	5.66	5.56	5.64
σ_{Aeolus} (m s^{-1})	6.42	6.39	6.54	4.80	4.68	4.77
Correlation	0.90	0.83	0.82	0.93	0.90	0.86
Slope	0.94	0.91	0.92	0.96	0.93	0.95
Intercept (m s^{-1})	-0.74	0.07	-1.38	-0.44	0.13	-0.81

baseline 2B02 period, the absolute biases of the Rayleigh-clear and Mie-cloudy winds are slightly larger for the ascending orbit than for the descending orbit during the baseline 2B10 period.

5.1.2 Vertical distribution of wind differences

330 The vertical distributions of the bias and standard deviation of the differences between Aeolus and WPR HLOS winds for baseline 2B02 are shown in Fig. 6. The vertical distributions of the number of compared data points are shown in Fig. S1. The values are binned into bins of 1 km height. The bias uncertainties estimated at 90 % confidence level for all data are reasonably small up to about 9 km altitude (Fig. 6a). But there are very few paired data points in 10 km altitude (Figs. S1e and S1f) and thus the biases in 10 km altitude are not reliable. For all data, the biases of Rayleigh-clear and WPR HLOS
 335 winds are significantly positive in all altitude ranges and less than 3.53 m s^{-1} up to 10 km. Although there is a local maximum at 6 to 7 km altitude, Rayleigh-clear biases tend to get more negative with altitude. The larger standard deviations at 0 to 2 km altitude for ascending and descending orbits (Figs. 6b and 6c) are caused by fewer paired data points (Figs. S1a




Figure 6. Vertical profiles in 1 km bins of the HLOS wind speed differences between the Aeolus and WPR HLOS winds for (a, b, c) Rayleigh-clear winds and (d, e, f) Mie-cloudy winds for (a, d) all data and (b, e) ascending and (c, f) descending orbits for baseline 2B02. Thick black lines show the bias with the blue shaded areas corresponding to the 90% confidence interval. The red shaded areas represent 1 standard deviation on each side of the bias.

and S1b). For Mie-cloudy winds, the biases for all data are also significantly positive in all altitude ranges except for 10 to 11 km (Fig. 6d). The biases are almost constant below 2 km, but they show a negative trend with altitude above 4 km. Although the biases are also positive below 8 km during ascending and descending orbits, the vertical distributions of bias are opposite to each other above 8 km (Figs. 6e and 6f). The mission requirement of 0.7 m s^{-1} is not achieved by both Rayleigh-clear and Mie-cloudy biases in all altitude ranges.

The same statistics are shown for the baseline 2B10 in Fig. 7 and the vertical distributions of the number of compared data points are shown in Fig. S2. As with the baseline 2B02, the bias uncertainties estimated at 90 % confidence level are reasonably small up to about 11 km altitude. For all data, the biases of Rayleigh-clear and WPR HLOS winds are slightly negative in all altitude ranges and less than -1.60 m s^{-1} up to 11 km (Fig. 7a). The systematic error is less than that of the baseline 2B02 due to the M1 mirror bias correction (Rennie and Isaksen, 2020; Weiler et al. 2021b) and the improvement of the hot pixel correction (see Sect. 5.1.1). Below 2 km altitude, the Rayleigh-clear winds meet the mission requirements for systematic errors. Although there are some local maxima and minima, Rayleigh-clear biases tend to get more negative with altitude above 2 km altitude. The bias and standard deviation in the altitude range of 0 to 1 km (atmospheric boundary layer) are almost the same as those in the upper level. However, this result is different from that in the other validation studies conducted during the baseline 2B10 period (Guo et al., 2021). Guo et al. (2021) reported a large bias of 3.23 m s^{-1} with a




Figure 7. Same as Fig. 6 but for baseline 2B10.

standard deviation of 17 m s^{-1} for the Rayleigh-clear winds in the altitude range of 0 to 1 km. The vertical distributions of bias during ascending and descending orbits are opposite to each other in the altitude range of 3 to 11 km (Figs. 7b and 7c).
 355 For all data, the biases of Mie-cloudy and WPR HLOS winds are also slightly negative in all altitude ranges except for 3 to 4 km (Fig. 7d). As with the Rayleigh-clear winds, the systematic error is improved as compared with that of the baseline 2B02. Below 5 km altitude, Mie-cloudy winds meet the mission requirements on systematic errors. As with the Rayleigh-clear winds, the vertical distributions of bias during ascending and descending orbits are opposite to each other in the altitude range of 3 to 11 km. As with the baseline 2B02, both Rayleigh-clear and Mie-cloudy biases show a negative trend with
 360 altitude for all data and descending orbit, whereas they show a positive trend for ascending orbit.

5.1.3 Time series variation of wind differences

The time series variation of the bias and standard deviation of the differences between Aeolus and WPR HLOS winds during the baseline 2B02 period are shown in Fig. 8. Immediately after the launch of Aeolus, the biases of the Rayleigh-clear and




Figure 8. Monthly averaged values of wind speed differences between the Aeolus and WPR HLOS winds for (a, b, c) Rayleigh-clear winds and (d, e, f) Mie-cloudy winds for (a, d) all data and (b, e) ascending and (c, f) descending orbits for baseline 2B02. Thick black lines show the bias with the blue shaded areas corresponding to the 90% confidence interval. The red shaded areas represent 1 standard deviation on each side of the bias.

365 Mie-cloudy winds are small for all data and both orbit phases. With time, the Rayleigh-clear and Mie-cloudy biases increase for all data and both orbit phases. The Rayleigh-clear bias reaches its maximum in January 2019. For the Mie-cloudy winds, the maximums occur in January and February 2019 for ascending and descending orbits, respectively. The Rayleigh-clear and Mie-cloudy biases tend to get more positive until April 2019, whereas they show a negative trend at the end of the baseline 2B02 period.

370 For the baseline 2B10, the same statistics are shown in Fig. 9. For all data, the biases of Rayleigh-clear and WPR HLOS winds are generally negative at all months except August 2020, but the biases do not show a significant seasonal trend (Fig. 9a). The standard deviations of Rayleigh-clear and WPR HLOS data gradually increase with time (from 6.34 to 8.77 m s^{-1}). A possible reason is the decrease in the level of the received signal after passing through the telescope (Reitebuch et al. 2020a and 2020b). The higher range-bin resolution in the lower troposphere after 21 October 2019 can also lead to increase

375 in the random error. The absolute biases are generally larger for the ascending orbit than for the descending orbit (Figs. 9b and 9c). For all data, the biases of Mie-cloudy and WPR HLOS winds gradually fluctuate and do not show a significant seasonal trend (Fig. 9d). The bias and standard deviation of Mie-cloudy winds are generally smaller than those of Rayleigh-clear winds. There is no significant increase in the standard deviations of Mie-cloudy winds with time, because the Mie return signal does not only depend on the laser energy but also on the presence of aerosols or clouds (Martin et al., 2021). It



Figure 9. Same as Fig. 8 but for baseline 2B10.

380 is interesting to note that the fluctuation of the bias is stronger for the descending orbit than for the ascending orbit in 2019
 (Figs. 9e and 9f). However, the biases for both orbit phases approach zero towards September 2020.

5.1.4 Rayleigh-clear wind bias dependence on scattering ratio

385 The scattering ratio on the Rayleigh channel is defined as the ratio of the total scattering signal (particles and molecules) to
 the molecular scattering signal. When the scattering ratio is large, a strong narrowband Mie return signal partly enters the
 Rayleigh spectrometer, changing the sensitivity of the Rayleigh channel (Witschas et al. 2020). Using the L2B products
 within the commissioning phase, Witschas et al. (2020) reported that the scattering ratio has a considerable influence on the
 bias of Rayleigh-clear winds. The dependence of the Rayleigh-clear wind bias on the scattering ratio given in the L2B
 product is shown in Fig. 10. It can be seen that the scattering ratio varies between 1.1 and 1.4 for baseline 2B02 and between
 390 1.05 and 1.65 for baseline 2B10. This means that the determination of the scattering ratio and the threshold for classifying
 the Rayleigh-clear winds changed between the baselines 2B02 and 2B10. During the baseline 2B02 period, the biases of
 Rayleigh-clear and WPR HLOS winds are positive in the range of 1.38 and 2.21 m s^{-1} (Fig. 10a). Since there is no




Figure 10. Dependence of wind speed differences between the Aeolus Rayleigh-clear and WPR HLOS winds on scattering ratio during the baseline (a) 2B02 and (b) 2B10 periods.

significant bias dependence on the scattering ratio, the influence of the cross talk of narrowband Mie return signals to the Rayleigh channel is not confirmed. This result is different from that obtained in Witschas et al. (2020). During the baseline 2B10 period, the Rayleigh-clear winds exhibit a slightly negative bias and there is no significant bias dependence on the scattering ratio (Fig. 10b). This means that the correction scheme of the scattering ratio was improved in the L2B processor.

5.2 Comparison of Aeolus and CDWL wind data

Scatterplots of Aeolus HLOS winds against CDWL HLOS winds for Rayleigh-clear and Mie-cloudy winds during the baseline 2B02 period are presented in Fig. 11. Summaries of the statistical parameters retrieved from the scatter plot analysis for the baseline 2B02 and 2B10 are given in Table 7. While Okinawa is located at the southern edge of the subtropical jet stream, Kobe is located just below the subtropical jet stream. Thus, the CDWL at Kobe sampled a higher wind speed of the subtropical jet stream. It can be seen that the acquired HLOS wind speed range is wider for Kobe than for Okinawa in Fig. 11. Both Rayleigh-clear and Mie-cloudy winds exhibit a slightly positive bias. The different colors indicate whether Aeolus had an ascending orbit (red) or descending orbit (blue). There is no significant difference between the ascending and descending orbits. The slopes of the linear regression lines are 1.05 (Rayleigh) and 1.05 (Mie) at Kobe and 0.99 (Rayleigh) and 1.01 (Mie) at Okinawa. The correlation coefficients are 0.98 (Rayleigh) and 0.98 (Mie) at Kobe and 0.93 (Rayleigh) and 0.97 (Mie) at Okinawa. That is, the slopes of the fit and the correlation coefficients of Rayleigh-clear and Mie-cloudy winds are not significantly different from 1 at Kobe and Okinawa. The intercepts of the linear regression lines are determined to be 0.61 m s⁻¹ (Rayleigh) and 1.76 m s⁻¹ (Mie) at Kobe and 1.07 m s⁻¹ (Rayleigh) and 2.37 m s⁻¹ (Mie) at Okinawa. A similar

Table 7. Statistical comparison of Aeolus HLOS winds and CDWL HLOS winds.

Baseline	2B02				2B10			
	Kobe		Okinawa		Kobe		Okinawa	
	Rayleigh	Mie	Rayleigh	Mie	Rayleigh	Mie	Rayleigh	Mie
N points	59	57	74	119	204	136	232	220
BIAS (m s ⁻¹)	0.46	1.63	1.08	2.38	-0.81	0.16	-0.48	-0.26
STD (m s ⁻¹)	6.17	4.80	6.57	3.64	5.69	5.15	6.53	4.74
Scaled MAD (m s ⁻¹)	4.92	3.55	5.68	3.76	5.21	3.92	5.58	3.86
σ_{Aeolus} (m s ⁻¹)	4.49	2.93	5.31	3.19	4.81	3.37	5.21	3.30
Correlation	0.98	0.98	0.93	0.97	0.96	0.97	0.79	0.86
Slope	1.05	1.05	0.99	1.01	0.98	1.02	1.03	0.86
Intercept (m s ⁻¹)	0.61	1.76	1.07	2.37	-0.88	0.22	-0.52	-0.04

finding is obtained from the biases that are 0.46 m s^{-1} (Rayleigh) and 1.63 m s^{-1} (Mie) at Kobe and 1.08 m s^{-1} (Rayleigh) and 2.38 m s^{-1} (Mie) at Okinawa. Both Rayleigh-clear and Mie-cloudy winds exhibit a slightly positive bias. Except for Rayleigh-clear winds measured at Kobe, the systematic error does not achieve the mission requirement of 0.7 m s^{-1} . This result is similar to that in the comparisons of Aeolus and WPR measurements, which provides biases of 1.69 m s^{-1} (Rayleigh) and 2.42 m s^{-1} (Mie). The systematic error of CDWL observations is smaller than 0.2 m s^{-1} (see Section 2.3) and thus does not significantly contribute to the biases here. The random errors represented by the scaled MADs of Rayleigh-clear (Mie-cloudy) winds are 4.92 (3.55) m s^{-1} at Kobe and 5.68 (3.76) m s^{-1} at Okinawa. The values are smaller than the scaled MADs of Rayleigh-clear (Mie-cloudy) versus WPR winds. The main reason for the difference is probably related to that the random error is larger for the WPR (3 m s^{-1}) than for the CDWL (2 m s^{-1}). The σ_{Aeolus} of Rayleigh-clear (Mie-




Figure 11. Aeolus against CDWL HLOS winds for (a, b) Rayleigh-clear winds and (c, d) Mie-cloudy winds at (a, c) Kobe and (b, d) Okinawa for baseline 2B02. Corresponding least-square line fits are indicated by the thick solid lines. The fit results are shown in the insets. The $x = y$ line is represented by the dashed line. Red circles represent measurements of an ascending orbit, whereas blue circles represent measurements of a descending orbit.

420 cloudy) winds is determined using Eq. 5 to be 4.49 (2.93) m s^{-1} at Kobe and 5.31 (3.19) m s^{-1} at Okinawa. Witschas et al. (2020) determined σ_{Aeolus} of 3.9 m s^{-1} for Rayleigh-clear winds and 2.0 m s^{-1} for Mie-cloudy winds by excluding the airborne $2 \mu\text{m}$ CDWL measurement error during the commissioning phase. The discrepancies are probably caused by the smaller representativeness error due to the spatial and temporal displacements between Aeolus and airborne CDWL measurements.

425 Figure 12 shows the correlation plots of the Aeolus HLOS winds against CDWL HLOS winds for Rayleigh-clear and Mie-cloudy winds at Kobe and Okinawa during the baseline 2B10 period. As with the baseline 2B02 period, a linear trend between Aeolus and CDWL measurements is clearly seen from the linear regression. At Kobe, the correlation coefficients are 0.96 and 0.97 for Rayleigh-clear and Mie-cloudy winds, respectively, and close to 1. At Okinawa, the correlation coefficients are 0.79 and 0.86 for Rayleigh-clear and Mie-cloudy winds, respectively, and are smaller than those at Kobe. At
 430 Okinawa, 47% and 62% of the data pairs for Rayleigh-clear and Mie-cloudy winds versus CDWL winds are obtained below 2 km altitude, respectively. This result is suggested to be linked to the strong convection in the atmospheric boundary layer




Figure 12. Same as Fig. 11 but for baseline 2B10.

at Okinawa, especially in summer. The intercepts of the linear regression lines are determined to be -0.88 m s^{-1} (Rayleigh) and 0.22 m s^{-1} (Mie) at Kobe and -0.52 m s^{-1} (Rayleigh) and -0.04 m s^{-1} (Mie) at Okinawa. The biases are -0.81 m s^{-1} (Rayleigh) and 0.16 m s^{-1} (Mie) at Kobe and -0.48 m s^{-1} (Rayleigh) and -0.26 m s^{-1} (Mie) at Okinawa. The absolute bias of Rayleigh-clear and Kobe CDWL winds is slightly larger than that for the baseline 2B02, the reason for which is unclear. Except for Rayleigh-clear winds measured at Kobe, the systematic error achieves the mission requirement of 0.7 m s^{-1} . The scaled MADs of Rayleigh-clear (Mie-cloudy) winds are 5.21 (3.92) m s^{-1} at Kobe and 5.58 (3.86) m s^{-1} at Okinawa. In contrast to the comparisons of Aeolus and WPR measurements, the random errors are almost the same as those for the baseline 2B02, and no improvement of the random error is evident. As with the scaled MADs, the estimated σ_{Aeolus} of Rayleigh-clear and Mie-cloudy winds at Kobe and Okinawa are almost the same as those for the baseline 2B02.

5.3 Comparison of Aeolus and GPS-RS wind data

For the validation of the Aeolus wind products, we launched 12 and 6 GPS-RSs from NICT Okinawa during the baseline 2B02 and 2B10 periods, respectively (Table 4). The GPS-RSs obtained wind profiles with a vertical range up to 25 km. Thus, the GPS-RSs could measure winds of the upper troposphere and lower stratosphere which cannot be measured by the WPRs and CDWLs.

Figure 13a shows HLOS wind speed profiles measured by the GPS-RSs with the Rayleigh-clear and Mie-cloudy profiles on 8 November 2018. The Mie-cloudy winds are available below 4.5 km and at high altitudes of 9 to 11.5 km owing to the occurrence of cirrus clouds. A cirrus cloud layer was also observed by the CDWL during the overpass of Aeolus (not shown). There are large deviations between Mie-cloudy and GPS-RS winds below 2 km. Since the horizontal distance between the Mie-cloudy measurements and the GPS-RS is about 100 km in this height region, one can assume that the reason for the large deviations is the spatial heterogeneity of the horizontal wind in the atmospheric boundary layer. The Rayleigh-clear winds show good coverage and closely follow the shape of the wind profile at altitudes higher than 2 km, but there are large deviations between Rayleigh-clear and GPS-RS winds at 3 km and 8 km. The scattering ratio on the Rayleigh channel is 1.15 and the relative humidity obtained from the GPS-RS is about 30% at 3 km. Although there is a valid Mie-cloudy wind at 3 km, it is filtered out due to the HLOS error threshold of 5 m s^{-1} . This suggests that the atmospheric classification in the Rayleigh channel was not working properly and the cross talk of Mie signals in the Rayleigh channel could have led to the large deviation. At 8 km, there is no valid Mie-cloudy wind. The scattering ratio and relative humidity are 1.13 and about 20%, respectively. This suggests that the cross talk has a small influence on the large deviation. The reason for that is unclear. Since the horizontal distance between the Rayleigh-clear measurements and the GPS-RS is about 80 km in this height region, large horizontal wind gradients in this height region potentially have an influence on the deviation. The subtropical jet stream with westerly winds can be seen in the GPS-RS and Rayleigh-clear observations at around 14 km. A maximum absolute wind speed higher than 50 m s^{-1} was observed in this height region according to the high-resolution GPS-RS profile.

Despite the coarse range resolution (2 km) of the Aeolus measurements in this height region, the Rayleigh-clear winds are able to detect the high wind speed.

The second case discussed in this study is from 1 December 2018 (Fig. 13b). The Mie-cloudy winds are available below 4 km. As compared with the previous case (8 November 2018), the Mie-cloudy winds agree with the GPS-RS winds in the lowermost 2 km. The reason for the agreement is that the Aeolus ground track was relatively near the radiosonde launching position (about 50 km). The Rayleigh-clear winds are available at altitudes higher than 2 km. The occurrence of cloud was sporadically detected by the CDWL and the relative humidity obtained from the GPS-RS was about 90% at 3 to 4 km altitude (not shown). It is assumed that the clouds were partly existent in the Aeolus observational domain. The Rayleigh-clear wind shows a large bias at 3 to 4 km altitude, but the scattering ratios on the Rayleigh channel is 1.15. This suggests




Figure 13. (a) HLOS wind speed profiles measured by the GPS-RS (thin black line) with the Rayleigh-clear (red) and Mie-cloudy (blue) profiles on for the descending orbit 8 November 2018. (b) Same as Fig. 13a but on for the ascending orbit 1 December 2018. (c) Rayleigh-clear and (d) Mie-cloudy HLOS winds versus the radiosonde measurements for baseline 2B02. Red circles represent measurements of an ascending orbit, whereas blue circles represent measurements of a descending orbit.

that there was an issue with the cross talk correction of Mie signals in the Rayleigh channel. As with the previous case, the subtropical jet stream with westerly winds is seen in the GPS-RS and Rayleigh-clear observations at around 12 km altitude.

475 The Rayleigh-clear wind measurements can detect the high wind speed, but they are slightly overestimated, the reason for that is unclear. Potentially, large horizontal wind gradients in this height region have an influence on the differences. Figures 13c and 13d show the correlation plots of the Rayleigh-clear and Mie-cloudy HLOS winds against GPS-RS HLOS winds during the baseline 2B02 period, respectively. Summaries of the statistical parameters retrieved from the scatter plot analysis for the baseline 2B02 and 2B10 are given in Table 8. A linear trend between Aeolus and GPS-RS measurements is

480 clearly seen from the linear regression. The linear regression line has a slope of 0.99 (0.97) with an intercept of 1.00 (2.07) m s^{-1} for the comparison of Rayleigh-clear (Mie-cloudy) and GPS-RS winds. Both Rayleigh-clear and Mie-cloudy winds exhibit a slightly positive bias. The different colors indicate whether Aeolus had an ascending orbit (red) or a descending orbit (blue). No significant difference is found between the ascending and descending orbits. The biases of Rayleigh-clear and Mie-cloudy winds are 1.00 and 2.15 m s^{-1} , respectively. These values are almost the same as the intercept of the linear

485 regression line. The random error represented by the scaled MAD of Rayleigh-clear winds (4.77 m s^{-1}) is slightly larger than that of Mie-cloudy winds (4.14 m s^{-1}). Baars et al. (2020) compared the Rayleigh-clear and Mie-cloudy winds with winds obtained from the radiosonde launches on board the German RV *Polarstern* during cruise PS116 carried out in the Atlantic Ocean west of the African continent from 17 November to 10 December 2018 (i.e., during the baseline 2B02 period). They reported biases of 1.52 and 0.95 m s^{-1} with random errors of 4.84 and 1.58 m s^{-1} for Rayleigh-clear and Mie-cloudy winds,

490 respectively. The slope and intercept of the linear regression line were 0.97 (0.95) and 1.57 (1.13) m s^{-1} for the comparison of Rayleigh-clear (Mie-cloudy) and radiosonde winds, respectively. Therefore, the slightly positive bias of Rayleigh-clear versus GPS-RS winds obtained in this study are almost the same as those obtained by Baars et al. (2020). The bias of Mie-cloudy versus GPS-RS winds is larger than that from Baars et al. (2020). The result that the random error of Mie-cloudy winds is much smaller than that of Rayleigh-clear wind contrasts with our results. The discrepancies are probably caused by

495 different observation location, meteorological conditions, and distance between the measurements. Figures 14a and 14b show HLOS wind speed profiles measured by the GPS-RS with the Rayleigh-clear and Mie-cloudy profiles on 19 December 2019 and 21 December 2019, respectively. The range-bin settings of Aeolus were changed to a resolution of 1 km up to an altitude of 19 km on 26 February 2019. Owing to the high range resolution, the Rayleigh-clear wind measurements of Aeolus can detect the rapid changes in the wind speed profiles in the subtropical jet stream. On 19

500 December 2019, the CDWL observed a cloud layer at around 1 km under rainy conditions during the overpass of Aeolus (not shown), and the Mie-cloudy winds were detected above the cloud layer. On 21 December 2019, the CDWL observed multiple cloud layers up to about 9 km during the overpass of Aeolus (not shown), and the Mie-cloudy winds were detected at these cloud layers.

Figures 14c and 14d show the correlation plots of the Rayleigh-clear and Mie-cloudy HLOS winds against GPS-RS HLOS

505 winds during the baseline 2B10 period, respectively. As with the baseline 2B02, a linear trend between Aeolus and GPS-RS observations is clearly seen from the linear regression. The linear regression line has a slope of 1.01 (0.92) with an intercept

of 0.38 (-0.22) m s^{-1} for the comparison of Rayleigh-clear (Mie-cloudy) and GPS-RS winds. The intercepts of Rayleigh-clear and Mie-cloudy winds are smaller than those for the baseline 2B02. As with the baseline 2B02, no significant difference is found between the ascending and descending orbits. The biases of Rayleigh-clear and Mie-cloudy winds are 0.45 and -0.71 m s^{-1} , respectively. Both Rayleigh-clear and Mie-cloudy winds generally meet the mission requirements on systematic errors. These values are almost the same as the intercept of the linear regression line and are smaller than those for the baseline 2B02. The scaled MAD of Rayleigh-clear winds is 3.97 m s^{-1} and smaller than that for the baseline 2B02. On the other hand, the scaled MAD of Mie-cloudy wind is 3.99 m s^{-1} and almost the same as that for the baseline 2B02. Martin et al. (2021) estimated the radiosonde representativeness error σ_{r_GPS-RS} by considering spatial and temporal displacements, and the different measurement geometries of the radiosonde and the Aeolus observations. They determined that the radiosonde representativeness errors σ_{r_GPS-RS} is 2.48 m s^{-1} for the Rayleigh-clear winds, 2.49 m s^{-1} for the Mie-




Figure 14. (a) HLOS wind speed profiles measured by the radiosonde (thin black line) with the Rayleigh-clear (red) and Mie-cloudy (blue) profiles for the descending orbit on 19 December 2019. (b) Same as Fig. 14a but for the ascending orbit on 21 December 2019. (c, d) Same as Figs. 13c and 13d but for baseline 2B10.

cloudy winds with 90 km horizontal resolution (corresponding to the baseline 2B02), and 2.66 m s^{-1} for the Mie-cloudy winds with 10 km horizontal resolution (corresponding to the baseline 2B10) based on the radiosonde and the Aeolus observations. The Aeolus random error σ_{Aeolus} considering the representativeness error σ_{r_GPS-RS} in addition to the
 520 radiosonde observational error can be calculated as follows:

$$\sigma_{Aeolus} = \sqrt{\sigma_{val}^2 - \sigma_{r_GPS-RS}^2 - \sigma_{GPS-RS}^2} \quad (7)$$

σ_{Aeolus} is determined using the Eq. 7 to be 4.01 m s^{-1} for Rayleigh-clear winds and 3.24 m s^{-1} for Mie-cloudy winds during the baseline 2B02 period. During the baseline 2B10 period, σ_{Aeolus} is determined to be 3.02 m s^{-1} for Rayleigh-clear winds, and 2.89 m s^{-1} for Mie-cloudy winds. Martin et al. (2021) estimated σ_{Aeolus} using the radiosonde observations in the
 525 midlatitudes of the northern hemisphere (23.5 to 65°N), resulting in σ_{Aeolus} of 4.23 to 4.37 m s^{-1} for Rayleigh-clear winds, and 2.60 to 2.76 m s^{-1} for Mie-cloudy winds with 90 km horizontal resolution, and 2.97 to 3.03 m s^{-1} for Mie-cloudy winds with 10 km horizontal resolution. Given that estimates of the representativeness error exhibit large uncertainties (Martin et al., 2021), the Rayleigh-clear and Mie-cloudy wind random errors during the baseline 2B02 period are consistent with the validation results of Martin et al. (2021). During the baseline 2B10 period, the Mie-cloudy wind random error is also in good
 530 agreement with the validation result of Martin et al. (2021), whereas the Rayleigh-clear wind random error significantly decreases. Both Rayleigh-clear and Mie-cloudy wind random errors are close to the mission requirement of 2.5 m s^{-1} in the free troposphere.

Table 8. Statistical comparison of Aeolus HLOS winds and GPS-RS HLOS winds.

Baseline	2B02		2B10	
	Rayleigh	Mie	Rayleigh	Mie
N points	126	59	92	43
BIAS (m s^{-1})	1.00	2.15	0.45	-0.71
STD (m s^{-1})	4.55	4.52	4.43	5.81
Scaled MAD (m s^{-1})	4.77	4.14	3.97	3.99
σ_{Aeolus} (m s^{-1})	4.71	4.08	3.91	3.92
Correlation	0.99	0.97	0.99	0.95
Slope	0.99	0.97	1.01	0.92
Intercept (m s^{-1})	1.00	2.07	0.38	-0.22

6 Summary

535 We validated the Aeolus L2B data product for Rayleigh-clear and Mie-cloudy winds using operational WPRs, ground-based
CDWLs, and GPS-RSs in Japan during the periods of the baseline 2B02 (from 1 October to 18 December 2018) and 2B10
(from 28 June to 31 December 2019 and from 20 April to 8 October 2020). Statistical analyses based on the three
independent reference instruments were performed to validate the Rayleigh-clear and Mie-cloudy wind data. Overall, the
systematic errors of the comparisons with the three reference data sets showed consistent tendency. During the baseline
540 2B02, both Rayleigh-clear and Mie-cloudy winds exhibited positive systematic errors in the ranges of 0.5 to 1.7 m s⁻¹ and
1.6 to 2.4 m s⁻¹, respectively. The statistical comparisons for the baseline 2B10 period showed smaller biases, -0.8 to 0.5 m
s⁻¹ for the Rayleigh-clear and -0.7 to 0.2 m s⁻¹ for the Mie-cloudy winds. This suggests that the derived systematic errors are
due to Aeolus Rayleigh-clear and Mie-cloudy wind systematic errors and not the reference data sets. The reduced bias of the
2B10 period compared to 2B02 is most likely due to the M1 mirror bias correction and the improvement of the hot pixel
545 correction.

In the comparisons of Aeolus and WPR measurements, the vertical distribution of wind difference, the wind bias dependence
on orbit phases, the time series variation of wind differences, and the Rayleigh-clear wind bias dependence on the scattering
ratio were investigated in addition to the statistical analyses. For the baseline 2B02, the systematic error was determined to
be 1.69 m s⁻¹ for Rayleigh-clear winds and 2.42 m s⁻¹ for Mie-cloudy winds. For the baseline 2B10, the systematic error was
550 determined to be -0.82 m s⁻¹ for Rayleigh-clear winds and -0.51 m s⁻¹ for Mie-cloudy winds. The systematic error for the
baseline 2B10 was less than that for the baseline 2B02. For the baseline 2B02, σ_{Aeolus} was determined to be 6.71 m s⁻¹ for
Rayleigh-clear winds and 5.12 m s⁻¹ for Mie-cloudy winds. For the baseline 2B10, σ_{Aeolus} was determined to be 6.42 m s⁻¹
for Rayleigh-clear winds and 4.80 m s⁻¹ for Mie-cloudy winds. The main reason for the large Aeolus random errors is the
lower laser energy compared to the target of 80 mJ. Additionally, the large representativeness error due to the large sampling
555 volume of the WPR is probably related to the larger Aeolus random error. The vertical distributions of differences between
Rayleigh-clear or Mie-cloudy winds and WPR winds showed that both Rayleigh-clear and Mie-cloudy biases in all altitude
ranges up to 11 km were positive during the baseline 2B02 period. During the baseline 2B10 period, the systematic errors of
Rayleigh-clear and Mie-cloudy winds were improved as compared with those during the baseline 2B02 period. The time
series of wind speed differences between Aeolus and WPR HLOS winds varied considerably during baseline 2B02 period.
560 Immediately after the launch of Aeolus, both Rayleigh-clear and Mie-cloudy biases were small. With time, the Rayleigh-
clear and Mie-cloudy biases increased. Within the baseline 2B02, the Rayleigh-clear and Mie-cloudy biases showed a
positive trend. For the baseline 2B10, the biases of Rayleigh-clear HLOS winds were generally negative at all months except
August 2020, but the biases did not show a clear seasonal trend. The biases of Mie-cloudy and WPR HLOS winds gradually
fluctuated and did also not show a clear seasonal trend. The Rayleigh-clear and Mie-cloudy wind biases were close to 0 m s⁻¹
565 towards September 2020. The dependence of the Rayleigh-clear wind bias on the scattering ratio was investigated, showing

that the influence of the cross talk of Mie signals to the Rayleigh channel was not confirmed during the baseline 2B02 period. As with the baseline 2B02, there was no significant bias dependence on the scattering ratio during the baseline 2B10 period. The statistical analyses based on the ground-based CDWLs at Kobe and Okinawa during the baseline 2B02 and 2B10 periods showed that the agreement between the Aeolus winds and CDWL winds is generally good. For the baseline 2B02, the systematic error was determined to be 0.46 m s⁻¹ (Rayleigh) and 1.63 m s⁻¹ (Mie) at Kobe and 1.08 m s⁻¹ (Rayleigh) and 2.38 m s⁻¹ (Mie) at Okinawa. Except for the Rayleigh-clear winds measured at Kobe, the systematic error did not achieve the mission requirement. σ_{Aeolus} was determined to be 4.49 m s⁻¹ (Rayleigh) and 2.93 m s⁻¹ (Mie) at Kobe and 5.31 m s⁻¹ (Rayleigh) and 3.19 m s⁻¹ (Mie) at Okinawa. The Aeolus random errors were larger than those from the validation study using the airborne 2 μ m CDWL (Witschas et al., 2020). The discrepancies were probably caused by the smaller representativeness error due to the spatial and temporal displacements between Aeolus and airborne CDWL measurements. For the baseline 2B10, the systematic error was determined to be -0.81 m s⁻¹ (Rayleigh) and 0.16 m s⁻¹ (Mie) at Kobe and -0.48 m s⁻¹ (Rayleigh) and -0.26 m s⁻¹ (Mie) at Okinawa. In contrast to the baseline 2B02, the systematic error decreased except for the Rayleigh-clear winds measured at Kobe. σ_{Aeolus} was determined to be 4.81 m s⁻¹ (Rayleigh) and 3.37 m s⁻¹ (Mie) at Kobe and 5.21 m s⁻¹ (Rayleigh) and 3.30 m s⁻¹ (Mie) at Okinawa. In contrast to the comparisons of Aeolus and WPR measurements, the Aeolus random errors were almost the same as those for the baseline 2B02, and no improvement of the Aeolus random error was evident.

With the analyses of results obtained from GPS-RSs launched from NICT Okinawa, it was shown that Aeolus can measure accurately wind profiles with a vertical range up to 25 km and capture the rapid changes in the wind speed profiles such as the subtropical jet stream. The statistical analyses based on the GPS-RSs also revealed the good performance of Aeolus during the baseline 2B02 and 2B10 periods. For the baseline 2B02, the systematic error was determined to be 1.00 m s⁻¹ for Rayleigh-clear winds and 2.15 m s⁻¹ for Mie-cloudy winds. For the baseline 2B10, the systematic error was determined to be 0.45 m s⁻¹ for Rayleigh-clear winds and -0.71 m s⁻¹ for Mie-cloudy winds. Both Rayleigh-clear and Mie-cloudy winds generally met the mission requirements on systematic errors. By taking the radiosonde representativeness error into account, σ_{Aeolus} was determined to be 4.01 m s⁻¹ for Rayleigh-clear winds and 3.24 m s⁻¹ for the Mie-cloudy winds during the baseline 2B02 period. During the baseline 2B10 period, σ_{Aeolus} was determined to be 3.02 m s⁻¹ for Rayleigh-clear winds and 2.89 m s⁻¹ for the Mie-cloudy winds. The random errors of the Rayleigh-clear and Mie-cloudy winds during the baseline 2B02 period were in line with the other validation results. During the baseline 2B10 period, the Aeolus random errors of the Rayleigh-clear and Mie-cloudy winds were improved as compared with those during the baseline 2B02 period.

To summarize, our validation results obtained from the comparison with the WPRs, CDWLs, and GPS-RSs revealed the quality of the Aeolus Rayleigh-clear and Mie-cloudy HLOS winds over Japan. The systematic errors for the baseline 2B10 were not greater than 1 m s⁻¹ and improved as compared with those for the baseline 2B02. The results confirm the necessity to validate the quality of the Aeolus HLOS winds and help to use the Aeolus wind products in NWP data assimilation. Now, we continue to conduct the validation of the Aeolus HLOS winds by using measurements from WPRs and CDWLs. As with this study, the validation activities will provide new insights into the quality of the Aeolus HLOS winds over Japan.

Data availability

The CDWL and GPS-RS data used in this paper can be provided by the corresponding author (iwai@nict.go.jp) upon request. The WINDAS data can be downloaded from <http://database.rish.kyoto-u.ac.jp/arch/jmadata/data/jma-radar/wprof/original/>. Aeolus data were obtained from the VirES visualization tool (<https://aeolus.services/>).

605

Author contributions

HI prepared the main part of the paper and performed the statistical analyses of Aeolus data and WPRs, CDWLs, and GPS-RSs data. MA supported the operation of CDWL and GPS-RS measurements. MO performed the GPS-RS measurements. SI was the principal investigator of validation campaigns in Japan and supported the preparation of this paper and discussed the experimental results. All co-authors helped review the manuscript.

610

Competing interests

The authors declare that they have no conflict of interest.

615 **Acknowledgements**

We are very grateful to the Japan Meteorological Agency for the operation and maintenance of WINDAS. We are also grateful to Jun Amagai, former Director of NICT Okinawa, for supporting the GPS-RS measurements.

Financial support

620 This work was supported by JSPS KAKENHI Grant Number JP17H06139, JP19K04849, and JP19H01973.

References

- Adachi, A., Kobayashi, T., Gage, K. S., Carter, D. V., Hartten, L. M., Clark, W. L., and Fukuda, M.: Evaluation of three-beam and four-beam profiler wind measurement techniques using a five-beam wind profiler and collocated meteorological tower, *J. Atmos. Oceanic Technol.*, 22, 1167–1180, <https://doi.org/10.1175/JTECH1777.1>, 2005.
- Aoki, M., Iwai, H., Nakagawa, K., and Mizutani, K.: Comparison of Doppler lidar, radiosonde, and sonic anemometer wind measurements, 62nd Japan Society of Applied Physics spring meeting, 2015 (in Japanese).
- 630 Aoki, M., Iwai, H., Nakagawa, K., Ishii, S., and Mizutani, K.: Measurements of rainfall velocity and raindrop size distribution using coherent Doppler lidar, *J. Atmos. Oceanic Technol.*, 33, 1949–1966, <https://doi.org/10.1175/JTECH-D-15-0111.1>, 2016.
- Baars, H., Herzog, A., Heese, B., Ohneiser, K., Hanbuch, K., Hofer, J., Yin, Z., Engelmann, R., and Wandinger, U.: Validation of Aeolus wind products above the Atlantic Ocean, *Atmos. Meas. Tech.*, 13, 6007–6024, <https://doi.org/10.5194/amt-13-6007-2020>, 2020.
- 635 Belova, E., Kirkwood, S., Voelger, P., Chatterjee, S., Satheesan, K., Hagelin, S., Lindskog, M., and Körnich, H.: Validation of Aeolus winds using ground-based radars in Antarctica and in northern Sweden, *Atmos. Meas. Tech.*, 14, 5415–5428, <https://doi.org/10.5194/amt-14-5415-2021>, 2021.
- 640 Bormann, N., Saarinen, S., Kelly, G., and Thèpaut, J.-N.: The spatial structure of observation errors in atmospheric motion vectors from geostationary satellite data, *Mon. Wea. Rev.*, 131, 706–718, [https://doi.org/10.1175/1520-0493\(2003\)131<0706:TSSOOE>2.0.CO;2](https://doi.org/10.1175/1520-0493(2003)131<0706:TSSOOE>2.0.CO;2), 2003.
- 645 Cariou, J.-P., Augere, B., and Valla, M.: Laser source requirements for coherent lidars based on fiber technology, *C. R. Phys.*, 7, 213–223, <https://doi.org/10.1016/j.crhy.2006.03.012>, 2006.
- Chanin, M. L., Garnier, A., Hauchecorne, A., and Porteneuve, J.: A Doppler lidar for measuring winds in the middle atmosphere, *Geophys. Res. Lett.*, 16, 1273–1276, <https://doi.org/10.1029/GL016i011p01273>, 1989.
- 650 Dabas, A., Denneulin, M. L., Flamant, P., Loth, C., Garnier, A., and Dolfi-Bouteyre, A.: Correcting winds measured with a Rayleigh Doppler lidar from pressure and temperature effects, *Tellus A*, 60, 206–215, <https://doi.org/10.1111/j.1600-0870.2007.00284.x>, 2008.

de Kloe, J., Stoffelen, A., Tan, D., Andersson, E., Rennie, M., Dabas, A., Poli, P., and Huber, D.: ADM-Aeolus Level-2B/2C Processor Input/Output Data Definitions Interface Control Document, available at: https://earth.esa.int/pi/esa?type=file&table=aotarget&cmd=image&alias=ADM_Aeolus_L2B_Input_Output_DD_ICD, 2016.

660 Dirksen, R. J., Sommer, M., Immler, F. J., Hurst, D. F., Kivi, R., and Vömel, H.: Reference quality upper-air measurements: GRUAN data processing for the Vaisala RS92 radiosonde, *Atmos. Meas. Tech.*, 7, 4463–4490, <https://doi.org/10.5194/amt-7-4463-2014>, 2014.

665 ESA: The four Candidate Earth Explorer Core Missions - Atmospheric Dynamics Mission, <https://earth.esa.int/documents/10174/1601629/vol4.pdf>, 1999.

Flesia, C. and Korb, C. L.: Theory of the double-edge molecular technique for Doppler lidar wind measurement, *Appl. Optics*, 38, 432–440, <https://doi.org/10.1364/AO.38.000432>, 1999.

670 Flesia, C. and Hirt, C.: Double-edge molecular measurement of lidar wind profiles at 355 nm, *Opt. Lett.*, 25, 1466–1468, <https://doi.org/10.1364/OL.25.001466>, 2000.

Folger, K. and Weissmann, M.: Height correction of atmospheric motion vectors using satellite lidar observations from CALIPSO, *J. Appl. Meteor. Climatol.*, 53, 1809–1819, <https://doi.org/10.1175/JAMC-D-13-0337.1>, 2014.

675

Gentry, B. M., Chen, H., and Li, S. X.: Wind measurements with 355-nm molecular Doppler lidar, *Opt. Lett.*, 25, 1231–1233, <https://doi.org/10.1364/OL.25.001231>, 2000.

680 Guo, J., Liu, B., Gong, W., Shi, L., Zhang, Y., Ma, Y., Zhang, J., Chen, T., Bai, K., Stoffelen, A., de Leeuw, G., and Xu, X.: Technical note: First comparison of wind observations from ESA’s satellite mission Aeolus and ground-based radar wind profiler network of China, *Atmos. Chem. Phys.*, 21, 2945–2958, <https://doi.org/10.5194/acp-21-2945-2021>, 2021.

Ingmann, P., and Straume, A. G.: ADM-Aeolus Mission Requirements Document, AE-RP-ESA-SY-001, available at: http://esamultimedia.esa.int/docs/EarthObservation/ADM-Aeolus_MRD.pdf, 2016.

685

Ishihara, M., Kato, Y., Abo, T., Kobayashi, K., and Izumikawa, Y.: Characteristics and performance of the operational wind profiler network of the Japan Meteorological Agency, *J. Meteor. Soc. Japan*, 84, 1085–1096, <https://doi.org/10.2151/jmsj.84.1085>, 2006.

690 Iwai, H., Ishii, S., Oda, R., Mizutani, K., Sekizawa, S., and Murayama, Y.: Performance and technique of coherent 2- μm differential absorption and wind lidar for wind measurement, *J. Atmos. Oceanic Technol.*, 30, 429–449, <https://doi.org/10.1175/JTECH-D-12-00111.1>, 2013.

Jensen, M. P., Holdridge, D. J., Survo, P., Lehtinen, R., Baxter, S., Toto, T., and Johnson, K. L.: Comparison of Vaisala
695 radiosondes RS41 and RS92 at the ARM Southern Great Plains site, *Atmos. Meas. Tech.*, 9, 3115–3129, <https://doi.org/10.5194/amt-9-3115-2016>, 2016.

Kanitz, T., Lochard, J., Marshall, J., McGoldrick, P., Lecrenier, O., Bravetti, P., Reitebuch, O., Rennie, M., Wernham, D.,
and Elfving, A.: Aeolus first light: first glimpse, in: International Conference on Space Optics — ICSO 2018, International
700 Conference on Space Optics — ICSO 2018, 111801R, <https://doi.org/10.1117/12.2535982>, 2019.

Kawai, Y., Katsumata, M., Oshima, K., Hori, M. E., and Inoue, J.: Comparison of Vaisala radiosondes RS41 and RS92
launched over the oceans from the Arctic to the tropics, *Atmos. Meas. Tech.*, 10, 2485–2498, <https://doi.org/10.5194/amt-10-2485-2017>, 2017.

705

Levin, M. J.: Power spectrum parameter estimation, *IEEE Trans. Inform. Theory*, 11, 100–107, <https://doi.org/10.1109/TIT.1965.1053714>, 1965.

Lux, O., Wernham, D., Bravetti, P., McGoldrick, P., Lecrenier, O., Riede, W., D’Ottavi, A., Sanctis, V. D., Schillinger, M.,
710 Lochard, J., Marshall, J., Lemmerz, C., Weiler, F., Mondin, L., Ciapponi, A., Kanitz, T., Elfving, A., Parrinello, T., and
Reitebuch, O.: High-power and frequency-stable ultraviolet laser performance in space for the wind lidar on Aeolus, *Opt. Lett.*, 45, 1443–1446, <https://doi.org/10.1364/OL.387728>, 2020a.

Lux, O., Lemmerz, C., Weiler, F., Marksteiner, U., Witschas, B., Rahm, S., Geiß, A., and Reitebuch, O.: Intercomparison of
715 wind observations from the European Space Agency’s Aeolus satellite mission and the ALADIN Airborne Demonstrator,
Atmos. Meas. Tech., 13, 2075–2097, <https://doi.org/10.5194/amt-13-2075-2020>, 2020b.

Martin, A., Weissmann, M., Reitebuch, O., Rennie, M., Geiß, A., and Cress, A.: Validation of Aeolus winds using
radiosonde observations and numerical weather prediction model equivalents, *Atmos. Meas. Tech.*, 14, 2167–2183,
720 <https://doi.org/10.5194/amt-14-2167-2021>, 2021.

Morancais, D., Fabre, F., Schillinger, M., Barthes, J.-C., Endemann, M., and Culoma, A.: ALADIN: The first European lidar in space, Proc. 22nd Int. Laser Radar Conf., Matera, Italy, International Radiation Commission, 127–129, 2004.

725 Reitebuch, O.: The Spaceborne Wind Lidar Mission ADM-Aeolus, in: Atmospheric Physics, Research Topics in Aerospace, edited by: Schumann, U., Springer, Berlin, Heidelberg, Germany, https://doi.org/10.1007/978-3-642-30183-4_49, 2012.

Reitebuch, O., Lemmerz, C., Lux, O., Marksteiner, U., Rahm, S., Weiler, F., Witschas, B., Meringer, M., Schmidt, K., Huber, D., Nikolaus, I., Geiss, A., Vaughan, M., Dabas, A., Flament, T., Stieglitz, H., Isaksen, L., Rennie, M., Kloe, J. de, Marseille, 730 G.-J., Stoffelen, A., Wernham, D., Kanitz, T., Straume, A.-G., Fehr, T., Bismarck, J. von, Floberghagen, R., and Parrinello, T.: Initial assessment of the performance of the first wind lidar in space on Aeolus, EPJ Web Conf., 237, 01010, <https://doi.org/10.1051/epjconf/202023701010>, 2020a.

Reitebuch, O., Krisch, I., Lemmerz, C., Lux, O., Marksteiner, U., Masoumzadeh, N., Weiler, F., Witschas, B., Bracci, F., 735 Meringer, M., Schmidt, K., Huber, D., Nikolaus, I., Fabre, F., Vaughan, M., Reissig, K., Dabas, A., Flament, T., Lacour, A., Mahfouf, J.-F., Savli, M., Trapon, D., Abdalla, S., Isaksen, L., Rennie, M., Donovan, D., Kloe, J. de, Marseille, G.-J., Stoffelen, A., Perron, G., Jupin-Langlois, S., Smeets, J., Veneziani, M., Bucci, S., Gostinicchi, G., Ehlers, F., Kanitz, T., Straume, A.-G., Wernham, D., Bismarck, J. von, Bley, S., Fischer, P., Laurentis, M. de, and Parrinello, T.: Assessment of Aeolus performance and bias correction – results from the Aeolus DISC, Aeolus Cal/Val and Science Workshop 2020, 740 <https://nikal.eventsair.com/QuickEventWebsitePortal/2nd-aeolus-post-launch-calval-and-science-workshop/aeolus>, 2020b.

Rennie, M. and Isaksen, L.: The NWP impact of Aeolus Level-2B winds at ECMWF, Technical Memorandum ECMWF, <https://doi.org/10.21957/alift7mhr>, <https://www.ecmwf.int/node/19538>, 2020.

745 Röttger, J. and Larsen M. F.: UHF/VHF radar techniques for atmospheric research and wind profiler applications. In: Atlas D. (eds) Radar in Meteorology. American Meteorological Society, Boston, MA. https://doi.org/10.1007/978-1-935704-15-7_23, 1990.

Ruppert, D. and Matteson, D. S.: Statistics and Data Analysis for Financial Engineering, 2nd edn., Springer, New York, NY, 750 <https://doi.org/10.1007/978-1-4939-2614-5>, 2015.

Rye, B. J. and Hardesty, R. M.: Discrete spectral peak estimation in incoherent backscatter heterodyne lidar. I: Spectral accumulation and the Cramer–Rao lower bound, IEEE Trans. Geosci. Remote Sens., 31, 16–27, <https://doi.org/10.1109/36.210440>, 1993.

755

- Schillinger M., Morançais D., Fabre F., and Culoma A.: ALADIN: the lidar instrument for the Aeolus mission, *Proc. SPIE, Sensors, Systems, and Next-Generation Satellites VI*, 4881, 40–51, <https://doi.org/10.1117/12.463024>, 2003.
- 760 Stoffelen, A., Pailleux, J., Källén, E., Vaughan, J. M., Isaksen, L., Flamant, P., Wergen, W., Andersson, E., Schyberg, H., Culoma, A., Meynart, R., Endemann, M., and Ingmann, P.: The Atmospheric Dynamics Mission for global wind field measurement, *Bull. Amer. Meteor. Soc.*, 86, 73–88, <https://doi.org/10.1175/BAMS-86-1-73>, 2005.
- 765 Stoffelen, A., Benedetti, A., Borde, R., Dabas, A., Flamant, P., Forsythe, M., Hardesty, M., Isaksen, L., Källén, E., Körnich, H., Lee, T., Reitebuch, O., Rennie, M., Riishøjgaard, L.-P., Schyberg, H., Straume, A. G., and Vaughan, M.: Wind profile satellite observation requirements and capabilities, *Bull. Amer. Meteor. Soc.*, 101, E2005–E2021, <https://doi.org/10.1175/BAMS-D-18-0202.1>, 2020.
- Tada, H.: Use of wind profiler data in Japan. Technical Report on Numerical Weather Prediction (in Japanese), 34, 55–58, Numerical Prediction Division, Japan Meteorological Agency, 2001.
- 770 Witschas, B., Lemmerz, C., Geiß, A., Lux, O., Marksteiner, U., Rahm, S., Reitebuch, O., and Weiler, F.: First validation of Aeolus wind observations by airborne Doppler wind lidar measurements, *Atmos. Meas. Tech.*, 13, 2381–2396, <https://doi.org/10.5194/amt-13-2381-2020>, 2020.
- 775 Weiler, F., Kanitz, T., Wernham, D., Rennie, M., Huber, D., Schillinger, M., Saint-Pe, O., Bell, R., Parrinello, T., and Reitebuch, O.: Characterization of dark current signal measurements of the ACCDs used on-board the Aeolus satellite, 5153–5177, <https://doi.org/10.5194/amt-14-5153-2021>, 2021a.
- 780 Weiler, F., Rennie, M., Kanitz, T., Isaksen, L., Checa, E., de Kloe, J., Okunde, N., and Reitebuch, O.: Correction of wind bias for the lidar on-board Aeolus using telescope temperatures, *Atmos. Meas. Tech. Discuss.* [preprint], <https://doi.org/10.5194/amt-2021-171>, in review, 2021b.