# Horizontal distribution of tropospheric NO<sub>2</sub> and aerosols derived by dual-scan multi-wavelength MAX-DOAS measurements in Uccle, Belgium

Ermioni Dimitropoulou<sup>1</sup>, François Hendrick<sup>1</sup>, Martina M. Friedrich<sup>1</sup>, Frederik Tack<sup>1</sup>, Gaia Pinardi<sup>1</sup>, Alexis Merlaud<sup>1</sup>, Caroline Fayt<sup>1</sup>, Christian Hermans<sup>1</sup>, Frans Fierens<sup>2</sup> and Michel Van Roozendael<sup>1</sup>

<sup>1</sup> Royal Belgian Institute for Space Aeronomy (BIRA-IASB), Brussels, 1180, Belgium <sup>2</sup> IRCEL-CELINE, Brussels, Belgium

Correspondence to: Ermioni Dimitropoulou (ermioni.dimitropoulou@aeronomie.be)

## Abstract

5

- 10 Dual-scan ground-based Multi-AXis Differential Optical Absorption Spectroscopy (MAX-DOAS) measurements of tropospheric nitrogen dioxide (NO<sub>2</sub>) and aerosols were carried out in Uccle (50.8°N, 4.35°E; Brussels region, Belgium) for two years, from March 2018 to February 2020. The MAX-DOAS instrument was operating in both UV and Visible wavelength ranges in a dual-scan configuration consisting of two sub-modes: (1) an elevation scan in a fixed viewing azimuthal direction and (2) an azimuthal scan in a fixed low elevation angle (2°). By analyzing the O<sub>4</sub> and NO<sub>2</sub> dSCDs at six different wavelength
- 15 intervals along every azimuthal direction and by applying a new Optimal-Estimation-based inversion approach (the so-called mapping MAX-DOAS technique), the horizontal distribution of the NO<sub>2</sub> near-surface concentrations and vertical column densities (VCDs) and the aerosols near-surface extinction coefficient are retrieved along ten azimuthal directions. The retrieved horizontal NO<sub>2</sub> concentration profiles allow the identification of the main NO<sub>2</sub> hotspots in the Brussels area. Correlative comparisons of the retrieved horizontal NO<sub>2</sub> distribution were conducted with airborne, mobile, air-quality model, and satellite
- 20 datasets, and overall a good agreement is found. The comparison with TROPOMI observations, from operational and scientific data products, reveals that the characterization of the horizontal distribution of tropospheric NO<sub>2</sub> VCDs by ground-based measurements and an adequate a priori NO<sub>2</sub> profile shape in TROPOMI retrievals lead to a better consistency between satellite and ground-based datasets.

#### **1** Introduction

25 Aerosols and nitrogen dioxide (NO<sub>2</sub>) play a crucial role in the tropospheric chemistry. NO<sub>2</sub> is an important tropospheric pollutant mainly emitted by combustion processes and nitrogen fertilizers used in agriculture (Seinfeld and Pandis, 1998). Traffic, domestic heating, industrial activities, and power plants are the largest NO<sub>2</sub> emitters (Tack et al., 2021). Beyond its harmful effects on human health (Chen et al., 2007), NO<sub>2</sub> participates in the formation of tropospheric ozone (O<sub>3</sub>) by a non-linear photochemical mechanism which involves volatile organic compounds (VOCs).

- 30 Aerosols with a small diameter can penetrate deeply into the lungs, causing millions of premature deaths around the world per year (Khomenko et al., 2021). Additionally, aerosols influence the Earth's climate system by changing its radiation budget by scattering and absorbing sunlight (Quaas et al., 2008). In the boundary layer of urban regions, the horizontal distribution of NO<sub>2</sub> is highly heterogeneous given the fact that it is a short-lived species (Beirle et al., 2003). For those reasons, the regional and global monitoring of  $NO_2$  and aerosols at high spatial resolution is crucial.
- 35 Since 1995, with the ERS-2 GOME (Global Ozone Monitoring Experiment) instrument (Burrows et al., 1999), satellite nadir air-quality measurements of atmospheric backscattered sunlight in the UV-visible range have provided daily global tropospheric column measurements of numerous trace gases, such as NO<sub>2</sub>. Many satellite missions dedicated to air-quality monitoring followed over the next years with increasing spatial resolution. More recently, the TROPOspheric Monitoring Instrument (TROPOMI) sensor launched onboard the Sentinel-5P Precursor (S5P) platform in October 2017 reached an initial
- 40 spatial resolution of 7x3.5 km<sup>2</sup>, and augmented on 6 August 2019 to 5.5x3.5 km<sup>2</sup>. Due to TROPOMI's fine spatial resolution, monitoring the horizontal distribution of  $NO_2$  in urban regions and identifying specific emission sources is made easier than with previous satellite missions but still, TROPOMI cannot fully capture the fine-scale (sub-kilometer) structures in the effective NO<sub>2</sub> field. Consequently, TROPOMI requires further attention concerning its measurements validation.

Tropospheric vertical columns of many trace gases like NO<sub>2</sub>, formaldehyde (HCHO), sulphur dioxide (SO<sub>2</sub>), nitrous acid

- 45 (HONO) and O<sub>3</sub> can be retrieved by the Multi-AXis Differential Optical Absorption Spectroscopy (MAX-DOAS) technique (Hönninger et al., 2004; Wittrock et al., 2004; Pinardi et al., 2008, 2013; Clémer et al., 2010; Hendrick et al., 2014; Irie et al., 2011, 2012; Sinreich et al., 2007; Wagner et al., 2011; Wang et al., 2018). In recent years, MAX-DOAS measurements have been widely used as reference datasets for the validation of nadir airborne and space-borne air-quality measurements. MAX-DOAS instruments measure the scattered sunlight in the UV and Visible spectral ranges at multiple elevation angles above the
- horizon. For absorbers located close to the surface, such as tropospheric NO<sub>2</sub>, the higher sensitivity is achieved for low MAX-50 DOAS elevation angles. During the last years, MAX-DOAS measurements in more than one azimuthal direction are emerging (Ortega et al., 2016; Wang et al., 2014; Chan et al., 2020; Schreier et al., 2021). Multi-azimuthal MAX-DOAS measurements offer many possibilities on air-quality monitoring, such as a better characterization of the effective NO<sub>2</sub> field around the station. These ground-based datasets can be valuable for validating satellite missions with fine spatial resolution in regions where the
- 55 NO<sub>2</sub> horizontal distribution is heterogeneous, such as urban and sub-urban areas. In this study, a new aerosol and NO<sub>2</sub> horizontal distribution inversion approach based on two years (March 2018-February 2020) of dual-scan multi-wavelength MAX-DOAS measurements in Uccle (Brussels-Capital region, Belgium) is presented. We refer to this new approach as mapping MAX-DOAS technique. In every azimuthal viewing direction, parameterized  $NO_2$ near-surface concentrations, NO<sub>2</sub> tropospheric columns and aerosol extinctions measured at six different wavelengths are used
- 60
- as input in a new horizontal distribution inversion approach. On this basis, the near-surface aerosol extinction and  $NO_2$ horizontal distributions are retrieved at a spatial resolution of about 3km in a range of about 20 km around the measurement site. These horizontal profiles are used to validate collocated TROPOMI tropospheric NO<sub>2</sub> columns. We use here (i) the operational TROPOMI data product, (ii) a so-called diagnostic data set, which is a small sample but with major updates

compared to the operational product (van Geffen et al., 2021b) and (ii) a European TROPOMI product where profiles from

- 65 CAMS regional CTM ensemble (S5P-CAMS) are used (Douros et al., 2021). One complete year of data (March 2018-March 2019) and two wavelength intervals (one in the UV and one in the Visible) have already been used in Dimitropoulou et al. (2020). It is proven that multi-azimuthal (the so-called dual-scan) MAX-DOAS measurements significantly improve the agreement between ground-based and TROPOMI tropospheric NO<sub>2</sub> column observations over the Brussels' area. By adding the multi-wavelength aspect, the present work represents an extension of the former study.
- The manuscript is organized into seven sections: in Sect. 2, the measurement site with the MAX-DOAS experimental set-up and the multi-wavelength DOAS analysis are presented. In Sect. 3 and 4, the TROPOMI tropospheric NO<sub>2</sub> measurements and ancillary measurements used in this study are described, respectively. Section 5 is composed of two main parts: Sect. 5.1 is a detailed description of the dual-scan multi-wavelength MAX-DOAS retrieval method and Sect. 5.2 is the horizontal aerosol and NO<sub>2</sub> distribution inversion approach (i.e., the mapping MAX-DOAS technique). In Sect. 6, main results followed by
- 75 correlative comparisons of the retrieved ground-based and satellite horizontal NO<sub>2</sub> distribution are presented. Finally, in Sect.
   7, conclusions and future perspectives are given.

# 2 Dual-scan multi-wavelength MAX-DOAS measurements

#### 2.1 Measurement site and experiment set-up


Brussels-Capital Region is the most densely populated area in Belgium, where pollutant concentrations, such as NO<sub>2</sub>, are often high because of anthropogenic activities (Tack et al., 2021).

A MAX-DOAS dual-scan instrument was operated by BIRA-IASB (Koninklijk Belgisch Instituut voor Ruimte-Aeronomie – Institut Royal d'Aeronomie Spatiale de Belgique) in Uccle from January 2017 to February 2020. Uccle is located to the South of the city-center of Brussels and to the West of a large forested area (Bois de la Cambre). Therefore, it is an ideal site to perform MAX-DOAS observations under moderate to high pollution level conditions. Additionally, the characterization of the

- 85 horizontal distribution of NO<sub>2</sub> and aerosols at high spatial resolution is of great interest here because of the heterogeneity of the pollution sources (car traffic, national airport, power plant) in the capital region of Brussels. The MAX-DOAS dual-scan instrument is composed of the following parts: the optical head mounted on a sun tracker, two spectrometers (UV and Visible) inside a thermo-regulated box and the data-acquisition unit. The optical head and the two
- spectrometers are connected with optical fibers. A more detailed description of the BIRA-IASB MAX-DOAS dual-scan 90 instrument can be found in Dimitropoulou et al. (2020).

From March 2018 to February 2020, the MAX-DOAS instrument operated in a dual-scan viewing mode. Two different submodes compose one complete measurement scan (see Dimitropoulou et al., 2020): (1) a vertical scan in nine different elevation angles (EAs) in one fixed telescope azimuth angle (TAA; Northeast direction i.e., towards the city center and the national airport) and (2) a horizontal scan in nine different azimuthal directions at a fixed elevation angle (2° above the horizon). 95 Several azimuthal viewing directions were tested to obtain an optimal horizontal sampling without any obstacle in the different viewing directions (see Fig. 1). The selection of more azimuthal directions towards the North, Northeast, and Northwest was made considering the location of the main NO<sub>2</sub> emission sources and, consequently, the highly variable NO<sub>2</sub> horizontal distribution towards these directions.

The integration time for each measured radiance spectrum is 60s, resulting in a full scan duration of approximately 20 minutes.



105 Figure 1. The experimental set-up of the BIRA-IASB dual-scan MAX-DOAS instrument. Each line is color-coded according to the different set-ups that were used from March 2018 to February 2020. The length of each line is equal to 20 km, which corresponds to the typical horizontal sensitivity for the MAX-DOAS measurements in the present

study (see Fig. 18). The black square shows the MAX-DOAS instrument location, the black polygon the National Airport, the black dots the NO<sub>2</sub> hotspots emitting more than 10 kg of NO<sub>x</sub> per hour (Emission Inventory of the Belgian

110 Interregional Environment Agency, 2017), and the black line represents the Brussels Ring motorway.

#### 2.2 Multi-wavelength DOAS analysis

The measured radiance spectra of a full measurement scan are analyzed using the QDOAS spectral fitting software developed by BIRA-IASB (Fayt et al., 2011). The DOAS technique separates the narrow absorption features of trace gases in the UV-115 Visible spectral range from a spectral background caused mainly by Mie and Rayleigh scattering and instrumental effects. The trace gas concentration integrated along the light-path in a measured spectrum relative to the amount of the same absorber in a reference spectrum is the primary product of the DOAS analysis and is called differential slant column density (dSCD). Here, average zenith spectra before and after each measurement scan are used as a reference.

- The  $O_4$  and  $NO_2$  dSCDs are retrieved in six different wavelength intervals: Three intervals in the UV spectral range (330-361 nm, 350-370 nm, and 360-383.5 nm) and three in the Visible range (420-460 nm, 450-490 nm, and 510-540.1 nm). These fitting windows were selected to optimize the determination of the  $O_4$  and  $NO_2$  dSCDs at the maximum number of different  $O_4$  absorption bands available in the wavelength domain of the instrument. Figure 2 shows an example of the  $O_4$  and  $NO_2$  fits in all the intervals used in the present work. In each chosen fitting window, we select a reference wavelength, which corresponds to the maximum of an  $O_4$  absorption peak (or close to it) in the respective wavelength intervals (see Fig. 2), and
- 125 it is subsequently used for radiative transport calculations and further analysis. The different reference wavelengths are 343 nm, 360 nm, 380 nm, 447 nm, 477 nm and 530 nm (see Fig. 2). To optimize the derivation of the dSCDs at the six selected wavelengths, the fit of a slope parameter, which accounts for the variation of the dSCD within the fitting interval (Pukīte et al., 2010), is necessary. This is especially important when the reference wavelength is not located in the center of the fitting window (i.e., 330-361 nm, 350-370 nm, 420-460 nm, and 450-490 nm). The DOAS settings used for each fitting interval are
- 130 presented in Table S1. As shown in this table, two different  $O_4$  cross-sections are used in this study: (1) Finkenzeller and Volkamer, (2022) in the UV fitting intervals and (2) Thalman and Volkamer, (2013) in the Vis fitting intervals. The main motivation for using the  $O_4$  cross-section from Finkenzeller (measured at 25°C) in the UV fitting intervals is the significant improvement of the fit quality and the reduction of the uncertainties for the UV retrievals. Sensitivity tests and comparisons with radiative transport simulations also show that the resulting  $O_4$  and  $NO_2$  dSCDs are consistent throughout the whole
- 135 wavelength range covered by the six intervals. For NO<sub>2</sub> and O<sub>3</sub>, which are the strongest absorbers in all the fitting windows, a correction for the solar  $I_0$  effect (Aliwell et al., 2002) is applied. A high-resolution solar atlas (Kurucz et al., 1984) is used for the wavelength calibration of the measured spectra.




Figure 2. Fit results of the  $O_4$  and  $NO_2$  fit at the six selected fitting windows from the dual-scan MAX-DOAS measurements in Uccle (2 June 2019 at 07:05 UTC). The measured spectra are represented with black lines, while the fit results are shown with red lines. The blue lines represent the six reference wavelengths.

## **3 TROPOMI tropospheric NO2 measurements**

145

In the present study, MAX-DOAS tropospheric NO<sub>2</sub> VCDs are used to validate collocated TROPOMI satellite observations. TROPOMI is a passive grating imaging spectrometer flying onboard the S5P satellite platform. It covers the UV-Visible (250-500 nm), near-infrared (710-770 nm), and short-wave infrared (2314-2382 nm) spectral ranges (Veefkind et al., 2011).

150 TROPOMI measures in a push-broom configuration with a full swath width as wide as 2600 km, and it provides daily global coverage at a spatial resolution (true-nadir pixel size) of 7x3.5 km<sup>2</sup>, further improved to 5.5x3.5 km<sup>2</sup> on 6 August 2019. The TROPOMI tropospheric NO<sub>2</sub> algorithm has been developed at KNMI and uses a retrieval-assimilation-modeling system that is based on the 3-D global TM5 chemistry transport model (van Geffen et al., 2021a; Williams et al., 2017).

We use the reprocessed (RPRO) and offline (OFFL) datasets of the TROPOMI L2 tropospheric  $NO_2$  column product (see

155 Table 1 for the corresponding versions). According to the guidelines provided by van Geffen et al. (2021a), RPRO dataset are available only for the first period of the present study (see Table 1). For the remaining periods, OFFL datasets are used, which are the main data products being available within two weeks from the TROPOMI measurement. To ensure best measurements' quality, only pixels with a quality assurance value larger than 0.75 are used. This quality flagging eliminates pixels with a cloud radiance fraction larger than 0.5, snow or ice, and erroneous retrievals (Eskes and Eichmann, 2020).

- 160 Next to operational products, two additional TROPOMI data sets are also used (see Section S2 in the supplement). In the first one, the TROPOMI retrieval is performed with different a priori profiles (Douros et al., in preparation). The coarse TM5-MP a priori NO<sub>2</sub> profiles, using a spatial resolution of 1° x 1°, is replaced by NO<sub>2</sub> profile shapes from the CAMS (Copernicus Atmospheric Monitoring Service) regional Chemistry Transport Model (CTM) ensemble at a spatial resolution of 0.1° x 0.1° (S5P-CAMS product). The replacement of a coarse a priori information by a finer one can lead to significant changes in the
- 165 TROPOMI retrieved NO<sub>2</sub> tropospheric columns. The available dataset covers October 2018 to March 2020 (OFFL dataset, L2, and version 01.02.00 up to 01.04.00, Eskes and Eichmann, 2020).

In the second additional product, the TROPOMI retrieval is performed with an improved cloud product (Eskes et al., 2020; van Geffen et al., 2021a). According to van Geffen et al. (2021a), the improvement in the FRESCO-S cloud pressure retrieval scheme to the FRESCO-wide product, has an impact on the NO<sub>2</sub> AMFs and consequently, on the NO<sub>2</sub> tropospheric columns

- 170 over polluted areas. More precisely, the existing FRESCO-S product had a negative bias in the cloud height values, which resulted in a low NO<sub>2</sub> tropospheric column (Compernolle et al., 2021). The TROPOMI tropospheric NO<sub>2</sub> columns are retrieved using an improved FRESCO-S cloud retrieval scheme, called FRESCO-wide, in v1.4 since 29 November 2020 (Eskes and Eichmann, 2020). In the present study, the diagnostic data sets (DDSv2) are used, which are an ensemble of reprocessed data for past periods analyzed with new versions (van Geffen et al., 2021b). Over the MAX-DOAS measurement time-period, only
- 175 DDSv2 data corresponding to OFFL datasets (v1.2 and v1.3) are available. Excluding the spin-up period needed by TM5-MP, only four data periods are available for our comparisons (i.e., 30/06/2018 06/07/2018, 30/12/2018 5/01/2019, 30/03/2019-05/04/2019, and 17/09/2019-23/09/2019).

Dataset	Version	Starting date	End date
RPRO	01.02.02	30/04/2018	17/10/2018
OFFL	01.02.00	17/10/2018	28/11/2018
OFFL	01.02.02	28/11/2018	20/03/2019
OFFL	01.03.00	20/03/2019	23/04/2019
OFFL	01.03.01	23/04/2019	26/06/2019
OFFL	01.03.02	26/06/2019	29/11/2020

Table 1. TROPOMI NO<sub>2</sub> processor versions used in the present study.

# **4** Ancillary measurements

In the present study, ancillary measurements are used for two main purposes: (1) as a priori information on the retrieval of the MAX-DOAS  $NO_2$  and aerosol horizontal profiles and (2) to validate the retrieved MAX-DOAS  $NO_2$  horizontal profiles. First, the CIMEL Sun photometer is a multi-channel photometer, which measured the direct solar irradiance and sky radiance

- 185 at the Earth's surface in discrete wavelengths in the UV, Visible and near-IR wavelengths of the spectrum. Aerosol optical thickness measurements at the Brussels-Capital Region from a co-located CIMEL Sun photometer of the AERONET network (<u>https://aeronet.gsfc.nasa.gov/</u>) are used on the retrieval of the MAX-DOAS aerosol horizontal profiles (see Section 5.3). Secondly, independent NO<sub>2</sub> horizontal profile, used as as a priori information in the new OEM-based horizontal distribution inversion approach, are provided by the RIO model. RIO is a land-use regression model based on the interpolation of the
- 190 hourly NO<sub>2</sub> near-surface concentrations measured by the in-situ telemetric air quality network in Belgium (Hooyberghs et al., 2006; Janssen et al., 2008; see http://irceline.be/en). RIO provides hourly NO<sub>2</sub> concentration maps on a 4x4 km<sup>2</sup> spatial resolution.

To validate the retrieved MAX-DOAS NO<sub>2</sub> horizontal profiles, independent measurements are necessary in the Brussels-Capital Region.

- 195 For the S5P validation campaign over Belgium (S5PVAL-BE, https://s5pcampaigns.aeronomie.be/), airborne measurements of the two largest urban regions over Belgium, i.e., Antwerp and Brussels, took place from 26 to 29 June 2019 (Tack et al., 2021). The Airborne Prism EXperiment (APEX) imaging spectrometer was used to measure the horizontal distribution of tropospheric NO<sub>2</sub> columns with a spatial resolution of approximately 75 m x 120 m (Tack et al., 2017; Tack et al., 2019). During the S5PVAL-BE flight over Brussels, car mobile-DOAS observations were performed by the BIRA-IASB mobile-
- 200 DOAS, the so-called AEROMOBIL (Merlaud, 2013). The AEROMOBIL consists of a compact double Avantes spectrometer recording simultaneously scattered light in two elevation angles (i.e., one at 30° elevation angle and one at zenith). The AEROMOBIL was used to measure the spatial distribution of tropospheric NO<sub>2</sub> columns mainly over the Ring road of Brussels. These airborne and car-mobile measurements are compared with the retrieved MAX-DOAS NO<sub>2</sub> horizontal profiles (see Section 6.2).

#### 205 **5 Description of the mapping MAX-DOAS technique**

First, the measured radiance spectra in the UV and Visible wavelength ranges are analyzed in the six different fitting windows listed in Section 2.2. Then, the Optimal Estimation Method (OEM)-based Mexican MAX-DOAS Fit (MMF) algorithm is applied to the  $O_4$  and  $NO_2$  dSCDs in the main azimuthal direction (and at 477 nm) to retrieve vertical  $NO_2$  profiles and obtain information about the vertical extent of  $NO_2$  in the troposphere via the Mixing Layer Height of  $NO_2$  (MLH<sub>NO2</sub>; see Section 5.1)

210 5.1).

As an intermediate step, radiative transfer model (RTM) simulations are performed (see Table 2 and Section 5.2) to obtain information about the horizontal sensitivity ( $L_{NO2}$ ) and AOD as a function of O<sub>4</sub> dSCDs, wavelength, and MLH<sub>NO2</sub>.

Then, in the next step, a new dual-scan parameterization technique is applied to the  $O_4$  and  $NO_2$  dSCDs at the six different wavelengths and in all the azimuthal directions with MLH<sub>NO2</sub>, measured  $O_4$  dSCDs, and measurement geometry being the

215 main input parameters to retrieve the horizontal sensitivity of  $NO_2$  and, consequently, the  $NO_2$  near-surface concentrations and VCDs, and near-surface aerosol extinction as a function of distance from the instrument (see Section 5.2).

In the final step, a new OEM-based horizontal distribution inversion approach is developed using the six near-surface  $NO_2$  concentrations and aerosol extinction values per azimuthal direction to retrieve  $NO_2$  and aerosol extinction horizontal profiles in an output grid of 500m thickness (see Section 5.3).

220 A flow chart describing the mapping MAX-DOAS technique is shown in Fig. 3.




Figure 3. Mapping MAX-DOAS technique flow chart.

# 5.1 Aerosol and NO2 OEM-based profile retrievals

The Optimal-estimation-based MMF inversion algorithm (Friedrich et al., 2019) is applied to retrieve the aerosol extinction coefficient and  $NO_2$  vertical profiles for each MAX-DOAS elevation scan in the main azimuthal direction at 360 nm and 477 nm. First, the  $O_4$  measurements are used to retrieve the aerosol extinction profile. Several studies indicated the importance of

- 230 applying a scaling factor (≠1) to the observed O<sub>4</sub> dSCDs to bring them in agreement with simulated O<sub>4</sub> dSCDs by radiative transfer modeling (Wagner et al., 2009; Clémer et al., 2010; Merlaud et al., 2011; see also Wagner et al., 2019 / Table 1 for a comprehensive list of all those studies). However, there is no consensus on the fundamental reason for applying this scaling (see e.g. Ortega et al., 2016). As found by Tirpitz et al. (2021), the choice of the scaling factor has only a small effect on the performance of the trace gas retrieval, so we decided not to apply it in the present study. The aerosol extinction profile retrieved
- from each scan is used as an input to the radiative transfer calculations used to retrieve the NO<sub>2</sub> retrieval profile. Further details about the MMF inversion algorithm, the input a priori parameters, the quality check of each scan, and the estimated uncertainties of the aerosol and NO<sub>2</sub> vertical profile can be found in Dimitropoulou et al. (2020).

A broken cloud-filtering approach based on Gielen et al. (2014) is applied to the MAX-DOAS measurements to exclude MAX-

240 DOAS aerosol and NO<sub>2</sub> scans influenced by the presence of clouds, which are known to potentially degrade the quality of the retrievals (Gielen et al. 2014, Wagner et al. 2014). Three sky conditions can be distinguished with this flagging approach: (1) clear sky, (2) homogeneous cloud coverage and (3) broken clouds conditions. Retrievals under broken cloud conditions are rejected from the present study.

The profile retrieval was performed to estimate the Mixing Layer Height of NO<sub>2</sub> (MLH<sub>NO2</sub>). The MLH<sub>NO2</sub> is estimated per

245 measurement scan, and it is the ratio of  $VCD_{NO2,main}$  to the NO<sub>2</sub> near-surface concentration ( $c_{NO2,main}$ ) as retrieved in the main azimuthal direction by the MMF inversion algorithm:

$$MLH_{NO_2} = \frac{VCD_{NO_2,main}}{c_{NO_2,main}}$$
(1)

Therefore, during one measurement scan, two assumptions were made: (1) the homogeneous distribution of  $NO_2$  inside the MLH<sub>NO2</sub> and (2) the homogeneous MLH<sub>NO2</sub> around the measurement site and its use in all the azimuthal directions. The validity of the second assumption is tested in Section 5.2.3.

#### 5.2 Dual-scan MAX-DOAS retrieval method

250

A complete MAX-DOAS measurement scan is composed of two different sub-scans, as described in Sect. 2.1. The aerosol and NO<sub>2</sub> vertical profiles are retrieved from the elevation scan in the main azimuthal direction. In the other azimuthal 255 directions, measurements are performed only in a single low elevation angle (2°), and therefore, the retrieval of aerosol and NO<sub>2</sub> vertical profiles is not possible. Using the fact that the lowest elevation angles have the highest sensitivity to trace gases located nearby the surface due to the long light path in this layer, a new dual-scan MAX-DOAS retrieval strategy was developed here. This new retrieval strategy is an extension of the work presented in Dimitropoulou et al. (2020) and aims to retrieve the near-surface  $NO_2$  box-averaged volume mixing ratios (VMRs) and the  $NO_2$  VCDs at six different wavelengths. In

260 Dimitropoulou et al. (2020), the applied dual-scan NO<sub>2</sub> MAX-DOAS retrieval was itself an adaptation of the parameterization technique proposed by Sinreich et al. (2013). More precisely, in the presence of sufficient aerosols in the atmosphere (i.e., sufficient aerosols to constrain the light path in a near-surface layer and ensure that the near-surface NO<sub>2</sub> concentration can be approximated by a near-surface box profile), the measured NO<sub>2</sub> dSCDs at one low elevation angle (2°) can be related to the near-surface NO<sub>2</sub> box-averaged concentration as follows:

$$dSCD_{NO_2} = c_{NO_2}L_{NO_2}$$
<sup>(2)</sup>

where  $dSCD_{NO2}$  is the differential slant column density of NO<sub>2</sub> and  $c_{NO2}$  its mean concentration along the differential effective light path,  $L_{NO2}$ .

- 270 Consequently, the knowledge of the differential effective light-path's length (i.e.,  $L_{NO2}$ ) is crucial to derive the near-surface NO<sub>2</sub> concentrations. The oxygen collisional complex (O<sub>4</sub>) can be used as a tracer for the effective light-path in the atmosphere, as its concentration is well-known (it is the square of O<sub>2</sub> concentration). As a result, observed changes of the O<sub>4</sub> dSCDs can be directly attributed to changes in the light-path due to the presence of particles like aerosols and clouds.  $L_{O4}$  is calculated by using Eq. 2 for O<sub>4</sub>.
- 275 However, the direct use of the O<sub>4</sub> light-path length in the NO<sub>2</sub> retrieval is not possible under moderate to high pollution conditions, such as those in Brussels, because the profile shapes of O<sub>4</sub> and NO<sub>2</sub> are not the same. In Dimitropoulou et al. (2020), we used radiative transfer model (RTM) simulations to estimate a unitless correction factor, which accounts for these profile shape differences. This unitless correction factor indicates that under moderate to high pollution conditions,  $L_{NO2}$  is equal to or smaller than  $L_{O4}$ . For a correction factor equal or close to one,  $L_{O4}$  is equal to  $L_{NO2}$ , which means that there is a moderate to
- 280 high aerosol load in the atmosphere during the measurement. On the other hand, correction factors smaller than unity are obtained for measurements performed under aerosol-free conditions or a thin MLH. Assuming a homogeneous NO<sub>2</sub> distribution inside the MLH, the MLH is derived from the NO<sub>2</sub> vertical profiles in the main azimuthal direction and is defined as the ratio of the NO<sub>2</sub> VCD to the near-surface concentration of NO<sub>2</sub>. In Dimitropoulou et al. (2020), the RTM simulations were performed for eight different MLH values of aerosols and NO<sub>2</sub> in the range of 500-2000 m (i.e. eight different
- 285 combinations) and for different measurement viewing geometries (Solar Zenith Angle (SZA), Relative Azimuth Angle (RAA) and the corresponding elevation angle of 2°). For every MAX-DOAS measurement, one value of the correction factor is given according to its viewing geometry and MLH value during the measurement. For further information, we refer the reader to Dimitropoulou et al. (2020).

In the present study, a new dual-scan NO<sub>2</sub> MAX-DOAS retrieval method, which is more suitable for interpreting multi-

290 wavelength measurements than the previous approach (Dimitropoulou et al., 2020), is developed. It is presented in detail in the following subsection.

# 5.2.1 Developed dual-scan MAX-DOAS retrieval method

The main advantages of the new dual-scan NO<sub>2</sub> MAX-DOAS retrieval method (which are also the main differences with respect to Dimitropoulou et al., 2020) are the following: (1) the direct use of the measured O<sub>4</sub> dSCDs to estimate  $L_{NO2}$  for

295 every measurement, (2) retrieval of near-surface aerosol extinction close to the ground, and (3) the exploitation of the wavelength dependency of the horizontal path representative of MAX-DOAS measurements for the retrieval of the horizontal distribution of aerosols (and therefore NO<sub>2</sub>) around the measurement site. The latter is done using O<sub>4</sub> and NO<sub>2</sub> dSCDs measured at six different wavelengths. This new method is described below.

Assuming that the NO<sub>2</sub> vertical distribution can be approximated by a box profile of height equal to mixing layer height  $(MLH_{NO2})$ , the following equation can be used:

$$c_{NO_2} = \frac{VCD_{NO_2}}{MLH_{NO_2}} = \frac{dSCD_{NO_2}}{L_{NO_2}}$$
(3)

This means that the NO<sub>2</sub> near-surface concentration can be expressed as a ratio of the dSCD<sub>NO2</sub> to the  $L_{NO2}$  (see Eq. 2) or as a ratio of the VCD<sub>NO2</sub> to the MLH<sub>NO2</sub>. When knowing MLH<sub>NO2</sub> and VCD<sub>NO2</sub>,  $L_{NO2}$  can be simulated as follows:

$$L_{NO_{2} simulated} = dSCD_{NO_{2} simulated} \cdot \frac{MLH_{NO_{2}}}{VCD_{NO_{2}}}$$
(4)

Here, NO<sub>2</sub> dSCDs and consequently  $L_{NO2}$  are simulated using the radiative transfer model VLIDORT version 2.7 (Spurr,

- 310 2006). Seasonal median MAX-DOAS NO<sub>2</sub> vertical profiles, as retrieved by applying the MMF inversion algorithm in the main azimuthal direction (see Sect. 5.1), show that the bulk (70 %) of the NO<sub>2</sub> concentration is located inside the MLH<sub>NO2</sub>, which is expected since MLH<sub>NO2</sub> is estimated as the ratio of VCD<sub>NO2</sub> to the near-surface NO<sub>2</sub> concentration. On the other hand, this is not the case for aerosols (only 30 % of the aerosol content is seen to be located inside the MLH<sub>NO2</sub>). Considering this feature, for the VLIDORT simulations, the NO<sub>2</sub> a priori profiles are modeled as box profiles with a constant concentration equal to
- 315 1.5x10<sup>11</sup> molec/cm<sup>3</sup> from the surface to the MLH<sub>NO2</sub>. Two layers compose the aerosol a priori profiles: (1) the MLH<sub>NO2</sub> and (2) the free troposphere. The equation, which is applied to estimate the aerosol extinction profile a(z), is the following (see Wang et al., 2014):

$$a(z) = AOD \frac{p}{MLH_{NO_2}}, \text{ for } z \le MLH_{NO_2}$$
(5a)

and,

300

320 
$$a(z) = b(\xi, MLH_{NO2}, p) \exp(-\frac{z}{\xi}), \text{ for } z > MLH_{NO2}$$
 (5b)

where AOD is the aerosol optical depth, p is the fraction of AOD inside the MLH<sub>NO2</sub>, b is a normalizing constant for the exponential component (Wang et al., 2014), z is the simulation altitude grid, and  $\xi$  is the scaling height for the aerosols located

outside the MLH<sub>NO2</sub>, which is set to 5 km (Wang et al., 2014). In the present study, the fraction of AOD located within the MLH<sub>NO2</sub> is set to p=0.3 (see above). The effect of the p value and the NO<sub>2</sub> profile shape on the retrieved NO<sub>2</sub> near-surface VMRs and VCDs were investigated and considered in the error budget (see Sect. 5.2.2).

The MLH<sub>NO2</sub> is a known parameter and it is estimated per measurement scan, as the ratio of VCD<sub>NO2</sub> to the NO<sub>2</sub> near-surface concentration as retrieved in the main azimuthal direction by the MMF inversion algorithm.

The RTM simulations have in total nine input parameters, which are the elevation angle, SZA, RAA, AOD, MLH<sub>NO2</sub>,  $c_{NO2}$ , AOD (p and  $\xi$ ), and wavelength. It should be noted that the elevation angle is kept constant (i.e., 2°). For the six different wavelengths (343 nm, 360 nm, 380 nm, 447 nm, 477 nm, and 530 nm), we separately perform RTM simulations and L<sub>NO2</sub> (see

Eq. 4) are simulated for the assumed SZA, RAA, MLH<sub>NO2</sub>, c<sub>NO2</sub>, and AOD input scenarios presented in Table 2.

Table 2. RTM inputs for the simulations of L<sub>NO2</sub> at the six selected wavelengths (343 nm, 360 nm, 380 nm, 447 nm, 477 nm, and 530 nm).

Parameter	Values			
Wavelength/ nm	343, 360, 380, 447, 477, 530			
SZA/ °	20, 30, 40, 50, 60, 70, 80			
RAA/ °	0, 10, 20, 30, 40, 50, 60, 90, 120, 150, 180			
AOD	0, 0.1, 0.3, 0.4, 0.6, 0.8, 1			
p of AOD	0.30			
ξ of AOD/ km	5			
asymmetry parameter	0.68			
Single Scattering Albedo				
(SSA)	0.92			
MLH/ m	500, 1000, 1500			
Elevation angle/ °	2			
C <sub>NO2</sub> / molec.cm <sup>-3</sup>	1.5 x 10 <sup>11</sup>			

335

340

325

330

The simulated  $O_4$  dSCDs are a function of the input parameter AOD. The relation between the simulated  $O_4$  dSCDs and the input AOD values is shown in Fig. 4a. A Piecewise cubic hermite interpolating polynomial fitting through the AOD as a function of the simulated  $O_4$  dSCDs for each SZA, RAA, and MLH<sub>NO2</sub> combination can be used in order to perform an inverse method (i.e. to estimate the near-surface aerosol extinction from the measured  $O_4$  dSCDs). Additionally, in Fig.4b, we can see that the relation between the  $O_4$  dSCDs and the AOD values is valid for MAX-DOAS measurements.

For every combination of all eight parameters (i.e., all the parameters of Table 2, except the AOD values), a polynomial fit of simulated  $L_{NO2}$  as a function of simulated  $O_4$  dSCDs is applied. Fig. 5a shows simulated  $L_{NO2}$  as a function of simulated  $O_4$  dSCDs, and a second-order polynomial is fitted through the data points. We observe, also, in Fig. 5b, in which an example day of MAX-DOAS measurements is presented, that the  $L_{NO2}$  as a function of the measured  $O_4$  dSCDs have the same relation as

- 345 the simulated quantities. Since NO<sub>2</sub> is an optically thin absorber, L<sub>NO2</sub> is not a function of c<sub>NO2</sub> and consequently, a L<sub>NO2</sub> value can be estimated by using the measured O<sub>4</sub> dSCD for each measurement. Based on the corresponding SZA, RAA, measured O<sub>4</sub> dSCD, and MLH<sub>NO2</sub>, a L<sub>NO2</sub> is attributed to each low elevation MAX-DOAS measurement through this polynomial fit. To express L<sub>NO2</sub> as a function of four different parameters (i.e., O<sub>4</sub> dSCD, SZA, RAA, and MLH<sub>NO2</sub>), L<sub>NO2</sub> is interpolated linearly at the O<sub>4</sub> dSCD, SZA, RAA, and MLH<sub>NO2</sub> of each measurement. For example, a MAX-DOAS measurement with SZA=30°,
- 350 RAA=60°, MLH<sub>NO2</sub>=1km, and measured O<sub>4</sub> dSCD= $6.10^{43}$  molec<sup>2</sup>.cm<sup>-5</sup> will have a L<sub>NO2</sub> equal to 15 km at 477 nm (see Fig. 5a).

Based on this approach, the near-surface  $NO_2$  concentration can be calculated at the six different wavelengths by using the measured dSCD<sub>NO2</sub> together with the simulated L<sub>NO2</sub> value (Eq. 2). The corresponding near-surface  $NO_2$  VMR are obtained by dividing the  $NO_2$  concentrations by the air number density. To derive the air number density, we use monthly averaged

- 355 pressure and temperature profiles over a 20-year period. These profiles are extracted from the European Centre for Medium-Range Weather Forecasts (ECMWF) ERA-Interim reanalysis. In the last step, the tropospheric  $NO_2$  VCD is calculated from the product of the near-surface  $NO_2$  concentration with the MLH<sub>NO2</sub>.
- Regarding aerosols, the AOD is estimated for every off-axis measurement (see Fig. 4a). The near-surface aerosol extinction is then calculated as the ratio between the aerosols inside the MLH<sub>NO2</sub> (i.e., AOD times p) and MLH<sub>NO2</sub>. The near-surface aerosol extinction refers to the layer that extends from the surface to the MLH<sub>NO2</sub>. As mentioned above, around 30% of the total aerosols is expected to be found inside this layer.

The effect of SZA, RAA, and MLH<sub>NO2</sub> on the simulated  $L_{NO2}$  is investigated in the supplement. First, the simulated  $L_{NO2}$  are presented in Fig. S1 as a function of RAA for different MLH<sub>NO2</sub> and wavelengths and a single AOD and SZA value.  $L_{NO2}$ strongly depends on MLH<sub>NO2</sub>. The lower the MLH<sub>NO2</sub>, the shorter the  $L_{NO2}$  is. The same NO<sub>2</sub> concentration and aerosol load are used for the three different MLH<sub>NO2</sub> scenarios. So, when aerosols are concentrated in a thin layer (i.e., MLH<sub>NO2</sub>=0.5 km),  $L_{NO2}$  becomes shorter. Secondly, we observe that  $L_{NO2}$  depends on RAA. The larger the RAA, the longer the  $L_{NO2}$ . In Fig. S2,

370 RAA). L<sub>NO2</sub> depends strongly on SZA. The highest dependency is observed for large SZA values, where L<sub>NO2</sub> becomes maximum. Finally, in both Fig. S1 and S2, we observe that L<sub>NO2</sub> becomes longer with wavelength, which is expected because of the less pronounced Rayleigh and Mie scattering at longer wavelengths.

simulated  $L_{NO2}$  are plotted for each wavelength and each considered MLH<sub>NO2</sub> as a function of SZA (at a constant AOD and

An example of dual-scan MAX-DOAS retrieval is shown in Fig. 6. Based on the RTM simulations described above, L<sub>NO2</sub> is

375 derived for the wavelengths of interest, and ultimately, near-surface NO<sub>2</sub> concentrations and tropospheric NO<sub>2</sub> VCDs are estimated. In the last step, the near-surface aerosol extinction values are assigned to the six different wavelengths.

380




Figure 4. (a) Dots: Simulated AOD for NO<sub>2</sub> box profile of 1 km at 477nm for a SZA of 40° and RAA of 30° as a function of the simulated O<sub>4</sub> DSCDs for the different AOD values (1, 0.8, 0.6, 0.4, 0.3, 0.1 and 0; see Table 2). Blue line: simulated AOD by applying an exponential fit through the data points. (b) Dots: Estimated AOD in the six wavelengths used in the retrieval for one example day (11 September 2018). Red line: fitted line through the data points.




Figure 5. (a) Dots (stars): Simulated L<sub>NO2</sub> for NO<sub>2</sub> box profile of 1 km at 477nm (530 nm) for a SZA of 30° and RAA of 60° as a function of the simulated O<sub>4</sub> DSCDs for the different AOD values (1, 0.8, 0.6, 0.4, 0.3, 0.1 and 0; see Table 2). Blue (red) line: 2nd-order polynomial fit through the data points. (b) Dots: Estimated L<sub>NO2</sub> in the six wavelengths used in the retrieval for one example day (11 September 2018). Red line: fitted line through the data points.




Figure 6. (a) Corresponding L<sub>NO2</sub>, (b) near-surface NO<sub>2</sub> concentrations, (c) NO<sub>2</sub> VCDs, and (d) aerosol optical densities 405 as a function of the six wavelengths used in the retrieval (11 September 2018, 11:51 UTC, 123.5° azimuthal direction).

#### 5.2.2 Uncertainty budget

To estimate uncertainties on the dual-scan parameterized  $NO_2$  near-surface concentration and VCD, the standard error propagation method is used as:

410

$$\sigma_{c_{NO_2}}^2 = \left(\sigma_{dSCD_{NO_2}} \frac{\partial c_{NO_2}}{\partial dSCD_{NO_2}}\right)^2 + \left(\sigma_{L_{NO_2}} \frac{\partial c_{NO_2}}{\partial L_{NO_2}}\right)^2 \tag{6}$$

which is solved as:

$$\sigma_{c_{NO_2}}^2 = \left(\frac{\sigma_{dSCD_{NO_2}}}{L_{NO_2}}\right)^2 + \left(-\frac{\sigma_{L_{NO_2}}dSCD_{NO_2}}{L_{NO_2}^2}\right)^2 \tag{7}$$

415 and then:

$$\sigma_{c_{NO_2}}^2 = \left(\sigma_{dSCD_{NO_2}} \frac{c_{NO_2}}{dSCD_{NO_2}}\right)^2 + \left(\sigma_{L_{NO_2}} \frac{c_{NO_2}}{L_{NO_2}}\right)^2 \tag{8}$$

where:

$$\sigma_{L_{NO2}}^2 = \left(\frac{L_{NO2}}{dSCD_{NO2}(sim)} \sigma_{dSCD_{NO2}}\right)^2 + \left(\frac{L_{NO2}}{MLH_{NO2}} \sigma_{MLH_{NO2}}\right)^2 \tag{9}$$

- 420 According to Kreher et al. (2019) and Bösch et al. (2018), in urban or suburban polluted conditions, the use of the DOAS fit uncertainty of NO<sub>2</sub> for the dSCD<sub>NO2</sub> uncertainty is not appropriate, because the dSCD<sub>NO2</sub> uncertainty is mostly driven by atmospheric variability as well as spatial and temporal fluctuations in the O<sub>4</sub> and NO<sub>2</sub> fields. In this study, a conservative value of  $3.5 \times 10^{15}$  molec.cm<sup>-2</sup> is attributed to  $\sigma_{dSCD_{NO_2}}$  (Kreher et al., 2019). This represents an error of up to 6.0% on the NO<sub>2</sub> dSCDs in the visible range (477 nm).
- 425 The second error source is related to the estimation of  $L_{NO2}$  from the RTM simulations. To estimate this error, sensitivity tests on the input aerosol and NO<sub>2</sub> vertical profiles were performed. The fraction of aerosols located inside the MLH<sub>NO2</sub> (40% and 60% instead of 30%) and the NO<sub>2</sub> profile shape (linearly decreasing instead of box) were modified. The error related to the RTM simulations of the simulated dSCD<sub>NO2</sub> is about 9.6% in the Visible range (477 nm). Additionally, according to Dimitropoulou et al. (2020), the uncertainty related to MLH<sub>NO2</sub> is about 4% in the Visible range (477 nm).
- 430 Combining all the error sources, the total uncertainties on the NO<sub>2</sub> near-surface concentration is about 12.7%, 12.4%, 11.4%, 11.1%, 11.3%, and 12.6% in 343 nm, 360 nm, 380 nm, 447 nm, 477 nm, and 530 nm, respectively.
  Finally, the total uncertainties on the NO<sub>2</sub> VCD is about 12.0%, 11.7%, 10.7%, 10.3%, 10.6%, and 11.9% in 343 nm, 360 nm, 380 nm, 447 nm, 477 nm, and 530 nm, respectively.

#### 435 5.2.3 Verification of the dual-scan MAX-DOAS retrieval method

The consistency check and verification of the dual-scan MAX-DOAS retrieval method in Uccle is based on two different correlative comparisons.

The consistency check compares the  $NO_2$  near-surface VMRs and tropospheric VCDs retrieved by the dual-scan parameterization in the main azimuthal direction to the same quantities retrieved with the MMF inversion algorithm at the two

440 main wavelengths (360 nm and 477 nm). As can be seen in Figures 7 and 8, both data sets are in good agreement, with correlation coefficient values in the range of 0.86 to 0.95 and slope values close to unity for all the four comparisons.

The verification step is based on the same type of comparison as the first one but for three additional azimuthal directions, where elevation scans, and hence profile retrievals, are available for some periods. Onward July 3, 2019, elevation scans were performed in these three additional azimuthal directions to complement the already existing measurement set-up. These

445

450

performed in these three additional azimuthal directions to complement the already existing measurement set-up. These elevation scans were performed once per day, around noon, in the 11°, 105°, and 262.5° azimuthal directions. Figure 9 shows the comparison between near-surface NO<sub>2</sub> VMRs and tropospheric VCDs retrieved by the dual-scan parameterization method and the corresponding results obtained with the MMF inversion algorithm. Overall good agreement is obtained (R=0.79 and 0.84 for near-surface VMR and VCD, respectively). We observe that the comparison concerning the near-surface NO<sub>2</sub> VMR seems to be noisier than in the main azimuth direction. This is mainly due to the use of the MLH<sub>NO2</sub> calculated in the main azimuthal direction for all the different azimuth angles in the dual-scan method. Additionally, the parameterization technique slightly underestimated the near-surface NO<sub>2</sub> VMR (s=0.84) while a slope value of 1.00 is obtained for tropospheric VCDs.




Figure 7. Comparison between MMF and parameterized NO<sub>2</sub> near-surface VMR at 477 nm (Visible, left panel), and 360 nm (UV, right panel), as derived from the main azimuthal direction (i.e., 35.5° azimuthal direction).




Figure 8. Comparison between MMF and parameterized NO<sub>2</sub> VCD at 477 nm (Visible, left panel), and 360 nm (UV, right panel), as derived from the main azimuthal direction (i.e., 35.5° azimuthal direction).




Figure 9. Visible range: comparison between MMF and (left panel) parameterized NO<sub>2</sub> near-surface VMR and (right panel) parameterized NO<sub>2</sub> VCD at three different azimuthal directions, as indicated in the color bar (11°, 105°, and 262.5° azimuthal directions). The elevation scans in these azimuthal directions were performed once per day from 3 July 2019.

465

470

#### 5.3 Horizontal distribution inversion approach

The parameterized  $NO_2$  near-surface concentrations at the six different wavelengths are used as input in a new horizontal distribution inversion approach. As parameterized  $NO_2$  near-surface concentrations, we refer to the conversion of the measured  $NO_2$  dSCDs (i.e. at the elevation angle of 2°) to near-surface  $NO_2$  concentrations by applying the dual-scan MAX-DOAS retrieval method as described in Sect. 5.2. Figure 10 shows a sketch of the assumed horizontal box model configuration, in

- which successive boxes of concentration  $c_N$  between the horizontal distances  $d_{N-1}$  and  $d_N$  from the MAX-DOAS instrument are considered along the light path. The index N is equal to the total number of successive boxes.
- The different horizontal lines illustrate the horizontal extent (or differential effective light path as described in Sect. 5.2) in 475 which the NO<sub>2</sub> near-surface concentrations are extended for the six different wavelengths. Generally, the MAX-DOAS horizontal sensitivities are longer for larger wavelengths because of the less pronounced Rayleigh scattering (see also Fig. 6; Ortega et al., 2016; Dimitropoulou et al., 2020). In Fig. 10, the shortest line represents the smallest wavelength's horizontal sensitivity (343 nm), and the longest line the largest wavelength's horizontal sensitivity (530 nm). As can be seen in the sketch, the effective horizontal light path at the six different wavelengths passes through different number of horizontal bins.
- 480 The parameterized NO<sub>2</sub> near-surface concentrations at the different wavelengths are the mean concentrations along the horizontal effective light paths (see Section 5.2), which are also called differential effective light paths because they are linked to the dSCD<sub>NO2</sub>. When having information coming from one wavelength only, it is not possible to know how the NO<sub>2</sub> is distributed along this light path. In the present work, the knowledge of mean NO<sub>2</sub> concentrations at six different wavelengths is used to retrieve a horizontal NO<sub>2</sub> profile, assuming the horizontal box model described in Fig. 10. This new retrieval method is described below.

The measurement vector y consists of the six retrieved surface concentrations (called as  $\bar{c}_{NO2}$ ; see method presented in Sect. 5.2) at the six different wavelengths. These near-surface concentrations can be expressed as functions of the different effective light paths (L<sub>NO2</sub>) and correspond to the average surface concentrations along those L<sub>NO2</sub>:

490

$$\mathbf{y} = \mathbf{F}_{\text{meas}}(\mathbf{c}_{NO2\_true}) = \bar{\mathbf{c}}_{NO2} = \frac{\text{dSCD}_{NO2}}{L_{NO2}}$$
(10)

 $\mathbf{F}_{calcul}$ , which represents the forward model, can be expressed as follows:

495 
$$\mathbf{F}_{calcul}(\mathbf{c}_{NO2\_true}) = \frac{1}{L_{NO2}^2} \int_0^{L_{NO2}} \mathbf{e}^{-\frac{x}{L_{NO2}}} \mathbf{c}_{NO2}(\mathbf{x}) \frac{d\mathbf{x}}{\cos(a)}$$
 (11)

where x is the horizontal distance, a is the elevation angle of the measurement and  $c_{NO2}$  the NO<sub>2</sub> near-surface concentration as a function of x, the distance from the MAX-DOAS instrument.

Our retrieval of the horizontal distribution of  $c_{NO_2}$  is based on the inversion theory (Rodgers, 2000), in which a horizontal 500 profile  $c_{NO_2}$  (state vector) is retrieved given an a-priori horizontal profile  $x_{\alpha}$ , the measurement vector y, the matrix of the weighting function K, the uncertainty covariance matrix of the a priori  $S_{\alpha}$  and the uncertainty covariance matrix of the measurement  $S_e$ :

$$c_{NO2} = \mathbf{x}_{a} + (\mathbf{K}^{\mathrm{T}} \mathbf{S}_{e}^{-1} \mathbf{K} + \mathbf{S}_{a}^{-1})^{-1} \mathbf{K}^{\mathrm{T}} \mathbf{S}_{e}^{-1} (\mathbf{y} - \mathbf{K} \mathbf{x}_{a})$$
(12)

505

The weighting function indicates the sensitivity of the measurement vector to a change in the horizontal profile. Following the Beer-Lambert law, the weighting function are following an exponential decrease between the instrument and  $L_{NO2}$ . Additionally, we should consider that the light path through the horizontal boxes is slanted and not horizontal by including the cosine of the elevation angle a (i.e., 2° elevation angle). The weighting functions are given by the following equation:

510 
$$\mathbf{K}(\lambda, x) = \frac{1}{L_{NO2}} e^{-\frac{x}{L_{NO2}}} \frac{\Delta x}{\cos(a)}$$
(13)

An example of weighting functions is presented in Fig. 11. The sensitivity decreases exponentially up to a distance corresponding to the differential effective light path length of each measurement. More precisely, each measurement is highly sensitive to the MAX-DOAS instrument location. This sensitivity decreases exponentially as a function of the horizontal distance. Then, it reaches a value equal to 1/e to the horizontal distance equal to the differential effective light path length of

515 each measurement. It should be noted that since NO<sub>2</sub> is an optically thin absorber, the measurements depend linearly on each horizontal box's concentration. For this reason, OEM for the linear case is considered here, and only one inversion step is needed (see Eq. 12).

The selected output horizontal grid for the retrieval extends from the MAX-DOAS instrument to the horizontal distance in which the weighting function of the largest wavelength (i.e., 530 nm) decreases at 10% of its value at the MAX-DOAS

- 520 instrument's location per azimuthal direction and consists of successive boxes of 0.5 km thickness on the horizontal axis. Since this inversion problem is ill-conditioned, more than one horizontal  $NO_2$  profile can be consistent with the measurement vector. To reject unrealistic solutions, the a priori profile  $x_a$  and its uncertainty covariance matrix must be included in the retrieval. In the OEM, the a priori information usually comes from an independent source, like a model or other correlative measurements. In the present study, RIO model data were chosen as a priori. Seasonal average maps of RIO  $NO_2$  near-surface
- 525 concentration are constructed (see Fig. S3) and after, seasonal averages of RIO NO<sub>2</sub> near-surface concentration horizontal

profiles were calculated in each azimuthal direction and interpolated on the retrieval's horizontal grid by regridding the initial  $4x4 \text{ km}^2$  spatial resolution to a finer one (see Fig. 12). The shape of the RIO a priori NO<sub>2</sub> profiles per azimuthal direction stays the same during different seasons of the year, indicating that the wind effect on NO<sub>2</sub> transportation disappears by the seasonal averaging and that the same sources contribute to the NO<sub>2</sub> horizontal field. A mean scaling factor equal to the mean ratio

530 between the measured and RIO NO<sub>2</sub> near-surface concentrations is applied because of the systematic underestimation of NO<sub>2</sub> near-surface concentrations by MAX-DOAS when compared to in-situ measurements (see Dimitropoulou et al., 2020 and Section S1).

For the aerosols horizontal distribution retrieval, there are not sufficient independent measurements that provide information about the horizontal distribution of AOD and can serve as an a priori AOD profile. Therefore, a constant a priori AOD profile

535 is used in the AOD retrieval based on CIMEL observations. An AOD equal to 0.18, which is the yearly-averaged AOD value from CIMEL at 477 nm, is used. To construct the near-surface aerosol extinction a priori profiles, it is considered that 30% of the total amount of AOD is located inside the MLH (i.e., known for each MAX-DOAS vertical scan from the MMF inversion algorithm; see Section 5.1).

The diagonal elements of the  $S_a$  matrix are set equal to the square of a scaling factor times the NO<sub>2</sub> concentration a priori

540 profile. The non-diagonal elements, which account for correlation between the different horizontal grid cells, are set as follows (Barret et al., 2002):

$$\mathbf{S}_{\mathbf{a}_{ij}} = \sqrt{\mathbf{S}_{\mathbf{a}_{ij}} \mathbf{S}_{\mathbf{a}_{ij}} \exp\left(-\ln(2)\left(\frac{\mathbf{x}_i - \mathbf{x}_j}{\gamma}\right)^2\right)} \tag{14}$$

545 where  $x_i$  and  $x_j$  are the horizontal distances at the i<sup>th</sup>, and j<sup>th</sup> horizontal boxes and  $\gamma$  is half of the correlation length. For NO<sub>2</sub>,  $\gamma$  is set equal to 3.5 km and for aerosols,  $\gamma$  is set equal to 2 km. To eliminate inversion instabilities,  $S_a$  elements which are smaller than 0.1% of the maximum  $S_a$  element are set equal to zero.

To estimate the correlation length, a covariance matrix was constructed by exploiting the airborne observations above Brussels (28 June 2019). The airborne observations have a spatial resolution of approximately  $100 \times 100 \text{ m}^2$ . NO<sub>2</sub> horizontal profiles

- 550 were constructed in different azimuthal directions in a spatial resolution of 500 x 500 m<sup>2</sup>, expanding from the MAX-DOAS's position to a maximum distance of 20 km, and were used to calculate a covariance matrix. A correlation length equal to 7 km, and consequently, a gamma value equal to 3.5 km, is found to be representative for the NO<sub>2</sub> horizontal profiles in Brussels. Using this correlation length, a variance of 45% is used. This choice was conducted based on the seasonal variance of the RIO a priori profiles compared to their seasonal mean value. It is found that the seasonal variance of RIO observations has a mean
- 555 value of 45%. Additionally, it is found to be a good compromise for obtaining reasonable retrieval results e.g. in terms of information content, and while avoiding unrealistic oscillations in the retrieved aerosol and NO<sub>2</sub> profiles. It should be noted that for aerosols, a variance of 65% is used.


The measurement covariance matrix  $S_e$  is chosen to be diagonal, with elements corresponding to the uncertainties of the dualscan parameterized NO<sub>2</sub> near-surface concentration (see Section 5.2.2).

- 560 Three examples of the retrieved NO<sub>2</sub> horizontal profile are presented in Fig. 13, together with corresponding measured and simulated  $\bar{c}_{NO2}$  at the six different wavelengths for July 2, 2018 (Fig, 13a; low NO<sub>2</sub> abundance condition), September 11, 2018 (Fig. 13b; medium NO<sub>2</sub> abundance condition), and September 30, 2018 (Fig. 13c; medium NO<sub>2</sub> abundance condition). RMS is calculated between measured and simulated NO<sub>2</sub> near-surface concentrations of the horizontal retrieval normalized by the mean of the measured NO<sub>2</sub> near-surface concentrations (upper panels in Fig. 13). As the NO<sub>2</sub> values become larger, the 565 agreement between measured and simulated  $\bar{c}_{NO2}$ , expressed via the RMS value, is improved.
- Similarly, examples of measured and retrieved near-surface aerosol extinction coefficient and retrieved aerosol horizontal profile are shown in Fig. 14, for different aerosol load conditions (low (Fig. 14a), medium (Fig. 14b) and high (Fig. 14c)) over the Brussels-Capital Region. We observe that the agreement between simulated and measured near-surface aerosol extinction coefficient at the six different wavelength tends to be worse than for NO<sub>2</sub>. This could be due to the use of a constructed
- 570 (constant) a priori aerosol horizontal profile due to the lack of information on the aerosol extinction horizontal distribution in the Brussels-Capital region.

An essential condition of the dual-scan MAX-DOAS retrieval and the new horizontal inversion approach at six different wavelengths is the increasing trend of the horizontal sensitivity as a function of wavelength. Consequently, every wavelength is sensitive to a different horizontal region and the six different wavelengths can be used to retrieve the horizontal distribution

575 of aerosols and trace gases. Sensitivity tests were conducted in which simulated  $L_{04}$  are expressed as a function of the six different wavelengths for different aerosol conditions. As can be seen in Fig. S4, the linear relationship between  $L_{04}$  (and  $L_{NO2}$ ) and wavelength exists for AOD values ranging from 0 to 1. An AOD equal to unity is chosen as the maximum AOD of the simulations because in Uccle, AOD values rarely exceed one (see in https://aeronet.gsfc.nasa.gov/ for the Brussels measurement site). Therefore, the relation stays linear as the aerosol load changes for the conditions observed in Uccle. The 580 only condition leading to non-linearity is when clouds are present. However, as explained in Sect. 5.1, a cloud filtering

approach is applied, rejecting the broken cloud scenes, which are the more problematic ones.



585 Figure 10. Schematic representation of the six different L<sub>NO2</sub> (i.e., one horizontal line for each wavelength) used in the new horizontal distribution inversion approach. The length of each line shows the sensitivity of each wavelength as a function of the horizontal distance. The shortest line represents the smallest wavelength.

590




Figure 11. Examples of weighting functions used in the new horizontal distribution inversion approach (11 September 2018, 11:26 UTC).




Figure 12. Example of seasonal RIO *a priori* NO<sub>2</sub> horizontal profiles for the new horizontal distribution inversion approach as a function of the horizontal distance from the MAX-DOAS instrument in six different azimuthal viewing directions, before the application of the scaling factor.




Figure 13. (Upper panels in a, b, and c) Measured and retrieved NO<sub>2</sub> near-surface concentrations at the six different wavelengths (i.e., horizontal distances) as a function of the estimated horizontal distances and (lower panels in a, b, and
c) the retrieved NO<sub>2</sub> near-surface horizontal profile and a priori profile. The two panels correspond to the (a) 11

September 2018, 12.91 UTC, 265° azimuthal direction, (b) 02 July 2018, 10.42 UTC, 25° azimuthal direction, and (c) 30 September 2018, 07.96 UTC, 167.5° azimuthal direction.




Figure 14. (Upper panels in a, b, and c) Measured and retrieved near-surface aerosol extinction at the six different
wavelengths (i.e., horizontal distances) as a function of the estimated horizontal distances and (lower panels in a, b, and c) the retrieved near-surface aerosol extinction horizontal profile. The two panels correspond to the (a) 11 September 2018, 11.48 UTC, 167.5° azimuthal direction, (b) 20 September 2018, 07.08 UTC, 25° azimuthal direction, and (c) 02 June 2018, 18.16 UTC, 35.5° azimuthal direction.

# 5.4 Characterization of the retrieval

To characterize the retrieval, the averaging kernels, **AK**, play a crucial role. The **AK** matrix is calculated as follows (Rodgers, 2000):

635

$$AK = \frac{dc_{NO2}}{dc_{NO2\ true}} = (K^T S_e^{-1} K + S_a^{-1})^{-1} K^T S_e^{-1} K$$
(15)

The AKs are the rows of the AK matrix. They present the sensitivity of the retrieved  $(c_{NO2})$  on the true  $(c_{NO2}_{true})$  atmospheric profile. Ideally, the AK matrix should be an identity matrix. In Fig. 15, an example of selected AKs is shown. As can be seen,

640 for distances smaller than the first measurement (e.g., near-surface NO<sub>2</sub> concentration retrieved at 343 nm), the **AKs** have maximum values and decrease exponentially as a function of the horizontal distance from the instrument. For this particular example, the **AKs** do not exceed the values of 0.12.

Another important information about the retrieval is the trace of the **AK** matrix, which refers to the number of degrees of freedom for signal (DOFS). The DOFS are an indication of the number of independent pieces of information that one can

- 645 retrieve from the measurements. Ideally, the DOFS would be equal to the number of horizontal boxes for the horizontal distribution. In reality, the DOFS are lower, because of the limited horizontal resolution of the measurements. In Fig. 15, the DOFS are close to two, which means that two independent pieces of information are contained in the measurements for this particular example.
- 650 In the present work, the total retrieval error is equal to the error related to the measurement noise and the smoothing of the true atmospheric profile. According to Rodgers (2000), the noise covariance matrix is estimated as:

$$S_{meas} = GS_e G^T \tag{16}$$

(17)

with, G being the gain matrix:

655 
$$G = (K^T S_e^{-1} K + S_a^{-1})^{-1} K^T S_e^{-1}$$

Then, the retrieval noise error is given as the square root of the diagonal elements of the noise covariance matrix. The smoothing error is calculated as follows:

$$S_{smooth} = (AK - I)S_x(AK - I)^T$$
<sup>(18)</sup>

with  $S_x$  being a realistic covariance metric of the true NO<sub>2</sub> horizontal profile.

660 The horizontal profiles of the measurement and smoothing error in percentage are shown in Fig. 16. As can be seen, the smoothing error is significantly larger than the measurement error (range of 3%-10% and 14%-40%, respectively). The smoothing error becomes also larger as the horizontal distances from the instrument become larger. This is mainly because of the exponential decrease of the sensitivity as a function of the horizontal distance (see weighting functions in Fig. 11), and consequently, the larger impact of the difference between the a priori profile and the true state of the atmosphere.

- To eliminate the unsuccessful retrievals, the percentage of accepted retrievals with respect to the total number of retrievals during the four seasons is investigated when a specific filtering on RMS and DOFS is applied (see Table 3 and Figures S7 and S8). As we can see in Fig. S8, DOFS are in the range of 1.0-1.6. From these tests, it is found that most of the retrievals have DOFS larger than 1.2 (see Fig. S8). RMS is defined as the root-mean-square deviation between measured and simulated  $c_{NO2}$  normalized by the mean of the measured  $c_{NO2}$  (e.g., same RMS as in Fig.13). Table 3 and Fig. S7 indicate that RMS values are
- 670 in the range of 0-30% and most of the retrievals have an RMS smaller than 9% with a median RMS value of around 5.6% during all seasons. Based on these investigations, DOFS>1.2 and RMS<9% are used as retrieval quality control criteria.

Table 3. Seasonally averaged root-mean-square (RMS) and DOFS values. RMS is calculated between measured and retrieved NO<sub>2</sub> near-surface concentrations of the horizontal retrieval (Fig. 13). DOFS represent the degrees of freedom of the horizontal retrieval (Fig. 15). The percentage of the accepted retrievals is presented for the different selection criteria.

Season	Spring	Summer	Autumn	Winter
Median RMS (%)	4.8	5.1	7.2	5.4
Median DOFS	1.3	1.3	1.3	1.3
Accepted retrievals (%) (DOFS>1.2)	75	80	94	83
Accepted retrievals (%) (RMS<9%)	89	71	68	85
Accepted retrievals (%) (RMS<8%)	83	68	57	74
Accepted retrievals (%) (RMS<7%)	75	59	49	65
Accepted retrievals (%) (RMS<6%)	66	47	36	53
Total accepted retrievals (%)	65	54	62	71




Figure 15. Example of NO<sub>2</sub> averaging kernels. They are calculated for observations on 11 September 2018 at 11:51 UTC and 300° azimuthal direction.




Figure 16. Example of the NO<sub>2</sub> measurement and smoothing error in percentage for the 02 July 2018 at 10.42 UTC and 695 25° azimuthal direction.

# 6 Retrieval results and discussion

# 6.1 Example of daily horizontal NO<sub>2</sub> distribution

The variation of the MAX-DOAS horizontal distribution of tropospheric NO<sub>2</sub> VCDs as a function of time over the course of June 28 2019, is presented in Fig. 17. This particular day is chosen because airborne measurements took place above the

700

Brussels region (see Sect. 6.2). The horizontal NO<sub>2</sub> profiles are plotted per azimuthal direction with the horizontal axis showing the time in UTC and the vertical axis the horizontal distance in km. Because of the quality check on the retrieved NO<sub>2</sub> horizontal profiles (see Sect. 5.3), some profiles were rejected (e.g. azimuthal direction equal to 262.5° and 265°).

During this day, maximum NO<sub>2</sub> columns are mainly observed around 05:00 UTC and 10:00 UTC, which correspond to 7am and noon local time. Early in the morning (05:00 UTC), high NO<sub>2</sub> columns are expected to be observed because of the low

- 705 MLH (MLH<sub>NO2</sub> in the range of 300 600 m height) in combination with the morning rush hour NO<sub>2</sub> emissions. Around 10:00 UTC, the maximum NO<sub>2</sub> columns are detected in the north (N), northeast (NE), and northwest (NW) direction (see Fig. 18). Same NO<sub>2</sub> horizontal distribution is found when investigating the NO<sub>2</sub> near-surface concentrations for this day (see Fig. S5). In the Brussels region, the main emission sources are located in the N and west (W) parts of the city and are linked to the motorway around Brussels (the so-called Ring), the Brussels city center, and the Drogenbos power plant (NW direction).
- 710 Concerning the NO<sub>2</sub> peaks, they are located at a distance around 0 to 8 km from the measurement site. It can be seen from Fig. 18 that the Ring, the Brussels city center, and the Drogenbos power plant are located within these distances. As measured by the meteorological station on the BIRA-IASB rooftop, the wind was coming from the E direction during that day, resulting in the progressive displacement of the NO<sub>2</sub> peak from the NNE to the W direction. On the contrary, the azimuthal directions pointing towards a large forested area (i.e., 62.5°, 75°, and 105°), the Bois de la Cambre, detect considerably lower NO<sub>2</sub>

# 715 columns than the other directions.

Maximum near-surface aerosol extinction coefficient values are observed during all day long and detected in the N, NW and NE direction (see Fig. S6). NO<sub>2</sub> and aerosol peaks are co-located towards the N and NW direction.





Figure 17. Diurnal variation of the retrieved NO<sub>2</sub> horizontal profiles per azimuthal direction as a function of time (UTC) for June 28, 2019.





735

Figure 18. Maps of hourly averaged NO<sub>2</sub> horizontal profiles per azimuthal direction for June 28, 2019 corresponding to Fig. 17. The wind direction is shown with the black arrow. The black square shows the MAX-DOAS instrument location, the black polygon the National Airport, the black dots the NO<sub>2</sub> hotspots emitting more than 10 kg of NO<sub>x</sub> per hour (Emission Inventory of the Belgian Interregional Environment Agency, 2017), and the black line represents the Brussels Ring road.

# 6.2 MAX-DOAS horizontal NO<sub>2</sub> distribution versus airborne, car mobile-DOAS, and TROPOMI: 28 June 2019 case study

- 740 The APEX tropospheric NO<sub>2</sub> columns are compared to the tropospheric NO<sub>2</sub> horizontal distribution as retrieved by applying our new mapping MAX-DOAS technique to the 28 June 2019 measurements. During the same day, TROPOMI pixels (OFFL 010302 product; see Table 1) selected over the Brussels region are compared to MAX-DOAS observations. During this day, the TROPOMI overpass time was at 12:19 UTC. MAX-DOAS horizontal profiles of tropospheric NO<sub>2</sub> VCDs are selected around TROPOMI overpass time (±1 hour). The horizontal profile of MAX-DOAS NO<sub>2</sub> VCDs on each horizontal line-of-sight has a horizontal sampling of 0.5 km (see Fig. 13). The MAX-DOAS NO<sub>2</sub> VCDs on the horizontal segment crossing a TROPOMI pixel and located inside the pixel are averaged and compared to the corresponding TROPOMI NO<sub>2</sub> VCD. It should be noted that the MAX-DOAS segments are weighted by their relative length inside each pixel. APEX observations located
- inside each TROPOMI pixel were used to assign one APEX NO<sub>2</sub> VCD value per pixel. Maps of co-located TROPOMI, AEROMOBIL, averaged MAX-DOAS, and averaged APEX NO<sub>2</sub> VCDs for the 28 June 2019 are shown in Fig. 19. Two maps
   of APEX and MAX-DOAS observations are presented: one with APEX and MAX-DOAS in their initial resolution and one

with spatially averaged APEX and MAX-DOAS observations in the area covered by a TROPOMI pixel. The NO<sub>2</sub> plume as detected by APEX is covering the NW, N, and NE parts of the Brussels region. MAX-DOAS successfully detected the same NO<sub>2</sub> plume in the NW and N but not in the NE direction. The correlation and agreement between APEX and MAX-DOAS observations is very good (R=0.89 and s=1.22).

- 755 During the S5PVAL-BE flight over Brussels, the AEROMOBIL was used to measure the spatial distribution of tropospheric NO<sub>2</sub> columns mainly over the Ring road of Brussels with start measurement time at 8:30 UTC and end time at 15:42 UTC. The AEROMOBIL NO<sub>2</sub> VCDs, which are located closest both in time and space to each MAX-DOAS horizontal grid are compared to the corresponding MAX-DOAS VCDs (see Fig. 19c and 19e). AEROMOBIL and MAX-DOAS agree perfectly on the location of maximum (i.e. NW direction) and minimum (i.e. SE direction) NO<sub>2</sub> tropospheric VCDs (Fig. 19c and 19e).
- 760 We can observe in Fig. 20b, that the correlation coefficient is moderate (R equal to 0.79) and the slope value is equal to 0.59. The correlation plot between both datasets reveals that AEROMOBIL gives higher NO<sub>2</sub> tropospheric VCDs compared to MAX-DOAS ones. This finding could be partly explained by the fact that AEROMOBIL follows busy routes, where the NO<sub>2</sub> tropospheric VCDs reach maximum values because of the contribution of NO<sub>2</sub> production resulted by vehicles' engines via fossil fuel combustion.
- 765 During the TROPOMI overpass (i.e., 12:19 UTC) above the Brussels-Capital Region, dual-scan MAX-DOAS tropospheric NO2 columns are retrieved, as it can be seen in Fig. 18. The correlation between TROPOMI and MAX-DOAS tropospheric NO<sub>2</sub> columns during the day of the airborne measurements above Brussels is presented in Fig. 20c. Excellent agreement is obtained, with a correlation coefficient value equal to 0.88. The slope value is equal to 0.70. During that day, MAX-DOAS and TROPOMI are in good agreement but TROPOMI tends to underestimate the tropospheric NO<sub>2</sub> columns. It should be noted
- that during that day, the range of observed NO<sub>2</sub> VCDs is from  $4.4x10^{15}$  to  $9.5x10^{15}$  molec.cm<sup>-2</sup>, as retrieved by the MAX-DOAS observations.

775




Figure 19. (a) Tropospheric NO<sub>2</sub> VCD as detected by the APEX instrument in its initial spatial resolution. Tropospheric NO<sub>2</sub> VCD maps (TROPOMI pixels) as retrieved over Brussels on 28<sup>th</sup> of June 2019 by the (b) APEX, (d) MAX-DOAS and (f) TROPOMI (overpass time at 12:19 UTC) instruments. Tropospheric NO<sub>2</sub> VCD as retrieved by the (c) MAX-785 DOAS and (e) AEROMOBIL (between 8:30 UTC and 15:42 UTC) in its initial spatial resolution. The black square shows the MAX-DOAS instrument location, the black polygon the National Airport, the black dots the NO<sub>2</sub> hotspots emitting more than 10 kg of NO<sub>x</sub> per hour (Emission Inventory of the Belgian Interregional Environment Agency, 2017), and the black line represents the Brussels Ring road.




Figure 20. Scatter plot between (a) the tropospheric NO<sub>2</sub> columns derived by airborne measurements (APEX) and the MAX-DOAS observations, (b) the tropospheric NO<sub>2</sub> columns derived by car mobile-DOAS measurements (AEROMOBIL), and the MAX-DOAS observations and (c) the tropospheric NO<sub>2</sub> columns derived by MAX-DOAS observations and the TROPOMI tropospheric NO<sub>2</sub> columns over Brussels on 28<sup>th</sup> of June 2019.

800

## 6.3 Comparison between MAX-DOAS horizontal NO2 distribution and TROPOMI observations

- To compare the TROPOMI and MAX-DOAS tropospheric NO<sub>2</sub> columns, the similar approach is used as in Section 6.2. Additionally, TROPOMI and MAX-DOAS tropospheric NO<sub>2</sub> columns are compared in a seasonal basis, and the seasonallyaveraged maps of those VCDs on the area covered by the TROPOMI pixels are created. To generate these maps, the ensemble of TROPOMI pixels recorded on 28 June 2019 is chosen as reference and TROPOMI pixels that coincide with this reference grid are averaged. The daily horizontal profiles of MAX-DOAS NO<sub>2</sub> columns are averaged on the daily TROPOMI grids and
- 810 then, the reference grid is used to create the seasonally-averaged MAX-DOAS maps. The seasonally and annually-averaged maps of TROPOMI and MAX-DOAS NO<sub>2</sub> VCDs are presented in Fig. 21 and Fig. 22. Only pixels including at least 20 comparison days are taken into account in the analysis. It is found that the locations of the NO<sub>2</sub> peaks and dips show a reasonably high degree of similarity between TROPOMI and MAX-DOAS during all seasons, except summer. The NO<sub>2</sub> peaks appear mainly above Brussels city center, the Drogenbos power plant (W direction) and the
- 815 NW part of the Ring road, which are the main known emission sources, as mentioned earlier. These maps also indicate that the tropospheric NO<sub>2</sub> column over the Brussels area has a clear seasonal cycle, with a maximum during winter.


Figure 22c shows the annual relative biases (e.g., 100 x (TROPOMI – MAX-DOAS)/MAX-DOAS) per pixel. It is found that negative biases (i.e., MAX-DOAS larger than TROPOMI), ranging from -3% to -38%, are found for all the pixels. The seasonal correlation plots for April 2018-February 2020 are displayed in Fig. 23. The highest correlation is found during

spring (R=0.70), while lower correlations are reported in autumn, summer, and winter, with correlation coefficient values of 0.67, 0.61, and 0.57, respectively. It should be noted that during spring (2018 and 2019), the number of comparison points is smaller than for the other seasons, because TROPOMI data start from end of April 2018. During spring, the slope value is equal to 0.88, while during winter, summer, and autumn, the slope values are smaller (0.67, 0.45, and 0.56, respectively). Similar findings have been reported in several studies (Verhoelst et al., 2021; Tack et al., 2021; Judd et al., 2020;
Dimitropoulou et al., 2020; Ialongo et al., 2019). When seasonally-averaged TROPOMI and MAX-DOAS pixels (the pixels

shown in Fig. 21) are compared one-by-one (see seasonal (SEAS) in Fig. 23), both correlation coefficient (R in the range of 0.62-0.85) and slope values (s in the range of 0.36-1.84) improve considerably for spring and autumn.

The seasonal regression analysis parameters between TROPOMI and dual-scan MAX-DOAS measurements derived in the present study are compared to the same parameters presented in Dimitropoulou et al. (2020), see Table 4. Both studies make use of the dual-scan MAX-DOAS instrument in Uccle. In addition to the different approach (i.e., the retrieval of NO<sub>2</sub> horizontal profiles), in the present study, almost two years of measurements are used, while in Dimitropoulou et al. (2020), only one year is exploited for the TROPOMI validation. In Table 4, for the present study, only one year of measurements are used to have a comparable time coverage for both studies. As presented in Table 4, the largest slope value is found in winter, both in the present study and in Dimitropoulou et al. (2020), in winter. The season in which the highest correlation coefficient is obtained

- differs between both studies (here, in spring, in autumn in Dimitropoulou et al. (2020)). The main advantage of the new mapping MAX-DOAS technique is the larger number of comparison points between TROPOMI and MAX-DOAS leading to significantly more reliable statistics. In the present study, the deviation of the comparison points from the fitted regression line is increased mainly because of the uncertainties in the horizontal inversion approach. The scatter increase is reflected in the
- 840 correlation coefficient values, which are smaller for all seasons, except spring and winter. Regarding the slope value, it is larger during all seasons.



845 Figure 21. Seasonal tropospheric NO<sub>2</sub> VCD grids (TROPOMI grids) as retrieved over Brussels by the TROPOMI and MAX-DOAS instruments. The black square shows the MAX-DOAS position, the black polygon the National Airport, the black dots the NO<sub>2</sub> hotspots, and the black line represents the Brussels Ring motorway.




Figure 22. Annual (e.g., based over the two years of observations) tropospheric NO<sub>2</sub> VCD grids (TROPOMI grids) as retrieved over Brussels by the (a) TROPOMI and (b) MAX-DOAS instruments. (c) Annual bias between tropospheric NO<sub>2</sub> VCD as observed by TROPOMI and MAX-DOAS instruments (the negative values are shown with blue color, zero with white, and positive values with red). The black square shows the MAX-DOAS instrument location, the black polygon the National Airport, the black dots the NO<sub>2</sub> hotspots, and the black line represents the Brussels Ring road.




Figure 23. Seasonal scatter plots of tropospheric NO<sub>2</sub> columns derived from the dual-scan MAX-DOAS and TROPOMI measurements over Brussels. Blue line: Regression analysis results when all the MAX-DOAS and TROPOMI pixels

are included in the comparison. Red line: Seasonal average analysis generated by the pixels in Fig. 21.

## 

Table 4. Summary of the regression analysis parameters (e.g., correlation coefficient (R) and slope (s)) and the number of data points (N) derived in the present study during only one year of observations (i.e., number of pixels) and in Dimitropoulou et al. (2020). Please note that R (seasonal) and s (seasonal) corresponds to SEAS in Figure 23.

Season	Spring	Summer	Autumn	Winter
R	0.70	0.65	0.45	0.67
R (seasonal)	0.76	0.62	0.85	0.75
R (Dimitropoulou et al., 2020)	0.69	0.77	0.85	0.60
S	0.88	0.64	0.73	1.71
s (seasonal)	1.84	0.43	0.62	0.36
s (Dimitropoulou et al., 2020)	0.47	0.58	0.61	0.81
Ν	134	252	99	84
N (Dimitropoulou et al., 2020)	16	58	36	13

930

## 7 Conclusions

Two years (March 2018 to February 2020) of dual-scan MAX-DOAS measurements in Uccle (urban background site located

915 in the south of the Brussels-Capital Region) were used to develop a new strategy for the retrieval of near-surface  $NO_2$  concentrations and aerosol extinction horizontal profiles. A full dual-scan measurement is composed of one vertical scan at a fixed azimuthal direction pointing towards the city center and horizontal scans in ten azimuthal directions at a fixed low elevation angle (2°).

The first step of this new retrieval strategy is to analyze measured radiance spectra in six different fitting windows. This

- 920 provides  $O_4$  and  $NO_2$  dSCDs at the following six wavelengths: 343 nm, 360 nm, 380 nm, 447 nm, 477 nm and 530 nm. Then, information about the vertical extent of  $NO_2$  in the troposphere (MLH<sub>NO2</sub>) is derived from profile retrievals in the main azimuthal direction performed using the OEM-based MMF algorithm. In the third step, a new parameterization technique is applied, with MLH<sub>NO2</sub>, measured  $O_4$  dSCDs, and measurement geometry being used as input parameters to retrieve the horizontal sensitivity of  $NO_2$  and, consequently, the  $NO_2$  near-surface concentrations and VCDs, near-surface aerosol
- 925 extinction and AODs in all the azimuthal directions for the six different wavelengths. Compared to the method presented in Dimitropoulou et al., (2020), the new retrieval method offers the possibility of the direct determination of  $L_{NO2}$ , and nearsurface aerosol extinction based on the measured O<sub>4</sub> dSCDs.

The retrieved dual-scan  $NO_2$  near-surface concentrations and VCDs are verified via comparisons to the MMF  $NO_2$  vertical profiles derived in the main azimuthal directions and in three additional azimuthal directions. A good overall agreement is found for the two comparisons during the two years of measurements.

The dependence of the horizontal sensitivity on the wavelength is then used to develop a new OEM-based horizontal distribution inversion approach. Considering a horizontal box model, horizontal NO<sub>2</sub> and aerosol extinction profiles are retrieved in an output horizontal grid of 500m thickness starting from the instrument to each of the measurement maximum horizontal representative distance.

935 The daily variability of NO<sub>2</sub> horizontal profiles in all the azimuthal directions provides information about the location of the NO<sub>2</sub> hotspots in the Brussels-Capital Region and how the plumes are transported. Similarly, the NO<sub>2</sub> horizontal profiles' seasonal variability over March 2018-February 2020 reveals that the NO<sub>2</sub> hotspots are mainly found above the Brussels citycenter, the Drogenbos power plant and the NW part of the Ring road during all seasons.

On 28 June 2019, airborne measurements (APEX) of NO<sub>2</sub> were performed over Brussels. The MAX-DOAS NO<sub>2</sub> VCD 940 horizontal profiles are compared to APEX, mobile car-DOAS (i.e., AEROMOBIL), and TROPOMI measurements, and a good

In the last part of the study, MAX-DOAS retrievals are compared to TROPOMI tropospheric NO<sub>2</sub> observations over the March 2018- February 2020 period. The comparison of seasonal maps shows a good overall agreement between both datasets as to the NO<sub>2</sub> horizontal distribution over the Brussels area. Results also show that during all seasons, TROPOMI underestimates

945 the MAX-DOAS tropospheric NO<sub>2</sub> columns.

Overall, our investigation about the spatial sampling lead to the following three important findings:

- 1. The dual-scan multi-wavelength approach allows a good identification of the main emissions sources in urban regions, in agreement with the spatial allocation of the main emission sources observed by APEX and TROPOMI.
- 2. The characterization of the NO<sub>2</sub> concentration horizontal field using the dual scan multi-wavelength approach results
- 950 in obtaining slope values closer to unity between TROPOMI and MAX-DOAS observations. The high spatial resolution of TROPOMI requires ground-based measurement that can provide information about the horizontal distribution of tropospheric NO<sub>2</sub> columns in urban regions.

To conclude, our study presents a new horizontal distribution inversion approach for NO<sub>2</sub> and aerosols developed by using dual-scan multi-wavelength MAX-DOAS measurements over an urban area. This approach provides a better characterization

- 955 of the horizontal distribution of an important urban pollutant, NO<sub>2</sub>, which leads to an improved agreement between satellite and MAX-DOAS measurements in moderate to highly polluted conditions. Based on our study, further modifications of the measurement mode aiming at a better sampling of the vertical and horizontal NO<sub>2</sub> distribution could be implemented and investigated. For instance, performing vertical scans in several azimuthal directions throughout the day and/or horizontal scans in more than ten azimuthal directions could further improve our knowledge about the tropospheric NO<sub>2</sub> spatial variability in urban regions, and therefore the satellite validation results in those conditions. 960

overall agreement is found between the different data sets for this day.

Data availability. The datasets generated and analyzed in the present work are available from the corresponding author on request.

965

Author contributions. ED undertook the development and validation of the dual-scan multi-wavelength MAX-DOAS retrieval strategy in Uccle, exploited the MAX-DOAS retrievals during two year, performed the validation of the TROPOMI tropospheric NO2 columns, and wrote the paper. FH supported and guided ED in the development of the dual-scan multiwavelength MAX-DOAS retrieval strategy, provided general guidelines, and revised and edited the paper. MMF provided the

- 970 MMF inversion algorithm and the RTM as well as supporting and guiding ED in the new OEM-based horizontal profile retrieval. FT provided the airborne APEX dataset and contributed to scientific discussions. GP provided the dataset of the TROPOMI tropospheric NO2 columns and supported ED in the TROPOMI validation approaches. AM provided the AEROMOBIL dataset and contributed to scientific discussions. CF and CH provided technical and software support for the MAX-DOAS instrument in Uccle. CF developed the QDOAS software and guided ED in the DOAS analysis. FF provided the
- 975 RIO model dataset. MVR supervised the present work, provided general guidelines and valuable comments during the whole process of the paper preparation, and revised and edited the paper. All authors reviewed, discussed and commented on the paper.

*Competing interests.* I declare that I or my co-authors have competing interests as follows: Michel Van Roozendael is associate editor of AMT.

## 985 **References**

980

- Aliwell, S.R., Van Roozendael, M., Johnston, P.V., Richter, A., Wagner, T., Arlander, D.W., Burrows, J.P., Fish, D.J., Jones, R.L., Tørnkvist, K.K. and Lambert, J.C., 2002. Analysis for BrO in zenith-sky spectra: An intercomparison exercise for analysis improvement. *Journal of Geophysical Research: Atmospheres*, 107(D14), pp.ACH-10.
- Barret, B., De Maziere, M., and Demoulin, P.: Retrieval and `characterisation of ozone profiles from solar infrared spectra at the Jungfraujoch, J. Geophys. Res., 107 (D24), 4788, doi:10.1029/2001JD001298, 2002.
- Beirle, S., Dörner, S., Donner, S., Remmers, J., Wang, Y., and Wagner, T.: The Mainz profile algorithm (MAPA), Atmos. Meas. Tech., 12, 1785–1806, https://doi.org/10.5194/amt-12- 1785-2019, 2019.
- Beirle, S., Platt, U., Wenig, M., and Wagner, T.: Weekly cycle of NO<sub>2</sub> by GOME measurements: a signature of anthropogenic sources, Atmos. Chem. Phys., 3, 2225–2232, https://doi.org/10.5194/acp-3-2225-2003, 2003.
- 995 Bösch, T., Rozanov, V., Richter, A., Peters, E., Rozanov, A., Wittrock, F., Merlaud, A., Lampel, J., Schmitt, S., de Haij, M., Berkhout, S., Henzing, B., Apituley, A., den Hoed, M., Vonk, J., Tiefengraber, M., Müller, M., and Burrows, J. P.: BOREAS – a new MAX-DOAS profile retrieval algorithm for aerosols and trace gases, Atmos. Meas. Tech., 11, 6833– 6859, https://doi.org/10.5194/amt-11-6833-2018, 2018.
- Burrows, J. P., Weber, M., Buchwitz, M., Rosanov, V. V., Ladstatter, A., Weissenmayer, A., Richter, A., DeBeek, R., Hoogen,
   R., Bramstedt, K., and Eichmann, K. U.: The Global Ozone Monitoring Experiment (GOME): Mission concept and first scientific results, J. Atmos. Sci., 56, 151–175, 1999.

Chance, K. V. and Spurr, R. J. D.: Ring effect studies: Rayleigh scattering, including molecular parameters for rotational Raman scattering, and the Fraunhofer spectrum, Appl. Optics, 36, 5224–5230, doi:10.1364/AO.36.005224, 1997.

- Chan, K. L., Wiegner, M., van Geffen, J., De Smedt, I., Alberti, C., Cheng, Z., Ye, S., and Wenig, M.: MAX-DOAS
   measurements of tropospheric NO<sub>2</sub> and HCHO in Munich and the comparison to OMI and TROPOMI satellite
   observations, Atmos. Meas. Tech., 13, 4499–4520, https://doi.org/10.5194/amt-13-4499-2020, 2020.
  - Chen, T. M., Kuschner, W. G., Gokhale, J., & Shofer, S. (2007). Outdoor air pollution: nitrogen dioxide, sulfur dioxide, and carbon monoxide health effects. *The American journal of the medical sciences*, *333*(4), 249-256.

Clémer, K., Van Roozendael, M., Fayt, C., Hendrick, F., Hermans, C., Pinardi, G., Spurr, R., Wang, P., and De Mazière, M.:

Multiple wavelength retrieval of tropospheric aerosol optical properties from MAXDOAS measurements in Beijing,
 Atmos. Meas. Tech., 3, 863–878, https://doi.org/10.5194/amt-3-863-2010, 2010.

1015

- Compernolle, S., Argyrouli, A., Lutz, R., Sneep, M., Lambert, J.-C., Fjæraa, A. M., Hubert, D., Keppens, A., Loyola, D., O'Connor, E., Romahn, F., Stammes, P., Verhoelst, T., and Wang, P.: Validation of the Sentinel-5 Precursor TROPOMI cloud data with Cloudnet, Aura OMI O<sub>2</sub>–O<sub>2</sub>, MODIS, and Suomi-NPP VIIRS, Atmos. Meas. Tech., 14, 2451–2476, https://doi.org/10.5194/amt-14-2451-2021, 2021.
- Dimitropoulou, E., Hendrick, F., Pinardi, G., Friedrich, M. M., Merlaud, A., Tack, F., De Longueville, H., Fayt, C., Hermans, C., Laffineur, Q., Fierens, F., and Van Roozendael, M.: Validation of TROPOMI tropospheric NO2 columns using dual scan multi-axis differential optical absorption spectroscopy (MAX-DOAS) measurements in Uccle, Brussels, Atmos. Meas. Tech., 13, 5165–5191, https://doi.org/10.5194/amt-13-5165-2020, 2020.
- 1020 Douros, J., Eskes, H., van Geffen, J., Boersma, F., Compernolle, S., Pinardi, G., Blechschmidt, A-M., Peuch, V-H., Colette, A., and Veefkind P.: Comparing Sentinel-5P TROPOMI NO<sub>2</sub> column observations with the CAMS-regional air quality ensemble, in preparation.
  - Eskes, H.J. and Eichmann, K.U.: *S5P MPC Product Readme Nitrogen Dioxide*. Report S5P-MPC-KNMI PRF-NO2, version 1.4, 6 August 2019, ESA, available at: http://www.tropomi.eu/documents/prf/, 17 March, 2020.
- 1025 Fayt, C., De Smedt, I., Letocart, V., Merlaud, A., Pinardi, G., and Van Roozendael, M.: QDOAS Software user manual, http: //uv-vis.aeronomie.be/software/QDOAS/index.php, 2011.
  - Finkenzeller, H., & Volkamer, R.: O2–2 CIA in the gas phase: Cross-section of weak bands, and continuum absorption between 297–500 nm. *Journal of Quantitative Spectroscopy and Radiative Transfer*, 108063, 2022.

Fleischmann, O. C., Hartmann, M., Burrows, J. P., and Orphal, J.: New ultraviolet absorption cross-sections of BrO at

- atmospheric temperatures measured by time-windowing Fourier transform spectroscopy, J. Photoch. Photobio. A, 168, 117–132, 2004.
  - Friedrich, M. M., Rivera, C., Stremme, W., Ojeda, Z., Arellano, J., Bezanilla, A., García-Reynoso, J. A., and Grutter, M.: NO<sub>2</sub> vertical profiles and column densities from MAX-DOAS measurements in Mexico City, Atmos. Meas. Tech., 12, 2545– 2565, https://doi.org/10.5194/amt-12-2545-2019, 2019.
- 1035 Hendrick, F., Müller, J.-F., Clémer, K., Wang, P., De Mazière, M., Fayt, C., Gielen, C., Hermans, C., Ma, J. Z., Pinardi, G.,

Stavrakou, T., Vlemmix, T., and Van Roozendael, M.: Four years of ground-based MAX-DOAS observations of HONO and NO2 in the Beijing area, Atmos. Chem. Phys., 14, 765–781, https://doi.org/10.5194/acp-14-765-2014, 2014.

- Hönninger, G., von Friedeburg, C., and Platt, U.: Multi axis differential optical absorption spectroscopy (MAX-DOAS), Atmos. Chem. Phys., 4, 231–254, doi:10.5194/acp-4-231-2004, 2004.
- 1040 Hooyberghs, J., Mensink, C., Dumont, G. and Fierens, F., 2006. Spatial interpolation of ambient ozone concentrations from sparse monitoring points in Belgium. *Journal of Environmental Monitoring*, *8*(11), pp.1129-1135.
  - Ialongo, I., Virta, H., Eskes, H., Hovila, J., and Douros, J.: Comparison of TROPOMI/Sentinel 5 Precursor NO<sub>2</sub> observations with ground-based measurements in Helsinki, Atmos. Meas. Tech. Discuss., https://doi.org/10.5194/amt-2019-329, in review, 2019.
- 1045 Irie, H., Takashima, H., Kanaya, Y., Boersma, K. F., Gast, L., Wittrock, F., Brunner, D., Zhou, Y., and Van Roozendael, M.: Eight-component retrievals from ground-based MAXDOAS observations, Atmos. Meas. Tech., 4, 1027–1044, https://doi.org/10.5194/amt-4-1027-2011, 2011.

1050

- Irie, H., Boersma, K. F., Kanaya, Y., Takashima, H., Pan, X., and Wang, Z. F.: Quantitative bias estimates for tropospheric NO2 columns retrieved from SCIAMACHY, OMI, and GOME-2 using a common standard for East Asia, Atmos. Meas. Tech., 5, 2403–2411, https://doi.org/10.5194/amt-5-2403-2012, 2012.
- Janssen, S., Dumont, G., Fierens, F. and Mensink, C., 2008. Spatial interpolation of air pollution measurements using CORINE land cover data. *Atmospheric Environment*, *42*(20), pp.4884-4903.
- Judd, L. M., Al-Saadi, J. A., Szykman, J. J., Valin, L. C., Janz, S. J., Kowalewski, M. G., Eskes, H. J., Veefkind, J. P., Cede, A., Mueller, M., Gebetsberger, M., Swap, R., Pierce, R. B., Nowlan, C. R., Abad, G. G., Nehrir, A., and Williams, D.:
- Evaluating Sentinel-5P TROPOMI tropospheric NO2 column densities with airborne and Pandora spectrometers near
   New York City and Long Island Sound, Atmos. Meas. Tech., 13, 6113–6140, <u>https://doi.org/10.5194/amt-13-6113-2020</u>, 2020.
  - Khomenko, S., Cirach, M., Pereira-Barboza, E., Mueller, N., Barrera-Gómez, J., Rojas-Rueda, D., de Hoogh, K., Hoek, G. and Nieuwenhuijsen, M., 2021. Premature mortality due to air pollution in European cities: a health impact assessment. *The Lancet Planetary Health*, 5(3), pp.e121-e134.
  - Klimont, Z., Kupiainen, K., Heyes, C., Purohit, P., Cofala, J., Rafaj, P., Borken-Kleefeld, J., and Schöpp, W.: Global anthropogenic emissions of particulate matter including black carbon, Atmos. Chem. Phys., 17, 8681–8723, https://doi.org/10.5194/acp-17-8681-2017, 2017.
- Kreher, K., Van Roozendael, M., Hendrick, F., Apituley, A., Dimitropoulou, E., Frieß, U., Richter, A., Wagner, T., Abuhassan,
  N., Ang, L., Anguas, M., Bais, A., Benavent, N., Bösch, T., Bognar, K., Borovski, A., Bruchkouski, I., Cede, A., Chan,
  K. L., Donner, S., Drosoglou, T., Fayt, C., Finkenzeller, H., Garcia-Nieto, D., Gielen, C., Gómez-Martín, L., Hao, N.,
  Herman, J. R., Hermans, C., Hoque, S., Irie, H., Jin, J., Johnston, P., Khayyam Butt, J., Khokhar, F., Koenig, T. K.,
  Kuhn, J., Kumar, V., Lampel, J., Liu, C., Ma, J., Merlaud, A., Mishra, A. K., Müller, M., Navarro-Comas, M., Ostendorf,
  M., Pazmino, A., Peters, E., Pinardi, G., Pinharanda, M., Piters, A., Platt, U., Postylyakov, O., Prados-Roman, C.,

- Puentedura, O., Querel, R., Saiz-Lopez, A., Schönhardt, A., Schreier, S. F., Seyler, A., Sinha, V., Spinei, E., Strong, K., Tack, F., Tian, X., Tiefengraber, M., Tirpitz, J.-L., van Gent, J., Volkamer, R., Vrekoussis, M., Wang, S., Wang, Z., Wenig, M., Wittrock, F., Xie, P. H., Xu, J., Yela, M., Zhang, C., and Zhao, X.: Intercomparison of NO<sub>2</sub>, O<sub>4</sub>, O<sub>3</sub> and HCHO slant column measurements by MAX-DOAS and zenith-sky UV-Visible spectrometers during the CINDI-2 campaign, Atmos. Meas. Tech. Discuss., https://doi.org/10.5194/amt-2019-157, in review, 2019.
- 1075 Kurucz, R.L., Furenlid, I., Brault, J., and Testerman, L.: Solar flux atlas from 296 to 1300 nm, National Solar Observatory, Sunspot, New Mexico, U.S.A., 1984.
  - Meller, R. and Moortgat, G. K.: Temperature dependence of the absorption cross sections of formaldehyde between 223 and 323K in the wavelength range 225–375nm, J. Geophys. Res., 105, 7089–7101, 2000.
  - Merlaud, A., Van Roozendael, M., Theys, N., Fayt, C., Hermans, C., Quennehen, B., Schwarzenboeck, A., Ancellet, G.,
- 1080 Pommier, M., Pelon, J., Burkhart, J., Stohl, A., and De Mazière, M.: Airborne DOAS measurements in Arctic: vertical distributions of aerosol extinction coefficient and NO2 concentration, Atmos. Chem. Phys., 11, 9219–9236, https://doi.org/10.5194/acp11-9219-2011, 2011.
  - Merlaud, A.: Development and use of compact instruments for tropospheric investigations based on optical spectroscopy from mobile platforms, Presses Universitaires de Louvain, 2013.
- 1085 Pinardi, G., Hendrick, F., Clémer, K., Lambert, J. C., Bai, J., and Van Roozendael, M.: On the use of the MAX-DOAS technique for the validation of tropospheric NO2 column measurements from satellite, Proc. Eumetsat Conf., ISBN 978-92-9110-082-8, 2008.
  - Puķīte, J., Kühl, S., Deutschmann, T., Platt, U., and Wagner, T.: Extending differential optical absorption spectroscopy for limb measurements in the UV, Atmos. Meas. Tech., 3, 631–653, https://doi.org/10.5194/amt-3-631-2010, 2010.
- 1090 Quaas, Johannes, Olivier Boucher, Nicolas Bellouin, and Stefan Kinne. "Satellite-based estimate of the direct and indirect aerosol climate forcing." *Journal of Geophysical Research: Atmospheres* 113, no. D5 (2008).
  - Rodgers, C. D.: Inverse Methods for Atmospheric Sounding, Theory and Practice, World Scientific Publishing, Singapore NewJersey London Hong Kong, 2000.
  - Rothman, L.S., Gordon, I.E., Babikov, Y., Barbe, A., Benner, D.C., Bernath, P.F., Birk, M., Bizzocchi, L., Boudon, V., Brown,
- 1095 L.R. and Campargue, A., 2013. The HITRAN2012 molecular spectroscopic database. *Journal of Quantitative Spectroscopy and Radiative Transfer*, 130, pp.4-50.Seinfeld, J. H. and Pandis, S. N.: Atmospheric Chemistry and Physics: From Air Pollution to Climate Change, John Wiley & Sons, Inc., 1998.
  - Schreier, S. F., Bösch, T., Richter, A., Lange, K., Revesz, M., Weihs, P., Vrekoussis, M., and Lotteraner, C.: Evaluation of UV-visible MAX-DOAS aerosol profiling products by comparison with ceilometer, sun photometer, and in situ
- observations in Vienna, Austria, Atmos. Meas. Tech., 14, 5299–5318, https://doi.org/10.5194/amt-14-5299-2021, 2021.
   Serdvuchenko, A., Gorshelev, V., Weber, M., Chehade, W., and Burrows, J. P.: High spectral resolution ozone absorption

crosssections - Part 2: Temperature dependence, Atmos. Meas. Tech., 7, 625-636, doi:10.5194/amt-7-625-2014, 2014.

Sinreich, R., Volkamer, R., Filsinger, F., Frieß, U., Kern, C., Platt, U., Sebastián, O., and Wagner, T.: MAX-DOAS detection

of glyoxal during ICARTT 2004, Atmos. Chem. Phys., 7, 1293–1303, https://doi.org/10.5194/acp-7-1293-2007, 2007.

- 1105 Sinreich, R., Merten, A., Molina, L., and Volkamer, R.: Parameterizing radiative transfer to convert MAX-DOAS dSCDs into near-surface box-averaged mixing ratios, Atmos. Meas. Tech., 6, 1521-1532, doi:10.5194/amt-6-1521-2013, 2013.
  - Spurr, R. J.: VLIDORT: A linearized pseudo-spherical vector discrete ordinate radiative transfer code for forward model and retrieval studies in multilayer multiple scattering media, J. Quant. Spectrosc. Ra., 102, 316-342, 2006.
- Tack, F., Merlaud, A., Iordache, M.-D., Danckaert, T., Yu, H., Fayt, C., Meuleman, K., Deutsch, F., Fierens, F., and Van 1110 Roozendael, M.: High-resolution mapping of the NO<sub>2</sub> spatial distribution over Belgian urban areas based on airborne APEX remote sensing, Atmos. Meas. Tech., 10, 1665–1688, https://doi.org/10.5194/amt-10-1665-2017, 2017.
  - Tack, F., Merlaud, A., Meier, A. C., Vlemmix, T., Ruhtz, T., Iordache, M.-D., Ge, X., van der Wal, L., Schuettemeyer, D., Ardelean, M., Calcan, A., Constantin, D., Schönhardt, A., Meuleman, K., Richter, A., and Van Roozendael, M.: Intercomparison of four airborne imaging DOAS systems for tropospheric NO<sub>2</sub> mapping – the AROMAPEX campaign,
- 1115 Atmos. Meas. Tech., 12, 211–236, https://doi.org/10.5194/amt-12-211-2019, 2019.
  - Tack, F., Merlaud, A., Iordache, M.-D., Pinardi, G., Dimitropoulou, E., Eskes, H., Bomans, B., Veefkind, P., and Van Roozendael, M.: Assessment of the TROPOMI tropospheric NO<sub>2</sub> product based on airborne APEX observations, Atmos. Meas. Tech., 14, 615-646, https://doi.org/10.5194/amt-14-615-2021, 2021.
  - Thalman, R. and Volkamer, R.: Temperature dependent absorption cross-sections of O2-O2 collision pairs between 340 and
- 1120 630nm and at atmospherically relevant pressure, Phys. Chem. Chem. Phys., 15. 15371-15381. doi:10.1039/C3CP50968K, 2013.
  - Tirpitz, J.-L., Frieß, U., Hendrick, F., Alberti, C., Allaart, M., Apituley, A., Bais, A., Beirle, S., Berkhout, S., Bognar, K., Bösch, T., Bruchkouski, I., Cede, A., Chan, K. L., den Hoed, M., Donner, S., Drosoglou, T., Fayt, C., Friedrich, M. M., Frumau, A., Gast, L., Gielen, C., Gomez-Martín, L., Hao, N., Hensen, A., Henzing, B., Hermans, C., Jin, J., Kreher, K.,
- 1125 Kuhn, J., Lampel, J., Li, A., Liu, C., Liu, H., Ma, J., Merlaud, A., Peters, E., Pinardi, G., Piters, A., Platt, U., Puentedura, O., Richter, A., Schmitt, S., Spinei, E., Stein Zweers, D., Strong, K., Swart, D., Tack, F., Tiefengraber, M., van der Hoff, R., van Roozendael, M., Vlemmix, T., Vonk, J., Wagner, T., Wang, Y., Wang, Z., Wenig, M., Wiegner, M., Wittrock, F., Xie, P., Xing, C., Xu, J., Yela, M., Zhang, C., and Zhao, X.: Intercomparison of MAX-DOAS vertical profile retrieval algorithms: studies on field data from the CINDI-2 campaign, Atmos. Meas. Tech., 14, 1-35, https://doi.org/10.5194/amt-14-1-2021, 2021.
- 1130
  - van Geffen, J. H. G. M., Eskes, H. J., Boersma, K. F. and Veefkind, J. P.: TROPOMI ATBD of the total and tropospheric NO<sub>2</sub> data products, Report S5P-KNMI-L2-0005-RP, version 2.2.0, released 16 June 2021, KNMI, De Bilt, The Netherlands, http://www.tropomi.eu/ data-products/nitrogen-dioxide/, 2021a.
  - van Geffen, J., Eskes, H., Compernolle, S., Pinardi, G., Verhoelst, T., Lambert, J.-C., Sneep, M., ter Linden, M., Ludewig, A.,
- 1135 Boersma, K. F., and Veefkind, J. P.: Sentinel-5P TROPOMI NO<sub>2</sub> retrieval: impact of version v2.2 improvements and comparisons with OMI and ground-based data, Atmos. Meas. Tech. Discuss. [preprint], https://doi.org/10.5194/amt-2021-329, in review, 2021b.Vandaele, A., Hermans, C., Simon, P., Carleer, M., Colin, R., Fally, S., Mérienne, M.,

Jenouvrier, A., and Coquart, B.: Measurements of the NO2 absorption cross-section from 42000cm-1 to 10000cm-1 (238-1000nm) at 220K and 294K, J. Quant. Spectrosc. Ra., 59, 171-184, 1998.

- 1140 Veefkind, J. P., Boersma, K. F., Wang, J., Kurosu, T. P., Krotkov, N., Chance, K., and Levelt, P. F.: Global satellite analysis of the relation between aerosols and short-lived trace gases, Atmos. Chem. Phys., 11, 1255–1267, doi:10.5194/acp-11-1255-2011, 2011.
  - Verhoelst, T., Compernolle, S., Pinardi, G., Lambert, J.-C., Eskes, H. J., Eichmann, K.-U., Fjæraa, A. M., Granville, J., Niemeijer, S., Cede, A., Tiefengraber, M., Hendrick, F., Pazmiño, A., Bais, A., Bazureau, A., Boersma, K. F., Bognar,
- K., Dehn, A., Donner, S., Elokhov, A., Gebetsberger, M., Goutail, F., Grutter de la Mora, M., Gruzdev, A., Gratsea, M., Hansen, G. H., Irie, H., Jepsen, N., Kanaya, Y., Karagkiozidis, D., Kivi, R., Kreher, K., Levelt, P. F., Liu, C., Müller, M., Navarro Comas, M., Piters, A. J. M., Pommereau, J.-P., Portafaix, T., Prados-Roman, C., Puentedura, O., Querel, R., Remmers, J., Richter, A., Rimmer, J., Rivera Cárdenas, C., Saavedra de Miguel, L., Sinyakov, V. P., Stremme, W., Strong, K., Van Roozendael, M., Veefkind, J. P., Wagner, T., Wittrock, F., Yela González, M., and Zehner, C.: Groundbased validation of the Copernicus Sentinel-5P TROPOMI NO<sub>2</sub> measurements with the NDACC ZSL-DOAS, MAX-DOAS and Pandonia global networks, Atmos. Meas. Tech., 14, 481–510, https://doi.org/10.5194/amt-14-481-2021, 2021.
- Vigouroux, C., Hendrick, F., Stavrakou, T., Dils, B., De Smedt, I., Hermans, C., Merlaud, A., Scolas, F., Senten, C., Vanhaelewyn, G., Fally, S., Carleer, M., Metzger, J.-M., Müller, J.-F., Van Roozendael, M., and De Mazière, M.:
  Ground-based FTIR and MAX-DOAS observations of formaldehyde at Réunion Island and comparisons with satellite
  - Wagner, T., Deutschmann, T., and Platt, U.: Determination of aerosol properties from MAX-DOAS observations of the Ring

and model data, Atmos. Chem. Phys., 9, 9523–9544, https://doi.org/10.5194/acp-9-9523-2009, 2009.

effect, Atmos. Meas. Tech., 2, 495-512, https://doi.org/10.5194/amt-2-495-2009, 2009.

- Wagner, T., Beirle, S., Brauers, T., Deutschmann, T., Frieß, U., Hak, C., Halla, J. D., Heue, K. P., Junkermann, W., Li, X.,
   Platt, U., and Pundt-Gruber, I.: Inversion of tropospheric profiles of aerosol extinction and HCHO and NO2 mixing ratios from MAX-DOAS observations in Milano during the summer of 2003 and comparison with independent data sets, Atmos. Meas. Tech., 4, 2685–2715, https://doi.org/10.5194/amt-4-2685-2011, 2011.
  - Wagner, T., Beirle, S., Benavent, N., Bösch, T., Chan, K. L., Donner, S., Dörner, S., Fayt, C., Frieß, U., García-Nieto, D., Gielen, C., González-Bartolome, D., Gomez, L., Hendrick, F., Henzing, B., Jin, J. L., Lampel, J., Ma, J., Mies, K.,
- 1165 Navarro, M., Peters, E., Pinardi, G., Puentedura, O., Pukīte, J., Remmers, J., Richter, A., Saiz-Lopez, A., Shaiganfar, R., Sihler, H., Van Roozendael, M., Wang, Y., and Yela, M.: Is a scaling factor required to obtain closure between measured and modelled atmospheric O<sub>4</sub> absorptions? An assessment of uncertainties of measurements and radiative transfer simulations for 2 selected days during the MAD-CAT campaign, Atmos. Meas. Tech., 12, 2745–2817, https://doi.org/10.5194/amt-12-2745-2019, 2019.
- 1170 Wang, Y., Li, A., Xie, P. H., Wagner, T., Chen, H., Liu, W. Q., and Liu, J. G.: A rapid method to derive horizontal distributions of trace gases and aerosols near the surface using multi-axis differential optical absorption spectroscopy, Atmos. Meas.

Tech., 7, 1663-1680, https://doi.org/10.5194/amt-7-1663-2014, 2014.

- Wang, Y., Pukite, J., Wagner, T., Donner, S., Beirle, S., Hilboll, A., Vrekoussis, M., Richter, A., Apituley, A., Piters, A., Allaart, M., Eskes, H., Frumau, A., Roozendael, M. V., Lampel, J., Platt, U., Schmitt, S., Swart, D., and Vonk, J.: Vertical
- 1175 Profiles of Tropospheric Ozone From MAX-DOAS Measurements During the CINDI-2 Campaign: Part 1 -Development of a New Retrieval Algorithm, J. Geophys. 123, 10637-10670, Res.-Atmos., https://doi.org/10.1029/2018JD028647, 2018.
  - Williams, J.E., Boersma, K.F., LeSager, P., and Verstraeten, W.W.: The high-resolution version of TM5-MP for optimized satellite retrievals: description and validation, Geosci. Model Dev., 10, 721-750, https://doi.org/10.5194/gmd-10-721-2017, 2017.
- 1180
  - Wittrock, F., Oetjen, H., Richter, A., Fietkau, S., Medeke, T., Rozanov, A., and Burrows, J. P.: MAX-DOAS measurements of atmospheric trace gases in Ny-Ålesund - Radiative transfer studies and their application, Atmos. Chem. Phys., 4, 955– 966, https://doi.org/10.5194/acp-4-955-2004, 2004.

1185

1190