

# Broadband Radiative Quantities for the EarthCARE Mission: The ACM-COM and ACM-RT Products

Jason N. S. Cole<sup>1</sup>, Howard W. Barker<sup>2</sup>, Zhipeng Qu<sup>1</sup>, Najda Villefranque<sup>3</sup>, Mark W. Shephard<sup>1</sup>

<sup>1</sup> Environment and Climate Change Canada, Toronto, ON, Canada

5 <sup>2</sup> Environment and Climate Change Canada, Victoria, ON, Canada

<sup>3</sup> Centre National de Recherches Météorologiques, Météo France / CNRS, Toulouse, France

*Correspondence to:* Howard W. Barker (howard.barker@canada.ca)

**Abstract.** The EarthCARE satellite mission’s objective is to retrieve profiles of aerosol and water cloud physical  
10 properties from measurements made by its cloud-profiling radar, backscattering lidar, and passive multi-spectral  
spectral imager (MSI). These retrievals, together with other geophysical properties, are input into broadband (BB)  
radiative transfer (RT) models that predict radiances, and fluxes, commensurate with measurements made, and  
inferred from, EarthCARE’s BB radiometer (BBR). The scientific goal is that modelled and “observed” BB fluxes  
differ, on average, by less than  $\pm 10 \text{ W m}^{-2}$ . When sound synergistic retrievals from the ACM-CAP process are  
15 available, they are acted on by the RT models. When they are not available, the RT models act on “composite”  
profiles of properties retrieved from measurements made by individual sensors. “Compositing” is performed in the  
ACM-COM process as described in this report.

The majority of this report describes the RT models, and their products, that make-up EarthCARE’s ACM-RT  
process. Profiles of BB shortwave (SW) and longwave (LW) fluxes and heating rates (HR) are computed by 1D RT  
20 models for each  $\sim 1 \text{ km}$  nadir column of inferred properties. 3D RT models compute radiances for the BBR’s three  
viewing directions, with the SW model also computing flux and HR profiles; the 3D LW model produces upwelling  
flux at just one level. All 3D RT products are averages over  $5 \times 21 \text{ km}$  “assessment domains” that are constructed  
using MSI data. Some of ACM-RT’s products are passed forward to the “radiative closure assessment” process that  
quantifies, for each assessment domain, the likelihood that EarthCARE’s goal has been achieved. As EarthCARE  
25 represents the first mission to make “operational” use of 3D RT models, emphasis in this report is placed on differ-  
ences between 1D and 3D RT results. For upwelling SW flux at 20 km altitude, 1D and 3D values can be expected to  
differ by more than EarthCARE’s scientific goal of  $\pm 10 \text{ W m}^{-2}$  at least 50% of the time.

## 1. Introduction

The EarthCARE satellite mission's primary objective is to make avant-garde observations of Earth's atmosphere that can be used to help improve representations of clouds and aerosols in numerical models that predict weather, air quality, and climatic change (Illingworth et al. 2015). Detailed descriptions of observations made by EarthCARE's cloud-profiling radar (CPR), backscattering lidar (ATLID), passive multi-spectral imager (MSI), and broadband radiometer (BBR), as well as the L2-retrieval algorithms that operate on them, are discussed in several papers of this special issue (Eisinger et al. 2023). EarthCARE's scientific goal is to retrieve cloud and aerosol properties with enough accuracy that when operated on by broadband (BB) radiative transfer (RT) models, their estimated top-of-atmosphere (TOA) BB fluxes, for domains covering  $\sim 100 \text{ km}^2$ , agree, more often than not, with their BBR-derived counterparts (Velázquez-Blázquez et al. 2023a) to within  $\pm 10 \text{ W m}^{-2}$  (ESA 2001). This "radiative closure assessment", which marks the end of the initial version of EarthCARE's formal "data production chain", provides a continuous radiative closure assessment of L2 retrievals with invaluable information to both L2-algorithm developers and data users.

The primary purpose of this paper is to describe and demonstrate the BB RT models used for both radiative closure assessment and provision of BB flux and heating rate (HR) profiles. Application of BB RT models to L2-retrieval products, along with auxiliary data, such as profiles of state variables and surface optical properties, will provide estimates of a range of diagnostic radiative flux and HR profiles. Examples of these products are presented here for simulated conditions along  $\sim 6,200 \text{ km}$ -long sections of EarthCARE orbits, which are referred to as "frames" (Qu et al. 2023). These simulations underpin most experiments reported in this special issue.

Both 1D and 3D shortwave (SW) and longwave (LW) RT models are used. Both SW and LW 3D models produce TOA radiances; the SW model also produces flux and HR profiles for all-sky conditions for a subset of  $\sim 100 \text{ km}^2$  assessment domains, while the LW model produces upwelling fluxes at a single level. The number of radiative closure assessment domains that can be processed per frame changes from frame-to-frame and will depend on computer resource availability during the mission as well as, to a lesser extent, cloud structure. Both SW and LW 1D models produce flux and HR profiles for each L2-column for all-sky, clear-sky (i.e., clouds removed), and pristine-sky (i.e., cloud and aerosol removed) conditions. This provides continuity with previous and ongoing missions such

as CloudSat (Stephens et al. 2002) and CERES (Wielicki et al. 1996). All applications of RT models occur in the  
 55 processor referred to as ACM-RT.

The current plan is for RT models to be applied to retrievals from the ACM-CAP process’s CAPTIVATE algorithm  
 (Mason et al. 2023). CAPTIVATE’s products, which are in the L2b class of products, are recognized formally as  
 EarthCARE’s “best estimates” for they represent the most complete, synergistic, use of observations made by the  
 CPR, ATLID, and MSI. Should CAPTIVATE fail, the contingency plan is to use a *composite* back-up “best esti-  
 60 mate” based on products arising from retrieval algorithms that operate on measurements from a single active sensor.  
 These products are in the L2a class. As such, the secondary purpose of this paper is to describe how the composite  
 cloud and aerosol profiles are generated within the ACM-COM process.


The following section provides an overview of the ACM-COM and ACM-RT processes and how they link to other  
 processes. This is followed by a description of how EarthCARE retrievals are prepared for use in RT models includ-  
 65 ing the creation of L2a-composite (back-up) cloud-aerosol profiles. In section 4 the SW and LW RT models are  
 described along with atmospheric and surface optical properties. RT model results are documented in section 5  
 making use of the synthetic test frames. This includes showing the full extent of products from the 1D models and  
 differences between SW and LW fluxes predicted by 1D and 3D RT models. Section 6 provides a summary.

## 2. Overview of EarthCARE’s radiation products

70 *Figure 1* encapsulates the main operations of ACM-COM and ACM-RT including its inputs and outputs. ACM-  
 COM prepares profiles of cloud and aerosol properties, produced by L2-retrieval processors as summarized by  
 Eisinger et al. (2023), for use by the BB RT models in ACM-RT. Main operations of these processors are addressed  
 in the subsequent two sections. The remainder of this section provides an overview of the components in *Figure 1*.

Arriving at ACM-COM are profiles of cloud and aerosol properties for each column, in the mission’s joint standard  
 75 grid (JSG) (Eisinger et al. 2023), along the L2-plane as retrieved by single active sensor L2a algorithms. ACM-COM  
 also receives similar profiles produced by the synergistic L2b CAPTIVATE algorithm in ACM-CAP, which utilizes  
 ATLID, CPR, and MSI measurements (Mason et al. 2023). While studies to date suggest that ACM-CAP products  
 will likely be EarthCARE’s default “best estimates” (Mason et al. 2023a), this will not be known for sure until  
 EarthCARE’s post-launch “commissioning phase”. Should ACM-CAP fail, and thus leave only (some) L2a retrievals

80 remain usable by RT models, a contingency plan was developed in which L2a products are merged to form alternate “best estimate” composite cloud-aerosol profiles. Compositing of L2a products is explained in section 3.2.




**Figure 1.** Flowchart summarizing the basic inputs to the ACM-COM and ACM-RT processes, their core operations, and their permanent output files. The operations are discussed in sections listed next to them.

85

Regardless of whether ACM-CAP or alternate L2a-composite profiles are acted on by ACM-RT’s RT models, they need to be readied for use there. Hence, the last steps of ACM-COM take profiles of meteorological variables and surface conditions, passed in from the X-MET processor (Eisinger et al. 2023) and databases, respectively, and merge them with ACM-CAP or L2a-composite products.

90 Following previous satellite missions (e.g., L’Ecuyer et al. 2008; Kato et al. 2013), ACM-RT computes SW and LW  
BB flux and HR profiles by applying 1D RT models to each admissible JSG profile along the L2-plane. EarthCARE  
makes a substantial step forward, however, with its operational use of 3D BB RT models for both SW and LW  
bands. For consistency, 1D and 3D models use, where possible, common descriptions of atmospheric and surface  
optical properties. Optical properties for pristine atmospheres, free of aerosol and cloud, come from the Rapid Radia-  
95 tive Transfer Model for General Circulation Models (RRTMG) (Iacono et al. 2008; Morcrette et al. 2008). RRTMG’s  
SW and LW 1D two-stream models compute flux and HR profiles for each JSG column along the L2-plane. The  
default is to use all ACM-CAP profiles available in an EarthCARE frame. If no ACM-CAP profiles are available, or  
if there is an explicit request for radiative closure assessment to be performed on ACM-COM results, radiative  
transfer calculations are performed for the L2a-composite profiles. These results are passed to ACMB-DF (Barker et  
100 al. 2023) where they are averaged over “radiative closure assessment domains”  $D$  as dictated by ACM-3D’s scene  
construction algorithm indices (Qu et al. 2023).

The 3D RT solvers are Monte Carlo solutions of the plane-parallel 3D RT equation. They use the same gaseous,  
aerosol, and cloud optical properties as the 1D models, but they use detailed scattering phase functions. The SW  
model produces profiles of fluxes and HRs, and TOA BB radiances commensurate with the BBR’s three telescopes.  
105 The LW model computes the same radiances along with an upwelling flux at a “reference height” as defined in the  
BMA-FLX process (Velázquez-Blázquez et al. 2023a). All 3D RT computations are done for “radiation computation  
domains”  $D^+$  that consist of  $D$  and buffer-zones around them (see *Figure 2*). Model-estimates of radiances and  
fluxes, and any available uncertainties, are averaged over  $D$  and passed to the ACMB-DF processor (Barker et al.  
2023) where they are compared to BBR radiances and their model-derived fluxes (Velázquez-Blázquez et al. 2023a,  
110 Velázquez-Blázquez et al. 2023b).



**Figure 2:** Schematic showing the radiative closure assessment domain  $D$  (black) and extended computation domain  $D^+$  (shaded), which is the union of  $D$  and its buffer-zones. These domains are centred on the L2a/L2b retrieved cross-section (RXS). See Qu et al. (2023) for details.

115

### 3. ACM-COM: Preparations for RT models and L2a-composites

As described in the next subsection, ACM-COM readies, for use by RT models in ACM-RT, cloud and aerosol information from various L2-retrieval processes and meteorological information from X-MET. This is followed by an explanation of how ACM-CAP's alternate *L2-composite profiles* are produced.

#### 3.1. Prepping L2-retrievals for RT models

The ACM-COM process begins by simply extracting, from X-MET files, information about atmospheric state as needed by all BB RT models. This includes profiles of pressure, temperature, humidity, and ozone concentration. Regarding aerosols, their classification information is provided by the AC-TC processor (Irbah et al. 2023) with extinction at  $0.355 \mu\text{m}$  obtained from A-EBD (Donovan et al. 2023). Six types of aerosols are considered: dust, sea salt, continental pollution, smoke, dusty smoke, and dusty mix. Grid-cells in AC-TC that are classed as *cloudy*, *uncertain*, *missing*, or *noisy* are considered to be aerosol-free.

125

Additionally, ACM-COM adds the following minor molecular species to X-MET profiles:  $\text{CO}_2$ ,  $\text{CH}_4$ ,  $\text{N}_2\text{O}$ , CFC-11, CFC-12, CFC-22, and  $\text{CCL}_4$ . These profiles come from climatologies generated by J.-J. Morcrette and A. Bozzo (per. comm., R. Hogan 2013). Values are functions of month, pressure, and latitude.


### 130 3.2. Construction of “L2a-composite” cloud and aerosol profiles

This subsection describes the algorithm that produces the alternate to ACM-CAP’s synergistic L2b “best estimates”. It is based on compositing L2a retrievals from ATLID (A-ICE) (Donovan et al. 2023) and CPR (C-CLD) (Mroz et al. 2023) observations.

The L2a-composite’s cloud properties depend on an indication of columnar cloudiness from the M-COP processor (Hünerbein et al. 2023). If a grid-cell in a column has *either* A-ICE *or* C-CLD cloud water content greater than zero, 135 the reported cloud properties enter directly into the L2a-composite. If, however, *both* A-ICE *and* C-CLD report valid cloud properties with ice water contents  $IWC > 0$ , aggregated normalized uncertainties for  $IWC$  and crystal effective radius  $r_{eff}$  are computed, respectively, as

$$\sigma_{A-ICE} = \sqrt{\left(\frac{\sigma_{IWC}^{A-ICE}}{IWC^{A-ICE}}\right)^2 + \left(\frac{\sigma_{r_{eff}}^{A-ICE}}{r_{eff}^{A-ICE}}\right)^2} \quad \text{and} \quad \sigma_{C-CLD} = \sqrt{\left(\frac{\sigma_{IWC}^{C-CLD}}{IWC^{C-CLD}}\right)^2 + \left(\frac{\sigma_{r_{eff}}^{C-CLD}}{r_{eff}^{C-CLD}}\right)^2}, \quad (1)$$

140 where  $\sigma_{IWC}^{A-ICE}$ ,  $\sigma_{IWC}^{C-CLD}$ ,  $\sigma_{r_{eff}}^{A-ICE}$ , and  $\sigma_{r_{eff}}^{C-CLD}$  are processor-specific 1-sigma uncertainties. Ice cloud properties for the product having  $\min(\sigma_{A-ICE}, \sigma_{C-CLD})$  enter into the L2a-composite. For grid-cells designated to contain only liquid cloud, C-CLD properties are used. Hence, L2a-composites resemble NASA’s CloudSat-CALIPSO-CERES (C3M) product (Kato et al. 2010), though it is simpler in that active sensor-derived water contents are *not* constrained, as they are in ACM-CAP, by MSI passive radiances.



145

**Figure 3:** (a) Lines represent profiles of IWC directly from the test frame (simulated by GEM), as well as those retrieved by the L2a algorithms in processors A-ICE and C-CLD. Filled circles are layer values that ACM-COM’s algorithm selected from A-ICE and C-CLD according to which one has the smallest aggregated relative uncertainty, defined by (1), as shown in (b). This profile, which has only ice cloud, is from the *Halifax* test frame at  $63.67^{\circ}\text{N}$ ;  
 150  $54.64^{\circ}\text{W}$ .

150

*Figure 3* shows an example of this compositing process for a column from a simulated frame (Qu et al. 2023). Only ice cloud was present, so both A-ICE and C-CLD reported hydrometeors. Above  $\sim 3.4$  km ATLID’s estimates have least uncertainty meaning that A-ICE values enter into the composite. At  $\sim 3.3$  km the CPR value is least uncertain and so C-CLD’s estimate is used. As ATLID failed to return useable signals at lower altitudes, CPR values fill the remainder of ACM-COM’s profile.

155

In this example, the “reference values”, as simulated by the Global Environmental Multi-scale (GEM) model (Qu et al. 2023), generally match ACM-COM’s better than ACM-CAP’s. This, however, does not mean that ACM-COM’s will be used by the RT models. First, during the mission “reference values” are, of course, unknown so a plot like  
 160 *Figure 3* cannot be made or used. Second, if and when ACM-CAP profiles exist, they are used by default.

160

#### 4. ACM-RT: Broadband radiative transfer models

As mentioned above, EarthCARE’s RT models are based on RRTMG (Iacono et al. 2003, 2008; Morcrette et al. 2008). Like its computationally taxing progenitor (Mlawer et al. 1997; Mlawer and Clough 1998), RRTMG is built



on the correlated  $k$ -distribution (CKD) method (Goody et al. 1989; Lacis and Oinas 1991). Broadband integrated flux and HR profiles are sums of calculations for quadrature points (112 for SW and 140 for LW) spread over spectral bands (14 for SW and 16 for LW). RRTMG is used widely in large-scale models (e.g., ECMWF, MPI, NCEP, NCAR, NASA/GSFC, LMD, CMA), and its verification has been documented elsewhere (e.g., Iacono et al. 2008; Oreopoulos et al. 2012). This section begins by describing atmospheric and surface optical properties, and follows with descriptions of the 1D and 3D transport solvers.

## 170 **4.1. Optical properties: Atmospheric constituents**

### **4.1.1. Gases**

Molecular optical depths are computed by the CKD method in RRTMG\_SW\_v3.9 and RRTMG\_LW v4.85 and used by both 1D and 3D RT models. Molecular absorption coefficients for RRTMG's  $k$ -distributions were obtained from the *line-by-line* RT model (LBLRTM), which has been evaluated against surface and laboratory observations (Clough et al. 2005; Shephard et al. 2009; Alvarado et al. 2012). LBLRTM's spectroscopic line parameters are essentially equivalent to HITRAN 2000 and HITRAN 1996 (SW) databases. Algorithmic accuracy of LBLRTM is 0.5% (Clough et al 2005) with limiting errors generally attributed to line shape and spectroscopic input parameters.

Wavenumber ranges for RRTMG's SW bands are: 2600-3250, 3250-4000, 4000-4650, 4650-5150, 5150-6150, 6150-7700, 7700-8050, 8050-12850, 12850-16000, 16000-22650, 22650-29000, 29000-38000, 38000-50000, and 820-2600  $\text{cm}^{-1}$ , with the last band coded out of sequence for spectral continuity with the LW bands. Sources of extinction are: absorption by  $\text{H}_2\text{O}$ ,  $\text{CO}_2$ ,  $\text{O}_3$ ,  $\text{CH}_4$ ,  $\text{O}_2$ ,  $\text{N}_2$ ; and Rayleigh scattering.

Wavenumber ranges for RRTMG's LW bands are: 10-350, 350-500, 500-630, 630-700, 700-820, 820-980, 980-1080, 1080-1180, 1180-1390, 1390-1480, 1480-1800, 1800-2080, 2080-2250, 2250-2380, 2380-2600, and 2600-3250  $\text{cm}^{-1}$ . Molecular absorption optical depths are computed for:  $\text{H}_2\text{O}$ ,  $\text{CO}_2$ ,  $\text{O}_3$ ,  $\text{N}_2\text{O}$ ,  $\text{CH}_4$ ,  $\text{O}_2$ ,  $\text{N}_2$ , CFC11, CFC12, CFC22, and  $\text{CCl}_4$ . Additionally, CKD\_v2.4's continuum model accounts for foreign- and self-broadening of lines for  $\text{H}_2\text{O}$ ,  $\text{CO}_2$ ,  $\text{O}_2$ ,  $\text{O}_3$ , and Rayleigh scattering.

For 1D SW RT, the Rayleigh scattering phase function is approximated as  $p_{\text{Ray}}(\mu) = 1$ , where  $\mu = \cos\theta$  and  $\theta$  is scattering angle. For 3D SW RT, on the other hand,

$$p_{Ray}(\mu) = \frac{3}{4}(1 + \mu^2), \quad (2)$$

190 which is, as are all phase functions used here, normalized as

$$\frac{1}{2} \int_{-1}^1 p_{Ray}(\mu) d\mu = 1. \quad (3)$$

Relative to LBLRTM, clear-sky RRTMG\_LW BB fluxes at all levels are accurate to within  $\pm 1.5 \text{ W m}^{-2}$  ( $\pm 1 \text{ W m}^{-2}$  for direct-beam and  $\pm 2 \text{ W m}^{-2}$  for diffuse-beam), with HRs agreeing to within  $\pm 0.2 \text{ K day}^{-1}$  in the troposphere and  $\pm 0.4 \text{ K day}^{-1}$  in the stratosphere. Likewise, RRTMG\_SW's accuracies, at  $\mu_0 \approx 0.7$ , are within  $\pm 3 \text{ W m}^{-2}$  at all  
 195 levels, with HRs agreeing to within  $\pm 0.1 \text{ K day}^{-1}$  in the troposphere, and  $\pm 0.35 \text{ K day}^{-1}$  in the stratosphere.

#### 4.1.2. Aerosols

As with gases, 1D and 3D RT models share the same spectral optical properties for aerosols: extinction coefficient  $\beta_{aero}$ , single-scattering albedo  $\omega_{aero}$ , and asymmetry parameter  $g_{aero}$ . Spectral  $\beta_{aero}$ ,  $\omega_{aero}$ , and  $g_{aero}$  are averaged over wavelength  $\lambda$  intervals listed above, and were generated so as to be consistent with retrieval algorithms  
 200 following Wandinger et al. (2023). Radiative properties for their basic aerosol types are then mixed externally yielding radiative properties for aerosol mixture classifications used in AC-TC. Aerosol extinction is provided at 355 nm, and so for each aerosol mixture the ratio  $\beta_{aero}(\lambda) / \beta_{aero}(0.355 \mu\text{m})$  at each  $\lambda$  is computed and then averaged spectrally using the same weightings as for cloud radiative properties as described below.

Aerosol scattering phase functions, as needed by the 3D RT codes, are represented by the Henyey-Greenstein (1941)  
 205 function, which is given by

$$p_{HG}(\mu; g_{aero}) = \frac{1 - g_{aero}^2}{(1 + g_{aero}^2 - 2g_{aero}\mu)^{3/2}}, \quad (4)$$

satisfies

$$g_{\text{aero}} = \frac{1}{2} \int_{-1}^1 p_{HG}(\mu; g_{\text{aero}}) \mu d\mu, \quad (5)$$

and is used directly in the models (i.e., no need for tabulation). Owing to the size and irregularity of aerosol particles,  
 210 and retrieval uncertainties, use of (4) is reasonable.

#### 4.1.3. Liquid clouds

The standard version of RRTMG uses Hu and Stamnes's (1993) parametrizations of spectral  $\beta$ ,  $\omega_0$ , and  $g$  for liquid droplets. For EarthCARE, however, these have been replaced by more precise Lorenz-Mie calculations tabulated for ranges of droplet effective radii  $r_{\text{eff}}$  and effective variances  $v_{\text{eff}}$ , which are defined, respectively, as

$$r_{\text{eff}} = \frac{\int_0^\infty n(r) r^3 dr}{\int_0^\infty n(r) r^2 dr} = \frac{\langle r^3 \rangle}{\langle r^2 \rangle}, \quad (6)$$

and

$$v_{\text{eff}} = \frac{\int_0^\infty (r - r_{\text{eff}})^2 n(r) r^2 dr}{r_{\text{eff}}^2 \int_0^\infty n(r) r^2 dr} = \frac{\langle r^2 \rangle \langle r^4 \rangle}{\langle r^3 \rangle^2} - 1, \quad (7)$$

where  $r$  is droplet radius. Droplet size distributions  $n(r)$  are assumed (Chýlek et al. 1992) to be

$$n(r) = \frac{N}{\Gamma(\nu)} \left( \frac{\nu}{\langle r \rangle} \right)^\nu r^{\nu-1} \exp\left( -\frac{r\nu}{\langle r \rangle} \right). \quad (8)$$

220 where  $\langle r \rangle = \nu r_{\text{eff}} v_{\text{eff}}$  and  $\nu = (1 - 2v_{\text{eff}}) / v_{\text{eff}}$ .

Lorenz-Mie computations (Wiscombe 1980), using Segelstein's (1981) refractive indices, were performed for  $r$  between 0.01 and 120  $\mu\text{m}$  in increments of 0.05  $\mu\text{m}$ , and for wavelengths  $\lambda$  between 0.25 and 100  $\mu\text{m}$  in increments

of: 0.02 for  $0.25 < \lambda < 2 \mu\text{m}$ ; 0.04 for  $2 < \lambda < 3 \mu\text{m}$ ; 0.05 for  $3 < \lambda < 10 \mu\text{m}$ ; 0.07 for  $10 < \lambda < 20 \mu\text{m}$ ; and 0.1 for  $20 < \lambda < 100 \mu\text{m}$ . Phase functions and optical properties were integrated over RRTMG's spectral intervals for combinations of  $r_{\text{eff}}$  and  $v_{\text{eff}}$ :  $r_{\text{eff}}$  from 0.5 - 40  $\mu\text{m}$  in increments of 0.5  $\mu\text{m}$ ; and  $v_{\text{eff}}$  from 0.02 - 0.4 in increments of 0.02  $\mu\text{m}$ . Spectral weightings for SW bands are the mean of downwelling irradiances at the tropopause and surface as predicted by a *line-by-line* RT model (Iacono et al. 2008) for the tropical atmosphere at solar zenith angle  $\theta_0 = 0^\circ$ . For LW bands, weightings are the Planck function at 275 K. In the RT models, values of  $r_{\text{eff}}$  and  $v_{\text{eff}}$  are rounded to the nearest value in the table, which usually results in errors for  $\beta$ ,  $\omega_0$ , and  $g$  of less than  $\pm 1\%$ .

As the 3D RT models are Monte Carlo solutions, they use normalized tabulated scattering phase functions  $p(\mu)$  for droplets. Broadband, spectrally-integrated  $p(\mu)$  have 1,800 equal angular bins, and their cumulative sums, as functions of  $\mu$ , were computed by

$$R(\mu_s) = \frac{1}{2} \int_{\mu_s}^1 p(\mu) d\mu, \quad (9)$$

where  $\mu_s$  is cosine of scattering angle, with  $R(\mu_s = 1) = 0$  (forescatter) and  $R(\mu_s = -1) = 1$  (backscatter). For efficiency, tables of  $\mu_s$  were constructed for 1800 equally spaced values of  $R$ ; when a scattering event occurs, a uniform pseudo-random number gets generated  $R \in [0, 1]$ , and linear interpolation sets  $\mu_s$ , which is used to update a photon's direction cosines.

#### 4.1.4. Ice clouds

Values of  $\beta$ ,  $\omega_0$ ,  $g$ , and scattering phase functions for ice clouds are based on Yang et al.'s (2013) theoretical functions for 11 crystal habits: droxtals, prolate spheroids, oblate spheroids, solid columns, hollow columns, aggregates composed of 8 solid columns, hexagonal plates, small aggregates composed of 5 plates, large aggregates composed of 10 plates, solid bullet rosettes, and hollow bullet rosettes. Maximum dimension for each habit ranges from 2  $\mu\text{m}$  to 10,000  $\mu\text{m}$  for 189 discrete sizes. Three surface roughness conditions were considered for each ice

habit: smooth, moderate, and severe. Each constituent has volume, projected area, effective size, extinction efficiency,  $\omega_0$ , and  $g$ . Their scattering phase functions are tabulated at 498 unequal angles, but were transformed into 1,800 equal angular bins for use in (9).

To make this dataset's size suitable for operational use, optical properties were averaged over  $\lambda$  and assumed distributions of habit, size, and roughness that were derived from CALIPSO observations (Baum et al. 2011). Resulting phase functions and optical properties are functions of effective diameter which is defined as


$$d_{eff} = \frac{3 \sum_i \int V_i(D) n(D) f_i(D) dD}{2 \sum_i \int A_i(D) n(D) f_i(D) dD}, \quad (10)$$

where  $V$ ,  $A$ , and  $D$  are geometric volume, orientation-averaged projected area, and maximum dimension of ice particle, respectively.  $n(D)$  denotes crystal size distribution, and  $f_i$  indicates the percentage of each ice particle habit and roughness. Values of  $d_{eff}$  range from 10  $\mu\text{m}$  to 120  $\mu\text{m}$  in increments of 5  $\mu\text{m}$ . Band-averaged optical properties were computed using the same weightings as in (10) while also weighting for spectral irradiance and then integrating over RRTMG's spectral intervals. Spectral weight for SW bands was the TOA spectrum while for the LW it was the Planck function at 250 K (per. comm., B. Yi, 2013).

#### 4.1.5. Solid hydrometeors and rain

Solid hydrometeors are retrieved as though they were ice cloud, and their optical properties appear as such. In addition to liquid cloud properties, however, ACM-CAP reports layer rain rates  $R$  ( $\text{mm h}^{-1}$ ). Raindrop size distributions are assumed to follow Ulbrich's (1983) gamma distribution. Spectrally-integrated single-scattering properties are defined using the same spectral weights as discussed in section 4.1.3 in conjunction with Mie scattering properties for droplet radii between 10  $\mu\text{m}$  and 2000  $\mu\text{m}$ ; larger drops tend to break-up (e.g., Cotton and Gokhale 1967). Tables of optical properties range from  $R = 0.5 \text{ mm h}^{-1}$  to  $50 \text{ mm h}^{-1}$  in increments of  $0.5 \text{ mm h}^{-1}$ . *Figure 4a* shows rain drop size distributions for three values of  $R$  for Ulbrich's (1983) formulation using  $\mu = 0.056R - 0.74102$  (NB. This  $\mu$  follows Ulbrich's Eq.2 and differs from  $\mu$  used elsewhere in this paper). *Figure 4b* shows corresponding drop

effective radius and variance; note that as rain intensity increases,  $V_{eff}$  decreases, droplet spectrum narrows, and with this format, Marshall and Palmer's (1948) distribution occurs near  $R = 13 \text{ mm h}^{-1}$ , which is, by most standards, fairly heavy rain.



270 **Figure 4:** (a) Raindrop size distributions for three values of rain rate ( $\text{mm/h}$ ). (b) Rain droplet effective radius and  
variance as functions of rain rate according to Ulbrich's (1983) formulation and the assumed gamma distribution  
parameter as discussed in section 4.1.5. (c) Rain water content as a function of rain rate.

The Mie phase functions that follow from *Figure 4* and (8) have very pronounced forward peaks that are difficult to  
275 capture well in the MC models. Hence, because rain usually resides beneath thick clouds where radiance fields are  
highly diffuse, the 3D RT models use  $p_{HG}(\mu; g)$ .

#### 4.2. Optical properties: Underlying surfaces

Snow-free surface albedo over land for visible ( $0.3\text{-}0.7 \mu\text{m}$ ) and infrared ( $0.7\text{-}5.0 \mu\text{m}$ ) SW bands were calculated  
from climatological bidirectional reflection distribution function parameters for 16-day periods based on 12 years  
280 (2002-2013) of MODIS MCD43GF data (Schaaf et al. 2002). Terrestrial snow albedo data for the same spectral  
bands are based on Moody et al. (2007) whose calculations were, in turn, based on five years (2000-2004) of clima-  
tological statistics of Northern Hemisphere white-sky albedos for 16 International Geosphere-Biosphere Program  
(IGBP) ecosystem classes when accompanied by the presence of snow on ground. For ice-covered land or water  
surfaces, BB averaged albedos over  $16,000 - 50,000 \text{ cm}^{-1}$  are provided by X-MET (via ECMWF).

285 Ideally, the 3D RT models should include bidirectional reflection and emission functions; such as Rahman et al.'s (1993) land surface model, which is in EarthCARE's SW 3D RT code but global parameters are too lacking. Hence, spectral albedos, as just described, and the Lambertian assumption are used.

For open water surfaces, spectrally-independent ocean albedo is approximated by

$$\alpha_{sfc} = 0.021 + x^2 \left( 0.0421 + x \left( 0.128 + x \left( -0.04 + x \left( \frac{3.12}{5.68 + w} + \frac{0.074x^2}{1 + 3w} \right) \right) \right) \right), \quad (11)$$

290 where  $x = 1 - \cos \theta_i$ ,  $\theta_i$  is zenith angle of an incident photon, and  $w$  is surface wind-speed ( $\text{m s}^{-1}$ ) (Hansen et al. 1983). The 3D SW model uses (11) for all photons arriving at a water surface. Additionally, it uses Cox and Munk's (1956) ergodic wave model to describe the probability of a SW photon incident at the surface being reflected, with probability defined by (11), toward a BBR telescope. As such, simulated radiances capture some semblance of Sun-glint; the effects of which are tempered by EarthCARE's orbit (Illingworth et al. 2015).

295 While the 1D SW model uses (11), with  $\theta_0$  replacing  $\theta_i$ , to describe direct-beam albedo, its diffuse-beam albedo is

$$\langle \alpha_{sfc} \rangle = 0.03815 + \frac{0.1486}{5.68 + w} + \frac{0.0026}{1 + 3w}, \quad (12)$$

which is just the integral of (11) assuming isotropic irradiance, regardless of sky condition. Last, hemispheric spectral emissivities for land and sea surfaces, for each RRTMG\_LW band, are based on Huang et al. (2016). Like albedo, emissivity is assumed to be Lambertian.

### 300 **4.3. 1D radiative transfer modelling**

The 1D RT models in RRTMG are meant to be applied to layered atmospheres with optical properties varying only in the vertical. As RRTMG was designed for use in large-scale models, it comes with algorithms that address unresolved horizontal fluctuations in cloud water content and cloud overlap. These algorithms are not needed for EarthCARE because RRTMG will be applied to individual JSG columns resolved at  $\sim 1$  km resolution with homogeneous  
305 layers.

The LW transport solver in RRTMG performs flux calculations for a single diffusivity angle with an adjustment for profiles that contain large H<sub>2</sub>O vapour contents. It is an emissivity model that neglects scattering by all atmospheric constituents. Its SW solver employs the multi-layer delta-Eddington two-stream approximation (Wiscombe 1977), which accounts for multiple scattering but, as with the LW solver, has well-documented conditional limitations for aerosol and cloud conditions (e.g., Li and Ramaswamy 1996; Barker et al. 2015a). Nevertheless, due to RRTMG’s widespread use at the time of writing, it is used for EarthCARE with a minimum of alterations so as to be consistent with other current applications.

There are three applications of the 1D SW and LW RT models to each valid JSG column along the retrieved cross-section. The first, denoted as “all-sky”, uses the full retrieved profiles. Second is “clear-sky” where clouds are removed leaving molecules and aerosols. The third application is “pristine-sky” in which clouds and aerosols are removed leaving just the molecular atmosphere.

#### 4.4. 3D radiative transfer modelling

Monte Carlo solutions of the 3D RT equation are used to calculate both SW and LW fluxes and radiances. This represents a break from, and advancement over, previous satellite missions that have been limited to use of 1D RT solvers. The 3D RT models are discussed in the following subsections.

##### 4.4.1. SW radiation

Solar fluxes and radiances are computed by a local estimation-based Monte Carlo algorithm (Marchuk et al. 1980; Barker et al. 2003). It is discussed here in general terms, except for aspects that have not been published or were designed specifically for EarthCARE.

Unlike the 1D RT models that act on individual columns, 3D RT models require collections of columns. Photons get injected uniformly across  $D^+$  that are expected to be at most ~60 km along-track by ~30 km across track (see *Figure 2*). Cosine of solar zenith angle  $\mu_0$  is uniform over  $D^+$  and set by its central pixel. Total numbers of injected photons per domain are to be determined, as they depend on computational resources, acceptable Monte Carlo sampling noise for either fluxes or radiances, and areal extents of individual  $D^+$ . Number of photons injected per spectral band is proportional to the weight associated with quadrature points in RRTMG’s CKD model.



Each atmospheric cell has a spectral cumulative extinction vector whose entries for attenuating constituents are ordered, for efficiency, as: ice cloud; liquid cloud; Rayleigh scatterers; absorbing gases; aerosols; and rain. When an interaction between an attenuator and a photon takes place, a uniform random number between 0 and 1 is generated, the (normalized) extinction vector is searched sequentially thus setting the attenuator, with its single-scattering properties used to establish whether absorption or scattering takes place (cf. Barker et al. 2003). When a scattering event occurs, a fraction  $1 - \omega_0$  of the photon's weight goes into local heating. What remains has its weight reduced by a factor  $\omega_0$ .

At each scattering event, the probability of photons being redirected toward a BBR telescope is determined using  $p(\mu)$ . Transmittance through total optical depth between scattering event and satellite sets the probability of scattered photons reaching the satellite; as this distance is large and the telescope's aperture small, any path deviation is assumed to result in undetected photons. These contributions are summed to produce final estimates of BBR radiances.

The local estimation method runs into trouble when photons travelling directly toward a telescope undergo a scattering event by cloud particles whose  $p(\mu)$  have sharp diffraction peaks (Iwabuchi 2006). Such rare contributions are valid, but they catastrophically elevate uncertainties, which are difficult to counter with large numbers of "typical" contributions when number of injected photons is small, as for EarthCARE. A simple way to help, without impacting fluxes and HRs, is to use the tabulated exact  $p(\mu)$  to determine all photon forward trajectories but only those radiance contributions from the first  $N_{\text{Mie}}$  scattering events by cloud particles. Thereafter, the blunt-nosed  $p_{HG}(\mu; g)$  is used to compute radiance contributions (see Barker et al. 2003).

The rationale behind this approximation is that low-order scatterings that contribute to BBR radiances come largely from  $p(\mu < 0)$ , and because they do not spike radiances, several of them are allowed so as to capture details of  $p(\mu)$ . For optically thin clouds there will be few scattering events and so calls to  $p_{HG}(\mu; g)$  will be rare. For thicker clouds, however, after  $\sim 3$  scatterings photons will have had a fair chance of being redirected onto upward

travelling trajectories that can spike radiances. EarthCARE uses  $N_{\text{Mie}} = 4$  for, as shown in section 5.2, it strikes a  
 355 balance between bias and random radiance errors (Barker et al. 2003).

When a photon arrives at the surface, it undergoes Lambertian reflection for albedo  $\alpha_s$  with  $1 - \alpha_s$  of its weight removed and added to *net* surface irradiance. The probability of being reflected toward a BBR sensor goes according to Lambertian for land, ice and snow, and Cox and Munk (1956) for open water (see section 4.2).

A unique, memory saving, aspect of EarthCARE’s SW and LW 3D RT models is that the 3D atmosphere never  
 360 appears explicitly in them. This is because all columns in  $D^+$  exist along the retrieved cross-section; optical properties of columns off this plane come from a *donor* column in it, as dictated by ACM-3D’s scene construction algorithm (Barker et al. 2011; Qu et al. 2023).

#### 4.4.2. LW radiation

Longwave radiances are computed efficiently with the backward Monte Carlo technique (Walters and Buckius 1992;  
 365 Modest 2003). Cole’s (2005) implementation is used for EarthCARE. Much of the code resembles that of the SW Monte Carlo, and so discussion is focused on its unique aspects.

Unlike the SW Monte Carlo, photons are not injected uniformly onto the top of  $D^+$  since the domain itself is the source. Rather, reciprocity of paths from an emission source to a sensor is assumed to hold (Case 1957). Hence, photons trace back from the top of the assessment domain to their source of emission where the contribution to  
 370 radiance is computed using local temperature and optical properties. This process is repeated for each point at the in the assessment domain and radiance view angle. To reduce the number of rays traced, which is often the main computational expense, rather than trace a unique ray for each quadrature point in the CKD model it is assumed that scattering optical properties are the same for all quadrature points in a given wavelength interval.

For a given wavelength interval in the CKD model a band-representative photon path is traced backward from the top  
 375 of the domain to determine a scattering path that can be related to each photon injected for each quadrature point in the band. The photon travels straight through the domain until it has accumulated sufficient scattering optical depth to scatter in the atmosphere or scatter due to an interaction with the surface. Scatter within the atmosphere is determined based on the cumulative distribution of scattering extinction; similar to that in the SW algorithm. For each

quadrature point in CKD wavelength interval a random number is determined which sets the optical depth that must  
 380 be accumulated to have an absorption event. Absorption optical depth is accumulated along the path until the photon  
 undergoes an absorption event at which point  $(1 - \omega_0)B(T)$  is added to the radiance, where  $B(T)$  is integrated  
 Planck function, and  $T$  is temperature. If, however, the photon reaches the surface, a uniform random number is used  
 to determine if there is absorption by the surface. If the random number is less than surface emissivity  $\epsilon$  the radiance  
 is incremented by  $B(T_s)$ , where  $T_s$  is the surface temperature. Otherwise the path is reflected.

385 Upward thermal flux at a, potentially variable, reference height is also computed. This is done using a method similar  
 to that used for radiances. The main difference being the selection (i.e., random generation) of the direction of each  
 ray injected into the domain from the reference height. Once the ray direction is selected, accumulation of emission  
 contributions is the same as it is for radiances.

#### 4.4.3. Estimation of Monte Carlo uncertainty

390 For a fixed domain, 1D RT models produce single deterministic solutions. Monte Carlo algorithms, however, yield a  
 sample from a distribution. In general, the breadth of the distribution, or Monte Carlo uncertainty, depends on the  
 number of injected photons, the variable being diagnosed, and the geometric and optical properties of the field.

Monte Carlo uncertainties are estimated by explicitly producing  $M$  samples of a random variable  $x$ , each using  $N_s$   
 photons and initialized with a unique, uniformly distributed, random number. Estimated population mean is simply

395 
$$\hat{\mu}_x(M, N_s) = \frac{1}{M} \sum_{m=1}^M x(m, N_s), \quad (13)$$

where  $x(m, N_s)$  is the  $m^{\text{th}}$  realization of  $x$ . From the central limit theorem,

$$\lim_{M \rightarrow \infty} p \left[ \left| \frac{\hat{\mu}_x(M, N_s) - \mu_x}{\frac{\sigma_x(M, N_s)}{\sqrt{M}}} \right| \leq a \right] = \frac{1}{\sqrt{2\pi}} \int_{-a}^a e^{-u^2/2} du, \quad (14)$$

where  $\mu_x$  and  $\sigma_x$  are mean and standard deviation of the population from which samples are drawn. Letting  $\hat{\sigma}_x(M, N_s)$  be an estimate of  $\sigma_x$  based on  $M$  samples, Monte Carlo “uncertainty” is defined as one standard deviation under a Gaussian distribution of samples. This amounts to setting  $a = 1$  in (14), and implies that after  $M$  realizations,  $\hat{\mu}_x$  has a 68% chance of lying in

$$\left[ \hat{\mu}_x(M, N_s) - \frac{\hat{\sigma}_x(M, N_s)}{\sqrt{M}}, \hat{\mu}_x(M, N_s) + \frac{\hat{\sigma}_x(M, N_s)}{\sqrt{M}} \right], \quad (15)$$

making for an uncertainty of


$$\hat{\rho}_x(M, N_s) \approx \pm \frac{\hat{\sigma}_x(M, N_s)}{\sqrt{M}}. \quad (16)$$

As  $M$  increases, estimates of  $\hat{\sigma}_x$  stabilize; they do not go to zero.

## 5. Results

This section’s main purpose is to showcase a sample of EarthCARE’s radiation products; some of which get utilized directly for radiative closure assessment as will be reported in a later study. Results are shown using only ACM-CAP data; corresponding results for ACM-COM’s composites are qualitatively the same.

As noted in the Introduction, many radiative quantities are averaged over  $\sim 100 \text{ km}^2$  assessment domains. It is expected that these domains will be configured to 21 km along-track by 5 km across-track. This is to strike a balance for closure assessment between limiting the scene construction algorithm’s (Qu et al. 2023) impact on radiance and flux estimates, yet facilitating horizontal transport of photons. To simplify presentation of results, radiative transfer estimates are shown for a reference height of 20 km (cf. Loeb et al, 2002); in operations they will vary.



415

420

**Figure 5:** (a) Profiles of domain-average cloud liquid water content, (b) ice water content, and (c) aerosol extinction coefficient for 21 km-long assessment domains, for the *Halifax* frame, as inferred by ACM-CAP’s synergistic algorithm. (d) Corresponding domain-average, all-sky SW broadband heating rates computed by RRTMG’s 1D RT model. (e) Difference between HRs shown in (d) and those computed by RRTMG for clear-sky conditions. (f) As in (e) except these HR differences are for clear-skies and pristine-skies. (g), (h), and (i) are as in (d), (e), and (f), respectively, except these are for LW broadband heating rates.

### 5.1. RRTMG 1D fluxes: Pristine-, clear-, and all-sky

425

As discussed in section 2, broadband flux and heating rate profiles for all admissible L2 columns are computed by RRTMG’s SW and LW 1D RT models. The left column of *Figure 5* shows ~2,200 km of cloud and aerosol properties retrieved by ACM-CAP’s synergistic algorithm (Mason et al. 2023). These results pertain to 21 km-long non-overlapping assessment domains near the central of the *Halifax* test frame. The middle column shows corresponding SW all-sky HRs and differences between all-sky HRs and clear-sky HRs (cloud radiative effect: CRE), and clear-sky HRs and pristine-sky HRs (aerosol direct effect: ADE). Aside from the usual 1D RT features, such as large SW heating near cloudtop and much smaller values below relative to clear-sky, the only peculiarity is the fairly strong heating at ~5 km altitude in the south-end. This is due to an elevated layer of water vapour. The vast majority of minor heating due to aerosol is from continental pollution that overrides sea salt.


430

435

The rightmost column in *Figure 5* is like the middle column but it shows results for LW HRs. As expected, there is strong cooling in the upper 1 - 2 km, or so, of clouds, little net heating or cooling below, and general cooling from

cloudless-skies. LW CREs are generally stronger than in the SW and exhibit strong cooling near all cloudtops and warming in clouds, when they are of sufficient vertical extent. LW ADEs are an order of magnitude smaller than their SW counterparts, and manifest themselves as cooling just beneath their SW warming counterparts.

To demonstrate what will be available in the ACM-RT archive, *Figure 6* shows TOA CRE, ADE, and some integrated cloud and aerosol properties that correspond with *Figure 5*. Some noteworthy points here are SW CRE reaching  $\sim 300 \text{ W m}^{-2}$  at  $\mu_0 \approx 0.3$  due to clouds near  $41^\circ \text{N}$  with large cloud water paths (CWP), LW CRE reaching  $100 \text{ W m}^{-2}$  near  $37^\circ \text{N}$  due to supercooled liquid aloft, and weak ADE ( $\sim -10 \text{ W m}^{-2}$  in the SW and less than 1 in the LW) stemming from aerosol optical depth, at  $0.355 \mu\text{m}$ , being at most 0.2. Aside from this, there is very little to comment on in these plots; they serve to demonstrate what will be available in the ACM-RT archive.




445

**Figure 6:** Top panel: Cloud radiative effect (CRE) and aerosol direct effect (ADE) as functions of latitude for broadband SW at an altitude of 20 km for 21 km-long assessment domains as shown in *Figure 5*.  $\mu_0$  is cosine of solar zenith angle. Middle panel: As in top panel except it is for broadband LW. Lower panel: Assessment domain-average cloud water path (CWP) and aerosol optical depth (AOD).

450

## 5.2. On the benefits of employing 3D RT models

As mentioned above, one of EarthCARE's notable advancements over prior like-missions is operational use of both 1D and 3D RT models. The decision to use 3D RT models was fuelled by myriad studies that show systematic differences between 1D and 3D treatments of RT, especially for cloudy atmospheres at solar wavelengths. Results shown in this subsection help justify the computational expensive of using 3D RT models operationally.



**Figure 7:** Nadir broadband SW radiances for two sample regions in the Hawaii frame; both regions measure 128 km along-track by 20.25 km across-track. Small rectangles indicate a 5 x 21 km assessment domain. Central values of latitude and longitude are listed along with  $\theta_0$  and  $\varphi_r$  (measured clockwise from the satellite's tracking direction). Labels 3D and 1D indicate RT model dimensionality using horizontal grid-spacings of 0.25 km and  $10^6$  km.


Before getting to results that apply strictly to EarthCARE, consider a detailed view of the impact of neglecting multi-dimensional RT. *Figure 7* shows nadir SW radiances simulated by a Monte Carlo RT model (Villefranque et al.

465 2019) for two stretches of the *Hawaii* test frame, each measuring 128 km along-track by 20.25 km across-track (Qu  
et al. 2023). The 3D RT simulation used horizontal grid-spacing  $\Delta x = 0.25$  km while its 1D rendition used  $\Delta x$  set  
arbitrarily large. Hence, differences in their radiances stem entirely from the dimensionality of the RT solution. For  
this demonstration, the number of photons per column was 4,096, which is, on an areal density-basis, several times  
larger than what will be used operational for the EarthCARE mission.

470 These images display the varied and complicated ramifications on radiances when 1D RT modelling theory is as-  
sumed to apply. For sample 1, 1D radiances show much variability and sharp contrasts relative to their 3D counter-  
parts; off-nadir views (not shown) look much the same. This region is blanketed by thick overcast ice cloud, which at  
 $\Delta x = 0.25$  km, act to diffuse upwelling radiation, thus blurring localized reflection from low-level intermittent  
liquid clouds (e.g., Diner and Martonchik 1984). When 1D RT is affected by setting  $\Delta x$  large, however, flow of  
475 radiation is confined to the vertical and the sharp features of liquid clouds remain intact regardless of altitude.

On the other hand, sample 2 has mostly low-to-mid-level liquid clouds and shows, due in part to large  $\theta_0$ , the more  
familiar differences between 3D and 1D RT (e.g., Barker et al. 2017). In particular, 1D radiances lack texture, whilst  
their 3D counterparts exhibit much contrast due to shadowing and cloud-side illumination. Note, however, that  
imagery for thin liquid clouds at the northern edge of the sample depend little on  $\Delta x$ . This is because reflected  
480 photons undergo small numbers of scattering events and thus tend to exit clouds close to where they enter.






**Figure 8:** (a) Difference between upwelling SW fluxes at an altitude of 20 km as predicted by 3D and 1D RT models for 5 x 21 km assessment domains of the Hawaii frame. Shaded area indicates EarthCARE's goal of  $\pm 10 \text{ W m}^{-2}$ . (b) As in (a) except this is for SW surface irradiance. (c) Mean liquid and ice cloud water paths for the Hawaii frame's 5 x 21 km domains. (d) Corresponding total cloud fraction and solar zenith angle for the same assessment domains.

Consider now differences one can encounter in applications to EarthCARE retrievals. *Figure 8* shows differences between 3D and 1D RT modelled SW broadband upwelling fluxes at 20 km and surface irradiances for 5 x 21 km assessment domains across the *Hawaii* frame using ACM-CAP cloud properties. Values for 3D and 1D RT are from the Monte Carlo model using  $\Delta x = 1 \text{ km}$  and arbitrarily large  $\Delta x$ , respectively. Each simulation used  $2.5 \times 10^6$  photons, which is likely much larger than what will be used operationally throughout the mission. For almost cloud-free skies, thin ice cloud-only with ice water path IWP  $< 0.01 \text{ kg m}^{-2}$ , and very thick clouds with CWP  $> 0.5 \text{ kg m}^{-2}$ , differences are well within  $\pm 10 \text{ W m}^{-2}$  for fluxes at both levels. Clearly, under these conditions SW photon trajec-

495 ries are characterized by either extremely small or large numbers of scattering events with cloud particles for both 1D and 3D RT. For the majority of other cloud conditions, however, especially with CWP in the vicinity of  $\sim 0.1 \text{ kg m}^{-2}$ , differences can be much larger than  $\pm 30 \text{ W m}^{-2}$ , which far exceeds EarthCARE's goal (ESA 2001; Illingworth et al. 2015; Eisinger et al. 2023). The implication being that many attempts to perform a radiative closure assessment on EarthCARE's retrievals will be doomed to failure if 1D RT models are adhered to.

500 *Figure 9* shows cumulative frequency distributions of the differences shown in *Figure 8* for several ranges of total cloud fraction  $A_c$ . For upwelling fluxes at 20 km with  $A_c < 0.25$ , median differences are all close to zero. The same goes for 3D - 1D mean-bias errors (MBEs) as listed in *Table 1*. Differences tend to be distributed more or less symmetrically about zero with occasional large differences, exceeding  $\pm 50 \text{ W m}^{-2}$ , enhancing root mean-square errors (RMSEs) as  $A_c$  increases (see *Table 1*) relative to the 16- and 84-percentiles of the distributions, which can be  
 505 gleaned from the graphs.

There are at least two interesting points to these plots that involve extremal cloud conditions. First, 3D - 1D can be expected to be maximized for overcast domains, which implies that the geometry of overcast clouds is often anything but approximately plane-parallel and homogeneous (cf. Hogan et al. 2019). Second, for assessment domains  $D$  with  $A_c = 0$ , 3D - 1D values for upwelling flux at 20 km show a tendency to be positive on account of contributions  
 510 from clouds in the surrounding buffer-zone (see *Figure 2*).




**Figure 9:** (a) Cumulative frequency distributions for differences between 3D and 1D Monte Carlo RT model estimates of upwelling SW flux at an altitude of 20 km for 5 x 21 km assessment domains for the Hawaii frame partitioned according to assessment domain total cloud fraction  $A_c$  (see Table 1 and Figure 8). Shaded area indicates EarthCARE's goal of  $\pm 10$  W m<sup>-2</sup>. (b) As in (a) except these are for surface (SFC) irradiances.

515

**Table 1:** Mean 3D SW RT values, mean bias errors (MBEs), and root mean-square errors (RMSEs) for corresponding 3D - 1D RT results (see Figure 8 and Figure 9) for 5 x 21 km assessment domains for the Hawaii frame and several ranges of total cloud fraction  $A_c$ .

		upwelling flux at 20 km			SFC irradiance		
		(W m <sup>-2</sup> )			(W m <sup>-2</sup> )		
total cld frac	cases	3D RT	MBE	RMSE	3D RT	MBE	RMSE
$A_c = 0$	24	81.0	4.2	6.2	698.0	1.5	3.6
$0 < A_c < 0.25$	28	93.5	12.2	13.8	780.0	1.5	6.3
$0.25 < A_c < 0.75$	39	112.0	5.0	25.2	755.9	4.6	16.1
$0.75 < A_c < 1$	23	128.0	1.3	21.6	777.0	-5.6	19.7
$A_c = 1$	113	395.5	-11.5	41.8	462.7	8.6	35.2

520




**Figure 10:** Mean 3D RT SW heating rate (HR) profiles for 5 x 21 km assessment domains for the Hawaii frame partitioned according to assessment domain total cloud fraction  $A_c$  (see Figure 8). Also shown are mean bias errors (MBEs) and root mean-square errors (RMSEs) between 3D and 1D RT models. Numbers of cases per  $A_c$  range are listed in Table 1.

525

Figure 10 shows that SW HR differences between 3D and 1D RT for the Hawaii frame's 5 x 21 km assessment domains are much less dramatic than those seen in Figure 8 and Figure 9 for boundary fluxes. At all altitudes and ranges of  $A_c$ , MBEs are essentially zero and close in magnitude to Monte Carlo uncertainties for  $2.5 \times 10^6$  photons. There are several reasons why RMSE values are  $\sim 10$ x larger than Monte Carlo uncertainties, and only increase slightly as  $A_c$  increases. There are the obvious differences due to cloud side illumination, shadowing, and photon entrapment (Hogan et al. 2019), as well as impacts on flux profiles for 3D RT due to out-of-domain sources and sinks of photons; i.e., clouds outside  $D$ , but still in  $D^+$ , that cast shadows or scatter radiation into  $D$ .

530




535 Figure 11: (a) Line is 3D RT nadir broadband radiances using  $\Delta x = 1$  km when reverting to the Henyey-Greenstein  
 phase function  $p_{HG}$  after  $N_{\text{Mie}} = 4$  cloud particle scattering events for  $5 \times 21$  km assessment domains of the  
 Hawaii frame. Dots are Monte Carlo uncertainties when  $p_{HG}$  is never used ( $N_{\text{Mie}} \rightarrow \infty$ ) and when it is used after  
 4 cloud scattering events ( $N_{\text{Mie}} = 4$ ). (b) Using data in (a), Monte Carlo domain-average uncertainties relative to  
 mean values for both values of  $N_{\text{Mie}}$ . Each domain received  $2.5 \times 10^6$  photons.

540

There is the possibility that radiative closure assessments of cloud and aerosol retrievals could (i.e., should) use  
 broadband radiances rather than fluxes. There are reasons both for and against this. For instance, off-nadir BBR  
 radiances offer powerful assessments due to their weak correlation, relative to nadir BBR radiances, with MSI  
 radiances that are used for some retrievals. They can, however, arise from attenuators outside the domain being  
 545 assessed (see Barker et al 2015b). On the other hand, all of EarthCARE's performance goals are in terms of BBR  
 fluxes, which will be estimated regularly by tailor-made algorithms (Velázquez-Blázquez et al. 2023a) despite  
 adding, at times substantial, uncertainty at the last step of EarthCARE's processing chain.


Regardless, SW BBR radiances will be estimated throughout the mission. *Figure 11* shows nadir values for the *Hawaii* frame's assessment domains using  $2.5 \times 10^6$  photons per assessment domain and  $\Delta x = 1$  km. It also shows relative Monte Carlo uncertainties for  $N_{\text{Mie}} = 4$  and  $N_{\text{Mie}} \rightarrow \infty$ . As  $2.5 \times 10^6$  photons / domain is likely to be more than routine operations can afford, uncertainties for  $N_{\text{Mie}} \rightarrow \infty$  could be substantially larger than those shown here. This would render them useless for most assessments. While use of  $N_{\text{Mie}} = 4$  will help, as is evident for the thick clouds between  $0^\circ$  to  $10^\circ$  N and near  $20^\circ$  S, it will foster errors in radiances themselves. Two options are being considered: i) use radiances, instead of fluxes, for assessments when their relative Monte Carlo uncertainties are less than some specified value (e.g., 0.01; see *Figure 11*); and ii) unbiased variance reduction methods (e.g., Iwabuchi 2006).

As is well known, flux and radiance differences between 3D and 1D treatments of RT for LW radiation are usually much smaller than those for SW radiation (e.g., Ellingson and Takara 2005; Cole et al. 2005; Hogan et al. 2016; Fauchez et al. 2017). *Figure 12* shows the LW counterpart of the upper panel in *Figure 8*. When differences go beyond  $\pm 10$  W m<sup>-2</sup>, they do so along with corresponding large differences in SW fluxes; typically for overcast skies with CWP  $\sim 0.1$  kg m<sup>-2</sup>. As shown in *Figure 13*,  $\sim 5\%$  of overcast cases exhibit 3D fluxes that are less than their 1D counterparts by more than 10 W m<sup>-2</sup>. For these domains, CWPs are small relative to their neighbouring domains. This demonstrates a difficulty when interpreting "fluxes" for  $5 \times 21$  km domains: at 20 km altitude, fluxes for 3D RT can be influenced substantially by adjacent cloudier domains. *Table 2*, however, shows that 3D and 1D fluxes usually differ by less than  $\pm 1$  W m<sup>-2</sup> which is on the order of the Monte Carlo uncertainty for these calculations, roughly 0.2 W m<sup>-2</sup>.



**Figure 12:** Difference between upwelling LW fluxes at an altitude of 20 km as predicted by 3D and 1D RT models for 5 x 21 km assessment domains of the Hawaii frame. A positive value means that 3D upwelling flux exceeds its 1D counterpart. Shaded area indicates EarthCARE's goal of  $\pm 10$  W m<sup>-2</sup>.

570



**Figure 13:** Cumulative frequency distributions for differences between 3D and 1D RT model estimates of upwelling LW flux at an altitude of 20 km for 5 x 21 km assessment domains for the Hawaii frame partitioned according to assessment domain total cloud fraction  $A_c$  (see *Table 2*). Shaded area indicates EarthCARE's goal of  $\pm 10$  W m<sup>-2</sup>.

575

**Table 2:** Mean 3D LW RT values, mean bias errors (MBEs), and root mean-square errors (RMSEs) for corresponding 3D - 1D RT results (see *Figure 8* and *Figure 9*) for 5 x 21 km assessment domains for the Hawaii frame and several ranges of total cloud fraction  $A_c$ .

total cld frac	cases	upwelling flux at 20 km (W m <sup>-2</sup> )		
		3D RT	MBE	RMSE
$A_c = 0$	25	285.4	-0.2	0.4
$0 < A_c < 0.25$	26	289.2	-0.5	0.7
$0.25 < A_c < 0.75$	34	286.0	-0.5	1.0
$0.75 < A_c < 1$	23	287.5	-0.2	1.5
$A_c = 1$	112	208.9	-0.7	4.3

580

## 6. Summary

The EarthCARE satellite mission’s objective is to retrieve profiles of aerosol and water cloud physical properties from measurements made by its cloud-profiling radar (CPR), backscattering lidar (ATLID), and passive multi-spectral spectral imager (MSI). While several L2a processes infer geophysical properties using measurements from a single sensor (see several articles in this special issue), EarthCARE’s primary product comes from the L2b synergistic retrieval algorithm in ACM-CAP (Mason et al. 2023). These retrievals, together with other geophysical properties obtained either from pre-existing satellite data or real-time weather prediction models, are input into broadband (BB) radiative transfer (RT) models that predict radiances, and fluxes, commensurate with measurements made, and inferred from, EarthCARE’s BB radiometer (BBR). The scientific goal is that modelled and “observed” BB fluxes differ, on average, by less than  $\pm 10$  W m<sup>-2</sup>.

590

This report described the BB RT models used for EarthCARE and their products, which together comprise the ACM-RT process. Shortwave (SW) and longwave (LW) flux and heating rate (HR) profiles are computed by a 1D solver, based on RRTMG, for each ~1 km nadir column of inferred properties. In addition to the 1D RT models, which are ubiquitous to almost all operational and research satellite missions, EarthCARE is the first to employ 3D (Monte Carlo) RT models operationally. Both SW and LW models will compute radiances for the BBR’s three viewing

595



directions, with the SW model also computing flux and HR profiles. The 3D LW model produces only upwelling fluxes at a variable reference level as dictated by the BMA-FLX process (Velázquez-Blázquez et al. 2023a). All 3D RT products are averages over  $5 \times 21$  km “assessment domains” that are constructed in the ACM-3D process (Barker et al. 2023) using a radiance mapping algorithm and MSI data (Barker et al. 2011).

600 When the ACM-CAP process runs successfully, its retrievals are operated on by the RT models. Failing this, the RT models are applied to “composite” atmospheric profiles generated in the ACM-COM process by combining L2a retrievals from individual sensors. Usually, this involves filling grid-cells with retrievals from either CPR *or* ATLID data. When two L2a estimates exist for a cell, the one with the least relative uncertainty is selected. ACM-COM also prepares either ACM-CAP or composite atmospheres for use in RT models by bringing together information about  
605 atmospheric state and surface optical properties. Regardless of what atmosphere is used, nadir profiles are broadened across-track by mapping indices from ACM-3D in order to create 3D domains for the 3D RT models to use. A subset of ACM-RT’s products is passed forward to the ACMB-DF process where a “radiative closure assessment” executes in an attempt to quantify the likelihood that EarthCARE’s goal has been achieved.

Data from the EarthCARE test frames (Qu et al. 2023; Donovan et al. 2023) were used to demonstrate some of the  
610 products to be expected from ACM-COM and ACM-RT. In several respects, products associated with the 1D RT models resemble closely those available from the CloudSat mission (e.g., L’Ecuyer et al. 2008). The most notable extension is that ACM-RT will be reporting continuous cloud and aerosol radiative effects based on 3D RT model results.

The majority of the results reported here (see section 5.2) had to do with the benefits expected from operational  
615 application of 3D RT models. The ACM-RT process is the most computationally intensive one in EarthCARE’s processing chain. While a significant amount of computer time is required by both of the 1D RT models and 3D LW RT model, the lion’s share of ACM-RT’s allocated time is consumed (inevitably entirely) by the 3D SW RT model. Its voracity is such that only a portion of a frame’s available assessment domains will be operated on; the expectation is, however, that sufficient numbers of samples will be realized over the duration of the mission. This is because of  
620 the fairly large number of photons that have to be injected into the Monte Carlo RT model in order to produce flux and radiance estimates with uncertainties small enough to realize beneficial radiative closure assessments in the

ACMB-DF process (Barker et al. 2023). The most demanding product is off-nadir radiances. Finalization of exactly what the 3D RT models produce will be determined during EarthCARE's commissioning phase.

625 If results presented in *Table 1* and *Figures 5* through *7* can be taken as representative, operational use of SW 3D RT modelling will be well-worth its heavy computational load. This is because differences between 3D and 1D RT values of upwelling fluxes and radiances can be either positive or negative (cf. Hogan et al. 2019) and can often exceed EarthCARE's goal of being able to, effectively, retrieve properties to within  $\pm 10 \text{ W m}^{-2}$ . The tacit warning here is that continued reliance on just 1D RT models would amount to a heightened rate of radiative closure assessments being unwittingly nullified.

### 630 **Data availability**

The EarthCARE Level-2 demonstration products the ACM-COM products discussed in this paper are available from <https://doi.org/10.5281/zenodo.7117115> (van Zadelhoff et al. 2022) as are "operational" ACM-RT output. Specialized ACM-RT calculations presented in this paper, e.g., with increased photon count, and radiative transfer calculations are available from <https://doi.org/10.5281/zenodo.7272662> (Cole et al. 2022).

### 635 **Competing interests**

The authors have no competing interests to declare.

### **Author contributions**

640 HWB drafted the manuscript, developed the ACM-RT and ACM-COM algorithms, and the 3D solar radiative transfer model used in ACM-RT. JNSC developed the ACM-RT processor software and the 3D thermal radiative transfer model, performed all ACM-RT calculations, and drafted sections of the manuscript. ZQ developed ACM-COM's algorithms and software plus aerosol look-up table for ACM-RT. NV contributed to development and testing of ACM-RT and performed independent 3D solar radiative transfer calculations. MS integrated the 1D RRTMG model

into ACM-RT. All authors were involved in development of ACM-RT and ACM-COM and contributed material and text to the manuscript.

## 645 **Acknowledgements**

We are especially indebted to Dr. Tobias Wehr, who passed away on 1-Feb-2023, for his unwavering support and encouragement over many years of work. We also wish to thank Michael Eisinger and all EarthCARE algorithm development team members for their ongoing support.

## 650 **References**

- Alvarado, M.J., V. H. Payne, E. J. Mlawer, G. Uymun, M. W. Shephard, K. E. Cady-Pereira, J. S. Delamere, and J.-L. Moncet, 2012: Performance of the line-by-line radiative transfer model (LBLRTM) for temperature, water vapor, and trace gas retrievals: Recent updates evaluated with IASI case studies, submitted to ACPD acp-2012-813.
- 655 Barker, H. W., R. K. Goldstein, and D. E. Stevens, 2003: Monte Carlo simulation of solar reflectances for cloudy atmospheres. *J. Atmos. Sci.*, **60**, 1881-1894.
- Barker, H. W., J. N. S. Cole, J. Li, B. Yi, and P. Yang, 2015a: Estimation of Errors for Two-Stream Approximations of the Solar Radiative Transfer Equation for Cloudy Atmospheres. *J. Atmos. Sci.*, **72**, 4053-4074.
- 660 Barker, H. W., J. N. S. Cole, C. Domenech, M. Shephard, C. Sioris, F. Tornow, and T. Wehr, 2015b: Assessing the Quality of Active-Passive Satellite Retrievals using Broadband Radiances. *Q. J. R. Meteorol. Soc.*, **141**, 1294–1305, DOI:10.1002/qj.2438.
- Barker, H.W., M. P. Jerg, T. Wehr, S. Kato, D. Donovan, and R. Hogan, 2011: A 3D Cloud Construction Algorithm for the EarthCARE satellite mission. *Q. J. R. Meteorol. Soc.*, DOI:10.1002/qj.824
- 665 Barker, H. W., Z. Qu, S. Belair, S. Leroyer, J. A. Milbrandt, P. A. Vaillancourt, 2017: Scaling Properties of Observed and Simulated Satellite Visible Radiances. *J. Geophys. Res.*, **122**, 9413–9429, doi:10.1002/2017JD027146.
- Barker, H. W., J. N. S. Cole, Z. Qu, N. Villefranque, and M. W. Shephard, 2023 : Radiative closure assessment of retrieved cloud and aerosol properties for the EarthCARE mission: the ACMB-DF product. *Atmospheric Measurement Techniques*, to be submitted.
- 670 Baum, B. A., P. Yang, A. J. Heymsfield, C. Schmitt, Y. Xie, A. Bansemmer, Y. X. Hu, and Z. Zhang, 2011: Improvements to shortwave bulk scattering and absorption models for the remote sensing of ice clouds. *J. Appl. Meteor. Clim.*, **50**, 1037-1056.
- Case, K. M., 1957: Transfer problems and the reciprocity principle. *Reviews of Modern Physics*, **29**, 651-663.

- Chýlek, P., P. Damiano, and E. P. Shettle, 1992: Infrared emittance of water clouds, *J. Atmos. Sci.*, **49**, 1459–1472.
- 675 Clough, S. A., M. W. Shephard, E. J. Mlawer, J. S. Delamere, M. J. Iacono, K. Cady-Pereira, S. Boukabara, and P. D. Brown, 2005: Atmospheric radiative transfer modeling: a summary of the AER codes, Short Communication, *J. Quant. Spectrosc. Radiat. Transfer*, **91**, 233-244.
- Cole, J. N. S. 2005: *Assessing the importance of Unresolved Cloud-Radiation Interactions in Atmospheric Global Climate Models Using the Multiscale Modelling Framework*. PhD thesis, The Pennsylvania State University, University Park.
- 680 Cole, Jason N. S., H. W. Barker, Z., Qu, N., Villefranche, and M. W. Shephard, 2022 : Enhanced 3D radiative transfer ACM-RT calculations and output for Cole et al., 2022 [Data set]. Zenodo. <https://doi.org/10.5281/zenodo.7272662>
- 685 Cotton, W. R. and N. R. Gokhale, 1967: Collision, coalescence and breakup of large water drops in a vertical wind tunnel. *J. Geophys. Res.* **72**, 4041–4049.
- Cox C. and W. Munk, 1956: Slopes of the sea surface deduced from photographs of the sun glitter. *Bull Scripps Inst Oceanog*, **6**, 401–488.
- Diner, D. J. and J. V. Martonchik, 1984: Atmospheric transfer of radiation above an inhomogeneous non-Lambertian ground: 1 – Theory. *J. Quant. Spectrosc. Radiat. Trans.*, **31**, 97–125.
- 690 Donovan, D., G.-J., van Zadelhoff, and P. Wang 2023: The ATLID L2a profile processor (A-AER, A-EBD, A-TC and A-ICE products). *Atmospheric Measurement Techniques*, to be submitted.
- Donovan, D., P. Kollias, and G.-J. van Zadelhoff, 2023: The Generation of EarthCARE L1 Test Data sets Using Atmospheric Model Data Sets. *Atmospheric Measurement Techniques*, to be submitted.
- 695 Ellingson, R. G. and E. E. Takara, 2005: Longwave Radiative Transfer in Inhomogeneous Cloud Layers. Pg 487 - 519 in *Three-dimensional Cloud Structure and Radiative Transfer*. Eds. A. Marshak and A., Davis. Springer-Verlag, 686pp.
- Eisinger, M., T. Wehr, T., Kubota, D., Bernaerts, and K. Wallace, 2023: The EarthCARE production model and auxiliary products. *Atmospheric Measurement Techniques*, to be submitted.
- 700 ESA., 2001: *The Five Candidate Earth Explorer Missions: EarthCARE –Earth Clouds, Aerosols and Radiation Explorer*, ESA SP-1257(1), September 2001. ESA Publications Division: Noordwijk, The Netherlands.
- Faucheux, T., A. Davis, C. Cornet, F. Szczap, S. Platnick, et al., 2017: A fast hybrid (3-D/1-D) model for thermal radiative transfer in cirrus via successive orders of scattering. *J. Geophys. Res.*, 122 (1), 344-366. 10.1002/2016JD025607.
- Friedman, D., 1969: Infrared characteristics of ocean water. *Appl. Opt.*, **8**, 2073-2078.
- 705 Goody, R. M., R. West, L. Chen, and D. Crisp, 1989: The correlated k-distribution method for radiation calculation in nonhomogeneous atmospheres. *J. Quant. Spectrosc. Radiat. Transfer*, **42**, 539–550, doi:10.1016/0022-4073(89)90044-7.

- Hale, G. M. and M. R. Querry, 1973: Optical constants of water in the 200nm to 200 $\mu$ m wavelength region. *Appl. Opt.*, **12**, 555-563.
- 710 Hansen, J., G. Russell, D. Rind, P. Stone, A. Lacis, S. Lebedeff, R. Ruedy, and L. Travis, 1983: Efficient three-dimensional global models for climate studies: models i and ii. *Mon. Wea. Rev.*, **111**, 609–662.
- Heney, L. G., and J. L. Greenstein, 1941: Diffuse light in the galaxy. *Astro. Phys. J.*, **93**, 70.
- Hogan, R. J., S. A. K. Schäfer, C. Klinger, J.-C. Chiu, and B. Mayer, 2016: Representing 3D cloud-radiation effects in two-stream schemes: 2. Matrix formulation and broadband evaluation. *J. Geophys. Res. Atmos.*, **121**, 8583–8599, <https://doi.org/10.1002/2016JD024875>.
- 715 Hogan, R. J., M. D. Fielding, H. W. Barker, N. Villefranque, and S. A. K. Schafer, 2019: Entrapment: An important mechanism to explain the shortwave 3D radiative effect of clouds. *J. Atmos. Sci.*, **76**, 2123-2141.
- Hu Y. X., and Stamnes, 1993: An accurate parameterization of the radiative properties of water clouds suitable for use in climate models. *J. Climate*, **6**, 728-742.
- 720 Huang, X., Chen, X., Zhou, D. K., & Liu, X.: An observationally based global band-by-band surface emissivity dataset for climate and weather simulations. *J. Atmos. Sci.*, **73(9)**, 3541– 3555. <https://doi.org/10.1175/jas-d-15-0355.1>, 2016.
- Hünerbein, A., S. Bley, H., Deneke, J. F., Meirink, G.-J., van Zadelhoff, and A. Walther, 2023: Cloud optical and physical property retrievals from the EarthCARE multi-spectral imager: the M-COP product. *Atmospheric Measurement Techniques*, to be submitted.
- 725 Iacono, M. J., J. S. Delamere, E. J. Mlawer, and S. A. Clough, 2003: Evaluation of upper tropospheric water vapor in the NCAR Community Climate Model, CCM3, using modeled and observed HIRS radiances. *J. Geophys. Res.*, **108**, 4037, doi:10.1029/2002JD002539.
- Iacono, M. J., J. S. Delamere, E. J. Mlawer, M. W. Shephard, S. A. Clough, and W. D. Collins, 2008: Radiative forcing by long-lived greenhouse gases: Calculations with the AER radiative transfer models, *J. Geophys. Res.*, **113**, D13103, doi:10.1029/2008JD009944.
- 730 Illingworth, A. + others, 2015: THE EARTHCARE SATELLITE: The next step forward in global measurements of clouds, aerosols, precipitation and radiation. *Bull. Am. Met. Soc.*, **96**, 1311-1332. DOI:10.1175/BAMS-D-12-00227.1.
- 735 Irbah, A., J. Delanoë, G.-J., Zadelhoff, D., Donovan, P., Kollias, A., Tatarevic, B. P., Treserras, S., Mason, S., and Hogan 2023: The classification of atmospheric hydrometeors and aerosols from EarthCare radar and lidar: the A-TC, C-TC and AC-TC products. *Atmospheric Measurement Techniques*, to be submitted.
- Iwabuchi, H., 2006: Efficient Monte Carlo methods for radiative transfer modeling. *J. Atmos. Sci.*, **63**, 2324-2339.
- Kato, S., N. G. Loeb, F. G. Rose, D. R. Doelling, D. A. Rutan, T. E. Caldwell, L. Yu, and R. A. Weller, 2013: Surface irradiances consistent with CERES-derived top-of-atmosphere shortwave and longwave irradiances. *J. Clim.*, **26**, 2719–2740.
- 740 Lacis, A. A., and V. Oinas, 1991: A description of the correlated k-distribution method for modeling nongray gaseous absorption, thermal emission, and multiple scattering in vertically inhomogeneous atmospheres. *J. Geophys. Res.*, **96**, 9027–9074, doi:10.1029/90JD01945.

- 745 L'Ecuyer, T., N. Wood, T. Haladay, G. L. Stephens, and P. W. Stackhouse, 2008: Impact of clouds on atmospheric heating based on the R04 CloudSat fluxes and heating rates dataset. *J. Geophys. Res.*, **113**:D00A15. doi:10.1029/2008JD009951.
- Li, J. and V. Ramaswamy, 1996: Four-Stream Spherical Harmonic Expansion Approximation for Solar Radiative Transfer. *J. Atmos. Sci.*, **53**, 1174–1186.
- 750 Loeb, N. G., S. Kato, and B. A. Wielicki, 2002: Defining Top-of-the-Atmosphere Flux Reference Level for Earth Radiation Budget Studies. *J. Climate*, **15**, 3301-3309.
- Marchuk, G. I., G. A. Mikhailov, M. A. Nazarialiev, R. A. Darbinjan, B. A. Kargin, and B. S. Elepov, 1980: *Monte Carlo Methods in Atmospheric Optics*. Optical Science Series, 12, Springer Verlag, 208 pp.
- Marshall, J. S. and W. M. Palmer, 1948: The distribution of raindrops with size. *J. of Meteor.*, **5** (4), 165–166.
- 755 Mason, S., R. J. Hogan, A. Bozzo, and N. Pounder, 2023: A unified synergistic retrieval of clouds, aerosols and precipitation from EarthCARE: the ACM-CAP product, 2022: EGU sphere [preprint], <https://doi.org/10.5194/egusphere-2022-1195>. Mason, S., R. J. Hogan, D. Donovan, G.-J., van Zadelhoff, P., Kollias, B. P., Treserras, and Z., Qu, 2023a: An intercomparison of EarthCARE cloud, aerosol and precipitation retrieval products. *Atmospheric Measurement Techniques*, to be submitted.
- 760 Masuda, K., T. Takashima, and Y. Takayama, 1988: Emissivity of pure and sea waters for the model sea surface in the infrared window regions. *Rem. Sens. Env.*, **24**, 313-329
- Milbrandt, J. A., S. Bélair, M. Faucher, M. Vallée, M. L. Carrera, and A. Glazer, 2016: The Pan-Canadian high resolution (2.5km) deterministic prediction system. *Weather and Forecasting*, **31**, 1791-1816.
- Mlawer, E. J., S. J. Taubman, P. D. Brown, M. J. Iacono, and S. A. Clough, 1997: Radiative transfer for inhomogeneous atmospheres: RRTM, a validated correlated-k model for the longwave. *J. Geophys. Res.*, **102**, 16 663–16 682, doi:10.1029/97JD00237.
- 765 Mlawer, E. J., and S. A. Clough, 1998: Shortwave and longwave enhancements in the rapid radiative transfer model. Proc. Seventh Atmospheric Radiation Measurement (ARM) Science Team Meeting, San Antonio, TX, U.S. Dept. of Energy, 409–413. [Available online at [https://www.arm.gov/publications/proceedings/conf07/extended\\_abs/mlawer\\_ej.pdf](https://www.arm.gov/publications/proceedings/conf07/extended_abs/mlawer_ej.pdf).]
- 770 Modest, M. F., 2003: Backward Monte Carlo simulations in radiative heat transfer. *ASME Journal of Heat Transfer*, **125**, 57-62.
- Morcrette, J.-J., H.W. Barker, J.N.S. Cole, M.J. Iacono, and R. Pincus, 2008: Impact of a new radiation package, McRad, in the ECMWF Integrated Forecasting System. *Mon. Wea. Rev.*, **136**, 4773–4798.
- 775 Mroz, K., B. P. Treserras, A., Battaglia, P. Kollias, A. Tatarevic, and F. Tridon, 2023 : Cloud and Precipitation Microphysical Retrievals from the EarthCARE Cloud Profiling Radar: the C-CLD product, EGU sphere [preprint], <https://doi.org/10.5194/egusphere-2023-56>. Oreopoulos, L., and Coauthors, 2012: The continual intercomparison of radiation codes: Results from Phase I. *J. Geophys. Res.*, **117**, D06118, doi:10.1029/2011JD016821.
- 780 Qu, Z., D. P. Donovan, H. W., Barker, J. N. S., Cole, and M. W. Shephard, and V. Huijnen., 2022: Numerical model generation of test frames for pre-launch studies of EarthCARE's retrieval algorithms and data management system. *Atmos. Meas. Tech. Discuss.* [preprint], <https://doi.org/10.5194/amt-2022-300>, in review.

- Rahman, H., Pinty, B. and Verstraete, M.M., 1993, Coupled surface-atmosphere reflectance (CSAR) model 2. Semiempirical surface model usable with NOAA Advanced Very High Resolution Radiometer data. *J. Geophys. Res.*, **98**, 20,791–20,801.
- 785 Schaaf, C. B., F. Gao, A. H. Strahler, W. Lucht, X. Li, T. Tsang, N. C. Strugnell, X. Zhang, Y. Jin, J.-P. Muller, P. Lewis, M. Barnsley, P. Hobson, M. Disney, G. Roberts, M. Dunderdale, C. Doll, R. d'Entremont, B. Hu, S. Liang, and J. L. Privette, 2002: First Operational BRDF, Albedo and Nadir Reflectance Products from MODIS, *Remote Sens. Environ.*, **83**, 135-148.
- Segelstein, D., 1981: "The Complex Refractive Index of Water", M.S. Thesis, University of Missouri--Kansas City.
- 790 Shephard M. W., S. A. Clough, V. H. Payne, W. L. Smith, S. Kireev, and K. E. Cady-Pereira, 2009: Performance of the line-by-line radiative transfer model (LBLRTM) for temperature and species retrievals: IASI case studies from JAIVEx. *Atmos. Chem. Phys.*, **9**, 7397-7417.
- Stephens, G.L., Vane, D.G., Boain, R.J., Mace, G.G., Sassen, K., Wang, Z., Ilingworth, A.J., O'Connor, E.J., Rossow, W.B., Durden, S.L., Miller, S.D., Austin, R.T., Benedetti, A., Mitrescu, C., and the CloudSat Science Team., 2002: The CloudSat mission and the A-Train: A new dimension of space-based observations of clouds and precipitation. *Bull. Amer. Meteor. Soc.*, **83**, 1771–1790, <https://doi.org/10.1175/BAMS-83-12-1771>.
- 795
- Ulbrich, C. W., 1983: Natural variations in the form of raindrop size distribution. *J. Clim. Appl. Met.*, **22**, 1764-1775.
- van Zadelhoff, G.-J., H. W., Barker, E., Baudrez, S., Bley, N., Clerbaux, J. N. S., Cole, J., de Kloe, N., Docter, C., Domenech, D. P., Donovan, J.-L. Dufresne, M., Eisinger, J., Fischer, R., García-Marañón, M., Haarig, R. J., Hogan, A., Hünerbein, P., Kollias, R., Koopman, T., Wehr, 2022: EarthCARE level-2 demonstration products from simulated scenes (09.01) [Data set]. Zenodo. <https://doi.org/10.5281/zenodo.7117116>
- 800
- Velázquez-Blázquez, A., E. Baudrez, N., Clerbaux, C., Domenech, R. G., Marañón, and N. Madenach, 2023a: Towards instantaneous top-of-atmosphere fluxes from EarthCARE: The BMA-FLX product. *Atmospheric Measurement Techniques*, to be submitted.
- 805 Velázquez-Blázquez, A., E. Baudrez, N., Clerbaux, and C. Domenech, 2023b: Unfiltering of the EarthCARE Broadband Radiometer (BBR) observations: the BM-RAD product. *Atmospheric Measurement Techniques*, to be submitted.
- Villefranche, N., Fournier, R., Couvreur, F., Blanco, S., Cornet, C., Eymet, V., Forest, V., and Tregan, J.-M. (2019), A Path-Tracing Monte Carlo Library for 3-D Radiative Transfer in Highly Resolved Cloudy Atmospheres, *J. Adv. Model. Earth Syst.*, **11**, 2449– 2473. doi:<https://doi.org/10.1029/2018MS001602>.
- 810
- Walters, D. V. and R. O. Buckius, 1992: Rigorous development for radiation heat transfer in nonhomogeneous absorbing, emitting and scattering media. *Int. J. Heat Mass Transfer*, **35**, 3323-3333.
- Wandinger, U., A. A. Floutsi, H. Baars, M. Haarig, A. Ansmann, A. Hünerbein, N. Docter, D. Donovan, G.-J. van Zadelhoff, S. Mason and J. Cole, 2023: HETEAC - The Hybrid End-To-End Aerosol Classification model for EarthCARE. EGU sphere [preprint], <https://doi.org/10.5194/egusphere-2022-1241>.
- 815
- Wielicki, B. A., B. R. Barkstrom, E. F. Harrison, R. B. Lee III, G. L. Smith, and J. E. Cooper, 1996: Clouds and the Earth's Radiant Energy System (CERES): An Earth Observing System experiment. *Bull. Amer. Meteor. Soc.*, **77**, 853–868.
- Wiscombe, W. J., 1980: Improved Mie scattering algorithms. *Appl. Opt.*, **19**, 1505-1509.

- 820 Wiscombe W. J., 1977: The Delta-M Method: Rapid yet accurate radiative flux calculations for strongly asymmetric phase functions *J. Atmos. Sci.*, **34**, 1408-1422.
- Wu, X. and W.L. Smith, 1997: Emissivity of rough sea surface for 8-13 $\mu$ m: model-ing and verification. *Appl. Opt.*, **36**, 2609-2619.
- 825 Yang, P., L. Bi, B. A. Baum, K.-N. Liou, G. Kattawar, M. Mishchenko, and B. Cole, 2013: Spectrally consistent scattering, absorption, and polarization properties of atmospheric ice crystals at wavelengths from 0.2  $\mu$ m to 100  $\mu$ m. *J. Atmos. Sci.*, **70**, 330-347.